

VOLTAGE-RESISTANCE CHART OF TX-62

Voltages are given in volts; Resistance values are in ohms. K indicates X 1,000; M indicates X 1,000,000.
V - Voltage. R - Resistance. See Notes on Page 7.

Tube	Pin No.	V or R	6 METERS				2 METERS			
			C W		PHONE		C W		PHONE	
			Key Down	Key Up	Key Down	Key Up	Key Down	Key Up	Key Down	Key Up
V1	1	V*	2.5	28	2.5	85	2.5	35	2.5	85
		R	200	∞	200	∞	200	∞	200	∞
	2	V*	-4	0	-4	0	-4.4	0	-4.4	0
		R	4.7K	4.7K	4.7K	4.7K	4.7K	4.7K	4.7K	4.7K
	7	V	285	340	295	355	260	330	280	350
		R	33K	33K	72K	72K	33K	33K	72K	72K
	8	V	80	112	83	120	75	115	78	120
		R	20K	20K	20K	20K	20K	20K	20K	20K
V2	1	V	@2.5	@20	@2.5	85	@2.2	@35	@2.2	85
		R	150	∞	150	∞	150	∞	150	∞
	2	V*	@-80	0	@-80	0	@-80	0	@-80	0
		R	100K	100K	100K	100K	100K	100K	100K	100K
	7	V	285	340	295	355	260	340	280	355
		R	33K	33K	72K	72K	33K	33K	72K	72K
	8	V	10 to 250, depending on setting of drive control				-			
		R	1K to 26K, depending on setting of drive control				-			
V3	3	V	@108	34	@100	35	12	35	12	85
		R	∞	∞	∞	∞	150	∞	150	∞
	2,6	V	0	0	0	0	72	0	46	0
		R	22K	22K	22K	22K	22K	22K	22K	22K
	1,7	V	260	280	270	315	260	330	275	350
		R	33K	33K	72K	72K	33K	33K	72K	72K
	9	V	295	340	305	355	280	340	290	355
		R	33K	33K	72K	72K	33K	33K	72K	72K
V4	2,6,8,9	V	17	26	11	85	18	35	12	85
		R	100	∞	100	∞	100	∞	100	∞
	10	V	25	0	25	0	25	0	25	0
		R	8.2K	8.2K	8.2K	8.2K	8.2K	8.2K	8.2K	8.2K
	7,11	V	200	23	125	355	210	21	115	355
		R	130K	130K	130K	130K	130K	130K	130K	130K
	3,4,5	V	520	590	540	620	500	600	530	630
		R	130K	130K	170K	170K	130K	130K	170K	170K
V5a	6	V	230	230	230	230	230	230	230	230
		R	800K	800K	800K	800K	800K	800K	800K	800K
	7	V	-0.8	-0.8	-0.8	-0.8	-0.8	-0.8	-0.8	-0.8
		R	5.6M	5.6M	5.6M	5.6M	5.6M	5.6M	5.6M	5.6M
	8	V	0	0	0	0	0	0	0	0
		R	0	0	0	0	0	0	0	0
V5b	1	V	270	310	100	105	255	310	90	310
		R	350K	350K	350K	350K	350K	350K	350K	350K
	2	V	0	0	-0.8	-0.8	0	0	-0.8	-0.8
		R	5.6M	5.6M	5.6M	5.6M	5.6M	5.6M	5.6M	5.6M
	3	V	7	7	0	0	7	7	0	0
		R	∞	∞	0	0	∞	∞	0	0
V6	1	V	0	0	9	27	0	0	9	27
		R	0	0	@	@	0	0	@	@
	2	V	0	0	0	0	0	0	0	0
		R	570K	570K	470K	470K	570K	570K	470K	470K
	7	V	400	23	180	520	390	21	180	510
		R	130K	130K	180K	180K	130K	130K	180K	180K
	8	V	205	120	260	350	190	125	240	355
		R	30K	30K	90K	90K	30K	30K	90K	90K
Octal Socket On Rear	2,3	V	295	340	305	355	280	340	290	355
		R	33K	33K	72K	72K	33K	33K	72K	72K
	4,5	V	520	590	540	620	500	600	530	630
		R	130K	130K	170K	170K	130K	130K	170K	170K