

INSTRUCTION MANUAL

GONSET **"COMMUNICATOR II-B"**

Transmitter-Receiver

DIRECTORY OF COMMUNICATOR MODELS COVERED BY THIS BOOK:

- 3025-B 2 Meter Amateur 6/115 Volt
- 3043-B Ground-to-Air 6/115 Volt
- 3049-B 6 Meter Amateur 6/115 Volt
- 3057-B 2 Meter Amateur 12/115 Volt
- 3058-B 6 Meter Amateur 12/115 Volt
- 3064-B C.A.A. 6/115 Volt (Push-to-Talk)
- 3070-B C.A.A. 12/115 Volt (Push-to-Talk)
- 3073-B Ground-to-Air 12/115 Volt
- 3074-B Ground-to-Air 115 Volts A.C.
- 3077-B F.C.D.A. Certified 2 Meter 12/115 Volt
- 3079-B F.C.D.A. Certified 6 Meter 12/115 Volt
- 3087-B F.C.D.A. Certified 2 Meter 6/115 Volt
- 3088-B F.C.D.A. Certified 6 Meter 6/115 Volt

The following suffixes, when appended to the above designations, indicate deviations from the standard model as follows:

- P indicates push-to-talk has been added.
- S indicates special frequency (on special order).
- X indicates substitution of a crystal-controlled receiver for the tunable receiver normally supplied.

801 S. MAIN ST.



BURBANK, CALIF.