

TABLE OF CONTENTS

60-10-25

SECTION I.	General Specifications and Description	Page 1-3
SECTION II.	Controls and CW Operating Procedures, Crystal Control	Page 3-7
SECTION III.	CW Operating Procedure, VFO control	Page 8-11
SECTION IV.	AM Operating Procedure	Page 11-12
SECTION V.	SB Operating Procedure	Page 12-13
SECTION VI.	Important Information	Page 13-14
SECTION VII.	Antenna Considerations	Page 14-16
SECTION VIII.	VFO Alignment	Page 17-19
SECTION IX.	Typical Voltage Readings	Page 19-20
SECTION X.	Malfunctions and Possible Causes	Page 21
SECTION XI.	Parts List	Page 22-28
SECTION XII.	Schematics	
	Warranty (90 Days)	Back Cover

SPECIFICATIONS

FINAL POWER INPUT: 540 watts CW and Phone
700 watts SB Peak Envelope Power (with
external SB exciter).

OUTPUT: Coaxial into 52-300 ohm antenna.

BAND COVERAGE:

160 meters	1750-3000 KC
80 meters	3200-4800 KC
40 meters	6600-9000 KC
20 meters	13-19 MC
15 meters	13-24 MC
10 meters	16-31 MC

POWER REQUIREMENTS: 115 VAC.
50/60 cycles 1300 watts phone,
820 watts CW.

FREQUENCY CONTROL: Xtal or VFO.

DIMENSIONS: 31 inches high, 15
inches deep, 22 inches wide.

SHIPPING WEIGHT: 270 pounds.