

## 7-2 - PARTS LIST - SB-175 Meteor Transmitter

WRL Stk. No.	Schematic Diagram Designation	Description	Price
<u>Capacitors, Cont'd.</u>			
25-8	C10	180 mmf/sec., two sec. variable grid-tuning	\$ 2.40
25-9	C19	180 mmf/sec., two sec. variable plate-tuning	3.20
25-10	C20	452 mmf/sec., 3 sec. variable plate-loading	3.15
26-3	C11	25-280 pf, 4 plate trimmer, neutralizing	.60
<u>Chokes &amp; Coils</u>			
30-3	RFC1, 4	800 uhy RF choke, 50 ma, 2 pie	.45
30-4	RFC 5	50 uhy RF choke	.35
30-6	RFC 3	425 uhy RF choke ceramic form	.80
30-7	RFC 2	350 uhy RF choke, 50 ma, 1 pie	.40
34-2	R16, R17, (PS)	Parasitic suppressor	.30
40-5	L2	Slug tuned, buf. grid, 7 mc., coil	.70
40-6	L1	Slug tuned, buf. grid, 14 mc., coil	.70
40-7	L3	Phenolic form, final grid, 80-40-20, coil	.80
40-8	L4, L5	Air wound final grid, 15-10, coil	.15
40-9	L7	Phenolic form, final plate, 80-40-20 coil	1.15
40-10	L6	Air wound final plate, 15-10, coil	.35
<u>Switches</u>			
51-2	S5	Slide type, DPST, XTAL-VFO	.22
51-4	S6	Slide type, DPDT, METER	.22
53-1	S4	Rotary 6-pole, 4 pos., 2 wafers, FUNCTION	3.10
53-2	S2	Rotary bandswitch exciter 4-pole, 5-position, 3 wafer	5.50
53-3	S3	Rotary final plate bandswitch 1 wafer, 5-position, progressive shorting	1.60
<u>Miscellaneous</u>			
61-3		7 pin min. tube socket	.21
61-6		12 pin, compactron socket	.20
61-9		Octal tube socket	.20
61-8		Cable socket, female, 11 pin	.46
62-1S		9 pin mica filled tube socket top mt. /w. shield	.32