

TABLE OF INFORMATION FOR 2000

CONSTANTS AND CONVERSION FACTORS		UNITS		PREFIXES			
		Name	Symbol	Factor	Prefix	Symbol	
1 unified atomic mass unit,	$1u = 1.66 \times 10^{-27} \text{ kg}$ $= 931 \text{ MeV}/c^2$	meter	m	10^9	giga	G	
Proton mass,	$m_p = 1.67 \times 10^{-27} \text{ kg}$	kilogram	kg	10^6	mega	M	
Neutron mass,	$m_n = 1.67 \times 10^{-27} \text{ kg}$	second	s	10^3	kilo	k	
Electron mass,	$m_e = 9.11 \times 10^{-31} \text{ kg}$	ampere	A	10^{-2}	centi	c	
Magnitude of the electron charge,	$e = 1.60 \times 10^{-19} \text{ C}$	kelvin	K	10^{-3}	milli	m	
Avogadro's number,	$N_0 = 6.02 \times 10^{23} \text{ mol}^{-1}$	mole	mol	10^{-6}	micro	μ	
Universal gas constant,	$R = 8.31 \text{ J}/(\text{mol} \cdot \text{K})$	hertz	Hz	10^{-9}	nano	n	
Boltzmann's constant,	$k_B = 1.38 \times 10^{-23} \text{ J/K}$	newton	N	10^{-12}	pico	p	
Speed of light,	$c = 3.00 \times 10^8 \text{ m/s}$	pascal	Pa	VALUES OF TRIGONOMETRIC FUNCTIONS FOR COMMON ANGLES			
Planck's constant,	$h = 6.63 \times 10^{-34} \text{ J} \cdot \text{s}$ $= 4.14 \times 10^{-15} \text{ eV} \cdot \text{s}$	joule	J				
	$hc = 1.99 \times 10^{-25} \text{ J} \cdot \text{m}$ $= 1.24 \times 10^3 \text{ eV} \cdot \text{nm}$	watt	W				
Vacuum permittivity,	$\epsilon_0 = 8.85 \times 10^{-12} \text{ C}^2/\text{N} \cdot \text{m}^2$	coulomb	C				
Coulomb's law constant,	$k = 1/4\pi\epsilon_0 = 9.0 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$	volt	V				
Vacuum permeability,	$\mu_0 = 4\pi \times 10^{-7} (\text{T} \cdot \text{m})/\text{A}$	ohm	Ω				
Magnetic constant,	$k' = \mu_0/4\pi = 10^{-7} (\text{T} \cdot \text{m})/\text{A}$	henry	H				
Universal gravitational constant,	$G = 6.67 \times 10^{-11} \text{ m}^3/\text{kg} \cdot \text{s}^2$	farad	F				
Acceleration due to gravity at the Earth's surface,	$g = 9.8 \text{ m/s}^2$	tesla	T				
1 atmosphere pressure,	$1 \text{ atm} = 1.0 \times 10^5 \text{ N/m}^2$ $= 1.0 \times 10^5 \text{ Pa}$	degree Celsius	$^\circ\text{C}$				
1 electron volt,	$1 \text{ eV} = 1.60 \times 10^{-19} \text{ J}$	electron- volt	eV				
				θ	$\sin \theta$	$\cos \theta$	$\tan \theta$
				0°	0	1	0
				30°	1/2	$\sqrt{3}/2$	$\sqrt{3}/3$
				37°	3/5	4/5	3/4
				45°	$\sqrt{2}/2$	$\sqrt{2}/2$	1
				53°	4/5	3/5	4/3
				60°	$\sqrt{3}/2$	1/2	$\sqrt{3}$
				90°	1	0	∞

The following conventions are used in this examination.

- I. Unless otherwise stated, the frame of reference of any problem is assumed to be inertial.
- II. The direction of any electric current is the direction of flow of positive charge (conventional current).
- III. For any isolated electric charge, the electric potential is defined as zero at an infinite distance from the charge.
- IV. The work done by a thermodynamic system is defined as a positive quantity.

ADVANCED PLACEMENT PHYSICS B EQUATIONS FOR 2000

NEWTONIAN MECHANICS

$v = v_0 + at$	$a = \text{acceleration}$
$x = x_0 + v_0t + \frac{1}{2}at^2$	$F = \text{force}$
$v^2 = v_0^2 + 2a(x - x_0)$	$f = \text{frequency}$
$\Sigma \mathbf{F} = \mathbf{F}_{net} = m\mathbf{a}$	$h = \text{height}$
$F_{fric} \leq \mu N$	$J = \text{impulse}$
$a_c = \frac{v^2}{r}$	$K = \text{kinetic energy}$
$\tau = rF \sin \theta$	$k = \text{spring constant}$
$\mathbf{p} = m\mathbf{v}$	$\ell = \text{length}$
$\mathbf{J} = \mathbf{F}\Delta t = \Delta\mathbf{p}$	$m = \text{mass}$
$K = \frac{1}{2}mv^2$	$N = \text{normal force}$
$\Delta U_g = mgh$	$P = \text{power}$
$W = \mathbf{F} \cdot \mathbf{s} = Fs \cos \theta$	$p = \text{momentum}$
$P_{avg} = \frac{W}{\Delta t}$	$r = \text{radius or distance}$
$P = Fv$	$s = \text{displacement}$
$\mathbf{F}_s = -k\mathbf{x}$	$T = \text{period}$
$U_s = \frac{1}{2}kx^2$	$t = \text{time}$
$T_s = 2\pi\sqrt{\frac{m}{k}}$	$U = \text{potential energy}$
$T_p = 2\pi\sqrt{\frac{\ell}{g}}$	$v = \text{velocity or speed}$
$T = \frac{1}{f}$	$W = \text{work}$
$F_G = -\frac{Gm_1m_2}{r^2}$	$x = \text{position}$
$U_G = -\frac{Gm_1m_2}{r}$	$\mu = \text{coefficient of friction}$
	$\theta = \text{angle}$
	$\tau = \text{torque}$

ELECTRICITY AND MAGNETISM

$F = \frac{1}{4\pi\epsilon_0} \frac{q_1q_2}{r^2}$	$A = \text{area}$
$\mathbf{E} = \frac{\mathbf{F}}{q}$	$B = \text{magnetic field}$
$U_E = qV = \frac{1}{4\pi\epsilon_0} \frac{q_1q_2}{r}$	$C = \text{capacitance}$
$E_{avg} = -\frac{V}{d}$	$d = \text{distance}$
$V = \frac{1}{4\pi\epsilon_0} \sum_i \frac{q_i}{r_i}$	$E = \text{electric field}$
$C = \frac{Q}{V}$	$\mathcal{E} = \text{emf}$
$C = \frac{\epsilon_0 A}{d}$	$F = \text{force}$
$U_c = \frac{1}{2}QV = \frac{1}{2}CV^2$	$I = \text{current}$
$I_{avg} = \frac{\Delta Q}{\Delta t}$	$\ell = \text{length}$
$R = \frac{\rho\ell}{A}$	$P = \text{power}$
$V = IR$	$Q = \text{charge}$
$P = IV$	$q = \text{point charge}$
$C_p = \sum_i C_i$	$R = \text{resistance}$
$\frac{1}{C_s} = \sum_i \frac{1}{C_i}$	$r = \text{distance}$
$R_s = \sum_i R_i$	$t = \text{time}$
$\frac{1}{R_p} = \sum_i \frac{1}{R_i}$	$U = \text{potential (stored) energy}$
$F_B = qvB \sin \theta$	$V = \text{electric potential or potential difference}$
$F_B = BI\ell \sin \theta$	$v = \text{velocity or speed}$
$B = \frac{\mu_0 I}{2\pi r}$	$\rho = \text{resistivity}$
$\phi_m = \mathbf{B} \cdot \mathbf{A} = BA \cos \theta$	$\phi_m = \text{magnetic flux}$
$\mathcal{E}_{avg} = -\frac{\Delta\phi_m}{\Delta t}$	
$\mathcal{E} = B\ell v$	

ADVANCED PLACEMENT PHYSICS B EQUATIONS FOR 2000

THERMAL PHYSICS

$$\Delta l = \alpha l_0 \Delta T$$

$$Q = mL$$

$$Q = mc\Delta T$$

$$p = \frac{F}{A}$$

$$pV = nRT$$

$$K_{avg} = \frac{3}{2} k_B T$$

$$v_{rms} = \sqrt{\frac{3RT}{M}} = \sqrt{\frac{3k_B T}{\mu}}$$

$$W = p\Delta V$$

$$Q = nc\Delta T$$

$$\Delta U = Q - W$$

$$\Delta U = nc_V \Delta T$$

$$e = \frac{W}{Q_H} = \frac{Q_H - Q_C}{Q_H}$$

$$e_c = \frac{T_H - T_C}{T_H}$$

A = area

c = specific heat or molar specific heat

e = efficiency

K_{avg} = average molecular kinetic energy

L = heat of transformation

l = length

M = molecular mass

m = mass of sample

n = number of moles

p = pressure

Q = heat transferred

T = temperature

U = internal energy

V = volume

v_{rms} = root-mean-square velocity

W = work done by system

α = coefficient of linear expansion

μ = mass of molecule

WAVES AND OPTICS

$$v = f\lambda$$

$$n = \frac{c}{v}$$

$$n_1 \sin \theta_1 = n_2 \sin \theta_2$$

$$\sin \theta_c = \frac{n_2}{n_1}$$

$$\frac{1}{s_i} + \frac{1}{s_o} = \frac{1}{f}$$

$$M = \frac{h_i}{h_o} = -\frac{s_i}{s_o}$$

$$f = \frac{R}{2}$$

$$d \sin \theta = m\lambda$$

$$x_m \approx \frac{m\lambda L}{d}$$

d = separation

f = frequency or focal length

h = height

L = distance

M = magnification

m = an integer

n = index of refraction

R = radius of curvature

s = distance

v = speed

x = position

λ = wavelength

θ = angle

ATOMIC AND NUCLEAR PHYSICS

$$E = hf = pc$$

$$K_{max} = hf - \phi$$

$$\lambda = \frac{h}{p}$$

$$\Delta E = (\Delta m)c^2$$

E = energy

f = frequency

K = kinetic energy

m = mass

p = momentum

λ = wavelength

ϕ = work function

GEOMETRY AND TRIGONOMETRY

Rectangle

$$A = bh$$

Triangle

$$A = \frac{1}{2}bh$$

Circle

$$A = \pi r^2$$

$$C = 2\pi r$$

Parallelepiped

$$V = \ell wh$$

Cylinder

$$V = \pi r^2 \ell$$

$$S = 2\pi r \ell + 2\pi r^2$$

Sphere

$$V = \frac{4}{3}\pi r^3$$

$$S = 4\pi r^2$$

Right Triangle

$$a^2 + b^2 = c^2$$

$$\sin \theta = \frac{a}{c}$$

$$\cos \theta = \frac{b}{c}$$

$$\tan \theta = \frac{a}{b}$$

A = area

C = circumference

V = volume

S = surface area


b = base

h = height

ℓ = length

w = width

r = radius



ADVANCED PLACEMENT PHYSICS C EQUATIONS FOR 2000

MECHANICS

$v = v_0 + at$	$a = \text{acceleration}$
$x = x_0 + v_0t + \frac{1}{2}at^2$	$F = \text{force}$
$v^2 = v_0^2 + 2a(x - x_0)$	$f = \text{frequency}$
$\sum \mathbf{F} = \mathbf{F}_{net} = m\mathbf{a}$	$h = \text{height}$
$\mathbf{F} = \frac{d\mathbf{p}}{dt}$	$I = \text{rotational inertia}$
$\mathbf{J} = \int \mathbf{F} dt = \Delta\mathbf{p}$	$J = \text{impulse}$
$\mathbf{p} = m\mathbf{v}$	$K = \text{kinetic energy}$
$F_{fric} \leq \mu N$	$k = \text{spring constant}$
$W = \int \mathbf{F} \cdot d\mathbf{s}$	$\ell = \text{length}$
$K = \frac{1}{2}mv^2$	$L = \text{angular momentum}$
$P = \frac{dW}{dt}$	$m = \text{mass}$
$\Delta U_g = mgh$	$N = \text{normal force}$
$a_c = \frac{v^2}{r} = \omega^2 r$	$P = \text{power}$
$\boldsymbol{\tau} = \mathbf{r} \times \mathbf{F}$	$p = \text{momentum}$
$\sum \boldsymbol{\tau} = \boldsymbol{\tau}_{net} = I\boldsymbol{\alpha}$	$r = \text{radius or distance}$
$I = \int r^2 dm = \sum mr^2$	$s = \text{displacement}$
$\mathbf{r}_{cm} = \sum m\mathbf{r} / \sum m$	$T = \text{period}$
$v = r\omega$	$t = \text{time}$
$\mathbf{L} = \mathbf{r} \times \mathbf{p} = I\boldsymbol{\omega}$	$U = \text{potential energy}$
$K = \frac{1}{2}I\omega^2$	$v = \text{velocity or speed}$
$\omega = \omega_0 + \alpha t$	$W = \text{work}$
$\theta = \theta_0 + \omega_0 t + \frac{1}{2}\alpha t^2$	$x = \text{position}$
$\mathbf{F}_s = -k\mathbf{x}$	$\mu = \text{coefficient of friction}$
$U_s = \frac{1}{2}kx^2$	$\theta = \text{angle}$
$T = \frac{2\pi}{\omega} = \frac{1}{f}$	$\tau = \text{torque}$
$T_s = 2\pi\sqrt{\frac{m}{k}}$	$\omega = \text{angular speed}$
$T_p = 2\pi\sqrt{\frac{\ell}{g}}$	$\alpha = \text{angular acceleration}$
$\mathbf{F}_G = -\frac{Gm_1m_2}{r^2} \hat{\mathbf{r}}$	
$U_G = -\frac{Gm_1m_2}{r}$	

ELECTRICITY AND MAGNETISM

$F = \frac{1}{4\pi\epsilon_0} \frac{q_1q_2}{r^2}$	$A = \text{area}$
$\mathbf{E} = \frac{\mathbf{F}}{q}$	$B = \text{magnetic field}$
$\oint \mathbf{E} \cdot d\mathbf{A} = \frac{Q}{\epsilon_0}$	$C = \text{capacitance}$
$E = -\frac{dV}{dr}$	$d = \text{distance}$
$V = \frac{1}{4\pi\epsilon_0} \sum_i \frac{q_i}{r_i}$	$E = \text{electric field}$
$U_E = qV = \frac{1}{4\pi\epsilon_0} \frac{q_1q_2}{r}$	$\mathcal{E} = \text{emf}$
$C = \frac{Q}{V}$	$F = \text{force}$
$C = \frac{\kappa\epsilon_0 A}{d}$	$I = \text{current}$
$C_p = \sum_i C_i$	$L = \text{inductance}$
$\frac{1}{C_s} = \sum_i \frac{1}{C_i}$	$\ell = \text{length}$
$I = \frac{dQ}{dt}$	$n = \text{number of loops of wire}$
$U_c = \frac{1}{2}QV = \frac{1}{2}CV^2$	per unit length
$R = \frac{\rho\ell}{A}$	$P = \text{power}$
$V = IR$	$Q = \text{charge}$
$R_s = \sum_i R_i$	$q = \text{point charge}$
$\frac{1}{R_p} = \sum_i \frac{1}{R_i}$	$R = \text{resistance}$
$P = IV$	$r = \text{distance}$
$\mathbf{F}_M = q\mathbf{v} \times \mathbf{B}$	$t = \text{time}$
$\oint \mathbf{B} \cdot d\boldsymbol{\ell} = \mu_0 I$	$U = \text{potential or stored energy}$
$\mathbf{F} = \int Id\boldsymbol{\ell} \times \mathbf{B}$	$V = \text{electric potential}$
$B_s = \mu_0 nI$	$v = \text{velocity or speed}$
$\phi_m = \int \mathbf{B} \cdot d\mathbf{A}$	$\rho = \text{resistivity}$
$\mathcal{E} = -\frac{d\phi_m}{dt}$	$\phi_m = \text{magnetic flux}$
$\mathcal{E} = -L \frac{dI}{dt}$	$\kappa = \text{dielectric constant}$
$U_L = \frac{1}{2}LI^2$	

ADVANCED PLACEMENT PHYSICS C EQUATIONS FOR 2000

GEOMETRY AND TRIGONOMETRY

Rectangle

$$A = bh$$

Triangle

$$A = \frac{1}{2}bh$$

Circle

$$A = \pi r^2$$

$$C = 2\pi r$$

Parallelepiped

$$V = \ell wh$$

Cylinder

$$V = \pi r^2 \ell$$

$$S = 2\pi r \ell + 2\pi r^2$$

Sphere

$$V = \frac{4}{3}\pi r^3$$

$$S = 4\pi r^2$$

Right Triangle

$$a^2 + b^2 = c^2$$

$$\sin \theta = \frac{a}{c}$$

$$\cos \theta = \frac{b}{c}$$

$$\tan \theta = \frac{a}{b}$$

A = area

C = circumference

V = volume

S = surface area


b = base

h = height

ℓ = length

w = width

r = radius



CALCULUS

$$\frac{df}{dx} = \frac{df}{du} \cdot \frac{du}{dx}$$

$$\frac{d}{dx}(x^n) = nx^{n-1}$$

$$\frac{d}{dx}(e^x) = e^x$$

$$\frac{d}{dx}(\ln x) = \frac{1}{x}$$

$$\frac{d}{dx}(\sin x) = \cos x$$

$$\frac{d}{dx}(\cos x) = -\sin x$$

$$\int x^n dx = \frac{1}{n+1} x^{n+1}, n \neq -1$$

$$\int e^x dx = e^x$$

$$\int \frac{dx}{x} = \ln|x|$$

$$\int \cos x dx = \sin x$$

$$\int \sin x dx = -\cos x$$