

An Evaluation of the Risks and Benefits of Penetrations in Subsea Wellheads below the BOP Stack

TECHNICAL REPORT 17TR3
NOVEMBER 2004



An Evaluation of the Risks and Benefits of Penetrations in Subsea Wellheads below the BOP Stack

Upstream Segment

TECHNICAL REPORT 17TR3
NOVEMBER 2004



SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations under local, state, or federal laws.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. Sometimes a one-time extension of up to two years will be added to this review cycle. This publication will no longer be in effect five years after its publication date as an operative API standard or, where an extension has been granted, upon republication. Status of the publication can be ascertained from the API Standards department telephone (202) 682-8000. A catalog of API publications, programs and services is published annually and updated biannually by API, and available through Global Engineering Documents, 15 Inverness Way East, M/S C303B, Englewood, CO 80112-5776.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this standard or comments and questions concerning the procedures under which this standard was developed should be directed in writing to the Director of the Standards department, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should be addressed to the Director, Business Services.

API standards are published to facilitate the broad availability of proven, sound engineering and operating practices. These standards are not intended to obviate the need for applying sound engineering judgment regarding when and where these standards should be utilized. The formulation and publication of API standards is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, N.W., Washington, D.C. 20005.

Copyright © 2004 American Petroleum Institute

FOREWORD

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

Suggested revisions are invited and should be submitted to API, Standards department, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Executive Summary

(revised from original Report)

The purpose of this study was to provide an evaluation of the risks and benefits of allowing penetrations in subsea wellheads below the blowout preventer (BOP) stack. Current Minerals Management Service Regulations require that all annuli be monitored for casing pressure. However, industry standards (ISO 13628-4 & API 17D) for the design of subsea wellheads prohibit penetrations in the wellhead, thus allowing the monitoring of only the "A" (production tubing by production casing) annulus.

The scope of this study is limited to completed subsea wells in the Gulf of Mexico (GOM). Special attention was paid to the risks and benefits introduced by allowing penetrations to monitor annuli other than "A". The benefits of allowing penetrations were developed by a panel of experts – the API Spec 17D/ISO 13628-4 Task Group. The risks were evaluated using fault tree analysis for three systems: 1) wellhead system without penetrations, 2) wellhead system with one penetration and 3) wellhead system with two penetrations. The task group developed a risk index for each failure mode. The probability of failure for each of the fault trees was then normalized to one for the no penetration case to indicate relative risk value. In addition, sensitivity analyses were also run to compare the difference in failure between 2-inch wellhead penetrations (preferred by the Task Group) and ½-inch wellhead penetrations.

The benefits of adding penetrations to the subsea wellhead system were identified as follows:

- Allows the monitoring of pressure in annuli other than "A"
- Provides data for determining the collapse margin on the production casing as "A" annulus pressure is bled off
- Allows the monitoring of the pressure in adjacent annuli as the pressure in a particular annulus is increased or decreased
- Potentially allows pressure to be bled off

However, it must be noted that there is a strong likelihood that any wellhead penetration will become plugged at some point during well life; especially in the drilling and cementing phases. If the penetration is plugged, an invalid pressure reading will occur and possibly lead to an erroneous conclusion regarding annular pressure characteristics. If the penetration becomes plugged, the benefits listed above are compromised and the penetration will just provide another leak path in the system.

For the comparative risk analysis, fault trees were built with the top event of the fault tree being "The Inability of the Wellhead System to Maintain a Pressure Barrier over the Life of the Well." In the fault tree analysis, various potential leak sources and failure modes were identified and individual risk values assigned.

The comparative risk from the fault tree analysis gives the following results:

Relative Risk Analysis Summary				
Event	Configuration	No Penetrations	B-annulus Penetration	B & C-annulus Penetrations
Failure of system to maintain a pressure barrier	2-inch penetrations	1.00	2.50	2.69
Failure of system to maintain a pressure barrier	½-inch penetrations	1.00	3.59	3.75

Finally, the benefits of adding penetrations to the wellhead housing in the subsea wells were weighed against the risks. The study concludes that the risks outweigh the benefits since the risk of maintaining the pressure barrier using a wellhead with penetrations is approximately two-and-a-half times that of a system without penetrations. This is underscored by the task group's assessment that any potential benefit is lost since the additional penetrations will likely become plugged during a well's life and that the plugging is most likely to occur during the early portion of that period. Furthermore, it should be noted that over 50% of sustained casing pressure occurs in the "A" annulus and monitoring of this annulus is readily accomplished using current technology that conforms with global industry specifications.

In conclusion, it is recommended that API/ISO standards continue to prohibit penetrations in subsea wellheads. Emphasis should be placed on well construction and operational practices to minimize the likelihood of casing pressure becoming an unmanageable event.

Subsequent to completion of the report, the contractor submitted the following Addendum after further examination of the MMS data was performed to assess the homogeneity of the well population from a casing-string perspective.

"Initial results of indicate that the most prevalent well type by far has no intermediate casing. Therefore, the statement in section 3.2:

For pressures that are greater than 20% MIYP, 2.2% of wells exhibit pressure in the surface casing annulus, while only 1.7% of wells exhibit pressure in the intermediate casing annulus, but 5.8% of the wells exhibit pressure in the production casing annulus. This indicates that the surface casing annulus pressure frequently works its way inward from the formation instead of working outward from the "A" annulus pressure.

must be read in that context. That is to say, if a well with no intermediate casing exhibits pressure in the surface casing then the source may be from a formation rather than working outward from the "A" annulus."

Table of Contents

1	Purpose	1
2	Scope	1
3	Background.....	1
3.1	Regulatory Requirements	1
3.2	MMS Casing Pressure Data.....	2
4	Risk Analysis Method.....	3
4.1	General	3
4.2	Fault Tree Analysis	3
4.3	Failure Modes and Effects Analysis (FMEA)	4
4.4	Methodology Used	6
5	Casing Pressure Risk Analysis	6
5.1	Development Background.....	7
5.2	Risk Analysis Details	8
6	Results	3
6.1	Risk Analysis	4
6.2	Sensitivity Study	5
6.3	Benefits Analysis	6
6.4	Global Risk/Benefits Assessment	6
7	Conclusions	7
8	Recommendations.....	8
9	References	8
10	Tables	10
11	Figures	17
12	Appendix	1
12.1	Appendix A – Potential Leak Paths	
12.2	Appendix B – Fault Tree Details for No Penetrations	
12.3	Appendix C – Fault Tree Details with One Penetration	
12.4	Appendix D – Fault Tree Details with Two Penetrations	
12.5	Appendix E – Fault Tree Details with ½-inch Penetrations	
12.6	Appendix F – Sensitivity Analysis Scenario 1	
12.7	Appendix G – Sensitivity Analysis Scenario 2	
12.8	Appendix H – FMEA Data	

1 Purpose

The purpose of this study is to provide an evaluation of the risks and benefits of allowing penetrations in subsea wellheads below the blowout preventer (BOP) stack so annuli other than the production tubing (commonly referred to as the “A” annulus) could be monitored.

Current industry standards (API Spec 17D and ISO 13628-4) for the design of subsea wellheads prohibit penetrations below the (BOP) stack. In contrast, Minerals Management Service (MMS) regulations (30 CFR 250.517) require that all annuli be monitored for sustained casing pressure and that every occurrence of sustained casing pressure be reported immediately to the District Supervisor.

2 Scope

The American Petroleum Institute (API) contracted with Stress Engineering Services (SES) to analyze the risks and benefits inherent in continuing to prohibit penetrations in subsea wellheads and compare them to those introduced by allowing the practice. Special attention was paid to the risk and benefits introduced by monitoring annuli other than the “A” annulus (the annulus between the production tubing and the production casing strings). The “risk-based” portion of this specific study did not need to be fully quantitative, but the analysis was done in a way that will easily lead to a fully quantitative analysis as more complete data become available. The scope of this study is limited to completed conventional subsea wells in the Gulf of Mexico (GOM).

This report documents the results of this study of the risks and benefits of additional penetrations in subsea wellheads below the BOP stack for the purpose of monitoring additional casing annuli for sustained casing pressure (SCP).

3 Background

3.1 Regulatory Requirements

The current industry-standard design philosophy of subsea wellheads prohibits penetrations below the BOP stack. This is codified in the current standards (API Spec 17D and ISO 13628-4). The “no penetrations” language was instituted by the authors of the first edition of API Spec 17D based on intuition and industry practice. No formal reliability analysis (qualitative or quantitative) was performed to ascertain the risks and benefits of allowing penetrations in the wellhead housing below the BOP stack. At a high level, the authors of the standard were concerned with protecting the integrity of the well during drilling operations by preventing the likelihood of a leak below the BOP through a penetration. The apparent concern was that introducing a penetration below the BOP could lead either to a well-control incident caused by loss of the hydrostatic head of drilling fluid in the riser above the BOP or the exacerbation of an existing well-control incident by loss of integrity below the stack. Standard subsea wellhead designs have always provided for monitoring of the “A” annulus for pressure by means of an annulus monitor line in the tree’s production control umbilical and/or an electronic pressure sensor in the tree’s annular flowpath.

However, historically, subsea wellheads have not provided any annular access to outer casing string cavities once a wellhead packoff has been installed after cementing operations.

In 1989, the MMS established regulations, described in 30 CFR 250.517, for sustained casing pressure. These regulations required that all annuli be monitored for sustained casing pressure and that every occurrence of sustained casing pressure be reported immediately to the District Supervisor. In 1991, in an effort to streamline government and reduce burdensome paperwork, the MMS issued a letter that dictated changes in the sustained casing pressure policy. The revised policy allowed for continued operation if:

- The sustained casing pressure is less than 20% of the minimum internal yield pressure (MIYP), and
- The casing pressure bleeds to zero in 24 hours or less when bled through a ½-inch needle valve.

If both of these requirements were met, the lessee was not required to submit the diagnostic test results to the MMS for review and approval for continued operation. Wells meeting both of these criteria were placed into a separate category and referred to as *Self-Approved*.

Records of each diagnostic test must be maintained for each casing annulus with SCP. The records must contain:

- Identification of the casing annulus,
- SCP value at beginning of test,
- Pressure chart or time required to bleed pressure down to zero shown on the gauge,
- Type of fluids bled,
- Volume(s) of liquid(s) recovered,
- Pressure build-up chart or pressure recorded at least once per hour,
- Shut-in and flowing tubing pressure,
- Producing rates of gas, oil, and water, and
- Well status.

In 2002, the MMS requested that the industry perform an evaluation of the risks and benefits of allowing penetrations in subsea wells below the BOP stack. The intent of the request was to reconcile the difference between the MMS regulations for annular monitoring and the current industry standards (API Spec 17D and ISO 13628-4) for subsea wellhead design. To accomplish this, the API contracted Stress Engineering Services to analyze the risks and benefits inherent in continuing to prohibit penetrations below the wellhead and compare them with those introduced by allowing the practice.

3.2 MMS Casing Pressure Data

The MMS maintains a database on casing pressure events in outer continental shelf (OCS) platform wells in the GOM. Table 1 is a summary of the MMS database of 15,516 OCS wells and is shown graphically in Figure 1. Of these wells, 1446 (9.3%) of them are reported to have casing pressure greater than 20% of the minimum internal yield pressure (MIYP) of the casing. Within these 1446 wells, 906 of them have casing pressure in the production casing annulus ("A" annulus – accessible via current subsea designs), 261 of them have casing pressure in the intermediate casing annulus ("B" annulus), 347 of them have casing pressure in the surface casing annulus ("C" annulus), and 95 of them have casing pressure in the conductor casing annulus ("D" annulus).

The data shows that only about 4.5% of the wells are affected by casing pressure in the outer annuli (B, C, or D) at a level greater than 20% of the MIYP pressure of the casing. This drops to 1.8% when the pressure is greater than 30% of the MIYP, and further drops to 0.3% when the pressure is greater than 50% of the MIYP. This indicates that the frequency of occurrence of casing pressure is very low and still has a design margin of two. This data of casing pressure in the outer annuli is shown in Figure 2.

The occurrence index scale defined in Table 2 is based upon this information. One of the observations made from this data (Table 1) is that the frequency of occurrence of casing pressure is greater in the surface casing annulus than the intermediate casing annulus for all levels of pressure. For pressures that are greater than 20% MIYP, 2.2% of wells exhibit pressure in the surface casing annulus, while only 1.7% of wells exhibit pressure in the intermediate casing annulus, but 5.8% of the wells exhibit pressure in the production casing annulus. This indicates that the surface casing annulus pressure frequently works its way inward from the formation instead of working outward from the "A" annulus pressure.

Information from the OCS database is referenced in this analysis. This data covers all wells on the GOM OCS, both dry and subsea trees. It should be noted that the population of dry trees is much greater than that of subsea trees. However, since the well designs are similar, it is a reasonable assumption that the data is valid for the purposes of this study.

The MMS presented data at the American Association of Drilling Engineers (AADE) conference in Houston in January 2003 showing OCS wells in the GOM affected by casing pressure as a function of the age of the well. The data have since been updated as of 9 October 2003 to include all OCS wells affected by casing pressure regardless of the casing annulus and regardless of the pressure level (see Figures 3 and 4).

4 Risk Analysis Method

4.1 General

Risk assessment is a technical and scientific process in which outcomes for various system scenarios are modeled and quantified. Risk assessment provides qualitative and quantitative

data to decision-makers for use in risk management. Qualitative risk analysis uses expert opinion to evaluate relative probabilities and consequences for an undesirable event. Quantitative risk analysis relies on probabilistic statistical methods and databases to concretely identify probabilities and consequences for all credible failure scenarios of a system. Failure Modes and Effects Analysis (FMEA) and Fault Tree Analysis (FTA) are generally considered to be qualitative risk analysis techniques.

Although quantitative analysis is the preferred method, it is statistically impractical to perform a quantitative analysis unless all of the wellhead designs and construction methods are mechanically identical. Since subsea wellhead systems vary greatly (different subsea wellhead designs, number of casing strings, where they are “hung off”, how they are sealed with both metal and elastomer sealing packoffs, etc.), a qualitative analysis is the only practical way to evaluate the merits of adding penetrations to the subsea wellhead. For this study, the reliability “numbers” generated through qualitative analysis have been normalized relative to the current subsea system design of no wellhead penetrations. This enables a quantitative reliability comparison of equipment performance of proposed subsea wellhead designs with penetrations to the current designs that provide “A” annulus access only.

4.2 Fault Tree Analysis

Fault tree analysis (FTA) can be described as an analytical technique, whereby an undesired state of the system or safety event is specified and the system is analyzed in the context of its environment and operation to find all credible ways in which the undesired event can occur. The fault tree itself is a graphic model of the various parallel and sequential combinations of faults that lead to the undesired event – which is the top event of the fault tree. Based upon a set of rules and logic symbols from probability theory and Boolean algebra, the fault tree uses a top-down approach to generate a logic model that provides for both qualitative and quantitative evaluation of system reliability.

It is important to understand that a fault tree is not a model of all possible system failures or all possible causes for system failure. A fault tree is tailored to its top event, a particular system failure model, and thus includes only those faults that contribute to this top event. Moreover, these faults are not exhaustive; they cover only the most credible faults as assessed by the analyst.

It is also important to note that a fault tree is not in itself a quantitative model. It is a qualitative model that can be evaluated quantitatively and often is. The fact that a fault tree is a particularly convenient model to quantify does not change the qualitative nature of the model itself. Finally, a fault tree analysis addresses the likelihood of the failure to occur, but does not address the severity of the occurrence.

4.3 Failure Modes and Effects Analysis (FMEA)

A Failure Modes and Effects Analysis (FMEA) is defined as a procedure by which each potential failure mode in a system is analyzed to determine the results or effects thereof on the system and to classify each potential failure mode according to its severity.

Failure mode(s) is defined as the manner by which a failure is observed. It generally describes the way the failure occurs and its impact on equipment operation. It is sometimes defined as the problem, the concern, the opportunity to improve, or the failure. It is the physical description of the manner in which a failure occurs. Examples of failure modes are cracked, leaked, broken, warped, corroded, and binding.

The effect(s) of failure is defined as the outcome of the failure on the system, design, process, or service. In essence, the effect(s) of failure attempts to answer the questions: What happens when a failure occurs? What is (are) the consequence(s) of that failure? The effects of a failure must be addressed from both a local and a global viewpoint. The local viewpoint is that in which the failure is isolated and does not affect anything else in the system. The global viewpoint is that in which the failure can and does affect other functions and/or components. Therefore, a failure with a global effect is more serious than one with a localized effect.

The cause(s) of failure is defined as the physical or chemical processes, design defect(s), quality defect(s), part misapplication, or other processes that are the basic reasons for failure or those that initiate the physical process by which deterioration proceeds to failure. It is the root cause of the noted failure mode. When looking for the cause of the failure, one must look for the root cause, not the symptom of the failure. The cause of a failure may also be due to human error. There may be several causes for one failure mode and all causes should be listed on the FMEA report.

The detection method is the means or method by which a failure can be discovered during normal system operation or by some diagnostic action.

The purpose of the FMEA is to identify and prevent known and potential problems from reaching the customer. The FMEA process helps to define and rank the problems so that they can be addressed with respect to their overall importance. A risk priority number (RPN) is used to articulate the priority of a problem.

The risk priority number (RPN) is defined as the product of the severity of the failure, the frequency of occurrence, and the reliability of the detection method. The highest RPN value is assigned to the problem that should be addressed first to prevent future failures. If the FMEA is to follow the guidelines of a qualitative analysis, the RPN should follow theoretical (expected) behavior of the component. If the guideline is quantitative, it must be specific. It must follow actual data, statistical process control data, historical data, and/or similar or surrogate data for the evaluation.

The severity of failure is a rating that indicates the seriousness of the effect of the potential system failure mode. The rating is based upon a scale of 1 to 10 with 10 being the most severe.

Occurrence is the rating value corresponding to the estimated number of failures that could occur for a given cause over the design life of the system. The rating is based upon a scale of 1 to 10 with 10 being the most frequent.

The detection is a rating corresponding to the likelihood that the proposed system controls will detect a specific root cause of a failure mode. The rating is based upon a scale of 1 to 10 with 10 being the highest likelihood of detecting the cause of failure.

Examples of the FMEA work is shown in Appendix H.

4.4 Methodology Used

Following is the process used in performing the analysis for this study:

1. An FMEA analysis listing each potential failure mode, causes of failure, effects of the failure, and current design controls to detect the failure was developed. An index value (from 1 to 10) was assigned for each of the following: frequency of occurrence, severity of effects, and likelihood of detection. These indices were multiplied together resulting in a risk priority number (RPN) used to rank the design characteristics that were most important to address first. See Reference 6 for method.
2. Once the preliminary results from the FMEA analysis were obtained, it was determined that a better method for meeting the objectives of this study would be to switch to the (FTA) method. The FTA method is more appropriate for developing a comparative risk analysis between two designs (wellhead without penetrations and a wellhead with penetrations). See Reference 8 for method.
3. The FMEA data along with a literature search and brainstorming sessions with well systems experts was used to define the failure modes (causes) for each of the major system components – wellhead penetrations, casing/pipe connections, casing hanger packoff, and casing cement. These failure modes are defined in Tables 3 through 7.
4. An Expert's Forum comprised of members from the API Spec 17D/ISO 13628-4 Task Group was convened to refine (add to or delete from) the list of failure modes and to rank the likelihood of occurrence of each failure mode on a scale of 1 to 10 (10 being almost likely occurrence).
5. The fault tree logic diagram was constructed for three cases – no penetrations; “B” annulus penetration only (one penetration); and “B” annulus plus “C” annulus penetrations (two penetrations).
6. A Weibull analysis (see Figure 5) was performed on the MMS data for OCS wells with casing pressure as a function of well age (see Reference 9). From this Weibull analysis,

the cumulative distribution function (CDF) curve shown in Figure 6 was created. This curve was used to determine the probability that the event will have occurred as a function of time.

7. The probability values from the CDF curve were used for each of the index values in the failure occurrence index table found in Table 2.
8. Based upon each of the frequency index values defined in the Expert's Forum, the failure occurrence values from Table 2 were assigned to each of the lower level failure modes on the fault tree diagram using Boolean logic (see Reference 8). By definition, the "Or-Gate" probability of occurrence is: $P_O = P_1 + P_2 - (P_1 \times P_2)$. For an "And-Gate" the probability of occurrence is: $P_A = P_1 \times P_2$.
9. The probability of failure for each of the fault tree cases (no penetrations, one penetration, and two penetrations) was then normalized relative to the No Penetrations case to give a relative risk value, i.e., the likelihood of failure for a wellhead with one penetration is 2.5 times that of a wellhead with no penetrations.
10. The benefits of allowing penetrations in the subsea wellhead were developed from brainstorming sessions with the project steering committee and the Expert's Forum. They did not come from using specific risk analysis methodologies.

5 Casing Pressure Risk Analysis

5.1 Development Background

The initial objective of this project was to develop a qualitative risk assessment to compare a subsea wellhead design with penetrations (thus allowing for monitoring of pressure in the "B" and "C" annuli) to the existing subsea wellhead design without penetrations. The planned method to accomplish this was to use the FMEA or the Failure Modes, Effects and Criticality Analysis (FMECA). An FMEA is usually recommended as the first step of any risk analysis effort. After meeting with the project Steering Committee in February 2003, this effort was started.

The initial effort involved a literature search on sustained casing pressure. This search yielded some very valuable information on the subject that was used in the analysis and is referenced below. The literature provided useful information regarding the root causes of casing pressure in existing offshore systems. However, the literature did not address the issue of adding penetrations in the subsea wellhead housing for the purpose of monitoring additional annuli for casing pressure.

Based upon the literature research, an FMEA was initiated to identify the causes of failure, frequency of occurrence, and the severity of each mode of failure. This was initially developed for the existing subsea wellhead system design without penetrations. Following this, several brainstorming sessions were held to begin development of the risks associated with adding penetrations in the wellhead housing.

Following this preliminary FMEA effort, a second session with the project steering committee was held in June 2003 evaluate the results. After lengthy discussions, it was decided that the best step forward would be to convert the FMEA data into a fault tree analysis for this study.

Then the main question, in order to properly develop the fault tree, became: What should be the top event of the fault tree? It was decided that the top event should be "The Inability of the Wellhead System to Maintain a Pressure Barrier over the Life of the Well." From this, preliminary fault trees were developed for the two systems – 1) Wellhead System without Penetrations, and 2) Wellhead System with Penetrations.

A typical subsea wellhead system was used for the FTA model. This model is shown in Figure 7 and consists of a production casing string, one intermediate casing string, a surface casing string, and the conductor pipe.

Two meetings were held in August 2003 with reliability engineering experts to review and discuss the preliminary fault trees. It was the consensus of the group at these meetings that: 1) the fault tree was the appropriate method to analyze the risk of wellhead penetrations, 2) the top event of the fault trees was properly defined, and 3) the methodology used for the fault tree construction was correct.

In August 2003, a workshop was held with the API Spec 17D/ISO 13628-4 task group for the following purposes:

- Review the root cause failures for each of the failure modes for relevancy,
- Add to the list of root cause failures as needed, and
- Rank each of the failures by frequency of occurrence based on their consensus opinions.

5.2 Risk Analysis Details

The top event of the fault tree is “The Inability of the Wellhead System to Maintain a Pressure Barrier over the Life of the Well.” This means that the wellhead system should be able maintain a pressure barrier between each formation zone and the environment. This is in keeping with the objective of the MMS regulations. In developing the overall fault tree, the FTA looks at each of the potential pressure leak paths. In some cases the leak path is pressure from the “A” annulus leaking to an outer casing annulus and/or to the environment. In other cases it is pressure leaking from the formation to either an inner annulus or to the environment via an annulus. These potential leak paths are shown in each of the illustrations in Appendix A.

There are four groups of potential leak paths. These groups were developed further to determine the root causes of the failure and the frequency of occurrence of failures. The four groups are:

- Leakage through the wellhead housing penetrations,
- Leakage through the casing and/or the casing connections,
- Leakage through the casing’s hanger packoff, and
- Leakage through the casing’s cement.

In evaluating the risk of subsea-wellhead-housing penetrations, five potential failure modes were identified. Each of these failure modes could have multiple causes for the failure. The following list details these failure modes and the potential causes. They are listed in decreasing order of frequency of occurrence as judged by the task group.

- **False pressure reading from the monitoring port sensor,**
 - The pressure sensor being inoperable,
 - The pressure sensor operating, but giving a wrong signal due to being out of calibration, etc.,
 - The pressure port to the sensor being plugged, or
 - Losing the signal from the pressure sensor,
- **Damage to the valves attached to the wellhead housing penetration from external influences,**
 - Damage to the valves and/or the wellhead housing during the running/installation process,
 - Damage to the valves resulting from contact with the ROV,
 - Damage occurring while landing the tree, or
 - Damage from dropped equipment,
- **Leakage from valve connections or from the valves themselves,**
 - Leakage due to vibration, or
 - Leakage due to corrosion,

- **Failure of the valve to function,**
 - Valve fails to function when in the closed position, or
 - Valve fails to function when in the open position,
- **Wellhead housing integrity,**
 - Structural integrity of the wellhead housing resulting from higher bending moments due to design requiring a taller housing, or
 - Structural integrity of the wellhead housing resulting from stress concentration factors due to penetrations.

The above ranking of the risks associated with the wellhead housing penetrations is based upon the premise of using current industry standard 2-inch valves with a 2-inch penetration in the wellhead. If the size of the penetration is reduced from 2-inch to approximately ½-inch, then the task group felt that the risks would increase in at least two areas: 1) the likelihood of the penetration being plugged would significantly increase, and 2) the occurrence of leakage due to vibration would also increase.

Leakage via the casing and/or the casing connections mode of failure resulted in the identification of seven principal causes of failure. These causes of failure are listed in decreasing order of frequency of occurrence as judged by the task group.

- Corrosion of the pipe and/or corrosion of the connection sealing surfaces
- Thermal cycling loads on the casing string
- Damaged threads
- Wear on the casing string from drilling operations
- Damaged connection sealing surfaces
- Bad or wrong thread compound being used
- Improper make-up of the connections (either over-torqued or under-torqued)

When the task group examined loss of pressure integrity through the casing-hanger-packoff mode of failure, nine principal causes of failure were generated. These causes of failure are listed in decreasing order of frequency of occurrence as judged by the task group.

- Damaged sealing surface
- Thermal cycling loads resulting in additional axial loads on the hanger
- Installation anomalies or improper setting of the hanger packoff
- Corrosion of the sealing surfaces
- Packoff seal damage resulting from high temperatures
- Loss of seal contact pressure during thermal cycling
- Incompatibility between the seal and the fluids
- Solids contamination on the sealing surface
- Vibration

Consideration of leak paths through the casing-cement mode of failure yielded five principal causes. The task group deferred ranking these because of their collective judgments that this was outside their area of expertise. Therefore, additional information was obtained from the API Subcommittee on Well Cements (SC10). Based on that input, the following causes of failure are listed in decreasing order of frequency of occurrence.

- Frac-Pac operations
- Expansion and contraction due to thermal cycling
- Micro-annulus cracks
- Poor formation/cement bonding
- Gas in the cement

Based on the MMS data discussed in section 3.2, a standard Weibull analysis was run to determine the shape of the distribution curve. This defined the statistical probability of the well being affected by casing pressure as a function of the age of the well. The result of the Weibull analysis is shown in Figure 5 and the cumulative distribution function curve is shown in Figure 6. The Weibull analysis yielded a characteristic life of 34.42 years and a shape parameter (beta) of 1.707. Based on the Weibull analysis, casing pressure is expected to affect 32.7% of the wells within the first 20 years of life. However, this does not differentiate on the magnitude of casing pressure or the specific annulus experiencing the pressure. The shape parameter of 1.707 indicates that the wells with casing pressure exhibit more of a “wear out” phenomenon than a purely random failure ($\beta = 1$) or an infantile failure (defective equipment failure $\beta < 1$). It also indicates that the failures resulting in casing pressure come from mixed modes, i.e., sweet vs. sour wells; production rates; pressure; temperature; design configurations; etc. Since subsea wells have design characteristics similar to those in the population analyzed, the shape parameter of the failure distribution curve is expected to be similar; however, the characteristic life may be different.

6 Results

6.1 Risk Analysis

The relative frequency of occurrence values for each of the failure causes was advanced to successively higher levels in the fault trees using Boolean logic for the “And” gates and “Or” gates to obtain a top level value. This value was then normalized to the value obtained for the current subsea wellhead design with no penetrations (rather than using the absolute frequency of occurrence value) and used to compare one fault tree to another. Relative frequency values were used in the analysis since actual field performance data does not exist. Based upon this analysis, the risk of not being able to maintain a pressure barrier with one wellhead housing penetration is about 2.5 times that of having no penetrations. The risk in having two penetrations is about 2.7 times that of having no penetrations. These results are summarized in the table below. This analysis is based upon a 2-inch penetration and 2-inch valves attached to the wellhead. Details of these calculations are included in Appendices B, C, and D.

Event	No Penetration	2-inch B-annulus Penetration	2-inch B & C-annulus Penetrations
Failure of system to maintain a pressure barrier	10.1 % (1.00)	25.3 % (2.50)	27.3 % (2.69)

Another analysis was run to compare ½-inch penetrations with the 2-inch penetrations. Evaluation by the task group suggested that some root cause failures were higher with the ½-inch penetrations. Therefore, an analysis was done to evaluate the overall system reliability. Details of the analysis are contained in Appendix E and summarized in the following table. In this case, the risk associated with a single ½-inch penetration is approximately 3.6 times that of no penetrations and increases to over 3.7 times with two penetrations.

Event	No Penetration	1/2-inch B-annulus Penetration	1/2-inch B & C-annulus Penetration
Failure of system to maintain a pressure barrier	10.1 % (1.00)	36.3 % (3.59)	37.9 % (3.75)

6.2 Sensitivity Study

An analysis was run to evaluate the sensitivity of the 1-to-10 occurrence index values used for each of the root cause failures for the casing pipe / connections (Table 5), casing hanger packoff (Table 6), and the casing cement (Table 7). For the upper limit analysis, each of the risk index values in these tables was reduced by a value of one. In some cases this reduced the frequency of occurrence for that root cause to zero indicating no chance of occurrence. The risk indices for the 2-inch penetrations remained unchanged from the original analysis. The result of this analysis is shown in the following summary table with the details included in Appendix F.

Event	No Penetration	2-inch B-annulus Penetration	2-inch B & C-annulus Penetration
Failure of system to maintain a pressure barrier	3.5 % (1.00)	18.9 % (5.45)	19.7 % (5.66)

A second sensitivity analysis was run to evaluate a lower limit state where the risk index values were increased by two for the casing pipe / connections (Table 5), casing hanger packoff (Table 6), and the casing cement (Table 7). Again, the indices for the 2-inch penetrations remained

unchanged from the original analysis. The result of this analysis is shown in the following summary table with the details included in Appendix G.

Event	No Penetration	2-inch B-annulus Penetration	2-inch B & C-annulus Penetration
Failure of system to maintain a pressure barrier	37.4 % (1.00)	48.7 % (1.30)	53.9 % (1.44)

As seen from this sensitivity analysis, the overall system risk certainly changes as the risk for each of the root causes changes. This is as one would expect. However, the risk associated with adding two penetrations to the wellhead housing ranged from a low of 1.44 to a high of 5.66 based on the sensitivity analysis and a mean value of 2.69 times the risk associated with no penetrations.

6.3 Benefits Analysis

The benefits associated with having penetrations in the wellhead are not clear and quantifiable. The consensus of the task group during the workshop was that a penetration in the wellhead housing would permit the monitoring of pressure in the outer annuli casing strings, but would not be a viable remediation avenue. Wellhead penetrations were viewed as an additional diagnostic tool to be used in conjunction with the “A” annulus monitoring, already in use, to determine the source and severity of casing pressure events.

Remediation techniques were also discussed during the workshop. The only two likely remediation techniques, based upon today’s technology, are 1) plug and abandon the well, or 2) re-enter the casing and repair the well.

One of the main concerns associated with having the ability to monitor the outer annuli pressure is the validity of the pressure reading. The consensus of the task group was that at some point during the life of the well a penetration will get plugged and therefore give a false pressure reading – most likely during drilling and cementing phases of the well.

Two benefits of being able to monitor the pressure in the outer annuli casing strings have been identified:

- **Use of outer annuli penetrations for a more complete diagnostic tool.**

One would know (if plugging does not occur) the magnitude of pressure and pressure changes in each of the outer annuli. This adds to the knowledge of the collapse margin on the production casing as the “A” annulus pressure is being bled off. However, because of the plugging concern, the validity of the reading would always be questioned. With penetrations, more detailed evaluations could be performed, such as:

- Determining if the pressure is the result of thermal changes or involves communication with a pressure source and

- Monitoring the pressure in adjacent annuli as the pressure in a particular annulus is being increased or decreased.
- **Having the ability to bleed off pressure from a particular annulus.**
This is a benefit only if the port does not become plugged.

These benefits, when taken with remediation techniques to bleed off the annulus pressure and the ability to perform preventive maintenance, could reduce the risks associated with pressure penetrating the secondary barrier. This would act to reduce the overall system risk from the current risk associated with having penetrations. This new risk could then be compared to the risk associated with no penetrations.

6.4 Global Risk/Benefits Assessment

So far, the discussion of risks and benefits has focused on a single subsea well. But, there are global risk/benefit tradeoffs if penetrations in the outer annuli are required.

Assume for this discussion that 1000 subsea wells were installed with side penetrations. Further assume (using the same data on which this report is based) that 4.5% of the wells exhibit casing pressure in the outer annuli (“B”, “C”, and “D”) above 20% of MIYP. In this case, the benefits of doing better diagnostic testing is available for the 45 wells, but the risks of having side penetrations will affect the other 955 wells without having the corresponding benefits as a tradeoff.

Further, the benefits of being able to perform more comprehensive diagnostics on the 45 wells and thus reducing the risk of maintaining a pressure barrier must be contrasted with the increased risk in 955 wells of immediate pressure loss in the event (with penetrations) of leakage in the penetrations. In the latter case on penetrations, there is no secondary barrier to prevent catastrophic failure from penetration leakage.

7 Conclusions

An evaluation of the risks and benefits of penetrations in subsea wellheads below the BOP stack was completed. A fault tree analysis methodology was used to evaluate the ability of a wellhead system to maintain a pressure barrier, and the existing wellhead system without penetrations was compared to a system with penetrations. A qualitative risk analysis was performed based on a risk index for each failure mode as assigned by a committee of experts from the API Spec 17D/ISO 13628-4 task group. Based on this analysis, the risk of not being able to maintain a pressure barrier with one wellhead housing penetration is about 2.5 times that of the existing industry-standard design with no penetrations. The risk with having two penetrations is about 2.7 times that of having no penetrations. These results are summarized in the table below. This analysis is based upon a 2-inch penetration and 2-inch valves attached to the wellhead. The experts agreed that the ideal penetration size was 2-inch. However, for some applications designing this size access into subsea wellheads would be prohibitive over a smaller access size. However, the risk associated with having a single ½-inch penetration is about 3.6 times that of having no penetrations and increases to over 3.7 times when you have two penetrations.

On the other hand, the benefits of having penetrations are seen as an additional diagnostic tool to compliment the currently available “A” annulus monitoring. The ability to use a side penetration as a remediation port is questionable. The concern being that at some point the penetration will likely become plugged and present a false reading.

Based upon this analysis, weighing both risks and benefits of adding penetrations to the wellhead housing in subsea wells, it is believed that the additional risks associated with adding penetrations far outweigh the apparent diagnostic benefits achieved from those penetrations. It would be more beneficial to place emphasis on design and operational issues to minimize the likelihood of casing pressure occurring than to address remediation after casing pressure has occurred. Hence, emphasis should be placed on well construction and operational practices that help prevent casing pressure instead of mechanical remediation.

Relative Risk Analysis Summary				
Event	Configuration	No Penetrations	B-annulus Penetration	B & C-annulus Penetrations
Failure of system to maintain a pressure barrier	2-inch penetrations	1.00	2.50	2.69
Failure of system to maintain a pressure barrier	½-inch penetrations	1.00	3.59	3.75

8 Recommendations

Based upon this risk analysis, the risks associated with adding penetrations to the wellhead housing far exceed the benefits from the knowledge obtained with the penetrations. Therefore, it is recommended that API/ISO standards continue to prohibit penetrations in subsea wellheads.

If future technology results in more and improved remediation techniques, then the risk analysis should be reviewed at that time.

9 References

1. Verret, A.J., *Addressing the Issue of Casing Pressure Risks*, Offshore Magazine, page 116, July 2002.

2. Bourgoyne, A.T., Jr., Scott, S.L., and Regg, J.B., Sustained Casing Pressure in Offshore Producing Wells, Offshore Technology Conference, OTC 11029, May 1999.
3. Bourgoyne, A.T., Jr., Scott, S.L., and Manowski, W., A Review of Sustained Casing Pressure (SCP) Occurring on the OCS, Final Report to the Mineral Management Services, 1999.
4. Riggs, K.R., et al, Best Practices for Prevention and Management of Sustained Casing Pressure, A Joint Industry Project by H.O. Mohr Research and Engineering, October 2001.
5. MIL-STD-1629A, "Military Standard Procedures for Performing a Failure Mode, Effects and Criticality Analysis," dated 24 November 1980.
6. Stamatis, D.H., "Failure Mode and Effect Analysis, FMEA from Theory to Execution," ASQ Quality Press, 1995.
7. O'Connor, P.D.T, "Practical Reliability Engineering," Fourth Edition, 2001.
8. ASME, "Fault Tree Handbook" included on CD ROM in "Risk-Based Methods for Equipment Life Management: An Application Handbook," CRTD Vol. 41, ASME Press, 2003.
9. Abernethy, Dr. Robert B., "The New Weibull Handbook," Fourth Edition, published by Dr. Robert B. Abernethy, ISBN 0-9653062-1-6.

10 Tables

Table 1: GOM Shelf Wells with Casing Pressure

% MIYP	Wells with Casing Pressure	Casing String Affected				
		Prod Casing	Intmd Casing	Surface Casing	Conductor Casing	Total Strings Affected
> 0%	6,692	4,783	1,655	2,660	1055	10,153
> 20%	1,446	906	261	347	95	1,609
> 30%	482	229	91	130	55	505
> 40%	174	78	30	51	22	181
> 50%	80	37	12	22	9	80
> 60%	35	14	7	10	4	35
> 0%	43.1%	30.8%	10.7%	17.1%	6.8%	65.4%
> 20%	9.3%	5.8%	1.7%	2.2%	0.6%	10.4%
> 30%	3.1%	1.5%	0.6%	0.8%	0.4%	3.3%
> 40%	1.1%	0.5%	0.2%	0.3%	0.1%	1.2%
> 50%	0.5%	0.2%	0.1%	0.1%	0.1%	0.5%
> 60%	0.2%	0.1%	0.0%	0.1%	0.0%	0.2%
15,516		Total Number of Wells				

Table 2: Relative Failure Occurrence Index

Relative Failure Occurrence Index		
Index	Description	Relative Frequency of Occurrence (CDF)
10	Almost certain	11.34%
9	Very high	9.56%
8	High	7.89%
7	Moderately high	6.34%
6	Medium	4.91%
5	Occasional	3.62%
4	Slight	2.49%
3	Very slight	1.53%
2	Rare	0.77%
1	Unlikely	0.24%

Table 3: Relative Failure Occurrence Index of 2" Penetrations

Risk Index	Relative Failure Occurrence	Failure Mode
	15.62%	Failure of B or C Annulus Penetration, 2"
	0.0869	False Pressure Reading
6	0.0491	Pressure sensor inoperable
4	0.0249	Pressure sensor lost calibration
2	0.0077	Lost umbilical signal
2	0.0077	Pressure port plugged
	0.0047	Leakage from connections
1	0.0024	Leakage due to vibration
1	0.0024	Leakage due to corrosion
	0.0100	Failure of manual valve to function
2	0.0077	Valve malfunctions closed
1	0.0024	Valve malfunctions open
	0.0000	Wellhead housing integrity
1	0.0024	Higher bending moments due to taller housing
1	0.0024	Stress concentrations due to penetrations
	0.0545	Damage to valves from external forces
4	0.0249	Running / Installation damage
3	0.0153	Damage from ROV contact
2	0.0077	Damage when landing tree
2	0.0077	Dropped equipment

Table 4: Relative Failure Occurrence Index of ½" Penetrations

Risk Index	Relative Failure Occurrence	Failure Mode
	27.08%	Failure of B or C Annulus Penetration, 1/2"
	0.1679	False Pressure Reading
6	0.0491	Pressure sensor inoperable
4	0.0249	Pressure sensor lost calibration
2	0.0077	Lost umbilical signal
9	0.0956	Pressure port plugged
	0.0385	Leakage from connections
5	0.0362	Leakage due to vibration
1	0.0024	Leakage due to corrosion
	0.0100	Failure of manual valve to function
2	0.0077	Valve malfunctions closed
1	0.0024	Valve malfunctions open
	0.0000	Wellhead housing integrity
1	0.0024	Higher bending moments due to taller housing
1	0.0024	Stress concentrations due to penetrations
	0.0545	Damage to valves from external forces
4	0.0249	Running / Installation damage
3	0.0153	Damage from ROV contact
2	0.0077	Damage when landing tree
2	0.0077	Dropped equipment

Table 5: Relative Failure Occurrence Index of Casing Pipe / Connections

Risk Index	Relative Failure Occurrence	Failure Mode
	2.69%	Failure of Production Casing Pipe / Connections to Maintain a Pressure Barrier
2	0.0077	Corrosion
1	0.0024	Thermal cycling
1	0.0024	Damaged threads
2	0.0077	Damaged sealing surface
1	0.0024	Wear
1	0.0024	Bad / wrong thread compound
1	0.0024	Improper makeup of connection
	3.95%	Failure of Intermediate Casing Pipe / Connections to Maintain a Pressure Barrier
2	0.0077	Corrosion
1	0.0024	Thermal cycling
1	0.0024	Damaged threads
2	0.0077	Damaged sealing surface
3	0.0153	Wear
1	0.0024	Bad / wrong thread compound
1	0.0024	Improper makeup of connection
	5.99%	Failure of Surface Casing Pipe / Connections to Maintain a Pressure Barrier
2	0.0077	Corrosion
1	0.0024	Thermal cycling
1	0.0024	Damaged threads
2	0.0077	Damaged sealing surface
5	0.0362	Wear
1	0.0024	Bad / wrong thread compound
1	0.0024	Improper makeup of connection

Table 6: Relative Failure Occurrence Index of Casing Hanger Packoff

Risk Index	Relative Failure Occurrence	Failure Mode
	4.91%	Failure of Casing Hanger Packoff to Maintain a Pressure Barrier
3	0.0153	Damaged sealing surface
2	0.0077	Thermal cycling / axial movement
2	0.0077	Installation anomalies
2	0.0077	Corrosion
1	0.0024	Seal damage from high temperature
1	0.0024	Loss of seal contact pressure
1	0.0024	Seal / fluid incompatibility
1	0.0024	Solids contamination
1	0.0024	Vibration

Table 7: Relative Failure Occurrence Index of Casing Cement

Risk Index	Relative Failure Occurrence	Failure Mode
	5.98%	Failure of Production Casing Cement to Maintain a Pressure Barrier
3	0.0153	Micro-annulus cracks
3	0.0153	Frac-Pac operations
3	0.0153	Expansion and contraction
2	0.0077	Poor formation / cement bond
2	0.0077	Gas in cement
	6.70%	Failure of Intermediate Casing Cement to Maintain a Pressure Barrier
3	0.0153	Micro-annulus cracks
3	0.0153	Frac-Pac operations
3	0.0153	Expansion and contraction
3	0.0153	Poor formation / cement bond
2	0.0077	Gas in cement
	1.17%	Failure of Surface / Conductor Casing Cement to Maintain a Pressure Barrier
1	0.0024	Micro-annulus cracks
1	0.0024	Frac-Pac operations
1	0.0024	Expansion and contraction
1	0.0024	Poor formation / cement bond
1	0.0024	Gas in cement

11 Figures




Figure 1: Wells with Casing Pressure by Pipe Strength




Figure 2: Wells with Casing Pressure by Pipe Strength




Figure 3: Wells with Casing Pressure by Age




Figure 4: Wells with Casing Pressure by Age





Figure 5: Weibull Analysis of Wells with Casing Pressure by Age

**Figure 6: CDF of Wells with Casing Pressure**





Figure 7: Typical Subsea Wellhead System


12 Appendices

12.1 Appendix A – Potential Leak Paths


PRESSURE MIGRATES FROM
COND PIPE CEMENT



		IR		INITIAL RELEASE		DATE		BY		CHK'D	
		DESCRIPTION		DATE		BY		CHK'D			
ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES		DATE		BY		CHK'D		SCALE	
WATERMARK/STRENGTH		111986-05		DATE		BY		CHK'D		SCALE	


		TOI EXAGGERS: UNLESS OTHERWISE SPECIFIED	
IR REQ.		INITIAL RELEASE DISSEMINATION	
DESCRIPTION ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		DATE BY CHK'D. This drawing is the property of Mahr Engineering Institute. It is to be used only with express permission from Mahr.	
MATERIAL / FINISHING 316 SS / 304 SS		DATE BY CHK'D. 111986-05	

PRESSURE MIGRATES OUTWARD
FROM INTMD CSG CEMENT




		TOLERANCES: UNLESS OTHERWISE SPECIFIED FRACTIONS: 1/16" DECIMALS: .001" ANGLES: .01° SURFACE FINISH: 125 RMS UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
IR	INITIAL RELEASE	DATE	BY
DESCRIPTION	DESCRIPTION	DATE	BY
ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		This drawing is the property of MAHR Engineering Inc. It is to be used only with express written permission from MAHR.	DATE 8/19/2003 BY SCALC REV. IR
WORKING / REVISION		DWG. NO. 111986-05	


PRESSURE MIGRATES INWARD
FROM INTMD CSG CEMENT




		TOLERANCES: UNLESS OTHERWISE SPECIFIED FRACTIONS: 1/16" INCHES: 1/32" DECIMALS: 0.015"	
		DIMENSIONS: 1/16" INCHES: 1/32" DECIMALS: 0.015"	
IR ECU DESCRIPTION INITIAL RELEASE DATE SY DWG. NO.	ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D MATERIAL/SPECIFICATION DWG. NO. 111986-05		
This drawing is to be used only with the express approval of the Engineering Division. It is to be used only with the express approval of the Engineering Division.			
DATE: 8/19/2003 SCALE: 1/4" = 1'-0" REV: 1 IR			



		TOLERANCES: UNLESS OTHERWISE SPECIFIED IN: ± 0.015 THROAT: ± 0.010 HOLE: ± 0.010 BRASS: ± 0.010 STEEL: ± 0.010 CONCENTRICITY: ± 0.010 SURFACES: ± 0.010	
		ILLUMINATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D	
REV.	DATE	BY	CHK'D.
DESCRIPTION		DATE	
This drawing is the property of MAHR Engineering Inc. and is not to be reproduced or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without permission in writing from MAHR.		DATE 6/19/2003 SCALE 1:1 REV. IR	
WORKMAN/ATTENTION 111986-05		DATE 11/1986-05	




		TOLERANCES: UNLESS OTHERWISE SPECIFIED IN. = 0.015 FRACTIONS = 1/16"	
		DIMENSIONS IN PARENTHESIS ARE DIMENSIONS FOR THE WELL HEAD DIMENSIONS FOR THE WELL HEAD DIMENSIONS FOR THE WELL HEAD	
IR INITIAL RELEASE		DATE: BY: CHECKED: THIS DRAWING IS THE PROPERTY OF MAHR ENGINEERING INC. IT IS TO BE KEPT IN THE MAHR ARCHIVE FOR THE MAHR ARCHIVE FOR THE MAHR ARCHIVE FOR THE MAHR	
ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		DATE: BY: CHECKED: THIS DRAWING IS THE PROPERTY OF MAHR ENGINEERING INC. IT IS TO BE KEPT IN THE MAHR ARCHIVE FOR THE MAHR ARCHIVE FOR THE MAHR ARCHIVE FOR THE MAHR	
WORKING/PRODUCTION		DATE: BY: CHECKED: THIS DRAWING IS THE PROPERTY OF MAHR ENGINEERING INC. IT IS TO BE KEPT IN THE MAHR ARCHIVE FOR THE MAHR ARCHIVE FOR THE MAHR ARCHIVE FOR THE MAHR	
111986-05		DATE: BY: CHECKED: THIS DRAWING IS THE PROPERTY OF MAHR ENGINEERING INC. IT IS TO BE KEPT IN THE MAHR ARCHIVE FOR THE MAHR ARCHIVE FOR THE MAHR ARCHIVE FOR THE MAHR	




		TOLERANCES: UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES DECIMALS: 1/16" FRACTIONS: 1/32" ANGLES: 1/2° SURFACE FINISH: 125 RMS UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
		IR	
DESCRIPTION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		INITIAL RELEASE	
DATE 8/19/2003		SCALE 1" = 10'	
REV. 1		CHG. NO. 111986-05	

[illegible]




		IR		INITIAL RELEASE	
TOLERANCES: UNLESS OTHERWISE SPECIFIED 1/16" ± 0.015" 1/8" ± 0.010" 1/4" ± 0.010" 3/8" ± 0.010" 1/2" ± 0.010" 3/4" ± 0.010" 1" ± 0.010" 1 1/2" ± 0.010" 2" ± 0.010" 3" ± 0.010" 4" ± 0.010" 6" ± 0.010" 8" ± 0.010" 10" ± 0.010" 12" ± 0.010" 14" ± 0.010" 16" ± 0.010" 18" ± 0.010" 20" ± 0.010" 24" ± 0.010" 30" ± 0.010" 36" ± 0.010" 42" ± 0.010" 48" ± 0.010" 54" ± 0.010" 60" ± 0.010" 66" ± 0.010" 72" ± 0.010" 78" ± 0.010" 84" ± 0.010" 90" ± 0.010" 96" ± 0.010" 102" ± 0.010" 108" ± 0.010" 114" ± 0.010" 120" ± 0.010" 126" ± 0.010" 132" ± 0.010" 138" ± 0.010" 144" ± 0.010" 150" ± 0.010" 156" ± 0.010" 162" ± 0.010" 168" ± 0.010" 174" ± 0.010" 180" ± 0.010" 186" ± 0.010" 192" ± 0.010" 198" ± 0.010" 204" ± 0.010" 210" ± 0.010" 216" ± 0.010" 222" ± 0.010" 228" ± 0.010" 234" ± 0.010" 240" ± 0.010" 246" ± 0.010" 252" ± 0.010" 258" ± 0.010" 264" ± 0.010" 270" ± 0.010" 276" ± 0.010" 282" ± 0.010" 288" ± 0.010" 294" ± 0.010" 300" ± 0.010" 306" ± 0.010" 312" ± 0.010" 318" ± 0.010" 324" ± 0.010" 330" ± 0.010" 336" ± 0.010" 342" ± 0.010" 348" ± 0.010" 354" ± 0.010" 360" ± 0.010" 366" ± 0.010" 372" ± 0.010" 378" ± 0.010" 384" ± 0.010" 390" ± 0.010" 396" ± 0.010" 402" ± 0.010" 408" ± 0.010" 414" ± 0.010" 420" ± 0.010" 426" ± 0.010" 432" ± 0.010" 438" ± 0.010" 444" ± 0.010" 450" ± 0.010" 456" ± 0.010" 462" ± 0.010" 468" ± 0.010" 474" ± 0.010" 480" ± 0.010" 486" ± 0.010" 492" ± 0.010" 498" ± 0.010" 504" ± 0.010" 510" ± 0.010" 516" ± 0.010" 522" ± 0.010" 528" ± 0.010" 534" ± 0.010" 540" ± 0.010" 546" ± 0.010" 552" ± 0.010" 558" ± 0.010" 564" ± 0.010" 570" ± 0.010" 576" ± 0.010" 582" ± 0.010" 588" ± 0.010" 594" ± 0.010" 600" ± 0.010" 606" ± 0.010" 612" ± 0.010" 618" ± 0.010" 624" ± 0.010" 630" ± 0.010" 636" ± 0.010" 642" ± 0.010" 648" ± 0.010" 654" ± 0.010" 660" ± 0.010" 666" ± 0.010" 672" ± 0.010" 678" ± 0.010" 684" ± 0.010" 690" ± 0.010" 696" ± 0.010" 702" ± 0.010" 708" ± 0.010" 714" ± 0.010" 720" ± 0.010" 726" ± 0.010" 732" ± 0.010" 738" ± 0.010" 744" ± 0.010" 750" ± 0.010" 756" ± 0.010" 762" ± 0.010" 768" ± 0.010" 774" ± 0.010" 780" ± 0.010" 786" ± 0.010" 792" ± 0.010" 798" ± 0.010" 804" ± 0.010" 810" ± 0.010" 816" ± 0.010" 822" ± 0.010" 828" ± 0.010" 834" ± 0.010" 840" ± 0.010" 846" ± 0.010" 852" ± 0.010" 858" ± 0.010" 864" ± 0.010" 870" ± 0.010" 876" ± 0.010" 882" ± 0.010" 888" ± 0.010" 894" ± 0.010" 900" ± 0.010" 906" ± 0.010" 912" ± 0.010" 918" ± 0.010" 924" ± 0.010" 930" ± 0.010" 936" ± 0.010" 942" ± 0.010" 948" ± 0.010" 954" ± 0.010" 960" ± 0.010" 966" ± 0.010" 972" ± 0.010" 978" ± 0.010" 984" ± 0.010" 990" ± 0.010" 996" ± 0.010" 1000" ± 0.010"		ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		DATE: 8/19/2003 SCALE: 1" = 100' REV: 1 IR	
111986-05		111986-05			




		IR		INITIAL RELEASE	
		DESCRIPTION		DATE	
ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		DATE		BY	
DATE		DATE		DATE	
SCALE		SCALE		SCALE	
REV.		REV.		REV.	
IR		IR		IR	


TOLERANCES:
 UNLESS OTHERWISE SPECIFIED
 1/16" ± 0.005
 1/32" ± 0.005
 1/64" ± 0.005
 1/8" ± 0.005
 1/4" ± 0.005
 3/8" ± 0.005
 1/2" ± 0.005
 3/4" ± 0.005
 1" ± 0.005
 1 1/2" ± 0.005
 2" ± 0.005
 3" ± 0.005
 4" ± 0.005
 6" ± 0.005
 8" ± 0.005
 10" ± 0.005
 12" ± 0.005
 14" ± 0.005
 16" ± 0.005
 18" ± 0.005
 20" ± 0.005
 22" ± 0.005
 24" ± 0.005
 26" ± 0.005
 28" ± 0.005
 30" ± 0.005
 32" ± 0.005
 34" ± 0.005
 36" ± 0.005
 38" ± 0.005
 40" ± 0.005
 42" ± 0.005
 44" ± 0.005
 46" ± 0.005
 48" ± 0.005
 50" ± 0.005
 52" ± 0.005
 54" ± 0.005
 56" ± 0.005
 58" ± 0.005
 60" ± 0.005
 62" ± 0.005
 64" ± 0.005
 66" ± 0.005
 68" ± 0.005
 70" ± 0.005
 72" ± 0.005
 74" ± 0.005
 76" ± 0.005
 78" ± 0.005
 80" ± 0.005
 82" ± 0.005
 84" ± 0.005
 86" ± 0.005
 88" ± 0.005
 90" ± 0.005
 92" ± 0.005
 94" ± 0.005
 96" ± 0.005
 98" ± 0.005
 100" ± 0.005
 102" ± 0.005
 104" ± 0.005
 106" ± 0.005
 108" ± 0.005
 110" ± 0.005
 112" ± 0.005
 114" ± 0.005
 116" ± 0.005
 118" ± 0.005
 120" ± 0.005
 122" ± 0.005
 124" ± 0.005
 126" ± 0.005
 128" ± 0.005
 130" ± 0.005
 132" ± 0.005
 134" ± 0.005
 136" ± 0.005
 138" ± 0.005
 140" ± 0.005
 142" ± 0.005
 144" ± 0.005
 146" ± 0.005
 148" ± 0.005
 150" ± 0.005
 152" ± 0.005
 154" ± 0.005
 156" ± 0.005
 158" ± 0.005
 160" ± 0.005
 162" ± 0.005
 164" ± 0.005
 166" ± 0.005
 168" ± 0.005
 170" ± 0.005
 172" ± 0.005
 174" ± 0.005
 176" ± 0.005
 178" ± 0.005
 180" ± 0.005
 182" ± 0.005
 184" ± 0.005
 186" ± 0.005
 188" ± 0.005
 190" ± 0.005
 192" ± 0.005
 194" ± 0.005
 196" ± 0.005
 198" ± 0.005
 200" ± 0.005
 202" ± 0.005
 204" ± 0.005
 206" ± 0.005
 208" ± 0.005
 210" ± 0.005
 212" ± 0.005
 214" ± 0.005
 216" ± 0.005
 218" ± 0.005
 220" ± 0.005
 222" ± 0.005
 224" ± 0.005
 226" ± 0.005
 228" ± 0.005
 230" ± 0.005
 232" ± 0.005
 234" ± 0.005
 236" ± 0.005
 238" ± 0.005
 240" ± 0.005
 242" ± 0.005
 244" ± 0.005
 246" ± 0.005
 248" ± 0.005
 250" ± 0.005
 252" ± 0.005
 254" ± 0.005
 256" ± 0.005
 258" ± 0.005
 260" ± 0.005
 262" ± 0.005
 264" ± 0.005
 266" ± 0.005
 268" ± 0.005
 270" ± 0.005
 272" ± 0.005
 274" ± 0.005
 276" ± 0.005
 278" ± 0.005
 280" ± 0.005
 282" ± 0.005
 284" ± 0.005
 286" ± 0.005
 288" ± 0.005
 290" ± 0.005
 292" ± 0.005
 294" ± 0.005
 296" ± 0.005
 298" ± 0.005
 300" ± 0.005
 302" ± 0.005
 304" ± 0.005
 306" ± 0.005
 308" ± 0.005
 310" ± 0.005
 312" ± 0.005
 314" ± 0.005
 316" ± 0.005
 318" ± 0.005
 320" ± 0.005
 322" ± 0.005
 324" ± 0.005
 326" ± 0.005
 328" ± 0.005
 330" ± 0.005
 332" ± 0.005
 334" ± 0.005
 336" ± 0.005
 338" ± 0.005
 340" ± 0.005
 342" ± 0.005
 344" ± 0.005
 346" ± 0.005
 348" ± 0.005
 350" ± 0.005
 352" ± 0.005
 354" ± 0.005
 356" ± 0.005
 358" ± 0.005
 360" ± 0.005
 362" ± 0.005
 364" ± 0.005
 366" ± 0.005
 368" ± 0.005
 370" ± 0.005
 372" ± 0.005
 374" ± 0.005
 376" ± 0.005
 378" ± 0.005
 380" ± 0.005
 382" ± 0.005
 384" ± 0.005
 386" ± 0.005
 388" ± 0.005
 390" ± 0.005
 392" ± 0.005
 394" ± 0.005
 396" ± 0.005
 398" ± 0.005
 400" ± 0.005
 402" ± 0.005
 404" ± 0.005
 406" ± 0.005
 408" ± 0.005
 410" ± 0.005
 412" ± 0.005
 414" ± 0.005
 416" ± 0.005
 418" ± 0.005
 420" ± 0.005
 422" ± 0.005
 424" ± 0.005
 426" ± 0.005
 428" ± 0.005
 430" ± 0.005
 432" ± 0.005
 434" ± 0.005
 436" ± 0.005
 438" ± 0.005
 440" ± 0.005
 442" ± 0.005
 444" ± 0.005
 446" ± 0.005
 448" ± 0.005
 450" ± 0.005
 452" ± 0.005
 454" ± 0.005
 456" ± 0.005
 458" ± 0.005
 460" ± 0.005
 462" ± 0.005
 464" ± 0.005
 466" ± 0.005
 468" ± 0.005
 470" ± 0.005
 472" ± 0.005
 474" ± 0.005
 476" ± 0.005
 478" ± 0.005
 480" ± 0.005
 482" ± 0.005
 484" ± 0.005
 486" ± 0.005
 488" ± 0.005
 490" ± 0.005
 492" ± 0.005
 494" ± 0.005
 496" ± 0.005
 498" ± 0.005
 500" ± 0.005
 502" ± 0.005
 504" ± 0.005
 506" ± 0.005
 508" ± 0.005
 510" ± 0.005
 512" ± 0.005
 514" ± 0.005
 516" ± 0.005
 518" ± 0.005
 520" ± 0.005
 522" ± 0.005
 524" ± 0.005
 526" ± 0.005
 528" ± 0.005
 530" ± 0.005
 532" ± 0.005
 534" ± 0.005
 536" ± 0.005
 538" ± 0.005
 540" ± 0.005
 542" ± 0.005
 544" ± 0.005
 546" ± 0.005
 548" ± 0.005
 550" ± 0.005
 552" ± 0.005
 554" ± 0.005
 556" ± 0.005
 558" ± 0.005
 560" ± 0.005
 562" ± 0.005
 564" ± 0.005
 566" ± 0.005
 568" ± 0.005
 570" ± 0.005
 572" ± 0.005
 574" ± 0.005
 576" ± 0.005
 578" ± 0.005
 580" ± 0.005
 582" ± 0.005
 584" ± 0.005
 586" ± 0.005
 588" ± 0.005
 590" ± 0.005
 592" ± 0.005
 594" ± 0.005
 596" ± 0.005
 598" ± 0.005
 600" ± 0.005
 602" ± 0.005
 604" ± 0.005
 606" ± 0.005
 608" ± 0.005
 610" ± 0.005
 612" ± 0.005
 614" ± 0.005
 616" ± 0.005
 618" ± 0.005
 620" ± 0.005
 622" ± 0.005
 624" ± 0.005
 626" ± 0.005
 628" ± 0.005
 630" ± 0.005
 632" ± 0.005
 634" ± 0.005
 636" ± 0.005
 638" ± 0.005
 640" ± 0.005
 642" ± 0.005
 644" ± 0.005
 646" ± 0.005
 648" ± 0.005
 650" ± 0.005
 652" ± 0.005
 654" ± 0.005
 656" ± 0.005
 658" ± 0.005
 660" ± 0.005
 662" ± 0.005
 664" ± 0.005
 666" ± 0.005
 668" ± 0.005
 670" ± 0.005
 672" ± 0.005
 674" ± 0.005
 676" ± 0.005
 678" ± 0.005
 680" ± 0.005
 682" ± 0.005
 684" ± 0.005
 686" ± 0.005
 688" ± 0.005
 690" ± 0.005
 692" ± 0.005
 694" ± 0.005
 696" ± 0.005
 698" ± 0.005
 700" ± 0.005
 702" ± 0.005
 704" ± 0.005
 706" ± 0.005
 708" ± 0.005
 710" ± 0.005
 712" ± 0.005
 714" ± 0.005
 716" ± 0.005
 718" ± 0.005
 720" ± 0.005
 722" ± 0.005
 724" ± 0.005
 726" ± 0.005
 728" ± 0.005
 730" ± 0.005
 732" ± 0.005
 734" ± 0.005
 736" ± 0.005
 738" ± 0.005
 740" ± 0.005
 742" ± 0.005
 744" ± 0.005
 746" ± 0.005
 748" ± 0.005
 750" ± 0.005
 752" ± 0.005
 754" ± 0.005
 756" ± 0.005
 758" ± 0.005
 760" ± 0.005
 762" ± 0.005
 764" ± 0.005
 766" ± 0.005
 768" ± 0.005
 770" ± 0.005
 772" ± 0.005
 774" ± 0.005
 776" ± 0.005
 778" ± 0.005
 780" ± 0.005
 782" ± 0.005
 784" ± 0.005
 786" ± 0.005
 788" ± 0.005
 790" ± 0.005
 792" ± 0.005
 794" ± 0.005
 796" ± 0.005
 798" ± 0.005
 800" ± 0.005
 802" ± 0.005
 804" ± 0.005
 806" ± 0.005
 808" ± 0.005
 810" ± 0.005
 812" ± 0.005
 814" ± 0.005
 816" ± 0.005
 818" ± 0.005
 820" ± 0.005
 822" ± 0.005
 824" ± 0.005
 826" ± 0.005
 828" ± 0.005
 830" ± 0.005
 832" ± 0.005
 834" ± 0.005
 836" ± 0.005
 838" ± 0.005
 840" ± 0.005
 842" ± 0.005
 844" ± 0.005
 846" ± 0.005
 848" ± 0.005
 850" ± 0.005
 852" ± 0.005
 854" ± 0.005
 856" ± 0.005
 858" ± 0.005
 860" ± 0.005
 862" ± 0.005
 864" ± 0.005
 866" ± 0.005
 868" ± 0.005
 870" ± 0.005
 872" ± 0.005
 874" ± 0.005
 876" ± 0.005
 878" ± 0.005
 880" ± 0.005
 882" ± 0.005
 884" ± 0.005
 886" ± 0.005
 888" ± 0.005
 890" ± 0.005
 892" ± 0.005
 894" ± 0.005
 896" ± 0.005
 898" ± 0.005
 900" ± 0.005
 902" ± 0.005
 904" ± 0.005
 906" ± 0.005
 908" ± 0.005
 910" ± 0.005
 912" ± 0.005
 914" ± 0.005
 916" ± 0.005
 918" ± 0.005
 920" ± 0.005
 922" ± 0.005
 924" ± 0.005
 926" ± 0.005
 928" ± 0.005
 930" ± 0.005
 932" ± 0.005
 934" ± 0.005
 936" ± 0.005
 938" ± 0.005
 940" ± 0.005
 942" ± 0.005
 944" ± 0.005
 946" ± 0.005
 948" ± 0.005
 950" ± 0.005
 952" ± 0.005
 954" ± 0.005
 956" ± 0.005
 958" ± 0.005
 960" ± 0.005
 962" ± 0.005
 964" ± 0.005
 966" ± 0.005
 968" ± 0.005
 970" ± 0.005
 972" ± 0.005
 974" ± 0.005
 976" ± 0.005
 978" ± 0.005
 980" ± 0.005
 982" ± 0.005
 984" ± 0.005
 986" ± 0.005
 988" ± 0.005
 990" ± 0.005
 992" ± 0.005
 994" ± 0.005
 996" ± 0.005
 998" ± 0.005
 1000" ± 0.005
 1002" ± 0.005
 1004" ± 0.005
 1006" ± 0.005
 1008" ± 0.005
 1010" ± 0.005
 1012" ± 0.005
 1014" ± 0.005
 1016" ± 0.005
 1018" ± 0.005
 1020" ± 0.005
 1022" ± 0.005
 1024" ± 0.005
 1026" ± 0.005
 1028" ± 0.005
 1030" ± 0.005
 1032" ± 0.005
 1034" ± 0.005
 1036" ± 0.005
 1038" ± 0.005
 1040" ± 0.005
 1042" ± 0.005
 1044" ± 0.005
 1046" ± 0.005
 1048" ± 0.005
 1050" ± 0.005
 1052" ± 0.005
 1054" ± 0.005
 1056" ± 0.005
 1058" ± 0.005
 1060" ± 0.005
 1062" ± 0.005
 1064" ± 0.005
 1066" ± 0.005
 1068" ± 0.005
 1070" ± 0.005
 1072" ± 0.005
 1074" ± 0.005
 1076" ± 0.005
 1078" ± 0.005
 1080" ± 0.005
 1082" ± 0.005
 1084" ± 0.005
 1086" ± 0.005
 1088" ± 0.005
 1090" ± 0.005
 1092" ± 0.005
 1094" ± 0.005
 1096" ± 0.005
 1098" ± 0.005
 1100" ± 0.005
 1102" ± 0.005
 1104" ± 0.005
 1106" ± 0.005
 1108" ± 0.005
 1110" ± 0.005
 1112" ± 0.005
 1114" ± 0.005
 1116" ± 0.005
 1118" ± 0.005
 1120" ± 0.005
 1122" ± 0.005
 1124" ± 0.005
 1126" ± 0.005
 1128" ± 0.005
 1130" ± 0.005
 1132" ± 0.005
 1134" ± 0.005
 1136" ± 0.005
 1138" ± 0.005
 1140" ± 0.005
 1142" ± 0.005
 1144" ± 0.005
 1146" ± 0.005
 1148" ± 0.005
 1150" ± 0.005
 1152" ± 0.005
 1154" ± 0.005
 1156" ± 0.005
 1158" ± 0.005
 1160" ± 0.005
 1162" ± 0.005
 1164" ± 0.005
 1166" ± 0.005
 1168" ± 0.005
 1170" ± 0.005
 1172" ± 0.005
 1174" ± 0.005
 1176" ± 0.005
 1178" ± 0.005
 1180" ± 0.005
 1182" ± 0.005
 1184" ± 0.005
 1186" ± 0.005
 1188" ± 0.005
 1190" ± 0.005
 1192" ± 0.005
 1194" ± 0.005
 1196" ± 0.005
 1198" ± 0.005
 1200" ± 0.005
 1202" ± 0.005
 1204" ± 0.005
 1206" ± 0.005
 1208" ± 0.005
 1210" ± 0.005
 1212" ± 0.005
 1214" ± 0.005
 1216" ± 0.005
 1218" ± 0.005
 1220" ± 0.005
 1222" ± 0.005
 1224" ± 0.005
 1226" ± 0.005
 1228" ± 0.005
 1230" ± 0.005
 1232" ± 0.005
 1234" ± 0.005
 1236" ± 0.005
 1238" ± 0.005
 1240" ± 0.005
 1242" ± 0.005
 1244" ± 0.005
 1246" ± 0.005
 1248" ± 0.005
 1250" ± 0.005
 1252" ± 0.005
 1254" ± 0.005
 1256" ± 0.005
 1258" ± 0.005
 1260" ± 0.005
 1262" ± 0.005
 1264" ± 0.005
 1266" ± 0.005
 1268" ± 0.005
 1270" ± 0.005
 1272" ± 0.005
 1274" ± 0.005
 1276" ± 0.005
 1278" ± 0.005
 1280" ± 0.005
 1282" ± 0.005
 1284" ± 0.005
 1286" ± 0.005
 1288" ± 0.005
 1290" ± 0.005
 1292" ± 0.005
 1294" ± 0.005
 1296" ± 0.005
 1298" ± 0.005
 1300" ± 0.005
 1302" ± 0.005
 1304" ± 0.005
 1306" ± 0.005
 1308" ± 0.005
 1310" ± 0.005
 1312" ± 0.005
 1314" ± 0.005
 1316" ± 0.005
 1318" ± 0.005
 1320" ± 0.005
 1322" ± 0.005
 1324" ± 0.005
 1326" ± 0.005
 1328" ± 0.005
 1330" ± 0.005
 1332" ± 0.005
 1334" ± 0.005
 1336" ± 0.005
 1338" ± 0.005
 1340" ± 0.005
 1342" ± 0.005
 1344" ± 0.005
 1346" ± 0.005
 1348" ± 0.005
 1350" ± 0.005
 1352" ± 0.005
 1354" ± 0.005
 1356" ± 0.005
 1358" ± 0.005
 1360" ± 0.005
 1362" ± 0.005
 1364" ± 0.005
 1366" ± 0.005
 1368" ± 0.005
 1370" ± 0.005
 1372" ± 0.005
 1374" ± 0.005
 1376" ± 0.005
 1378" ± 0.005
 1380" ± 0.005
 1382" ± 0.005
 1384" ± 0.005
 1386" ± 0.005
 1388" ± 0.005
 1390" ± 0.005




		IR		INITIAL RELEASE	
		DESCRIPTION		DATE	
ILLUSTRATION		DATE		BY	
SUBSEA PRODUCTION WELL		DATE		BY	
WITH PENETRATIONS		DATE		BY	
API 17D		DATE		BY	
111986-05		DATE		BY	
111986-05		DATE		BY	


TOLERANCES:
 UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS IN INCHES
 DECIMALS: 1/16"
 FRACTIONS: 1/8", 1/4", 3/8", 1/2", 5/8", 3/4", 7/8", 1 1/8", 1 1/4", 1 1/2", 1 3/4", 2, 2 1/4", 2 1/2", 2 3/4", 3, 3 1/4", 3 1/2", 3 3/4", 4, 4 1/4", 4 1/2", 4 3/4", 5, 5 1/4", 5 1/2", 5 3/4", 6, 6 1/4", 6 1/2", 6 3/4", 7, 7 1/4", 7 1/2", 7 3/4", 8, 8 1/4", 8 1/2", 8 3/4", 9, 9 1/4", 9 1/2", 9 3/4", 10, 10 1/4", 10 1/2", 10 3/4", 11, 11 1/4", 11 1/2", 11 3/4", 12, 12 1/4", 12 1/2", 12 3/4", 13, 13 1/4", 13 1/2", 13 3/4", 14, 14 1/4", 14 1/2", 14 3/4", 15, 15 1/4", 15 1/2", 15 3/4", 16, 16 1/4", 16 1/2", 16 3/4", 17, 17 1/4", 17 1/2", 17 3/4", 18, 18 1/4", 18 1/2", 18 3/4", 19, 19 1/4", 19 1/2", 19 3/4", 20, 20 1/4", 20 1/2", 20 3/4", 21, 21 1/4", 21 1/2", 21 3/4", 22, 22 1/4", 22 1/2", 22 3/4", 23, 23 1/4", 23 1/2", 23 3/4", 24, 24 1/4", 24 1/2", 24 3/4", 25, 25 1/4", 25 1/2", 25 3/4", 26, 26 1/4", 26 1/2", 26 3/4", 27, 27 1/4", 27 1/2", 27 3/4", 28, 28 1/4", 28 1/2", 28 3/4", 29, 29 1/4", 29 1/2", 29 3/4", 30, 30 1/4", 30 1/2", 30 3/4", 31, 31 1/4", 31 1/2", 31 3/4", 32, 32 1/4", 32 1/2", 32 3/4", 33, 33 1/4", 33 1/2", 33 3/4", 34, 34 1/4", 34 1/2", 34 3/4", 35, 35 1/4", 35 1/2", 35 3/4", 36, 36 1/4", 36 1/2", 36 3/4", 37, 37 1/4", 37 1/2", 37 3/4", 38, 38 1/4", 38 1/2", 38 3/4", 39, 39 1/4", 39 1/2", 39 3/4", 40, 40 1/4", 40 1/2", 40 3/4", 41, 41 1/4", 41 1/2", 41 3/4", 42, 42 1/4", 42 1/2", 42 3/4", 43, 43 1/4", 43 1/2", 43 3/4", 44, 44 1/4", 44 1/2", 44 3/4", 45, 45 1/4", 45 1/2", 45 3/4", 46, 46 1/4", 46 1/2", 46 3/4", 47, 47 1/4", 47 1/2", 47 3/4", 48, 48 1/4", 48 1/2", 48 3/4", 49, 49 1/4", 49 1/2", 49 3/4", 50, 50 1/4", 50 1/2", 50 3/4", 51, 51 1/4", 51 1/2", 51 3/4", 52, 52 1/4", 52 1/2", 52 3/4", 53, 53 1/4", 53 1/2", 53 3/4", 54, 54 1/4", 54 1/2", 54 3/4", 55, 55 1/4", 55 1/2", 55 3/4", 56, 56 1/4", 56 1/2", 56 3/4", 57, 57 1/4", 57 1/2", 57 3/4", 58, 58 1/4", 58 1/2", 58 3/4", 59, 59 1/4", 59 1/2", 59 3/4", 60, 60 1/4", 60 1/2", 60 3/4", 61, 61 1/4", 61 1/2", 61 3/4", 62, 62 1/4", 62 1/2", 62 3/4", 63, 63 1/4", 63 1/2", 63 3/4", 64, 64 1/4", 64 1/2", 64 3/4", 65, 65 1/4", 65 1/2", 65 3/4", 66, 66 1/4", 66 1/2", 66 3/4", 67, 67 1/4", 67 1/2", 67 3/4", 68, 68 1/4", 68 1/2", 68 3/4", 69, 69 1/4", 69 1/2", 69 3/4", 70, 70 1/4", 70 1/2", 70 3/4", 71, 71 1/4", 71 1/2", 71 3/4", 72, 72 1/4", 72 1/2", 72 3/4", 73, 73 1/4", 73 1/2", 73 3/4", 74, 74 1/4", 74 1/2", 74 3/4", 75, 75 1/4", 75 1/2", 75 3/4", 76, 76 1/4", 76 1/2", 76 3/4", 77, 77 1/4", 77 1/2", 77 3/4", 78, 78 1/4", 78 1/2", 78 3/4", 79, 79 1/4", 79 1/2", 79 3/4", 80, 80 1/4", 80 1/2", 80 3/4", 81, 81 1/4", 81 1/2", 81 3/4", 82, 82 1/4", 82 1/2", 82 3/4", 83, 83 1/4", 83 1/2", 83 3/4", 84, 84 1/4", 84 1/2", 84 3/4", 85, 85 1/4", 85 1/2", 85 3/4", 86, 86 1/4", 86 1/2", 86 3/4", 87, 87 1/4", 87 1/2", 87 3/4", 88, 88 1/4", 88 1/2", 88 3/4", 89, 89 1/4", 89 1/2", 89 3/4", 90, 90 1/4", 90 1/2", 90 3/4", 91, 91 1/4", 91 1/2", 91 3/4", 92, 92 1/4", 92 1/2", 92 3/4", 93, 93 1/4", 93 1/2", 93 3/4", 94, 94 1/4", 94 1/2", 94 3/4", 95, 95 1/4", 95 1/2", 95 3/4", 96, 96 1/4", 96 1/2", 96 3/4", 97, 97 1/4", 97 1/2", 97 3/4", 98, 98 1/4", 98 1/2", 98 3/4", 99, 99 1/4", 99 1/2", 99 3/4", 100, 100 1/4", 100 1/2", 100 3/4", 101, 101 1/4", 101 1/2", 101 3/4", 102, 102 1/4", 102 1/2", 102 3/4", 103, 103 1/4", 103 1/2", 103 3/4", 104, 104 1/4", 104 1/2", 104 3/4", 105, 105 1/4", 105 1/2", 105 3/4", 106, 106 1/4", 106 1/2", 106 3/4", 107, 107 1/4", 107 1/2", 107 3/4", 108, 108 1/4", 108 1/2", 108 3/4", 109, 109 1/4", 109 1/2", 109 3/4", 110, 110 1/4", 110 1/2", 110 3/4", 111, 111 1/4", 111 1/2", 111 3/4", 112, 112 1/4", 112 1/2", 112 3/4", 113, 113 1/4", 113 1/2", 113 3/4", 114, 114 1/4", 114 1/2", 114 3/4", 115, 115 1/4", 115 1/2", 115 3/4", 116, 116 1/4", 116 1/2", 116 3/4", 117, 117 1/4", 117 1/2", 117 3/4", 118, 118 1/4", 118 1/2", 118 3/4", 119, 119 1/4", 119 1/2", 119 3/4", 120, 120 1/4", 120 1/2", 120 3/4", 121, 121 1/4", 121 1/2", 121 3/4", 122, 122 1/4", 122 1/2", 122 3/4", 123, 123 1/4", 123 1/2", 123 3/4", 124, 124 1/4", 124 1/2", 124 3/4", 125, 125 1/4", 125 1/2", 125 3/4", 126, 126 1/4", 126 1/2", 126 3/4", 127, 127 1/4", 127 1/2", 127 3/4", 128, 128 1/4", 128 1/2", 128 3/4", 129, 129 1/4", 129 1/2", 129 3/4", 130, 130 1/4", 130 1/2", 130 3/4", 131, 131 1/4", 131 1/2", 131 3/4", 132, 132 1/4", 132 1/2", 132 3/4", 133, 133 1/4", 133 1/2", 133 3/4", 134, 134 1/4", 134 1/2", 134 3/4", 135, 135 1/4", 135 1/2", 135 3/4", 136, 136 1/4", 136 1/2", 136 3/4", 137, 137 1/4", 137 1/2", 137 3/4", 138, 138 1/4", 138 1/2", 138 3/4", 139, 139 1/4", 139 1/2", 139 3/4", 140, 140 1/4", 140 1/2", 140 3/4", 141, 141 1/4", 141 1/2", 141 3/4", 142, 142 1/4", 142 1/2", 142 3/4", 143, 143 1/4", 143 1/2", 143 3/4", 144, 144 1/4", 144 1/2", 144 3/4", 145, 145 1/4", 145 1/2", 145 3/4", 146, 146 1/4", 146 1/2", 146 3/4", 147, 147 1/4", 147 1/2", 147 3/4", 148, 148 1/4", 148 1/2", 148 3/4", 149, 149 1/4", 149 1/2", 149 3/4", 150, 150 1/4", 150 1/2", 150 3/4", 151, 151 1/4", 151 1/2", 151 3/4", 152, 152 1/4", 152 1/2", 152 3/4", 153, 153 1/4", 153 1/2", 153 3/4", 154, 154 1/4", 154 1/2", 154 3/4", 155, 155 1/4", 155 1/2", 155 3/4", 156, 156 1/4", 156 1/2", 156 3/4", 157, 157 1/4", 157 1/2", 157 3/4", 158, 158 1/4", 158 1/2", 158 3/4", 159, 159 1/4", 159 1/2", 159 3/4", 160, 160 1/4", 160 1/2", 160 3/4", 161, 161 1/4", 161 1/2", 161 3/4", 162, 162 1/4", 162 1/2", 162 3/4", 163, 163 1/4", 163 1/2", 163 3/4", 164, 164 1/4", 164 1/2", 164 3/4", 165, 165 1/4", 165 1/2", 165 3/4", 166, 166 1/4", 166 1/2", 166 3/4", 167, 167 1/4", 167 1/2", 167 3/4", 168, 168 1/4", 168 1/2", 168 3/4", 169, 169 1/4", 169 1/2", 169 3/4", 170, 170 1/4", 170 1/2", 170 3/4", 171, 171 1/4", 171 1/2", 171 3/4", 172, 172 1/4", 172 1/2", 172 3/4", 173, 173 1/4", 173 1/2", 173 3/4", 174, 174 1/4", 174 1/2", 174 3/4", 175, 175 1/4", 175 1/2", 175 3/4", 176, 176 1/4", 176 1/2", 176 3/4", 177, 177 1/4", 177 1/2", 177 3/4", 178, 178 1/4", 178 1/2", 178 3/4", 179, 179 1/4", 179 1/2", 179 3/4", 180, 180 1/4", 180 1/2", 180 3/4", 181, 181 1/4", 181 1/2", 181 3/4", 182, 182 1/4", 182 1/2", 182 3/4", 183, 183 1/4", 183 1/2", 183 3/4", 184, 184 1/4", 184 1/2", 184 3/4", 185, 185 1/4", 185 1/2", 185 3/4", 186, 186 1/4", 186 1/2", 186 3/4", 187, 187 1/4", 187 1/2", 187 3/4", 188, 188 1/4", 188 1/2", 188 3/4", 189, 189 1/4", 189 1/2", 189 3/4", 190, 190 1/4", 190 1/2", 190 3/4", 191, 191 1/4", 191 1/2", 191 3/4", 192, 192 1/4", 192 1/2", 192 3/4", 193, 193 1/4", 193 1/2", 193 3/4", 194, 194 1/4", 194 1/2", 194 3/4", 195, 195 1/4", 195 1/2", 195 3/4", 196, 196 1/4", 196 1/2", 196 3/4", 197, 197 1/4", 197 1/2", 197 3/4", 198, 198 1/4", 198 1/2", 198 3/4", 199, 199 1/4", 199 1/2", 199 3/4", 200, 200 1/4", 200 1/2", 200 3/4", 201, 201 1/4", 201 1/2", 201 3/4", 202, 202 1/4", 202 1/2", 202 3/4", 203, 203 1/4", 203 1/2", 203 3/4", 204, 204 1/4", 204 1/2", 204 3/4", 205, 205 1/4", 205 1/2", 205 3/4", 206, 206 1/4", 206 1/2", 206 3/4", 207, 207 1/4", 207 1/2", 207 3/4", 208, 208 1/4", 208 1/2", 208 3/4", 209, 209 1/4", 209 1/2", 209 3/4", 210, 210 1/4", 210 1/2", 210 3/4", 211, 211 1/4", 211 1/2", 211 3/4", 212, 212 1/4", 212 1/2", 212 3/4", 213, 213 1/4", 213 1/2", 213 3/4", 214, 214 1/4", 214 1/2", 214 3/4", 215, 215 1/4", 215 1/2", 215 3/4", 216, 216 1/4", 216 1/2", 216 3/4", 217, 217 1/4", 217 1/2", 217 3/4", 218, 218 1/4", 218 1/2", 218 3/4", 219, 219 1/4", 219 1/2", 219 3/4", 220, 220 1/4", 220 1/2", 220 3/4", 221, 221 1/4", 221 1/2", 221 3/4", 222, 222 1/4", 222 1/2", 222 3/4", 223, 223 1/4", 223 1/2", 223 3/4", 224, 224 1/4", 224 1/2", 224 3/4", 225, 225 1/4", 225 1/2", 225 3/4", 226, 226 1/4", 226 1/2", 226 3/4", 227, 227 1/4", 227 1/2", 227 3/4", 228, 228 1/4", 228 1/2", 228 3/4", 229, 229 1/4", 229 1/2", 229 3/4", 230, 230 1/4", 230 1/2", 230 3/4", 231, 231 1/4", 231 1/2", 231 3/4", 232, 232 1/4", 232 1/2", 232 3/4", 233, 233 1/4", 233 1/2", 233 3/4", 234, 234 1/4", 234 1/2", 234 3/4", 235, 235 1/4", 235 1/2", 235 3/4", 236, 236 1/4", 236 1/2", 236 3/4", 237, 237 1/4", 237 1/2", 237 3/4", 238, 238 1/4", 238 1/2", 238 3/4", 239, 239 1/4", 239 1/2", 239 3/4", 240, 240 1/4", 240 1/2", 240 3/4", 241, 241 1/4", 241 1/2", 241 3/4", 242, 242 1/4", 242 1/2", 242 3/4", 243, 243 1/4", 243 1/2", 243 3/4", 244, 244 1/4", 244 1/2", 244 3/4", 245, 245 1/4", 245 1/2", 245 3/4", 246, 246 1/4", 246 1/2", 246 3/4", 247, 247 1/4", 247 1/2", 247 3/4", 248, 248 1/4", 248 1/2", 248 3/4", 249, 249 1/4", 249 1/2", 249 3/4", 250, 250 1/4", 250 1/2", 250 3/4", 251, 251 1/4", 251 1/2", 251 3/4", 252, 252 1/4", 252 1/2", 252 3/4", 253, 253 1/4", 253 1/2", 253 3/4", 254, 254 1/4", 254 1/2", 254 3/4", 255, 255 1/4", 255 1/2", 255 3/4", 256, 256 1/4", 256 1/2", 256 3/4", 257, 257 1/4", 257 1/2", 257 3/4", 258, 258 1/4", 258 1/2", 258 3/4", 259, 259 1/4", 259 1/2", 259 3/4", 260, 260 1/4", 260 1/2", 260 3/4", 261, 261 1/4", 261 1/2", 261 3/4", 262, 262 1/4", 262 1/2", 262 3/4", 263, 263 1/4", 263 1/2", 263 3/4", 264, 264 1/4", 264 1/2", 264 3/4", 265, 265 1/4", 265 1/2", 265 3/4", 266, 266 1/4", 266 1/2", 266 3/4", 267, 267 1/4", 267 1/2", 267 3/4", 268, 268 1/4", 268 1/2", 268 3/4", 269, 269 1/4", 269 1/2", 269 3/4", 270, 270 1/4", 270 1/2", 270 3/4", 271, 271 1/4", 271 1/2", 271 3/4", 272, 272 1/4", 272 1/2", 272 3/4", 273, 273 1/4", 273 1/2", 273 3/4", 274, 274 1/4", 274 1/2", 274 3/4", 275, 275 1/4", 275 1/2", 275 3/4", 276, 276 1/4", 276 1/2", 276 3/4", 277, 277 1/4", 277 1/2", 277 3/4", 278, 278 1/4", 278 1/2", 278 3/4", 279, 279 1/4", 279 1/2", 279 3/4", 280, 280 1/4", 280 1/2", 280 3/4", 281, 281 1/4", 281 1/2", 281 3/4", 282, 282 1/4", 282 1/2", 282 3/4", 283, 283 1/4", 283 1/2", 283 3/4", 284, 284 1/4", 284 1/2", 284 3/4", 285, 285 1/4", 285 1/2", 285 3/4", 286, 286 1/4", 286 1/2", 286 3/4", 287, 287 1/4", 287 1/2", 287 3/4", 288, 288 1/4", 288 1/2", 288 3/4", 289, 289 1/4", 289 1/2", 289 3/4", 290, 290 1/4", 290 1/2", 290 3/4", 291, 291 1/4", 291 1/2", 291 3/4", 292, 292 1/4", 292 1/2", 292 3/4", 293, 293 1/4", 293 1/2", 293 3/4", 294, 294 1/4", 294 1/2", 294 3/4", 295, 295 1/4", 295 1/2", 295 3/4", 296, 296 1/4", 296 1/2", 296 3/4", 297, 297 1/4", 297 1/2", 297 3/4", 298, 298 1/4", 298 1/2", 298 3/4", 299, 299 1/4", 299 1/2", 299 3/4", 300, 300 1/4", 300 1/2", 300 3/4", 301, 301 1/4", 301 1/2", 301 3/4", 302, 302 1/4", 302 1/2", 302 3/4", 303, 303 1/4", 303 1/2", 303 3/4", 304, 304 1/4", 304 1/2", 304 3/4", 305, 305 1/4", 305 1/2", 305 3/4", 306, 306 1/4", 306 1/2", 306 3/4", 307, 307 1/4", 307 1/2", 307 3/4", 308, 308 1/4", 308 1/2", 308 3/4", 309, 309 1/4", 309 1/2", 309 3/4", 310, 310 1/4", 310 1/2", 310 3/4", 311, 311 1/4", 311 1/2", 311 3/4", 312, 312 1/4", 312 1/2", 312 3/4", 313, 313 1/4", 313 1/2", 313 3/4", 314, 314 1/4", 314 1/2", 314 3/4", 315, 315 1/4", 315 1/2", 315 3/4", 316, 316 1/4", 316 1/2", 316 3/4", 317, 317 1/4", 317 1/2", 317 3/4", 318, 318 1/4", 318 1/2", 318 3/4", 319, 319 1/4", 319 1/2", 319 3/4", 320, 320 1/4", 320 1/2", 320 3/4", 321, 321 1/4", 321 1/2", 321 3/4", 322, 322 1/4", 322 1/2", 322 3/4", 323, 323 1/4", 323 1/2", 323 3/4", 324, 324 1/4", 324 1/2", 324 3/4", 325, 325 1/4", 325 1/2", 325 3/4", 326, 326 1/4", 326 1/2", 326 3/4", 327, 327 1/4", 327 1/2", 327 3/4", 328, 328 1/4", 328 1/2", 328 3/4", 329, 329 1/4", 329 1/2", 329 3/4", 330, 330 1/4", 330 1/2", 330 3/4", 331, 331 1/4", 331 1/2", 331 3/4", 332, 332 1/4", 332 1/2", 332 3/4", 333, 333 1/4", 333 1/2", 333 3/4", 334, 334 1/4", 334 1/2", 334 3/4", 335, 335 1/4", 335 1/2", 335 3/4", 336, 336 1/4", 336 1/2", 336 3/4", 337, 337 1/4", 337 1/2", 337 3/4", 338, 338 1/4", 338 1/2", 338 3/4", 339, 339 1/4", 339 1/2", 339 3/4", 340, 340 1/4", 340 1/2", 340 3/4", 341, 341 1/4", 341 1/2", 341 3/4", 342, 342 1/4", 342 1/2", 342 3/4", 343, 343 1/4", 343 1/2", 343 3/4", 344, 344 1/4", 344 1/2", 344 3/4", 345, 345 1/4", 345 1/2", 345 3/4", 346, 346 1/4", 346 1/2", 346 3/4", 347, 347 1/4", 347 1/2", 347 3/4", 348, 348 1/4", 348 1/2", 348 3/4", 349, 349 1/4", 349 1/2", 349 3/4", 350, 350 1/4", 350 1/2", 350 3/4", 351, 351 1/4", 351 1/2", 351 3/4", 352, 352 1/4", 352 1/2", 352 3/4", 353, 353 1/4", 353 1/2", 353 3/4", 354, 354 1/4", 354 1/2", 354 3/4", 355, 355 1/4", 355 1/2", 355 3/4", 356, 356 1/4", 356 1/2", 356 3/4", 357, 357 1/4", 357 1/2", 357 3/4", 358, 358 1/4", 358 1/2", 358 3/4", 359, 359 1/4", 359 1/2", 359 3/4", 360, 360 1/4", 360 1/2", 360 3/4", 361, 361 1/4", 361 1/2", 361 3/4", 362, 362 1/4", 362 1/2", 362 3/4", 363, 363 1/4", 363 1/2", 363 3/4", 364, 364 1/4", 364 1/2", 364 3/4", 365, 365 1/4", 365 1/2", 365 3/4", 366, 366 1/4", 366 1/2", 366 3/4", 367, 367 1/4", 367 1/2", 367 3/4", 368, 368 1/4", 368 1/2", 368 3/4", 369, 369 1/4", 369 1/2", 369 3/4", 370, 370 1/4", 370 1/2", 370 3/4", 371, 371 1/4", 371 1/2", 371 3/4", 372, 372 1/4", 372 1/




		TOLERANCES:	
		UNLESS OTHERWISE SPECIFIED	
1/8" ± 0.01 1/16" ± 0.005 3/16" ± 0.005 1/2" ± 0.005 3/4" ± 0.005 1" ± 0.005 1 1/2" ± 0.005 2" ± 0.005 3" ± 0.005 4" ± 0.005 6" ± 0.005 8" ± 0.005 10" ± 0.005 12" ± 0.005 14" ± 0.005 16" ± 0.005 18" ± 0.005 20" ± 0.005 22" ± 0.005 24" ± 0.005 26" ± 0.005 28" ± 0.005 30" ± 0.005 32" ± 0.005 34" ± 0.005 36" ± 0.005 38" ± 0.005 40" ± 0.005 42" ± 0.005 44" ± 0.005 46" ± 0.005 48" ± 0.005 50" ± 0.005 52" ± 0.005 54" ± 0.005 56" ± 0.005 58" ± 0.005 60" ± 0.005 62" ± 0.005 64" ± 0.005 66" ± 0.005 68" ± 0.005 70" ± 0.005 72" ± 0.005 74" ± 0.005 76" ± 0.005 78" ± 0.005 80" ± 0.005 82" ± 0.005 84" ± 0.005 86" ± 0.005 88" ± 0.005 90" ± 0.005 92" ± 0.005 94" ± 0.005 96" ± 0.005 98" ± 0.005 100" ± 0.005 102" ± 0.005 104" ± 0.005 106" ± 0.005 108" ± 0.005 110" ± 0.005 112" ± 0.005 114" ± 0.005 116" ± 0.005 118" ± 0.005 120" ± 0.005 122" ± 0.005 124" ± 0.005 126" ± 0.005 128" ± 0.005 130" ± 0.005 132" ± 0.005 134" ± 0.005 136" ± 0.005 138" ± 0.005 140" ± 0.005 142" ± 0.005 144" ± 0.005 146" ± 0.005 148" ± 0.005 150" ± 0.005 152" ± 0.005 154" ± 0.005 156" ± 0.005 158" ± 0.005 160" ± 0.005 162" ± 0.005 164" ± 0.005 166" ± 0.005 168" ± 0.005 170" ± 0.005 172" ± 0.005 174" ± 0.005 176" ± 0.005 178" ± 0.005 180" ± 0.005 182" ± 0.005 184" ± 0.005 186" ± 0.005 188" ± 0.005 190" ± 0.005 192" ± 0.005 194" ± 0.005 196" ± 0.005 198" ± 0.005 200" ± 0.005 202" ± 0.005 204" ± 0.005 206" ± 0.005 208" ± 0.005 210" ± 0.005 212" ± 0.005 214" ± 0.005 216" ± 0.005 218" ± 0.005 220" ± 0.005 222" ± 0.005 224" ± 0.005 226" ± 0.005 228" ± 0.005 230" ± 0.005 232" ± 0.005 234" ± 0.005 236" ± 0.005 238" ± 0.005 240" ± 0.005 242" ± 0.005 244" ± 0.005 246" ± 0.005 248" ± 0.005 250" ± 0.005 252" ± 0.005 254" ± 0.005 256" ± 0.005 258" ± 0.005 260" ± 0.005 262" ± 0.005 264" ± 0.005 266" ± 0.005 268" ± 0.005 270" ± 0.005 272" ± 0.005 274" ± 0.005 276" ± 0.005 278" ± 0.005 280" ± 0.005 282" ± 0.005 284" ± 0.005 286" ± 0.005 288" ± 0.005 290" ± 0.005 292" ± 0.005 294" ± 0.005 296" ± 0.005 298" ± 0.005 300" ± 0.005 302" ± 0.005 304" ± 0.005 306" ± 0.005 308" ± 0.005 310" ± 0.005 312" ± 0.005 314" ± 0.005 316" ± 0.005 318" ± 0.005 320" ± 0.005 322" ± 0.005 324" ± 0.005 326" ± 0.005 328" ± 0.005 330" ± 0.005 332" ± 0.005 334" ± 0.005 336" ± 0.005 338" ± 0.005 340" ± 0.005 342" ± 0.005 344" ± 0.005 346" ± 0.005 348" ± 0.005 350" ± 0.005 352" ± 0.005 354" ± 0.005 356" ± 0.005 358" ± 0.005 360" ± 0.005 362" ± 0.005 364" ± 0.005 366" ± 0.005 368" ± 0.005 370" ± 0.005 372" ± 0.005 374" ± 0.005 376" ± 0.005 378" ± 0.005 380" ± 0.005 382" ± 0.005 384" ± 0.005 386" ± 0.005 388" ± 0.005 390" ± 0.005 392" ± 0.005 394" ± 0.005 396" ± 0.005 398" ± 0.005 400" ± 0.005 402" ± 0.005 404" ± 0.005 406" ± 0.005 408" ± 0.005 410" ± 0.005 412" ± 0.005 414" ± 0.005 416" ± 0.005 418" ± 0.005 420" ± 0.005 422" ± 0.005 424" ± 0.005 426" ± 0.005 428" ± 0.005 430" ± 0.005 432" ± 0.005 434" ± 0.005 436" ± 0.005 438" ± 0.005 440" ± 0.005 442" ± 0.005 444" ± 0.005 446" ± 0.005 448" ± 0.005 450" ± 0.005 452" ± 0.005 454" ± 0.005 456" ± 0.005 458" ± 0.005 460" ± 0.005 462" ± 0.005 464" ± 0.005 466" ± 0.005 468" ± 0.005 470" ± 0.005 472" ± 0.005 474" ± 0.005 476" ± 0.005 478" ± 0.005 480" ± 0.005 482" ± 0.005 484" ± 0.005 486" ± 0.005 488" ± 0.005 490" ± 0.005 492" ± 0.005 494" ± 0.005 496" ± 0.005 498" ± 0.005 500" ± 0.005 502" ± 0.005 504" ± 0.005 506" ± 0.005 508" ± 0.005 510" ± 0.005 512" ± 0.005 514" ± 0.005 516" ± 0.005 518" ± 0.005 520" ± 0.005 522" ± 0.005 524" ± 0.005 526" ± 0.005 528" ± 0.005 530" ± 0.005 532" ± 0.005 534" ± 0.005 536" ± 0.005 538" ± 0.005 540" ± 0.005 542" ± 0.005 544" ± 0.005 546" ± 0.005 548" ± 0.005 550" ± 0.005 552" ± 0.005 554" ± 0.005 556" ± 0.005 558" ± 0.005 560" ± 0.005 562" ± 0.005 564" ± 0.005 566" ± 0.005 568" ± 0.005 570" ± 0.005 572" ± 0.005 574" ± 0.005 576" ± 0.005 578" ± 0.005 580" ± 0.005 582" ± 0.005 584" ± 0.005 586" ± 0.005 588" ± 0.005 590" ± 0.005 592" ± 0.005 594" ± 0.005 596" ± 0.005 598" ± 0.005 600" ± 0.005 602" ± 0.005 604" ± 0.005 606" ± 0.005 608" ± 0.005 610" ± 0.005 612" ± 0.005 614" ± 0.005 616" ± 0.005 618" ± 0.005 620" ± 0.005 622" ± 0.005 624" ± 0.005 626" ± 0.005 628" ± 0.005 630" ± 0.005 632" ± 0.005 634" ± 0.005 636" ± 0.005 638" ± 0.005 640" ± 0.005 642" ± 0.005 644" ± 0.005 646" ± 0.005 648" ± 0.005 650" ± 0.005 652" ± 0.005 654" ± 0.005 656" ± 0.005 658" ± 0.005 660" ± 0.005 662" ± 0.005 664" ± 0.005 666" ± 0.005 668" ± 0.005 670" ± 0.005 672" ± 0.005 674" ± 0.005 676" ± 0.005 678" ± 0.005 680" ± 0.005 682" ± 0.005 684" ± 0.005 686" ± 0.005 688" ± 0.005 690" ± 0.005 692" ± 0.005 694" ± 0.005 696" ± 0.005 698" ± 0.005 700" ± 0.005 702" ± 0.005 704" ± 0.005 706" ± 0.005 708" ± 0.005 710" ± 0.005 712" ± 0.005 714" ± 0.005 716" ± 0.005 718" ± 0.005 720" ± 0.005 722" ± 0.005 724" ± 0.005 726" ± 0.005 728" ± 0.005 730" ± 0.005 732" ± 0.005 734" ± 0.005 736" ± 0.005 738" ± 0.005 740" ± 0.005 742" ± 0.005 744" ± 0.005 746" ± 0.005 748" ± 0.005 750" ± 0.005 752" ± 0.005 754" ± 0.005 756" ± 0.005 758" ± 0.005 760" ± 0.005 762" ± 0.005 764" ± 0.005 766" ± 0.005 768" ± 0.005 770" ± 0.005 772" ± 0.005 774" ± 0.005 776" ± 0.005 778" ± 0.005 780" ± 0.005 782" ± 0.005 784" ± 0.005 786" ± 0.005 788" ± 0.005 790" ± 0.005 792" ± 0.005 794" ± 0.005 796" ± 0.005 798" ± 0.005 800" ± 0.005 802" ± 0.005 804" ± 0.005 806" ± 0.005 808" ± 0.005 810" ± 0.005 812" ± 0.005 814" ± 0.005 816" ± 0.005 818" ± 0.005 820" ± 0.005 822" ± 0.005 824" ± 0.005 826" ± 0.005 828" ± 0.005 830" ± 0.005 832" ± 0.005 834" ± 0.005 836" ± 0.005 838" ± 0.005 840" ± 0.005 842" ± 0.005 844" ± 0.005 846" ± 0.005 848" ± 0.005 850" ± 0.005 852" ± 0.005 854" ± 0.005 856" ± 0.005 858" ± 0.005 860" ± 0.005 862" ± 0.005 864" ± 0.005 866" ± 0.005 868" ± 0.005 870" ± 0.005 872" ± 0.005 874" ± 0.005 876" ± 0.005 878" ± 0.005 880" ± 0.005 882" ± 0.005 884" ± 0.005 886" ± 0.005 888" ± 0.005 890" ± 0.005 892" ± 0.005 894" ± 0.005 896" ± 0.005 898" ± 0.005 900" ± 0.005 902" ± 0.005 904" ± 0.005 906" ± 0.005 908" ± 0.005 910" ± 0.005 912" ± 0.005 914" ± 0.005 916" ± 0.005 918" ± 0.005 920" ± 0.005 922" ± 0.005 924" ± 0.005 926" ± 0.005 928" ± 0.005 930" ± 0.005 932" ± 0.005 934" ± 0.005 936" ± 0.005 938" ± 0.005 940" ± 0.005 942" ± 0.005 944" ± 0.005 946" ± 0.005 948" ± 0.005 950" ± 0.005 952" ± 0.005 954" ± 0.005 956" ± 0.005 958" ± 0.005 960" ± 0.005 962" ± 0.005 964" ± 0.005 966" ± 0.005 968" ± 0.005 970" ± 0.005 972" ± 0.005 974" ± 0.005 976" ± 0.005 978" ± 0.005 980" ± 0.005 982" ± 0.005 984" ± 0.005 986" ± 0.005 988" ± 0.005 990" ± 0.005 992" ± 0.005 994" ± 0.005 996" ± 0.005 998" ± 0.005 1000" ± 0.005 1002" ± 0.005 1004" ± 0.005 1006" ± 0.005 1008" ± 0.005 1010" ± 0.005 1012" ± 0.005 1014" ± 0.005 1016" ± 0.005 1018" ± 0.005 1020" ± 0.005 1022" ± 0.005 1024" ± 0.005 1026" ± 0.005 1028" ± 0.005 1030" ± 0.005 1032" ± 0.005 1034" ± 0.005 1036" ± 0.005 1038" ± 0.005 1040" ± 0.005 1042" ± 0.005 1044" ± 0.005 1046" ± 0.005 1048" ± 0.005 1050" ± 0.005 1052" ± 0.005 1054" ± 0.005 1056" ± 0.005 1058" ± 0.005 1060" ± 0.005 1062" ± 0.005 1064" ± 0.005 1066" ± 0.005 1068" ± 0.005 1070" ± 0.005 1072" ± 0.005 1074" ± 0.005 1076" ± 0.005 1078" ± 0.005 1080" ± 0.005 1082" ± 0.005 1084" ± 0.005 1086" ± 0.005 1088" ± 0.005 1090" ± 0.005 1092" ± 0.005 1094" ± 0.005 1096" ± 0.005 1098" ± 0.005 1100" ± 0.005 1102" ± 0.005 1104" ± 0.005 1106" ± 0.005 1108" ± 0.005 1110" ± 0.005 1112" ± 0.005 1114" ± 0.005 1116" ± 0.005 1118" ± 0.005 1120" ± 0.005 1122" ± 0.005 1124" ± 0.005 1126" ± 0.005 1128" ± 0.005 1130" ± 0.005 1132" ± 0.005 1134" ± 0.005 1136" ± 0.005 1138" ± 0.005 1140" ± 0.005 1142" ± 0.005 1144" ± 0.005 1146" ± 0.005 1148" ± 0.005 1150" ± 0.005 1152" ± 0.005 1154" ± 0.005 1156" ± 0.005 1158" ± 0.005 1160" ± 0.005 1162" ± 0.005 1164" ± 0.005 1166" ± 0.005 1168" ± 0.005 1170" ± 0.005 1172" ± 0.005 1174" ± 0.005 1176" ± 0.005 1178" ± 0.005 1180" ± 0.005 1182" ± 0.005 1184" ± 0.005 1186" ± 0.005 1188" ± 0.005 1190" ± 0.005 1192" ± 0.005 1194" ± 0.005 1196" ± 0.005 1198" ± 0.005 1200" ± 0.005 1202" ± 0.005 1204" ± 0.005 1206" ± 0.005 1208" ± 0.005 1210" ± 0.005 1212" ± 0.005 1214" ± 0.005 1216" ± 0.005 1218" ± 0.005 1220" ± 0.005 1222" ± 0.005 1224" ± 0.005 1226" ± 0.005 1228" ± 0.005 1230" ± 0.005 1232" ± 0.005 1234" ± 0.005 1236" ± 0.005 1238" ± 0.005 1240" ± 0.005 1242" ± 0.005 1244" ± 0.005 1246" ± 0.005 1248" ± 0.005 1250" ± 0.005 1252" ± 0.005 1254" ± 0.005 1256" ± 0.005 1258" ± 0.005 1260" ± 0.005 1262" ± 0.005 1264" ± 0.005 1266" ± 0.005 1268" ± 0.005 1270" ± 0.005 1272" ± 0.005 1274" ± 0.005 1276" ± 0.005 1278" ± 0.005 1280" ± 0.005 1282" ± 0.005 1284" ± 0.005 1286" ± 0.005 1288" ± 0.005 1290" ± 0.005 1292" ± 0.005 1294" ± 0.005 1296" ± 0.005 1298" ± 0.005 1300" ± 0.005 1302" ± 0.005 1304" ± 0.005 1306" ± 0.005 1308" ± 0.005 1310" ± 0.005 1312" ± 0.005 1314" ± 0.005 1316" ± 0.005 1318" ± 0.005 1320" ± 0.005 1322" ± 0.005 1324" ± 0.005 1326" ± 0.005 1328" ± 0.005 1330" ± 0.005 1332" ± 0.005 1334" ± 0.005 1336" ± 0.005 1338" ± 0.005 1340" ± 0.005 1342" ± 0.005 1344" ± 0.005 1346" ± 0.005 1348" ± 0.005 1350" ± 0.005 1352" ± 0.005 1354" ± 0.005 1356" ± 0.005 1358" ± 0.005 1360" ± 0.005 1362" ± 0.005 1364" ± 0.005 1366" ± 0.005 1368" ± 0.005 1370" ± 0.005 1372" ± 0.005 1374" ± 0.005 1376" ± 0.005 1378" ± 0.005 1380" ± 0.005 1382" ± 0.005 1384" ± 0.005 1386" ± 0.005 1388" ± 0.005 1390" ± 0.005 1392" ± 0.005 1394" ± 0.005 1396" ± 0.005 1398" ± 0.005 1400" ± 0.005 1402" ± 0.005 1404" ± 0.005 1406" ± 0.005 1408" ± 0.005 1410" ± 0.005 1412" ± 0.005 1414" ± 0.005 1416" ± 0.005 1418" ± 0.005 1420" ± 0.005 1422" ± 0.005 1424" ± 0.005 1426" ± 0.005 1428" ± 0.005 1430" ± 0.005 1432" ± 0.005 1434" ± 0.005 1436" ± 0.005 1438" ± 0.005 1440" ± 0.005 1442" ± 0.005 1444" ± 0.005 1446" ± 0.005 1448" ± 0.005 1450" ± 0.005 1452" ± 0.005 1454" ± 0.005			




		IR		INITIAL RELEASE	
		DESCRIPTION		DATE	
ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		DATE		BY	
DATE		DATE		DATE	
SCALE		SCALE		SCALE	
REV.		REV.		REV.	
111986-05		111986-05		111986-05	




PRESSURE MIGRATING
INWARDS FROM PROD CSG CEMENT





		TOLERANCES: UNLESS OTHERWISE SPECIFIED	
		1/16" = 0.0625" 1/8" = 0.125" 1/4" = 0.25" 3/8" = 0.375" 1/2" = 0.5" 5/8" = 0.625" 3/4" = 0.75" 7/8" = 0.875" 1" = 1.0" 1 1/8" = 1.125" 1 1/4" = 1.25" 1 3/8" = 1.375" 1 1/2" = 1.5" 1 5/8" = 1.625" 1 3/4" = 1.75" 1 7/8" = 1.875" 2" = 2.0" 2 1/8" = 2.125" 2 1/4" = 2.25" 2 3/8" = 2.375" 2 1/2" = 2.5" 2 5/8" = 2.625" 2 3/4" = 2.75" 2 7/8" = 2.875" 3" = 3.0" 3 1/8" = 3.125" 3 1/4" = 3.25" 3 3/8" = 3.375" 3 1/2" = 3.5" 3 5/8" = 3.625" 3 3/4" = 3.75" 3 7/8" = 3.875" 4" = 4.0" 4 1/8" = 4.125" 4 1/4" = 4.25" 4 3/8" = 4.375" 4 1/2" = 4.5" 4 5/8" = 4.625" 4 3/4" = 4.75" 4 7/8" = 4.875" 5" = 5.0" 5 1/8" = 5.125" 5 1/4" = 5.25" 5 3/8" = 5.375" 5 1/2" = 5.5" 5 5/8" = 5.625" 5 3/4" = 5.75" 5 7/8" = 5.875" 6" = 6.0" 6 1/8" = 6.125" 6 1/4" = 6.25" 6 3/8" = 6.375" 6 1/2" = 6.5" 6 5/8" = 6.625" 6 3/4" = 6.75" 6 7/8" = 6.875" 7" = 7.0" 7 1/8" = 7.125" 7 1/4" = 7.25" 7 3/8" = 7.375" 7 1/2" = 7.5" 7 5/8" = 7.625" 7 3/4" = 7.75" 7 7/8" = 7.875" 8" = 8.0" 8 1/8" = 8.125" 8 1/4" = 8.25" 8 3/8" = 8.375" 8 1/2" = 8.5" 8 5/8" = 8.625" 8 3/4" = 8.75" 8 7/8" = 8.875" 9" = 9.0" 9 1/8" = 9.125" 9 1/4" = 9.25" 9 3/8" = 9.375" 9 1/2" = 9.5" 9 5/8" = 9.625" 9 3/4" = 9.75" 9 7/8" = 9.875" 10" = 10.0" 10 1/8" = 10.125" 10 1/4" = 10.25" 10 3/8" = 10.375" 10 1/2" = 10.5" 10 5/8" = 10.625" 10 3/4" = 10.75" 10 7/8" = 10.875" 11" = 11.0" 11 1/8" = 11.125" 11 1/4" = 11.25" 11 3/8" = 11.375" 11 1/2" = 11.5" 11 5/8" = 11.625" 11 3/4" = 11.75" 11 7/8" = 11.875" 12" = 12.0" 12 1/8" = 12.125" 12 1/4" = 12.25" 12 3/8" = 12.375" 12 1/2" = 12.5" 12 5/8" = 12.625" 12 3/4" = 12.75" 12 7/8" = 12.875" 13" = 13.0" 13 1/8" = 13.125" 13 1/4" = 13.25" 13 3/8" = 13.375" 13 1/2" = 13.5" 13 5/8" = 13.625" 13 3/4" = 13.75" 13 7/8" = 13.875" 14" = 14.0" 14 1/8" = 14.125" 14 1/4" = 14.25" 14 3/8" = 14.375" 14 1/2" = 14.5" 14 5/8" = 14.625" 14 3/4" = 14.75" 14 7/8" = 14.875" 15" = 15.0" 15 1/8" = 15.125" 15 1/4" = 15.25" 15 3/8" = 15.375" 15 1/2" = 15.5" 15 5/8" = 15.625" 15 3/4" = 15.75" 15 7/8" = 15.875" 16" = 16.0" 16 1/8" = 16.125" 16 1/4" = 16.25" 16 3/8" = 16.375" 16 1/2" = 16.5" 16 5/8" = 16.625" 16 3/4" = 16.75" 16 7/8" = 16.875" 17" = 17.0" 17 1/8" = 17.125" 17 1/4" = 17.25" 17 3/8" = 17.375" 17 1/2" = 17.5" 17 5/8" = 17.625" 17 3/4" = 17.75" 17 7/8" = 17.875" 18" = 18.0" 18 1/8" = 18.125" 18 1/4" = 18.25" 18 3/8" = 18.375" 18 1/2" = 18.5" 18 5/8" = 18.625" 18 3/4" = 18.75" 18 7/8" = 18.875" 19" = 19.0" 19 1/8" = 19.125" 19 1/4" = 19.25" 19 3/8" = 19.375" 19 1/2" = 19.5" 19 5/8" = 19.625" 19 3/4" = 19.75" 19 7/8" = 19.875" 20" = 20.0" 20 1/8" = 20.125" 20 1/4" = 20.25" 20 3/8" = 20.375" 20 1/2" = 20.5" 20 5/8" = 20.625" 20 3/4" = 20.75" 20 7/8" = 20.875" 21" = 21.0" 21 1/8" = 21.125" 21 1/4" = 21.25" 21 3/8" = 21.375" 21 1/2" = 21.5" 21 5/8" = 21.625" 21 3/4" = 21.75" 21 7/8" = 21.875" 22" = 22.0" 22 1/8" = 22.125" 22 1/4" = 22.25" 22 3/8" = 22.375" 22 1/2" = 22.5" 22 5/8" = 22.625" 22 3/4" = 22.75" 22 7/8" = 22.875" 23" = 23.0" 23 1/8" = 23.125" 23 1/4" = 23.25" 23 3/8" = 23.375" 23 1/2" = 23.5" 23 5/8" = 23.625" 23 3/4" = 23.75" 23 7/8" = 23.875" 24" = 24.0" 24 1/8" = 24.125" 24 1/4" = 24.25" 24 3/8" = 24.375" 24 1/2" = 24.5" 24 5/8" = 24.625" 24 3/4" = 24.75" 24 7/8" = 24.875" 25" = 25.0" 25 1/8" = 25.125" 25 1/4" = 25.25" 25 3/8" = 25.375" 25 1/2" = 25.5" 25 5/8" = 25.625" 25 3/4" = 25.75" 25 7/8" = 25.875" 26" = 26.0" 26 1/8" = 26.125" 26 1/4" = 26.25" 26 3/8" = 26.375" 26 1/2" = 26.5" 26 5/8" = 26.625" 26 3/4" = 26.75" 26 7/8" = 26.875" 27" = 27.0" 27 1/8" = 27.125" 27 1/4" = 27.25" 27 3/8" = 27.375" 27 1/2" = 27.5" 27 5/8" = 27.625" 27 3/4" = 27.75" 27 7/8" = 27.875" 28" = 28.0" 28 1/8" = 28.125" 28 1/4" = 28.25" 28 3/8" = 28.375" 28 1/2" = 28.5" 28 5/8" = 28.625" 28 3/4" = 28.75" 28 7/8" = 28.875" 29" = 29.0" 29 1/8" = 29.125" 29 1/4" = 29.25" 29 3/8" = 29.375" 29 1/2" = 29.5" 29 5/8" = 29.625" 29 3/4" = 29.75" 29 7/8" = 29.875" 30" = 30.0" 30 1/8" = 30.125" 30 1/4" = 30.25" 30 3/8" = 30.375" 30 1/2" = 30.5" 30 5/8" = 30.625" 30 3/4" = 30.75" 30 7/8" = 30.875" 31" = 31.0" 31 1/8" = 31.125" 31 1/4" = 31.25" 31 3/8" = 31.375" 31 1/2" = 31.5" 31 5/8" = 31.625" 31 3/4" = 31.75" 31 7/8" = 31.875" 32" = 32.0" 32 1/8" = 32.125" 32 1/4" = 32.25" 32 3/8" = 32.375" 32 1/2" = 32.5" 32 5/8" = 32.625" 32 3/4" = 32.75" 32 7/8" = 32.875" 33" = 33.0" 33 1/8" = 33.125" 33 1/4" = 33.25" 33 3/8" = 33.375" 33 1/2" = 33.5" 33 5/8" = 33.625" 33 3/4" = 33.75" 33 7/8" = 33.875" 34" = 34.0" 34 1/8" = 34.125" 34 1/4" = 34.25" 34 3/8" = 34.375" 34 1/2" = 34.5" 34 5/8" = 34.625" 34 3/4" = 34.75" 34 7/8" = 34.875" 35" = 35.0" 35 1/8" = 35.125" 35 1/4" = 35.25" 35 3/8" = 35.375" 35 1/2" = 35.5" 35 5/8" = 35.625" 35 3/4" = 35.75" 35 7/8" = 35.875" 36" = 36.0" 36 1/8" = 36.125" 36 1/4" = 36.25" 36 3/8" = 36.375" 36 1/2" = 36.5" 36 5/8" = 36.625" 36 3/4" = 36.75" 36 7/8" = 36.875" 37" = 37.0" 37 1/8" = 37.125" 37 1/4" = 37.25" 37 3/8" = 37.375" 37 1/2" = 37.5" 37 5/8" = 37.625" 37 3/4" = 37.75" 37 7/8" = 37.875" 38" = 38.0" 38 1/8" = 38.125" 38 1/4" = 38.25" 38 3/8" = 38.375" 38 1/2" = 38.5" 38 5/8" = 38.625" 38 3/4" = 38.75" 38 7/8" = 38.875" 39" = 39.0" 39 1/8" = 39.125" 39 1/4" = 39.25" 39 3/8" = 39.375" 39 1/2" = 39.5" 39 5/8" = 39.625" 39 3/4" = 39.75" 39 7/8" = 39.875" 40" = 40.0" 40 1/8" = 40.125" 40 1/4" = 40.25" 40 3/8" = 40.375" 40 1/2" = 40.5" 40 5/8" = 40.625" 40 3/4" = 40.75" 40 7/8" = 40.875" 41" = 41.0" 41 1/8" = 41.125" 41 1/4" = 41.25" 41 3/8" = 41.375" 41 1/2" = 41.5" 41 5/8" = 41.625" 41 3/4" = 41.75" 41 7/8" = 41.875" 42" = 42.0" 42 1/8" = 42.125" 42 1/4" = 42.25" 42 3/8" = 42.375" 42 1/2" = 42.5" 42 5/8" = 42.625" 42 3/4" = 42.75" 42 7/8" = 42.875" 43" = 43.0" 43 1/8" = 43.125" 43 1/4" = 43.25" 43 3/8" = 43.375" 43 1/2" = 43.5" 43 5/8" = 43.625" 43 3/4" = 43.75" 43 7/8" = 43.875" 44" = 44.0" 44 1/8" = 44.125" 44 1/4" = 44.25" 44 3/8" = 44.375" 44 1/2" = 44.5" 44 5/8" = 44.625" 44 3/4" = 44.75" 44 7/8" = 44.875" 45" = 45.0" 45 1/8" = 45.125" 45 1/4" = 45.25" 45 3/8" = 45.375" 45 1/2" = 45.5" 45 5/8" = 45.625" 45 3/4" = 45.75" 45 7/8" = 45.875" 46" = 46.0" 46 1/8" = 46.125" 46 1/4" = 46.25" 46 3/8" = 46.375" 46 1/2" = 46.5" 46 5/8" = 46.625" 46 3/4" = 46.75" 46 7/8" = 46.875" 47" = 47.0" 47 1/8" = 47.125" 47 1/4" = 47.25" 47 3/8" = 47.375" 47 1/2" = 47.5" 47 5/8" = 47.625" 47 3/4" = 47.75" 47 7/8" = 47.875" 48" = 48.0" 48 1/8" = 48.125" 48 1/4" = 48.25" 48 3/8" = 48.375" 48 1/2" = 48.5" 48 5/8" = 48.625" 48 3/4" = 48.75" 48 7/8" = 48.875" 49" = 49.0" 49 1/8" = 49.125" 49 1/4" = 49.25" 49 3/8" = 49.375" 49 1/2" = 49.5" 49 5/8" = 49.625" 49 3/4" = 49.75" 49 7/8" = 49.875" 50" = 50.0" 50 1/8" = 50.125" 50 1/4" = 50.25" 50 3/8" = 50.375" 50 1/2" = 50.5" 50 5/8" = 50.625" 50 3/4" = 50.75" 50 7/8" = 50.875" 51" = 51.0" 51 1/8" = 51.125" 51 1/4" = 51.25" 51 3/8" = 51.375" 51 1/2" = 51.5" 51 5/8" = 51.625" 51 3/4" = 51.75" 51 7/8" = 51.875" 52" = 52.0" 52 1/8" = 52.125" 52 1/4" = 52.25" 52 3/8" = 52.375" 52 1/2" = 52.5" 52 5/8" = 52.625" 52 3/4" = 52.75" 52 7/8" = 52.875" 53" = 53.0" 53 1/8" = 53.125" 53 1/4" = 53.25" 53 3/8" = 53.375" 53 1/2" = 53.5" 53 5/8" = 53.625" 53 3/4" = 53.75" 53 7/8" = 53.875" 54" = 54.0" 54 1/8" = 54.125" 54 1/4" = 54.25" 54 3/8" = 54.375" 54 1/2" = 54.5" 54 5/8" = 54.625" 54 3/4" = 54.75" 54 7/8" = 54.875" 55" = 55.0" 55 1/8" = 55.125" 55 1/4" = 55.25" 55 3/8" = 55.375" 55 1/2" = 55.5" 55 5/8" = 55.625" 55 3/4" = 55.75" 55 7/8" = 55.875" 56" = 56.0" 56 1/8" = 56.125" 56 1/4" = 56.25" 56 3/8" = 56.375" 56 1/2" = 56.5" 56 5/8" = 56.625" 56 3/4" = 56.75" 56 7/8" = 56.875" 57" = 57.0" 57 1/8" = 57.125" 57 1/4" = 57.25" 57 3/8" = 57.375" 57 1/2" = 57.5" 57 5/8" = 57.625" 57 3/4" = 57.75" 57 7/8" = 57.875" 58" = 58.0" 58 1/8" = 58.125" 58 1/4" = 58.25" 58 3/8" = 58.375" 58 1/2" = 58.5" 58 5/8" = 58.625" 58 3/4" = 58.75" 58 7/8" = 58.875" 59" = 59.0" 59 1/8" = 59.125" 59 1/4" = 59.25" 59 3/8" = 59.375" 59 1/2" = 59.5" 59 5/8" = 59.625" 59 3/4" = 59.75" 59 7/8" = 59.875" 60" = 60.0" 60 1/8" = 60.125" 60 1/4" = 60.25" 60 3/8" = 60.375" 60 1/2" = 60.5" 60 5/8" = 60.625" 60 3/4" = 60.75" 60 7/8" = 60.875" 61" = 61.0" 61 1/8" = 61.125" 61 1/4" = 61.25" 61 3/8" = 61.375" 61 1/2" = 61.5" 61 5/8" = 61.625" 61 3/4" = 61.75" 61 7/8" = 61.875" 62" = 62.0" 62 1/8" = 62.125" 62 1/4" = 62.25" 62 3/8" = 62.375" 62 1/2" = 62.5" 62 5/8" = 62.625" 62 3/4" = 62.75" 62 7/8" = 62.875" 63" = 63.0" 63 1/8" = 63.125" 63 1/4" = 63.25" 63 3/8" = 63.375" 63 1/2" = 63.5" 63 5/8" = 63.625" 63 3/4" = 63.75" 63 7/8" = 63.875" 64" = 64.0" 64 1/8" = 64.125" 64 1/4" = 64.25" 64 3/8" = 64.375" 64 1/2" = 64.5" 64 5/8" = 64.625" 64 3/4" = 64.75" 64 7/8" = 64.875" 65" = 65.0" 65 1/8" = 65.125" 65 1/4" = 65.25" 65 3/8" = 65.375" 65 1/2" = 65.5" 65 5/8" = 65.625" 65 3/4" = 65.75" 65 7/8" = 65.875" 66" = 66.0" 66 1/8" = 66.125" 66 1/4" = 66.25" 66 3/8" = 66.375" 66 1/2" = 66.5" 66 5/8" = 66.625" 66 3/4" = 66.75" 66 7/8" = 66.875" 67" = 67.0" 67 1/8" = 67.125" 67 1/4" = 67.25" 67 3/8" = 67.375" 67 1/2" = 67.5" 67 5/8" = 67.625" 67 3/4" = 67.75" 67 7/8" = 67.875" 68" = 68.0" 68 1/8" = 68.125" 68 1/4" = 68.25" 68 3/8" = 68.375" 68 1/2" = 68.5" 68 5/8" = 68.625" 68 3/4" = 68.75" 68 7/8" = 68.875" 69" = 69.0" 69 1/8" = 69.125" 69 1/4" = 69.25" 69 3/8" = 69.375" 69 1/2" = 69.5" 69 5/8" = 69.625" 69 3/4" = 69.75" 69 7/8" = 69.875" 70" = 70.0" 70 1/8" = 70.125" 70 1/4" = 70.25" 70 3/8" = 70.375" 70 1/2" = 70.5" 70 5/8" = 70.625" 70 3/4" = 70.75" 70 7/8" = 70.875" 71" = 71.0" 71 1/8" = 71.125" 71 1/4" = 71.25" 71 3/8" = 71.375" 71 1/2" = 71.5" 71 5/8" = 71.625" 71 3/4" = 71.75" 71 7/8" = 71.875" 72" = 72.0" 72 1/8" = 72.125" 72 1/4" = 72.25" 72 3/8" = 72.375" 72 1/2" = 72.5" 72 5/8" = 72.625" 72 3/4" = 72.75" 72 7/8" = 72.875" 73" = 73.0" 73 1/8" = 73.125" 73 1/4" = 73.25" 73 3/8" = 73.375" 73 1/2" = 73.5" 73 5/8" = 73.625" 73 3/4" = 73.75" 73 7/8" = 73.875" 74" = 74.0" 74 1/8" = 74.125" 74 1/4" = 74.25" 74 3/8" = 74.375" 74 1/2" = 74.5" 74 5/8" = 74.625" 74 3/4" = 74.75" 74 7/8" = 74.875" 75" = 75.0" 75 1/8" = 75.125" 75 1/4" = 75.25" 75 3/8" = 75	


		TOI EXERCISES: UNLESS OTHERWISE SPECIFIED	
IR REQ.		ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D	
INITIAL RELEASE DISSEMINATION		DATE BY DATE BY	
This drawing is the property of McGraw-Hill Engineering Division. It is to be used only with express permission from McGraw-Hill.		DATE BY	
DRAWN BY YOK	CHECKED BY DWT	DATE 8/19/2003	SCALE REV.
DATE NO. 111986-05		IR	




		TOLERANCES: UNLESS OTHERWISE SPECIFIED 1/16" ± 0.015 1/8" ± 0.010 1/4" ± 0.010 3/8" ± 0.010 1/2" ± 0.010 3/4" ± 0.010 1" ± 0.010 1 1/2" ± 0.010 2" ± 0.010 3" ± 0.010 4" ± 0.010 6" ± 0.010 8" ± 0.010 10" ± 0.010 12" ± 0.010 14" ± 0.010 16" ± 0.010 18" ± 0.010 20" ± 0.010 24" ± 0.010 30" ± 0.010 36" ± 0.010 42" ± 0.010 48" ± 0.010 54" ± 0.010 60" ± 0.010 66" ± 0.010 72" ± 0.010 78" ± 0.010 84" ± 0.010 90" ± 0.010 96" ± 0.010 102" ± 0.010 108" ± 0.010 114" ± 0.010 120" ± 0.010 126" ± 0.010 132" ± 0.010 138" ± 0.010 144" ± 0.010 150" ± 0.010 156" ± 0.010 162" ± 0.010 168" ± 0.010 174" ± 0.010 180" ± 0.010 186" ± 0.010 192" ± 0.010 198" ± 0.010 204" ± 0.010 210" ± 0.010 216" ± 0.010 222" ± 0.010 228" ± 0.010 234" ± 0.010 240" ± 0.010 246" ± 0.010 252" ± 0.010 258" ± 0.010 264" ± 0.010 270" ± 0.010 276" ± 0.010 282" ± 0.010 288" ± 0.010 294" ± 0.010 300" ± 0.010 306" ± 0.010 312" ± 0.010 318" ± 0.010 324" ± 0.010 330" ± 0.010 336" ± 0.010 342" ± 0.010 348" ± 0.010 354" ± 0.010 360" ± 0.010 366" ± 0.010 372" ± 0.010 378" ± 0.010 384" ± 0.010 390" ± 0.010 396" ± 0.010 402" ± 0.010 408" ± 0.010 414" ± 0.010 420" ± 0.010 426" ± 0.010 432" ± 0.010 438" ± 0.010 444" ± 0.010 450" ± 0.010 456" ± 0.010 462" ± 0.010 468" ± 0.010 474" ± 0.010 480" ± 0.010 486" ± 0.010 492" ± 0.010 498" ± 0.010 504" ± 0.010 510" ± 0.010 516" ± 0.010 522" ± 0.010 528" ± 0.010 534" ± 0.010 540" ± 0.010 546" ± 0.010 552" ± 0.010 558" ± 0.010 564" ± 0.010 570" ± 0.010 576" ± 0.010 582" ± 0.010 588" ± 0.010 594" ± 0.010 600" ± 0.010 606" ± 0.010 612" ± 0.010 618" ± 0.010 624" ± 0.010 630" ± 0.010 636" ± 0.010 642" ± 0.010 648" ± 0.010 654" ± 0.010 660" ± 0.010 666" ± 0.010 672" ± 0.010 678" ± 0.010 684" ± 0.010 690" ± 0.010 696" ± 0.010 702" ± 0.010 708" ± 0.010 714" ± 0.010 720" ± 0.010 726" ± 0.010 732" ± 0.010 738" ± 0.010 744" ± 0.010 750" ± 0.010 756" ± 0.010 762" ± 0.010 768" ± 0.010 774" ± 0.010 780" ± 0.010 786" ± 0.010 792" ± 0.010 798" ± 0.010 804" ± 0.010 810" ± 0.010 816" ± 0.010 822" ± 0.010 828" ± 0.010 834" ± 0.010 840" ± 0.010 846" ± 0.010 852" ± 0.010 858" ± 0.010 864" ± 0.010 870" ± 0.010 876" ± 0.010 882" ± 0.010 888" ± 0.010 894" ± 0.010 900" ± 0.010 906" ± 0.010 912" ± 0.010 918" ± 0.010 924" ± 0.010 930" ± 0.010 936" ± 0.010 942" ± 0.010 948" ± 0.010 954" ± 0.010 960" ± 0.010 966" ± 0.010 972" ± 0.010 978" ± 0.010 984" ± 0.010 990" ± 0.010 996" ± 0.010 1000" ± 0.010	
		ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D	
DATE: 8/19/2003 SCALE: 1" = 10'-0" REV: IR	DATE: 8/19/2003 SCALE: 1" = 10'-0" REV: IR		





		TOLERANCES:	
		UNLESS OTHERWISE SPECIFIED	
1/16" ± 0.015 1/32" ± 0.010 1/64" ± 0.005 1/8" ± 0.010 1/4" ± 0.015 3/8" ± 0.020 1/2" ± 0.025 3/4" ± 0.030 1" ± 0.040 1 1/2" ± 0.050 2" ± 0.060 3" ± 0.075 4" ± 0.090 6" ± 0.120 8" ± 0.150 10" ± 0.180 12" ± 0.210 14" ± 0.240 16" ± 0.270 18" ± 0.300 20" ± 0.330 24" ± 0.400 30" ± 0.500 36" ± 0.600 42" ± 0.700 48" ± 0.800 54" ± 0.900 60" ± 1.000		1/16" ± 0.015 1/32" ± 0.010 1/64" ± 0.005 1/8" ± 0.010 1/4" ± 0.015 3/8" ± 0.020 1/2" ± 0.025 3/4" ± 0.030 1" ± 0.040 1 1/2" ± 0.050 2" ± 0.060 3" ± 0.075 4" ± 0.090 6" ± 0.120 8" ± 0.150 10" ± 0.180 12" ± 0.210 14" ± 0.240 16" ± 0.270 18" ± 0.300 20" ± 0.330 24" ± 0.400 30" ± 0.500 36" ± 0.600 42" ± 0.700 48" ± 0.800 54" ± 0.900 60" ± 1.000	
ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		INITIAL RELEASE DATE: 11/19/2003 BY: [Signature] DWT: [Signature]	
111986-05		111986-05	




		TOLERANCES: UNLESS OTHERWISE SPECIFIED 1/16" = 0.0156" 1/32" = 0.0078" 1/64" = 0.0039" 3/16" = 0.0156" 1/2" = 0.0312" 3/4" = 0.0469" 1" = 0.0625" 1 1/2" = 0.0938" 2" = 0.125" 3" = 0.1875" 4" = 0.25" 6" = 0.375" 8" = 0.5" 10" = 0.625" 12" = 0.75" 14" = 0.875" 16" = 1.0" 18" = 1.125" 20" = 1.25" 24" = 1.5" 30" = 1.875" 36" = 2.25" 42" = 2.625" 48" = 3.0" 54" = 3.375" 60" = 3.75" 72" = 4.5" 84" = 5.25" 96" = 6.0" 108" = 6.75" 120" = 7.5" 132" = 8.25" 144" = 9.0" 156" = 9.75" 168" = 10.5" 180" = 11.25" 192" = 12.0" 204" = 12.75" 216" = 13.5" 228" = 14.25" 240" = 15.0" 252" = 15.75" 264" = 16.5" 276" = 17.25" 288" = 18.0" 300" = 18.75" 312" = 19.5" 324" = 20.25" 336" = 21.0" 348" = 21.75" 360" = 22.5" 372" = 23.25" 384" = 24.0" 396" = 24.75" 408" = 25.5" 420" = 26.25" 432" = 27.0" 444" = 27.75" 456" = 28.5" 468" = 29.25" 480" = 30.0" 492" = 30.75" 504" = 31.5" 516" = 32.25" 528" = 33.0" 540" = 33.75" 552" = 34.5" 564" = 35.25" 576" = 36.0" 588" = 36.75" 600" = 37.5" 612" = 38.25" 624" = 39.0" 636" = 39.75" 648" = 40.5" 660" = 41.25" 672" = 42.0" 684" = 42.75" 696" = 43.5" 708" = 44.25" 720" = 45.0" 732" = 45.75" 744" = 46.5" 756" = 47.25" 768" = 48.0" 780" = 48.75" 792" = 49.5" 804" = 50.25" 816" = 51.0" 828" = 51.75" 840" = 52.5" 852" = 53.25" 864" = 54.0" 876" = 54.75" 888" = 55.5" 900" = 56.25" 912" = 57.0" 924" = 57.75" 936" = 58.5" 948" = 59.25" 960" = 60.0" 972" = 60.75" 984" = 61.5" 996" = 62.25" 1008" = 63.0" 1020" = 63.75" 1032" = 64.5" 1044" = 65.25" 1056" = 66.0" 1068" = 66.75" 1080" = 67.5" 1092" = 68.25" 1104" = 69.0" 1116" = 69.75" 1128" = 70.5" 1140" = 71.25" 1152" = 72.0" 1164" = 72.75" 1176" = 73.5" 1188" = 74.25" 1200" = 75.0" 1212" = 75.75" 1224" = 76.5" 1236" = 77.25" 1248" = 78.0" 1260" = 78.75" 1272" = 79.5" 1284" = 80.25" 1296" = 81.0" 1308" = 81.75" 1320" = 82.5" 1332" = 83.25" 1344" = 84.0" 1356" = 84.75" 1368" = 85.5" 1380" = 86.25" 1392" = 87.0" 1404" = 87.75" 1416" = 88.5" 1428" = 89.25" 1440" = 90.0" 1452" = 90.75" 1464" = 91.5" 1476" = 92.25" 1488" = 93.0" 1500" = 93.75" 1512" = 94.5" 1524" = 95.25" 1536" = 96.0" 1548" = 96.75" 1560" = 97.5" 1572" = 98.25" 1584" = 99.0" 1596" = 99.75" 1608" = 100.5" 1620" = 101.25" 1632" = 102.0" 1644" = 102.75" 1656" = 103.5" 1668" = 104.25" 1680" = 105.0" 1692" = 105.75" 1704" = 106.5" 1716" = 107.25" 1728" = 108.0" 1740" = 108.75" 1752" = 109.5" 1764" = 110.25" 1776" = 111.0" 1788" = 111.75" 1800" = 112.5" 1812" = 113.25" 1824" = 114.0" 1836" = 114.75" 1848" = 115.5" 1860" = 116.25" 1872" = 117.0" 1884" = 117.75" 1896" = 118.5" 1908" = 119.25" 1920" = 120.0" 1932" = 120.75" 1944" = 121.5" 1956" = 122.25" 1968" = 123.0" 1980" = 123.75" 1992" = 124.5" 2004" = 125.25" 2016" = 126.0" 2028" = 126.75" 2040" = 127.5" 2052" = 128.25" 2064" = 129.0" 2076" = 129.75" 2088" = 130.5" 2100" = 131.25" 2112" = 132.0" 2124" = 132.75" 2136" = 133.5" 2148" = 134.25" 2160" = 135.0" 2172" = 135.75" 2184" = 136.5" 2196" = 137.25" 2208" = 138.0" 2220" = 138.75" 2232" = 139.5" 2244" = 140.25" 2256" = 141.0" 2268" = 141.75" 2280" = 142.5" 2292" = 143.25" 2304" = 144.0" 2316" = 144.75" 2328" = 145.5" 2340" = 146.25" 2352" = 147.0" 2364" = 147.75" 2376" = 148.5" 2388" = 149.25" 2400" = 150.0" 2412" = 150.75" 2424" = 151.5" 2436" = 152.25" 2448" = 153.0" 2460" = 153.75" 2472" = 154.5" 2484" = 155.25" 2496" = 156.0" 2508" = 156.75" 2520" = 157.5" 2532" = 158.25" 2544" = 159.0" 2556" = 159.75" 2568" = 160.5" 2580" = 161.25" 2592" = 162.0" 2604" = 162.75" 2616" = 163.5" 2628" = 164.25" 2640" = 165.0" 2652" = 165.75" 2664" = 166.5" 2676" = 167.25" 2688" = 168.0" 2700" = 168.75" 2712" = 169.5" 2724" = 170.25" 2736" = 171.0" 2748" = 171.75" 2760" = 172.5" 2772" = 173.25" 2784" = 174.0" 2796" = 174.75" 2808" = 175.5" 2820" = 176.25" 2832" = 177.0" 2844" = 177.75" 2856" = 178.5" 2868" = 179.25" 2880" = 180.0" 2892" = 180.75" 2904" = 181.5" 2916" = 182.25" 2928" = 183.0" 2940" = 183.75" 2952" = 184.5" 2964" = 185.25" 2976" = 186.0" 2988" = 186.75" 3000" = 187.5" 3012" = 188.25" 3024" = 189.0" 3036" = 189.75" 3048" = 190.5" 3060" = 191.25" 3072" = 192.0" 3084" = 192.75" 3096" = 193.5" 3108" = 194.25" 3120" = 195.0" 3132" = 195.75" 3144" = 196.5" 3156" = 197.25" 3168" = 198.0" 3180" = 198.75" 3192" = 199.5" 3204" = 200.25" 3216" = 201.0" 3228" = 201.75" 3240" = 202.5" 3252" = 203.25" 3264" = 204.0" 3276" = 204.75" 3288" = 205.5" 3300" = 206.25" 3312" = 207.0" 3324" = 207.75" 3336" = 208.5" 3348" = 209.25" 3360" = 210.0" 3372" = 210.75" 3384" = 211.5" 3396" = 212.25" 3408" = 213.0" 3420" = 213.75" 3432" = 214.5" 3444" = 215.25" 3456" = 216.0" 3468" = 216.75" 3480" = 217.5" 3492" = 218.25" 3504" = 219.0" 3516" = 219.75" 3528" = 220.5" 3540" = 221.25" 3552" = 222.0" 3564" = 222.75" 3576" = 223.5" 3588" = 224.25" 3600" = 225.0" 3612" = 225.75" 3624" = 226.5" 3636" = 227.25" 3648" = 228.0" 3660" = 228.75" 3672" = 229.5" 3684" = 230.25" 3696" = 231.0" 3708" = 231.75" 3720" = 232.5" 3732" = 233.25" 3744" = 234.0" 3756" = 234.75" 3768" = 235.5" 3780" = 236.25" 3792" = 237.0" 3804" = 237.75" 3816" = 238.5" 3828" = 239.25" 3840" = 240.0" 3852" = 240.75" 3864" = 241.5" 3876" = 242.25" 3888" = 243.0" 3900" = 243.75" 3912" = 244.5" 3924" = 245.25" 3936" = 246.0" 3948" = 246.75" 3960" = 247.5" 3972" = 248.25" 3984" = 249.0" 3996" = 249.75" 4008" = 250.5" 4020" = 251.25" 4032" = 252.0" 4044" = 252.75" 4056" = 253.5" 4068" = 254.25" 4080" = 255.0" 4092" = 255.75" 4104" = 256.5" 4116" = 257.25" 4128" = 258.0" 4140" = 258.75" 4152" = 259.5" 4164" = 260.25" 4176" = 261.0" 4188" = 261.75" 4200" = 262.5" 4212" = 263.25" 4224" = 264.0" 4236" = 264.75" 4248" = 265.5" 4260" = 266.25" 4272" = 267.0" 4284" = 267.75" 4296" = 268.5" 4308" = 269.25" 4320" = 270.0" 4332" = 270.75" 4344" = 271.5" 4356" = 272.25" 4368" = 273.0" 4380" = 273.75" 4392" = 274.5" 4404" = 275.25" 4416" = 276.0" 4428" = 276.75" 4440" = 277.5" 4452" = 278.25" 4464" = 279.0" 4476" = 279.75" 4488" = 280.5" 4500" = 281.25" 4512" = 282.0" 4524" = 282.75" 4536" = 283.5" 4548" = 284.25" 4560" = 285.0" 4572" = 285.75" 4584" = 286.5" 4596" = 287.25" 4608" = 288.0" 4620" = 288.75" 4632" = 289.5" 4644" = 290.25" 4656" = 291.0" 4668" = 291.75" 4680" = 292.5" 4692" = 293.25" 4704" = 294.0" 4716" = 294.75" 4728" = 295.5" 4740" = 296.25" 4752" = 297.0" 4764" = 297.75" 4776" = 298.5" 4788" = 299.25" 4800" = 300.0" 4812" = 300.75" 4824" = 301.5" 4836" = 302.25" 4848" = 303.0" 4860" = 303.75" 4872" = 304.5" 4884" = 305.25" 4896" = 306.0" 4908" = 306.75" 4920" = 307.5" 4932" = 308.25" 4944" = 309.0" 4956" = 309.75" 4968" = 310.5" 4980" = 311.25" 4992" = 312.0" 5004" = 312.75" 5016" = 313.5" 5028" = 314.25" 5040" = 315.0" 5052" = 315.75" 5064" = 316.5" 5076" = 317.25" 5088" = 318.0" 5100" = 318.75" 5112" = 319.5" 5124" = 320.25" 5136" = 321.0" 5148" = 321.75" 5160" = 322.5" 5172" = 323.25" 5184" = 324.0" 5196" = 324.75" 5208" = 325.5" 5220" = 326.25" 5232" = 327.0" 5244" = 327.75" 5256" = 328.5" 5268" = 329.25" 5280" = 330.0" 5292" = 330.75" 5304" = 331.5" 5316" = 332.25" 5328" = 333.0" 5340" = 333.75" 5352" = 334.5" 5364" = 335.25" 5376" = 336.0" 5388" = 336.75" 5400" = 337.5" 5412" = 338.25" 5424" = 339.0" 5436" = 339.75" 5448" = 340.5" 5460" = 341.25" 5472" = 342.0" 5484" = 342.75" 5496" = 343.5" 5508" = 344.25" 5520" = 345.0" 5532" = 345.75" 5544" = 346.5" 5556" = 347.25" 5568" = 348.0" 5580" = 348.75" 5592" = 349.5" 5604" = 350.25" 5616" = 351.0" 5628" = 351.75" 5640" = 352.5" 5652" = 353.25" 5664" = 354.0" 5676" = 354.75" 5688" = 355.5" 5700" = 356.25" 5712" = 357.0" 5724" = 357.75" 5736" = 358.5" 5748" = 359.25" 5760" = 360.0" 5772" = 360.75" 5784" = 361.5" 5796" = 362.25" 5808" = 363.0" 5820" = 363.75" 5832" = 364.5" 5844" = 365.25" 5856" = 366.0" 5868" = 366.75" 5880" = 367.5" 5892" = 368.25" 5904" = 369.0" 5916" = 369.75" 5928" = 370.5" 5940" = 371.25" 5952" = 372.0" 5964" = 372.75" 5976" = 373.5" 5988" = 374.25" 6000" = 375.0" 6012" = 375.75" 6024" = 376.5" 6036" = 377.25" 6048" = 378.0" 6060" = 378.75" 6072" = 379.5" 6084" = 380.25" 6096" = 381.0" 6108" = 381.75" 6120" = 382.5" 6132" = 383.25" 6144" = 384.0" 6156" = 384.75" 6168" = 385.5" 6180" = 386.25" 6192" = 387.0" 6204" = 387.75" 6216" = 388.5" 6228" = 389.25" 6240" = 390.0" 6252" = 390.75" 6264" = 391.5" 6276" = 392.25" 6288" = 393.0" 6300" = 393.75" 6312" = 394.5" 6324" = 395.25" 6336" = 396.0" 6348" = 396.75" 6360" = 397.5" 6372" = 398.25" 6384" = 399.0" 6396" = 399.75" 6408" = 400.5" 6420" = 401.25" 6432" = 402.0" 6444" = 402.75" 6456" = 403.5" 6468" = 404.25" 6480" = 405.0" 6492" = 405.75" 6504" = 406.5" 6516" = 407.25" 6528" = 408.0" 6540" = 408.75" 6552" = 409.5" 6564" = 410.25" 6576" = 411.0" 6588" = 411.75" 6600" = 412.5" 6612" = 413.25" 6624" = 414.0" 6636" = 414.75" 6648" = 415.5" 6660" = 416.25" 6672" = 417.0" 6684" = 417.75" 6696" = 418.5" 6708" = 419.25" 6720" = 420.0" 6732" = 420.75" 6744" = 421.5" 6756" = 422.25" 6768" = 423.0" 6780" = 423.75" 6792" = 424.5" 6804" = 425.25" 6816" = 426.0" 6828" = 426.75" 6840" = 427.5" 6852" = 428.25" 6864" = 429.0" 6876" = 429.75" 6888" = 430.5" 6900" = 431.25" 6912" = 432.0" 6924" = 432.75" 6936" = 433.5" 6948" = 434.25" 6960" = 435.0" 6972" = 435.75" 6984" = 436.5" 6996" = 437.25" 7008" = 438.0" 7020" = 438.75" 7032" = 439.5" 7044" = 440.25" 7056" = 441.0" 7068" = 441.75" 7080" = 442.5" 7092" = 443.25" 7104" = 444.0" 7116" = 444.75" 7128" = 445.5" 7140" = 446.25" 7152" = 447.0" 7164" = 447.75" 7176" = 448.5" 7188" = 449.25" 7200" = 450.0" 7212" = 450.75" 7224" = 451.5" 7236" = 452.25" 7248" = 453.0" 7260" = 453.75" 7272" = 454.5" 7284" = 455.25" 7296" = 456.0" 7308" = 456.75" 7320" = 457.5" 7332" = 458.25" 7344" = 459.0" 7356" = 459.75" 7368" = 460.5" 7380" = 461.25" 7392" = 462.0" 7404" = 462.75" 7416" = 463.5" 7428" = 464.25" 7440" = 465.0" 7452" = 465.75" 7464" = 466.5" 7476" = 467.25" 7488" = 468.0" 7500" = 468.75" 7512" = 469.5" 7524" = 470.25" 7536" = 471.0" 7548" = 471.75" 7560" = 472.5" 7572" = 473.25" 7584" = 474.0" 7596" = 474.75" 7608" = 475.5" 7620" = 476.25" 7632" = 477.0" 7644" = 477.75" 7656" = 478.5" 7668" = 479.25" 7680" = 480.0" 7692" = 480.75" 7704" = 481.5" 7716" = 482.25" 7728" = 483.0" 7740" = 483.75" 7752" = 484.	
--	--	--	--




		TOLERANCES: UNLESS OTHERWISE SPECIFIED IN. = 0.015 FRACTIONS = 1/16"	
		SURFACE CASING 13 3/8" INTERMEDIATE CASING 9 5/8" PRODUCTION CASING 4.5" CONDUCTOR PIPE 30" TUBING 4.5"	
IR REV. 1 DESCRIPTION INITIAL RELEASE	DATE 8/19/2003	BY [Signature]	CHECKED [Signature]
ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		This drawing is the property of M&H. It is to be used only with express permission from M&H.	
DRAWING NO. 111986-05		SCALE 1" = 10'	




		TOLERANCES: UNLESS OTHERWISE SPECIFIED IN = 0.015 FRACTIONS = 1/16" DECIMALS = 0.001" HOLE CIRCLES = 0.001" DIMENSIONS IN INCHES AND FEET	
		ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D	
IR INITIAL RELEASE	DATE: 07/19/2003 BY: [Signature] CHECKED: [Signature]	This drawing is the property of M&H. It is to be used only with express permission from M&H.	
Dwg No. 111986-05	IR	SCALE: 1" = 10'	




		TOLERANCES: UNLESS OTHERWISE SPECIFIED IN. = 0.015 FRACTIONS = 1/16"	
		FINISHES: SURFACES TO BE MACHINED UNLESS OTHERWISE SPECIFIED UNLESS OTHERWISE SPECIFIED UNLESS OTHERWISE SPECIFIED	
IR REV. 1 DESCRIPTION INITIAL RELEASE	DATE BY CHECKED DATE	DATE BY CHECKED DATE	DATE BY CHECKED DATE
ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		This drawing is the property of M&H. It is to be used only with express permission from M&H.	
111986-05		IR	




		TOLERANCES: UNLESS OTHERWISE SPECIFIED 1/16" ± 0.015 1/8" ± 0.010 3/16" ± 0.010 1/2" ± 0.015 3/4" ± 0.020 1" ± 0.030 1 1/2" ± 0.040 2" ± 0.050 3" ± 0.060 4" ± 0.070 6" ± 0.090 8" ± 0.110 10" ± 0.130 12" ± 0.150 14" ± 0.170 16" ± 0.190 18" ± 0.210 20" ± 0.230 24" ± 0.270 30" ± 0.330 36" ± 0.400 42" ± 0.470 48" ± 0.540 54" ± 0.610 60" ± 0.680 66" ± 0.750 72" ± 0.820 78" ± 0.890 84" ± 0.960 90" ± 1.030 96" ± 1.100 102" ± 1.170 108" ± 1.240 114" ± 1.310 120" ± 1.380 126" ± 1.450 132" ± 1.520 138" ± 1.590 144" ± 1.660 150" ± 1.730 156" ± 1.800 162" ± 1.870 168" ± 1.940 174" ± 2.010 180" ± 2.080 186" ± 2.150 192" ± 2.220 198" ± 2.290 204" ± 2.360 210" ± 2.430 216" ± 2.500 222" ± 2.570 228" ± 2.640 234" ± 2.710 240" ± 2.780 246" ± 2.850 252" ± 2.920 258" ± 2.990 264" ± 3.060 270" ± 3.130 276" ± 3.200 282" ± 3.270 288" ± 3.340 294" ± 3.410 300" ± 3.480 306" ± 3.550 312" ± 3.620 318" ± 3.690 324" ± 3.760 330" ± 3.830 336" ± 3.900 342" ± 3.970 348" ± 4.040 354" ± 4.110 360" ± 4.180 366" ± 4.250 372" ± 4.320 378" ± 4.390 384" ± 4.460 390" ± 4.530 396" ± 4.600 402" ± 4.670 408" ± 4.740 414" ± 4.810 420" ± 4.880 426" ± 4.950 432" ± 5.020 438" ± 5.090 444" ± 5.160 450" ± 5.230 456" ± 5.300 462" ± 5.370 468" ± 5.440 474" ± 5.510 480" ± 5.580 486" ± 5.650 492" ± 5.720 498" ± 5.790 504" ± 5.860 510" ± 5.930 516" ± 6.000 522" ± 6.070 528" ± 6.140 534" ± 6.210 540" ± 6.280 546" ± 6.350 552" ± 6.420 558" ± 6.490 564" ± 6.560 570" ± 6.630 576" ± 6.700 582" ± 6.770 588" ± 6.840 594" ± 6.910 600" ± 6.980 606" ± 7.050 612" ± 7.120 618" ± 7.190 624" ± 7.260 630" ± 7.330 636" ± 7.400 642" ± 7.470 648" ± 7.540 654" ± 7.610 660" ± 7.680 666" ± 7.750 672" ± 7.820 678" ± 7.890 684" ± 7.960 690" ± 8.030 696" ± 8.100 702" ± 8.170 708" ± 8.240 714" ± 8.310 720" ± 8.380 726" ± 8.450 732" ± 8.520 738" ± 8.590 744" ± 8.660 750" ± 8.730 756" ± 8.800 762" ± 8.870 768" ± 8.940 774" ± 9.010 780" ± 9.080 786" ± 9.150 792" ± 9.220 798" ± 9.290 804" ± 9.360 810" ± 9.430 816" ± 9.500 822" ± 9.570 828" ± 9.640 834" ± 9.710 840" ± 9.780 846" ± 9.850 852" ± 9.920 858" ± 9.990 864" ± 10.060 870" ± 10.130 876" ± 10.200 882" ± 10.270 888" ± 10.340 894" ± 10.410 900" ± 10.480 906" ± 10.550 912" ± 10.620 918" ± 10.690 924" ± 10.760 930" ± 10.830 936" ± 10.900 942" ± 10.970 948" ± 11.040 954" ± 11.110 960" ± 11.180 966" ± 11.250 972" ± 11.320 978" ± 11.390 984" ± 11.460 990" ± 11.530 996" ± 11.600 1002" ± 11.670 1008" ± 11.740 1014" ± 11.810 1020" ± 11.880 1026" ± 11.950 1032" ± 12.020 1038" ± 12.090 1044" ± 12.160 1050" ± 12.230 1056" ± 12.300 1062" ± 12.370 1068" ± 12.440 1074" ± 12.510 1080" ± 12.580 1086" ± 12.650 1092" ± 12.720 1098" ± 12.790 1104" ± 12.860 1110" ± 12.930 1116" ± 13.000 1122" ± 13.070 1128" ± 13.140 1134" ± 13.210 1140" ± 13.280 1146" ± 13.350 1152" ± 13.420 1158" ± 13.490 1164" ± 13.560 1170" ± 13.630 1176" ± 13.700 1182" ± 13.770 1188" ± 13.840 1194" ± 13.910 1200" ± 13.980 1206" ± 14.050 1212" ± 14.120 1218" ± 14.190 1224" ± 14.260 1230" ± 14.330 1236" ± 14.400 1242" ± 14.470 1248" ± 14.540 1254" ± 14.610 1260" ± 14.680 1266" ± 14.750 1272" ± 14.820 1278" ± 14.890 1284" ± 14.960 1290" ± 15.030 1296" ± 15.100 1302" ± 15.170 1308" ± 15.240 1314" ± 15.310 1320" ± 15.380 1326" ± 15.450 1332" ± 15.520 1338" ± 15.590 1344" ± 15.660 1350" ± 15.730 1356" ± 15.800 1362" ± 15.870 1368" ± 15.940 1374" ± 16.010 1380" ± 16.080 1386" ± 16.150 1392" ± 16.220 1398" ± 16.290 1404" ± 16.360 1410" ± 16.430 1416" ± 16.500 1422" ± 16.570 1428" ± 16.640 1434" ± 16.710 1440" ± 16.780 1446" ± 16.850 1452" ± 16.920 1458" ± 16.990 1464" ± 17.060 1470" ± 17.130 1476" ± 17.200 1482" ± 17.270 1488" ± 17.340 1494" ± 17.410 1500" ± 17.480 1506" ± 17.550 1512" ± 17.620 1518" ± 17.690 1524" ± 17.760 1530" ± 17.830 1536" ± 17.900 1542" ± 17.970 1548" ± 18.040 1554" ± 18.110 1560" ± 18.180 1566" ± 18.250 1572" ± 18.320 1578" ± 18.390 1584" ± 18.460 1590" ± 18.530 1596" ± 18.600 1602" ± 18.670 1608" ± 18.740 1614" ± 18.810 1620" ± 18.880 1626" ± 18.950 1632" ± 19.020 1638" ± 19.090 1644" ± 19.160 1650" ± 19.230 1656" ± 19.300 1662" ± 19.370 1668" ± 19.440 1674" ± 19.510 1680" ± 19.580 1686" ± 19.650 1692" ± 19.720 1698" ± 19.790 1704" ± 19.860 1710" ± 19.930 1716" ± 20.000 1722" ± 20.070 1728" ± 20.140 1734" ± 20.210 1740" ± 20.280 1746" ± 20.350 1752" ± 20.420 1758" ± 20.490 1764" ± 20.560 1770" ± 20.630 1776" ± 20.700 1782" ± 20.770 1788" ± 20.840 1794" ± 20.910 1800" ± 20.980 1806" ± 21.050 1812" ± 21.120 1818" ± 21.190 1824" ± 21.260 1830" ± 21.330 1836" ± 21.400 1842" ± 21.470 1848" ± 21.540 1854" ± 21.610 1860" ± 21.680 1866" ± 21.750 1872" ± 21.820 1878" ± 21.890 1884" ± 21.960 1890" ± 22.030 1896" ± 22.100 1902" ± 22.170 1908" ± 22.240 1914" ± 22.310 1920" ± 22.380 1926" ± 22.450 1932" ± 22.520 1938" ± 22.590 1944" ± 22.660 1950" ± 22.730 1956" ± 22.800 1962" ± 22.870 1968" ± 22.940 1974" ± 23.010 1980" ± 23.080 1986" ± 23.150 1992" ± 23.220 1998" ± 23.290 2004" ± 23.360 2010" ± 23.430 2016" ± 23.500 2022" ± 23.570 2028" ± 23.640 2034" ± 23.710 2040" ± 23.780 2046" ± 23.850 2052" ± 23.920 2058" ± 23.990 2064" ± 24.060 2070" ± 24.130 2076" ± 24.200 2082" ± 24.270 2088" ± 24.340 2094" ± 24.410 2100" ± 24.480 2106" ± 24.550 2112" ± 24.620 2118" ± 24.690 2124" ± 24.760 2130" ± 24.830 2136" ± 24.900 2142" ± 24.970 2148" ± 25.040 2154" ± 25.110 2160" ± 25.180 2166" ± 25.250 2172" ± 25.320 2178" ± 25.390 2184" ± 25.460 2190" ± 25.530 2196" ± 25.600 2202" ± 25.670 2208" ± 25.740 2214" ± 25.810 2220" ± 25.880 2226" ± 25.950 2232" ± 26.020 2238" ± 26.090 2244" ± 26.160 2250" ± 26.230 2256" ± 26.300 2262" ± 26.370 2268" ± 26.440 2274" ± 26.510 2280" ± 26.580 2286" ± 26.650 2292" ± 26.720 2298" ± 26.790 2304" ± 26.860 2310" ± 26.930 2316" ± 27.000 2322" ± 27.070 2328" ± 27.140 2334" ± 27.210 2340" ± 27.280 2346" ± 27.350 2352" ± 27.420 2358" ± 27.490 2364" ± 27.560 2370" ± 27.630 2376" ± 27.700 2382" ± 27.770 2388" ± 27.840 2394" ± 27.910 2400" ± 27.980 2406" ± 28.050 2412" ± 28.120 2418" ± 28.190 2424" ± 28.260 2430" ± 28.330 2436" ± 28.400 2442" ± 28.470 2448" ± 28.540 2454" ± 28.610 2460" ± 28.680 2466" ± 28.750 2472" ± 28.820 2478" ± 28.890 2484" ± 28.960 2490" ± 29.030 2496" ± 29.100 2502" ± 29.170 2508" ± 29.240 2514" ± 29.310 2520" ± 29.380 2526" ± 29.450 2532" ± 29.520 2538" ± 29.590 2544" ± 29.660 2550" ± 29.730 2556" ± 29.800 2562" ± 29.870 2568" ± 29.940 2574" ± 30.010 2580" ± 30.080 2586" ± 30.150 2592" ± 30.220 2598" ± 30.290 2604" ± 30.360 2610" ± 30.430 2616" ± 30.500 2622" ± 30.570 2628" ± 30.640 2634" ± 30.710 2640" ± 30.780 2646" ± 30.850 2652" ± 30.920 2658" ± 30.990 2664" ± 31.060 2670" ± 31.130 2676" ± 31.200 2682" ± 31.270 2688" ± 31.340 2694" ± 31.410 2700" ± 31.480 2706" ± 31.550 2712" ± 31.620 2718" ± 31.690 2724" ± 31.760 2730" ± 31.830 2736" ± 31.900 2742" ± 31.970 2748" ± 32.040 2754" ± 32.110 2760" ± 32.180 2766" ± 32.250 2772" ± 32.320 2778" ± 32.390 2784" ± 32.460 2790" ± 32.530 2796" ± 32.600 2802" ± 32.670 2808" ± 32.740 2814" ± 32.810 2820" ± 32.880 2826" ± 32.950 2832" ± 33.020 2838" ± 33.090 2844" ± 33.160 2850" ± 33.230 2856" ± 33.300 2862" ± 33.370 2868" ± 33.440 2874" ± 33.510 2880" ± 33.580 2886" ± 33.650 2892" ± 33.720 2898" ± 33.790 2904" ± 33.860 2910" ± 33.930 2916" ± 34.000 2922" ± 34.070 2928" ± 34.140 2934" ± 34.210 2940" ± 34.280 2946" ± 34.350 2952" ± 34.420 2958" ± 34.490 2964" ± 34.560 2970" ± 34.630 2976" ± 34.700 2982" ± 34.770 2988" ± 34.840 2994" ± 34.910 3000" ± 34.980 3006" ± 35.050 3012" ± 35.120 3018" ± 35.190 3024" ± 35.260 3030" ± 35.330 3036" ± 35.400 3042" ± 35.470 3048" ± 35.540 3054" ± 35.610 3060" ± 35.680 3066" ± 35.750 3072" ± 35.820 3078" ± 35.890 3084" ± 35.960 3090" ± 36.030 3096" ± 36.100 3102" ± 36.170 3108" ± 36.240 3114" ± 36.310 3120" ± 36.380 3126" ± 36.450 3132" ± 36.520 3138" ± 36.590 3144" ± 36.660 3150" ± 36.730 3156" ± 36.800 3162" ± 36.870 3168" ± 36.940 3174" ± 37.010 3180" ± 37.080 3186" ± 37.150 3192" ± 37.220 3198" ± 37.290 3204" ± 37.360 3210" ± 37.430 3216" ± 37.500 3222" ± 37.570 3228" ± 37.640 3234" ± 37.710 3240" ± 37.780 3246" ± 37.850 3252" ± 37.920 3258" ± 37.990 3264" ± 38.060 3270" ± 38.130 3276" ± 38.200 3282" ± 38.270 3288" ± 38.340 3294" ± 38.410 3300" ± 38.480 3306" ± 38.550 3312" ± 38.620 3318" ± 38.690 3324" ± 38.760 3330" ± 38.830 3336" ± 38.900 3342" ± 38.970 3348" ± 39.040 3354" ± 39.110 3360" ± 39.180 3366" ± 39.250 3372" ± 39.320 3378" ± 39.390 3384" ± 39.460 3390" ± 39.530 3396" ± 39.600 3402" ± 39.670 3408" ± 39.740 3414" ± 39.810 3420" ± 39.880 3426" ± 39.950 3432" ± 40.020 3438" ± 40.090 3444" ± 40.160 3450" ± 40.230 3456" ± 40.300 3462" ± 40.370 3468" ± 40.440 3474" ± 40.510 3480" ± 40.580 3486" ± 40.650 3492" ± 40.720 3498" ± 40.790 3504" ± 40.860 3510" ± 40.930 3516" ± 41.000 3522" ± 41.070 3528" ± 41.140 3534" ± 41.210 3540" ± 41.280 3546" ± 41.350 3552" ± 41.420 3558" ± 41.490 3564" ± 41.560 3570" ± 41.630 3576" ± 41.700 3582" ± 41.770 3588" ± 41.840 3594" ± 41.910 3600" ± 41.980 3606" ± 42.050 3612" ± 42.120 3618" ± 42.190 3624" ± 42.260 3630" ± 42.330 3636" ± 42.400 3642" ± 42.470 3648" ± 42.540 3654" ± 42.610 3660" ± 42.680 3666" ± 42.750 3672" ± 42.820 3678" ± 42.890 3684" ± 42.960 3690" ± 43.030 3696" ± 43.100 3702" ± 43.170 3708" ± 43.240 3714" ± 43.310 3720" ± 43.380 3726" ± 43.450 3732" ± 43.520 3738" ± 43.590 3744" ± 43.660 3750" ± 43.730 3756" ± 43.800 3762" ± 43.870 3768" ± 43.940 3774" ± 44.010 3780" ± 44.080 3786" ± 44.150 3792" ± 44.220 3798" ± 44.290 3804" ± 44.360 3810" ± 44.430 3816" ± 44.500 3822" ± 44.570 3828" ± 44.640 3834" ± 44.710 3840" ± 44.780 3846" ± 44.850 3852" ± 44.920 3858" ± 44.990 3864" ± 45.060 3870" ± 45.130 3876" ± 45.200 3882" ± 45.270 3888" ± 45.340 3894" ± 45.410 3900" ± 45.480 3906" ± 45.550 3912" ± 45.620 3918" ± 45.690 3924" ± 45.760 3930" ± 45.830 3936" ± 45.900 3942" ± 45.970 3948" ± 46.040 3954" ± 46.110 3960" ± 46.180 3966" ± 46.250 3972" ± 46.320 3978" ± 46.390 3984" ± 46.460 3990" ± 46.530 3996" ± 46.600 4002" ± 46.670 4008" ± 46.740 4014" ± 46.810 4020" ± 46.880 4026" ± 46.950 4032" ± 47.020 	
--	--	--	--




		TOLERANCES: UNLESS OTHERWISE SPECIFIED IN. = 0.015 FRACTIONS 1/16"		
		FINISHES: 1/16" 125 MAX BRINEL HARDNESS 125 MAX CONDUCTIVITY PER MIL. 600 MAX DIMENSIONS ARE IN INCHES		
IR	REV	DATE	BY	CHK'D
INITIAL RELEASE DESCRIPTION ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		This drawing is the property of M&H and is to be used only with express permission from M&H.		
UNIFORM/STANDARD		DATE	BY	CHK'D
111986-05		DATE	BY	CHK'D
IR		DATE	BY	CHK'D




		TOLERANCES: UNLESS OTHERWISE SPECIFIED IN = 0.015 FRACTIONS = 1/16 DECIMALS = 0.001 ANGLES = 1/16 SURFACE FINISH = 125 DIMENSIONS ARE IN INCHES DIMENSIONS ARE IN MILLIMETERS	
		THIS DRAWING IS THE PROPERTY OF IT IS TO BE KEPT IN THE OFFICE OF THE DESIGNER AND NOT TO BE REPRODUCED OR COPIED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF THE DESIGNER	
IR REV. 1 DATE BY CHECKED DATE	INITIAL RELEASE DESCRIPTION ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D	DATE BY CHECKED DATE	DATE BY CHECKED DATE
111986-05		IR	




		TOLERANCES:	
		UNLESS OTHERWISE SPECIFIED	
FINISH: 12.5 μm SURFACE: 12.5 μm DIMENSIONS: 12.5 μm DIMENSIONS: 12.5 μm DIMENSIONS: 12.5 μm DIMENSIONS: 12.5 μm		INITIAL RELEASE DATE: 11/19/05 BY: [Signature] CHECKED: [Signature]	
ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D		This drawing is the property of MAHA Engineering Inc. It is to be used for the purpose of design and construction only. It is not to be used for any other purpose without the written consent of MAHA Engineering Inc.	
WORKING/STANDARD 111986-05		DATE: 11/19/05 BY: [Signature] CHECKED: [Signature]	
111986-05		DATE: 11/19/05 BY: [Signature] CHECKED: [Signature]	




		TOLERANCES: UNLESS OTHERWISE SPECIFIED 1/16" ± 0.015 1/32" ± 0.010 1/64" ± 0.005 1/8" ± 0.010 1/4" ± 0.015 3/8" ± 0.020 1/2" ± 0.025 3/4" ± 0.030 1" ± 0.035 1 1/4" ± 0.040 1 3/4" ± 0.045 2" ± 0.050 2 1/2" ± 0.055 3" ± 0.060 3 1/2" ± 0.065 4" ± 0.070 4 1/2" ± 0.075 5" ± 0.080 5 1/2" ± 0.085 6" ± 0.090 6 1/2" ± 0.095 7" ± 0.100 7 1/2" ± 0.105 8" ± 0.110 8 1/2" ± 0.115 9" ± 0.120 9 1/2" ± 0.125 10" ± 0.130 10 1/2" ± 0.135 11" ± 0.140 11 1/2" ± 0.145 12" ± 0.150 12 1/2" ± 0.155 13" ± 0.160 13 1/2" ± 0.165 14" ± 0.170 14 1/2" ± 0.175 15" ± 0.180 15 1/2" ± 0.185 16" ± 0.190 16 1/2" ± 0.195 17" ± 0.200 17 1/2" ± 0.205 18" ± 0.210 18 1/2" ± 0.215 19" ± 0.220 19 1/2" ± 0.225 20" ± 0.230 20 1/2" ± 0.235 21" ± 0.240 21 1/2" ± 0.245 22" ± 0.250 22 1/2" ± 0.255 23" ± 0.260 23 1/2" ± 0.265 24" ± 0.270 24 1/2" ± 0.275 25" ± 0.280 25 1/2" ± 0.285 26" ± 0.290 26 1/2" ± 0.295 27" ± 0.300 27 1/2" ± 0.305 28" ± 0.310 28 1/2" ± 0.315 29" ± 0.320 29 1/2" ± 0.325 30" ± 0.330 30 1/2" ± 0.335 31" ± 0.340 31 1/2" ± 0.345 32" ± 0.350 32 1/2" ± 0.355 33" ± 0.360 33 1/2" ± 0.365 34" ± 0.370 34 1/2" ± 0.375 35" ± 0.380 35 1/2" ± 0.385 36" ± 0.390 36 1/2" ± 0.395 37" ± 0.400 37 1/2" ± 0.405 38" ± 0.410 38 1/2" ± 0.415 39" ± 0.420 39 1/2" ± 0.425 40" ± 0.430 40 1/2" ± 0.435 41" ± 0.440 41 1/2" ± 0.445 42" ± 0.450 42 1/2" ± 0.455 43" ± 0.460 43 1/2" ± 0.465 44" ± 0.470 44 1/2" ± 0.475 45" ± 0.480 45 1/2" ± 0.485 46" ± 0.490 46 1/2" ± 0.495 47" ± 0.500 47 1/2" ± 0.505 48" ± 0.510 48 1/2" ± 0.515 49" ± 0.520 49 1/2" ± 0.525 50" ± 0.530 50 1/2" ± 0.535 51" ± 0.540 51 1/2" ± 0.545 52" ± 0.550 52 1/2" ± 0.555 53" ± 0.560 53 1/2" ± 0.565 54" ± 0.570 54 1/2" ± 0.575 55" ± 0.580 55 1/2" ± 0.585 56" ± 0.590 56 1/2" ± 0.595 57" ± 0.600 57 1/2" ± 0.605 58" ± 0.610 58 1/2" ± 0.615 59" ± 0.620 59 1/2" ± 0.625 60" ± 0.630 60 1/2" ± 0.635 61" ± 0.640 61 1/2" ± 0.645 62" ± 0.650 62 1/2" ± 0.655 63" ± 0.660 63 1/2" ± 0.665 64" ± 0.670 64 1/2" ± 0.675 65" ± 0.680 65 1/2" ± 0.685 66" ± 0.690 66 1/2" ± 0.695 67" ± 0.700 67 1/2" ± 0.705 68" ± 0.710 68 1/2" ± 0.715 69" ± 0.720 69 1/2" ± 0.725 70" ± 0.730 70 1/2" ± 0.735 71" ± 0.740 71 1/2" ± 0.745 72" ± 0.750 72 1/2" ± 0.755 73" ± 0.760 73 1/2" ± 0.765 74" ± 0.770 74 1/2" ± 0.775 75" ± 0.780 75 1/2" ± 0.785 76" ± 0.790 76 1/2" ± 0.795 77" ± 0.800 77 1/2" ± 0.805 78" ± 0.810 78 1/2" ± 0.815 79" ± 0.820 79 1/2" ± 0.825 80" ± 0.830 80 1/2" ± 0.835 81" ± 0.840 81 1/2" ± 0.845 82" ± 0.850 82 1/2" ± 0.855 83" ± 0.860 83 1/2" ± 0.865 84" ± 0.870 84 1/2" ± 0.875 85" ± 0.880 85 1/2" ± 0.885 86" ± 0.890 86 1/2" ± 0.895 87" ± 0.900 87 1/2" ± 0.905 88" ± 0.910 88 1/2" ± 0.915 89" ± 0.920 89 1/2" ± 0.925 90" ± 0.930 90 1/2" ± 0.935 91" ± 0.940 91 1/2" ± 0.945 92" ± 0.950 92 1/2" ± 0.955 93" ± 0.960 93 1/2" ± 0.965 94" ± 0.970 94 1/2" ± 0.975 95" ± 0.980 95 1/2" ± 0.985 96" ± 0.990 96 1/2" ± 0.995 97" ± 1.000 97 1/2" ± 1.005 98" ± 1.010 98 1/2" ± 1.015 99" ± 1.020 99 1/2" ± 1.025 100" ± 1.030 100 1/2" ± 1.035 101" ± 1.040 101 1/2" ± 1.045 102" ± 1.050 102 1/2" ± 1.055 103" ± 1.060 103 1/2" ± 1.065 104" ± 1.070 104 1/2" ± 1.075 105" ± 1.080 105 1/2" ± 1.085 106" ± 1.090 106 1/2" ± 1.095 107" ± 1.100 107 1/2" ± 1.105 108" ± 1.110 108 1/2" ± 1.115 109" ± 1.120 109 1/2" ± 1.125 110" ± 1.130 110 1/2" ± 1.135 111" ± 1.140 111 1/2" ± 1.145 112" ± 1.150 112 1/2" ± 1.155 113" ± 1.160 113 1/2" ± 1.165 114" ± 1.170 114 1/2" ± 1.175 115" ± 1.180 115 1/2" ± 1.185 116" ± 1.190 116 1/2" ± 1.195 117" ± 1.200 117 1/2" ± 1.205 118" ± 1.210 118 1/2" ± 1.215 119" ± 1.220 119 1/2" ± 1.225 120" ± 1.230 120 1/2" ± 1.235 121" ± 1.240 121 1/2" ± 1.245 122" ± 1.250 122 1/2" ± 1.255 123" ± 1.260 123 1/2" ± 1.265 124" ± 1.270 124 1/2" ± 1.275 125" ± 1.280 125 1/2" ± 1.285 126" ± 1.290 126 1/2" ± 1.295 127" ± 1.300 127 1/2" ± 1.305 128" ± 1.310 128 1/2" ± 1.315 129" ± 1.320 129 1/2" ± 1.325 130" ± 1.330 130 1/2" ± 1.335 131" ± 1.340 131 1/2" ± 1.345 132" ± 1.350 132 1/2" ± 1.355 133" ± 1.360 133 1/2" ± 1.365 134" ± 1.370 134 1/2" ± 1.375 135" ± 1.380 135 1/2" ± 1.385 136" ± 1.390 136 1/2" ± 1.395 137" ± 1.400 137 1/2" ± 1.405 138" ± 1.410 138 1/2" ± 1.415 139" ± 1.420 139 1/2" ± 1.425 140" ± 1.430 140 1/2" ± 1.435 141" ± 1.440 141 1/2" ± 1.445 142" ± 1.450 142 1/2" ± 1.455 143" ± 1.460 143 1/2" ± 1.465 144" ± 1.470 144 1/2" ± 1.475 145" ± 1.480 145 1/2" ± 1.485 146" ± 1.490 146 1/2" ± 1.495 147" ± 1.500 147 1/2" ± 1.505 148" ± 1.510 148 1/2" ± 1.515 149" ± 1.520 149 1/2" ± 1.525 150" ± 1.530 150 1/2" ± 1.535 151" ± 1.540 151 1/2" ± 1.545 152" ± 1.550 152 1/2" ± 1.555 153" ± 1.560 153 1/2" ± 1.565 154" ± 1.570 154 1/2" ± 1.575 155" ± 1.580 155 1/2" ± 1.585 156" ± 1.590 156 1/2" ± 1.595 157" ± 1.600 157 1/2" ± 1.605 158" ± 1.610 158 1/2" ± 1.615 159" ± 1.620 159 1/2" ± 1.625 160" ± 1.630 160 1/2" ± 1.635 161" ± 1.640 161 1/2" ± 1.645 162" ± 1.650 162 1/2" ± 1.655 163" ± 1.660 163 1/2" ± 1.665 164" ± 1.670 164 1/2" ± 1.675 165" ± 1.680 165 1/2" ± 1.685 166" ± 1.690 166 1/2" ± 1.695 167" ± 1.700 167 1/2" ± 1.705 168" ± 1.710 168 1/2" ± 1.715 169" ± 1.720 169 1/2" ± 1.725 170" ± 1.730 170 1/2" ± 1.735 171" ± 1.740 171 1/2" ± 1.745 172" ± 1.750 172 1/2" ± 1.755 173" ± 1.760 173 1/2" ± 1.765 174" ± 1.770 174 1/2" ± 1.775 175" ± 1.780 175 1/2" ± 1.785 176" ± 1.790 176 1/2" ± 1.795 177" ± 1.800 177 1/2" ± 1.805 178" ± 1.810 178 1/2" ± 1.815 179" ± 1.820 179 1/2" ± 1.825 180" ± 1.830 180 1/2" ± 1.835 181" ± 1.840 181 1/2" ± 1.845 182" ± 1.850 182 1/2" ± 1.855 183" ± 1.860 183 1/2" ± 1.865 184" ± 1.870 184 1/2" ± 1.875 185" ± 1.880 185 1/2" ± 1.885 186" ± 1.890 186 1/2" ± 1.895 187" ± 1.900 187 1/2" ± 1.905 188" ± 1.910 188 1/2" ± 1.915 189" ± 1.920 189 1/2" ± 1.925 190" ± 1.930 190 1/2" ± 1.935 191" ± 1.940 191 1/2" ± 1.945 192" ± 1.950 192 1/2" ± 1.955 193" ± 1.960 193 1/2" ± 1.965 194" ± 1.970 194 1/2" ± 1.975 195" ± 1.980 195 1/2" ± 1.985 196" ± 1.990 196 1/2" ± 1.995 197" ± 2.000 197 1/2" ± 2.005 198" ± 2.010 198 1/2" ± 2.015 199" ± 2.020 199 1/2" ± 2.025 200" ± 2.030 200 1/2" ± 2.035 201" ± 2.040 201 1/2" ± 2.045 202" ± 2.050 202 1/2" ± 2.055 203" ± 2.060 203 1/2" ± 2.065 204" ± 2.070 204 1/2" ± 2.075 205" ± 2.080 205 1/2" ± 2.085 206" ± 2.090 206 1/2" ± 2.095 207" ± 2.100 207 1/2" ± 2.105 208" ± 2.110 208 1/2" ± 2.115 209" ± 2.120 209 1/2" ± 2.125 210" ± 2.130 210 1/2" ± 2.135 211" ± 2.140 211 1/2" ± 2.145 212" ± 2.150 212 1/2" ± 2.155 213" ± 2.160 213 1/2" ± 2.165 214" ± 2.170 214 1/2" ± 2.175 215" ± 2.180 215 1/2" ± 2.185 216" ± 2.190 216 1/2" ± 2.195 217" ± 2.200 217 1/2" ± 2.205 218" ± 2.210 218 1/2" ± 2.215 219" ± 2.220 219 1/2" ± 2.225 220" ± 2.230 220 1/2" ± 2.235 221" ± 2.240 221 1/2" ± 2.245 222" ± 2.250 222 1/2" ± 2.255 223" ± 2.260 223 1/2" ± 2.265 224" ± 2.270 224 1/2" ± 2.275 225" ± 2.280 225 1/2" ± 2.285 226" ± 2.290 226 1/2" ± 2.295 227" ± 2.300 227 1/2" ± 2.305 228" ± 2.310 228 1/2" ± 2.315 229" ± 2.320 229 1/2" ± 2.325 230" ± 2.330 230 1/2" ± 2.335 231" ± 2.340 231 1/2" ± 2.345 232" ± 2.350 232 1/2" ± 2.355 233" ± 2.360 233 1/2" ± 2.365 234" ± 2.370 234 1/2" ± 2.375 235" ± 2.380 235 1/2" ± 2.385 236" ± 2.390 236 1/2" ± 2.395 237" ± 2.400 237 1/2" ± 2.405 238" ± 2.410 238 1/2" ± 2.415 239" ± 2.420 239 1/2" ± 2.425 240" ± 2.430 240 1/2" ± 2.435 241" ± 2.440 241 1/2" ± 2.445 242" ± 2.450 242 1/2" ± 2.455 243" ± 2.460 243 1/2" ± 2.465 244" ± 2.470 244 1/2" ± 2.475 245" ± 2.480 245 1/2" ± 2.485 246" ± 2.490 246 1/2" ± 2.495 247" ± 2.500 247 1/2" ± 2.505 248" ± 2.510 248 1/2" ± 2.515 249" ± 2.520 249 1/2" ± 2.525 250" ± 2.530 250 1/2" ± 2.535 251" ± 2.540 251 1/2" ± 2.545 252" ± 2.550 252 1/2" ± 2.555 253" ± 2.560 253 1/2" ± 2.565 254" ± 2.570 254 1/2" ± 2.575 255" ± 2.580 255 1/2" ± 2.585 256" ± 2.590 256 1/2" ± 2.595 257" ± 2.600 257 1/2" ± 2.605 258" ± 2.610 258 1/2" ± 2.615 259" ± 2.620 259 1/2" ± 2.625 260" ± 2.630 260 1/2" ± 2.635 261" ± 2.640 261 1/2" ± 2.645 262" ± 2.650 262 1/2" ± 2.655 263" ± 2.660 263 1/2" ± 2.665 264" ± 2.670 264 1/2" ± 2.675 265" ± 2.680 265 1/2" ± 2.685 266" ± 2.690 266 1/2" ± 2.695 267" ± 2.700 267 1/2" ± 2.705 268" ± 2.710 268 1/2" ± 2.715 269" ± 2.720 269 1/2" ± 2.725 270" ± 2.730 270 1/2" ± 2.735 271" ± 2.740 271 1/2" ± 2.745 272" ± 2.750 272 1/2" ± 2.755 273" ± 2.760 273 1/2" ± 2.765 274" ± 2.770 274 1/2" ± 2.775 275" ± 2.780 275 1/2" ± 2.785 276" ± 2.790 276 1/2" ± 2.795 277" ± 2.800 277 1/2" ± 2.805 278" ± 2.810 278 1/2" ± 2.815 279" ± 2.820 279 1/2" ± 2.825 280" ± 2.830 280 1/2" ± 2.835 281" ± 2.840 281 1/2" ± 2.845 282" ± 2.850 282 1/2" ± 2.855 283" ± 2.860 283 1/2" ± 2.865 284" ± 2.870 284 1/2" ± 2.875 285" ± 2.880 285 1/2" ± 2.885 286" ± 2.890 286 1/2" ± 2.895 287" ± 2.900 287 1/2" ± 2.905 288" ± 2.910 288 1/2" ± 2.915 289" ± 2.920 289 1/2" ± 2.925 290" ± 2.930 290 1/2" ± 2.935 291" ± 2.940 291 1/2" ± 2.945 292" ± 2.950 292 1/2" ± 2.955 293" ± 2.960 293 1/2" ± 2.965 294" ± 2.970 294 1/2" ± 2.975 295" ± 2.980 295 1/2" ± 2.985 296" ± 2.990 296 1/2" ± 2.995 297" ± 3.000 297 1/2" ± 3.005 298" ± 3.010 298 1/2" ± 3.015 299" ± 3.020 299 1/2" ± 3.025 300" ± 3.030 300 1/2" ± 3.035 301" ± 3.040 301 1/2" ± 3.045 302" ± 3.050 302 1/2" ± 3.055 303" ± 3.060 303 1/2" ± 3.065 304" ± 3.070 304 1/2" ± 3.075 305" ± 3.080 305 1/2" ± 3.085 306" ± 3.090 306 1/2" ± 3.095 307" ± 3.100 307 1/2" ± 3.105 308" ± 3.110 308 1/2" ± 3.115 309" ± 3.120 309 1/2" ± 3.125 310" ± 3.130 310 1/2" ± 3.135 311" ± 3.140 311 1/2" ± 3.145 312" ± 3.150 312 1/2" ± 3.155 313" ± 3.160 313 1/2" ± 3.165 314" ± 3.170 314 1/2" ± 3.175 315" ± 3.180 315 1/2" ± 3.185 316" ± 3.190 316 1/2" ± 3.195 317" ± 3.200 317 1/2" ± 3.205 318" ± 3.210 318 1/2" ± 3.215 319" ± 3.220 319 1/2" ± 3.225 320" ± 3.230 320 1/2" ± 3.235 321" ± 3.240 321 1/2" ± 3.245 322" ± 3.250 322 1/2" ± 3.255 323" ± 3.260 323 1/2" ± 3.265 324" ± 3.270 324 1/2" ± 3.275 325" ± 3.280 325 1/2" ± 3.285 326" ± 3.290 326 1/2" ± 3.295 327" ± 3.300 327 1/2" ± 3.305 328" ± 3.310 328 1/2" ± 3.315 329" ± 3.320 329 1/2" ± 3.325 330" ± 3.330 330 1/2" ± 3.335 331" ± 3.340 331 1/2" ± 3.345 332" ± 3.350 332 1/2" ± 3.355 333" ± 3.360 333 1/2" ± 3.365 334" ± 3.370 334 1/2" ± 3.375 335" ± 3.380 335 1/	
--	--	---	--



		TOLERANCES: UNLESS OTHERWISE SPECIFIED FRACTIONS: 1/16" IN. DECIMALS: 0.015" ANGLES: 1/4° HOLE CIRCLES: 1/8" DIA. DIMENSIONS: AS SHOWN	
		THIS DRAWING IS THE PROPERTY OF IT IS TO BE USED ONLY WITH EXPRESS PERMISSION FROM MCHP	
IR REV. 1 DATE: 11/19/2003 BY: [Signature] CHECKED: [Signature] APPROVED: [Signature]	INITIAL RELEASE DESCRIPTION: ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D	DATE: 11/19/2003 BY: [Signature] CHECKED: [Signature] APPROVED: [Signature]	DATE: 11/19/2003 BY: [Signature] CHECKED: [Signature] APPROVED: [Signature]
DRAWING NO. 111986-05		IR	



		TOLERANCES: UNLESS OTHERWISE SPECIFIED FRACTIONS: 1/16" 1/8" 1/4" 3/8" 1/2" 5/8" 3/4" 1" 1 1/4" 1 1/2" 2" 3" 4" 6" 8" 10" 12" 14" 16" 18" 20" 22" 24" 26" 28" 30" 32" 34" 36" 38" 40" 42" 44" 46" 48" 50" 52" 54" 56" 58" 60" 62" 64" 66" 68" 70" 72" 74" 76" 78" 80" 82" 84" 86" 88" 90" 92" 94" 96" 98" 100" 102" 104" 106" 108" 110" 112" 114" 116" 118" 120" 122" 124" 126" 128" 130" 132" 134" 136" 138" 140" 142" 144" 146" 148" 150" 152" 154" 156" 158" 160" 162" 164" 166" 168" 170" 172" 174" 176" 178" 180" 182" 184" 186" 188" 190" 192" 194" 196" 198" 200" 202" 204" 206" 208" 210" 212" 214" 216" 218" 220" 222" 224" 226" 228" 230" 232" 234" 236" 238" 240" 242" 244" 246" 248" 250" 252" 254" 256" 258" 260" 262" 264" 266" 268" 270" 272" 274" 276" 278" 280" 282" 284" 286" 288" 290" 292" 294" 296" 298" 300" 302" 304" 306" 308" 310" 312" 314" 316" 318" 320" 322" 324" 326" 328" 330" 332" 334" 336" 338" 340" 342" 344" 346" 348" 350" 352" 354" 356" 358" 360" 362" 364" 366" 368" 370" 372" 374" 376" 378" 380" 382" 384" 386" 388" 390" 392" 394" 396" 398" 400" 402" 404" 406" 408" 410" 412" 414" 416" 418" 420" 422" 424" 426" 428" 430" 432" 434" 436" 438" 440" 442" 444" 446" 448" 450" 452" 454" 456" 458" 460" 462" 464" 466" 468" 470" 472" 474" 476" 478" 480" 482" 484" 486" 488" 490" 492" 494" 496" 498" 500" 502" 504" 506" 508" 510" 512" 514" 516" 518" 520" 522" 524" 526" 528" 530" 532" 534" 536" 538" 540" 542" 544" 546" 548" 550" 552" 554" 556" 558" 560" 562" 564" 566" 568" 570" 572" 574" 576" 578" 580" 582" 584" 586" 588" 590" 592" 594" 596" 598" 600" 602" 604" 606" 608" 610" 612" 614" 616" 618" 620" 622" 624" 626" 628" 630" 632" 634" 636" 638" 640" 642" 644" 646" 648" 650" 652" 654" 656" 658" 660" 662" 664" 666" 668" 670" 672" 674" 676" 678" 680" 682" 684" 686" 688" 690" 692" 694" 696" 698" 700" 702" 704" 706" 708" 710" 712" 714" 716" 718" 720" 722" 724" 726" 728" 730" 732" 734" 736" 738" 740" 742" 744" 746" 748" 750" 752" 754" 756" 758" 760" 762" 764" 766" 768" 770" 772" 774" 776" 778" 780" 782" 784" 786" 788" 790" 792" 794" 796" 798" 800" 802" 804" 806" 808" 810" 812" 814" 816" 818" 820" 822" 824" 826" 828" 830" 832" 834" 836" 838" 840" 842" 844" 846" 848" 850" 852" 854" 856" 858" 860" 862" 864" 866" 868" 870" 872" 874" 876" 878" 880" 882" 884" 886" 888" 890" 892" 894" 896" 898" 900" 902" 904" 906" 908" 910" 912" 914" 916" 918" 920" 922" 924" 926" 928" 930" 932" 934" 936" 938" 940" 942" 944" 946" 948" 950" 952" 954" 956" 958" 960" 962" 964" 966" 968" 970" 972" 974" 976" 978" 980" 982" 984" 986" 988" 990" 992" 994" 996" 998" 1000" 1002" 1004" 1006" 1008" 1010" 1012" 1014" 1016" 1018" 1020" 1022" 1024" 1026" 1028" 1030" 1032" 1034" 1036" 1038" 1040" 1042" 1044" 1046" 1048" 1050" 1052" 1054" 1056" 1058" 1060" 1062" 1064" 1066" 1068" 1070" 1072" 1074" 1076" 1078" 1080" 1082" 1084" 1086" 1088" 1090" 1092" 1094" 1096" 1098" 1100" 1102" 1104" 1106" 1108" 1110" 1112" 1114" 1116" 1118" 1120" 1122" 1124" 1126" 1128" 1130" 1132" 1134" 1136" 1138" 1140" 1142" 1144" 1146" 1148" 1150" 1152" 1154" 1156" 1158" 1160" 1162" 1164" 1166" 1168" 1170" 1172" 1174" 1176" 1178" 1180" 1182" 1184" 1186" 1188" 1190" 1192" 1194" 1196" 1198" 1200" 1202" 1204" 1206" 1208" 1210" 1212" 1214" 1216" 1218" 1220" 1222" 1224" 1226" 1228" 1230" 1232" 1234" 1236" 1238" 1240" 1242" 1244" 1246" 1248" 1250" 1252" 1254" 1256" 1258" 1260" 1262" 1264" 1266" 1268" 1270" 1272" 1274" 1276" 1278" 1280" 1282" 1284" 1286" 1288" 1290" 1292" 1294" 1296" 1298" 1300" 1302" 1304" 1306" 1308" 1310" 1312" 1314" 1316" 1318" 1320" 1322" 1324" 1326" 1328" 1330" 1332" 1334" 1336" 1338" 1340" 1342" 1344" 1346" 1348" 1350" 1352" 1354" 1356" 1358" 1360" 1362" 1364" 1366" 1368" 1370" 1372" 1374" 1376" 1378" 1380" 1382" 1384" 1386" 1388" 1390" 1392" 1394" 1396" 1398" 1400" 1402" 1404" 1406" 1408" 1410" 1412" 1414" 1416" 1418" 1420" 1422" 1424" 1426" 1428" 1430" 1432" 1434" 1436" 1438" 1440" 1442" 1444" 1446" 1448" 1450" 1452" 1454" 1456" 1458" 1460" 1462" 1464" 1466" 1468" 1470" 1472" 1474" 1476" 1478" 1480" 1482" 1484" 1486" 1488" 1490" 1492" 1494" 1496" 1498" 1500" 1502" 1504" 1506" 1508" 1510" 1512" 1514" 1516" 1518" 1520" 1522" 1524" 1526" 1528" 1530" 1532" 1534" 1536" 1538" 1540" 1542" 1544" 1546" 1548" 1550" 1552" 1554" 1556" 1558" 1560" 1562" 1564" 1566" 1568" 1570" 1572" 1574" 1576" 1578" 1580" 1582" 1584" 1586" 1588" 1590" 1592" 1594" 1596" 1598" 1600" 1602" 1604" 1606" 1608" 1610" 1612" 1614" 1616" 1618" 1620" 1622" 1624" 1626" 1628" 1630" 1632" 1634" 1636" 1638" 1640" 1642" 1644" 1646" 1648" 1650" 1652" 1654" 1656" 1658" 1660" 1662" 1664" 1666" 1668" 1670" 1672" 1674" 1676" 1678" 1680" 1682" 1684" 1686" 1688" 1690" 1692" 1694" 1696" 1698" 1700" 1702" 1704" 1706" 1708" 1710" 1712" 1714" 1716" 1718" 1720" 1722" 1724" 1726" 1728" 1730" 1732" 1734" 1736" 1738" 1740" 1742" 1744" 1746" 1748" 1750" 1752" 1754" 1756" 1758" 1760" 1762" 1764" 1766" 1768" 1770" 1772" 1774" 1776" 1778" 1780" 1782" 1784" 1786" 1788" 1790" 1792" 1794" 1796" 1798" 1800" 1802" 1804" 1806" 1808" 1810" 1812" 1814" 1816" 1818" 1820" 1822" 1824" 1826" 1828" 1830" 1832" 1834" 1836" 1838" 1840" 1842" 1844" 1846" 1848" 1850" 1852" 1854" 1856" 1858" 1860" 1862" 1864" 1866" 1868" 1870" 1872" 1874" 1876" 1878" 1880" 1882" 1884" 1886" 1888" 1890" 1892" 1894" 1896" 1898" 1900" 1902" 1904" 1906" 1908" 1910" 1912" 1914" 1916" 1918" 1920" 1922" 1924" 1926" 1928" 1930" 1932" 1934" 1936" 1938" 1940" 1942" 1944" 1946" 1948" 1950" 1952" 1954" 1956" 1958" 1960" 1962" 1964" 1966" 1968" 1970" 1972" 1974" 1976" 1978" 1980" 1982" 1984" 1986" 1988" 1990" 1992" 1994" 1996" 1998" 2000" 2002" 2004" 2006" 2008" 2010" 2012" 2014" 2016" 2018" 2020" 2022" 2024" 2026" 2028" 2030" 2032" 2034" 2036" 2038" 2040" 2042" 2044" 2046" 2048" 2050" 2052" 2054" 2056" 2058" 2060" 2062" 2064" 2066" 2068" 2070" 2072" 2074" 2076" 2078" 2080" 2082" 2084" 2086" 2088" 2090" 2092" 2094" 2096" 2098" 2100" 2102" 2104" 2106" 2108" 2110" 2112" 2114" 2116" 2118" 2120" 2122" 2124" 2126" 2128" 2130" 2132" 2134" 2136" 2138" 2140" 2142" 2144" 2146" 2148" 2150" 2152" 2154" 2156" 2158" 2160" 2162" 2164" 2166" 2168" 2170" 2172" 2174" 2176" 2178" 2180" 2182" 2184" 2186" 2188" 2190" 2192" 2194" 2196" 2198" 2200" 2202" 2204" 2206" 2208" 2210" 2212" 2214" 2216" 2218" 2220" 2222" 2224" 2226" 2228" 2230" 2232" 2234" 2236" 2238" 2240" 2242" 2244" 2246" 2248" 2250" 2252" 2254" 2256" 2258" 2260" 2262" 2264" 2266" 2268" 2270" 2272" 2274" 2276" 2278" 2280" 2282" 2284" 2286" 2288" 2290" 2292" 2294" 2296" 2298" 2300" 2302" 2304" 2306" 2308" 2310" 2312" 2314" 2316" 2318" 2320" 2322" 2324" 2326" 2328" 2330" 2332" 2334" 2336" 2338" 2340" 2342" 2344" 2346" 2348" 2350" 2352" 2354" 2356" 2358" 2360" 2362" 2364" 2366" 2368" 2370" 2372" 2374" 2376" 2378" 2380" 2382" 2384" 2386" 2388" 2390" 2392" 2394" 2396" 2398" 2400" 2402" 2404" 2406" 2408" 2410" 2412" 2414" 2416" 2418" 2420" 2422" 2424" 2426" 2428" 2430" 2432" 2434" 2436" 2438" 2440" 2442" 2444" 2446" 2448" 2450" 2452" 2454" 2456" 2458" 2460" 2462" 2464" 2466" 2468" 2470" 2472" 2474" 2476" 2478" 2480" 2482" 2484" 2486" 2488" 2490" 2492" 2494" 2496" 2498" 2500" 2502" 2504" 2506" 2508" 2510" 2512" 2514" 2516" 2518" 2520" 2522" 2524" 2526" 2528" 2530" 2532" 2534" 2536" 2538" 2540" 2542" 2544" 2546" 2548" 2550" 2552" 2554" 2556" 2558" 2560" 2562" 2564" 2566" 2568" 2570" 2572" 2574" 2576" 2578" 2580" 2582" 2584" 2586" 2588" 2590" 2592" 2594" 2596" 2598" 2600" 2602" 2604" 2606" 2608" 2610" 2612" 2614" 2616" 2618" 2620" 2622" 2624" 2626" 2628" 2630" 2632" 2634" 2636" 2638" 2640" 2642" 2644" 2646" 2648" 2650" 2652" 2654" 2656" 2658" 2660" 2662" 2664" 2666" 2668" 2670" 2672" 2674" 2676" 2678" 2680" 2682" 2684" 2686" 2688" 2690" 2692" 2694" 2696" 2698" 2700" 2702" 2704" 2706" 2708" 2710" 2712" 2714" 2716" 2718" 2720" 2722" 2724" 2726" 2728" 2730" 2732" 2734" 2736" 2738" 2740" 2742" 2744" 2746" 2748" 2750" 2752" 2754" 2756" 2758" 2760" 2762" 2764" 2766" 2768" 2770" 2772" 2774" 2776" 2778" 2780" 2782" 2784" 2786" 2788" 2790" 2792" 2794" 2796" 2798" 2800" 2802" 2804" 2806" 2808" 2810" 2812" 2814" 2816" 2818" 2820" 2822" 2824" 2826" 2828" 2830" 2832" 2834" 2836" 2838" 2840" 2842" 2844" 2846" 2848" 2850" 2852" 2854" 2856" 2858" 2860" 2862" 2864" 2866" 2868" 2870" 2872" 2874" 2876" 2878" 2880" 2882" 2884" 2886" 2888" 2890" 2892" 2894" 2896" 2898" 2900" 2902" 2904" 2906" 2908" 2910" 2912" 2914" 2916" 2918" 2920" 2922" 2924" 2926" 2928" 2930" 2932" 2934" 2936" 2938" 2940" 2942" 2944" 2946" 2948" 2950" 2952" 2954" 2956" 2958" 2960" 2962" 2964" 2966" 2968" 2970" 2972" 2974" 2976" 2978" 2980" 2982" 2984" 2986" 2988" 2990" 2992" 2994" 2996" 2998" 3000" 3002" 3004" 3006" 3008" 3010" 3012" 3014" 3016" 3018" 3020" 3022" 3024" 3026" 3028" 3030" 3032" 3034" 3036" 3038" 3040" 3042" 3044" 3046" 3048" 3050" 3052" 3054" 3056" 3058" 3060" 3062" 3064" 3066" 3068" 3070" 3072" 3074" 3076" 3078" 3080" 3082" 3084" 3086" 3088" 3090" 3092" 3094" 3096" 3098" 3100" 3102" 3104" 3106" 3108" 3110" 3112" 3114" 3116" 3118" 3120" 3122" 3124" 3126" 3128" 3130" 3132" 3134" 3136" 3138" 3140" 3142" 3144" 3146" 3148" 3150" 3152" 3154" 3156" 3158" 3160" 3162" 3164" 3166" 3168" 3170" 3172" 3174" 3176" 3178" 3180" 3182" 3184" 3186" 3188" 3190" 3192" 3194" 3196" 3198" 3200" 3202" 3204" 3206" 3208" 3210" 3212" 3214" 3216" 3218" 3220" 3222" 3224" 3226" 3228" 3230" 3232" 3234" 3236" 3238" 3240" 3242" 3244" 3246" 3248" 3250" 3252" 3254" 3256" 3258" 3260" 3262" 3264" 3266" 3268" 3270" 3272" 3274" 3276" 3278" 3280" 3282" 3284" 3286" 3288" 3290" 3292" 3294" 3296" 3298" 3300" 3302" 3304" 3306" 3308" 3310" 3312" 3314" 3316" 3318" 3320" 3322" 3324" 3326" 3328" 3330" 3332" 3334" 3336" 3338" 3340" 3342" 3344" 3346" 3348" 3350" 3352" 3354" 3356" 3358" 3360" 3362" 3364" 3366" 3368" 3370" 3372" 3374" 3376" 3378" 3380" 3382" 3384" 3386" 3388" 3390" 3392" 3394" 3396" 3398" 3400" 3402" 3404" 3406" 3408" 3410" 3412" 3414" 3416" 3418" 3420" 3422" 3424" 3426" 3428" 3430" 3432" 3434" 3436" 3438" 3440" 3442" 3444" 3446" 3448" 3450" 3452" 3454" 3456" 3458" 3460" 3462" 3464" 3466" 3468" 3470" 3472" 3474" 3476" 3478" 3480" 3482" 3484" 3486" 3488" 3490" 3492" 3494" 3496" 3498" 3500" 3502" 3504" 3506" 3508" 3510" 3512" 3514" 3516" 3518" 3520" 3522" 3524" 3526" 3528" 3530" 3532" 3534" 3536" 3538" 3540" 3542" 3544" 3546" 3548" 3550" 3552" 3554" 3556" 3558" 3560" 3562" 3564" 3566" 3568" 3570" 3572" 3574" 3576" 3578" 3580" 3582" 3584" 3586" 3588" 3590" 3592" 3594" 3596" 3598" 3600" 3602" 3604" 3606" 3608" 3610" 3612" 3614" 3616" 3618" 3620" 3622" 3624" 3626" 3628" 3630" 3632" 3634" 3636" 3638" 3640" 3642" 3644" 3646" 3648" 3650" 3652" 3654" 3656" 3658" 3660" 3662" 3664" 3666" 3668" 3670" 3672" 3674" 3676" 3678" 3680" 3682" 3684" 3686" 3688" 3690" 3692" 3694" 3696" 3698" 3700" 3702" 3704" 3706" 3708" 3710" 3712" 3714" 3716" 3718" 3720" 3722" 3724" 3726" 3728" 3730" 3732" 3734" 3736" 3738" 3740" 3742" 3744" 3746" 3748" 3750" 3752" 3754" 3756" 3758" 3760" 3762" 3764" 3766" 3768" 3770" 3772" 3774" 3776" 3778" 3780" 3782" 3784" 3786" 3788" 3790" 3792" 3794" 3796" 3798" 3800" 3802" 3804" 3806" 3808" 3810" 3812" 3814" 3816" 3818" 3820" 3822" 3824" 3826" 3828" 3830" 3832" 3834" 3836" 3838" 3840" 3842" 3844" 3846" 3848" 3850" 3852" 3854" 3856" 3858" 3860" 3862" 3864" 3866" 3868" 3870" 3872" 3874" 3876" 3878" 3880" 3882" 3884" 3886" 3888" 3890" 3892" 3894" 3896" 3898" 3900" 3902" 3904" 3906" 3908" 3910" 3912" 3914" 3916" 3918" 3920" 3922" 3924" 3926" 3928" 3930" 3932" 3934" 3936" 3938" 3940" 3942" 3944" 3946" 3948" 3950" 3952" 3954" 3956" 3958" 3960" 3962" 3964" 3966" 3968" 3970" 3972" 3974" 3976" 3978" 3980" 3982" 3984" 3986" 3988" 3990" 3992" 3994" 3996" 3998" 4000" 4002" 4004" 4006" 4008" 4010" 4012" 4014" 4016" 4018" 4020" 4022" 4024" 4026" 4028" 4030" 4032" 4034" 4036" 4038" 4040" 4042" 4044" 4046" 4048" 4050" 4052" 4054" 4056" 4058" 4060" 4062" 4064" 4066" 4068" 4070" 4072" 4074" 4076" 4078" 4080" 4082" 4084" 4086" 4088" 4090" 4092" 4094" 4096" 4098" 4100" 4102" 4104" 4106" 4108" 4110" 4112" 4114" 4116" 4118" 4120" 4122	
--	--	---	--



		TOLERANCES: UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES DECIMALS: 1/16" FRACTIONS: 1/8", 1/4", 3/8", 1/2" ANGLES: 1/2°, 1°, 2°, 3°, 4°, 5°, 6°, 8°, 10°, 12°, 15°, 20°, 25°, 30°, 35°, 40°, 45°, 50°, 55°, 60°, 65°, 70°, 75°, 80°, 85°, 90°, 95°, 100°, 105°, 110°, 115°, 120°, 125°, 130°, 135°, 140°, 145°, 150°, 155°, 160°, 165°, 170°, 175°, 180° SURFACE FINISH: 32 RMS UNLESS OTHERWISE SPECIFIED	
		THIS DRAWING IS THE PROPERTY OF IT IS TO BE USED ONLY WITH EXPRESS PERMISSION FROM MAHR	
REV	DATE	BY	CHK'D
INITIAL RELEASE DESCRIPTION ILLUSTRATION SUBSEA PRODUCTION WELL WITH PENETRATIONS API 17D			
WORKING/STATION		DWG NO. 111986-05	
DATE: 06/19/2003 TIME: 10:00 AM SCALE: 1" = 10'-0"		REV: 1 IR	

12.2 Appendix B – Fault Tree Details for No Penetrations

1. WITH WELLHEAD HOUSING PENETRATIONS
2. PRESSURE COULD EXIST IN THE 'A' ANNULUS
3. PRESSURE IN THE 'B' ANNULUS COMES FROM EITHER THE 'A' ANNULUS OR THE FORMATION
- 4.



A	UPDATE FROM COMMITTEE MEETING	8/26/2003	YDK
IR	INITIAL RELEASE		
REV.	DESCRIPTION	DATE	BY CHK'D.
REVISION:	<p>This drawing is the property of NRES Engineering Division It is to be used only with express written permission from NRES.</p>		
	FAULT TREE ANALYSIS	SCALE	IR
	SUSTAINED CASING PRESSURE	YDK	8/25/03
	WITHOUT PENETRATIONS	DATE	REV
	API 17D	CDL BY	
		APP BY	8/27/2003
		K. YOUNG	
MATERIAL STRENGTH	DWG NO.	111986-10	

Fault Tree without Penetrations	
Failure Occurrence	Failure Mode
10.12%	Inability to Maintain a Pressure Barrier
0.0003	Pressure migrates outward from "A" annulus through the production casing pipe / connections
0.0269	Failure of production casing pipe / connection
0.0109	Failure of secondary barrier
0.0049	Failure of intmd casing flow path
0.0395	Failure of intermediate casing pipe / connections
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0060	Failure of intmd csg hgr packoff flow path
0.0491	Failure of intermediate casing hanger packoff
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0005	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.0491	Failure of production casing hanger packoff
0.0109	Failure of secondary barrier
0.0060	Failure of intmd csg hgr packoff flow path
0.0491	Failure of intermediate casing hanger packoff
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0049	Failure of intmd casing flow path
0.0395	Failure of intermediate casing pipe / connection
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement

Fault Tree without Penetrations	
Failure Occurrence	Failure Mode
0.0734	Pressure migrates outward from production casing cement
0.0670	Failure of intermediate casing cement
0.0045	Failure of intmd csg hgr packoff flow path
0.0491	Failure of intermediate casing hanger packoff
0.0921	Failure of secondary barrier
0.0269	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0024	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connections
0.0599	Failure of surface casing pipe / connections
0.0016	Pressure migrates inward from production casing cement
0.0598	Failure of production casing cement
0.0269	Failure of production casing pipe / connections
0.0117	Failure of surface casing cement
0.0117	Failure of conductor pipe cement
0.0004	Pressure migrates inward from intermediate casing cement
0.0670	Failure of intermediate casing cement
0.0037	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.0747	Failure of secondary flow path
0.0491	Failure of production casing hanger packoff
0.0269	Failure of production casing pipe / connections
0.0019	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connections
0.0491	Failure of production casing hanger packoff
0.0040	Pressure migrates outward from intermediate casing cement
0.0670	Failure of intermediate casing cement
0.0599	Failure of surface casing pipe / connections

12.3 Appendix C – Fault Tree Details with One Penetration

Fault Tree with One Penetration

with 2" penetration / valves

Failure Occurrence	Failure Mode
25.30%	Inability to maintain Pressure Barrier
0.0044	Pressure migrates outward from "A" annulus thru production casing pipe / connections
0.0269	Failure of production casing pipe / connection
0.1653	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.0049	Failure of second flow path
0.0395	Failure of intermediate casing pipe / connections
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0060	Failure of third flow path
0.0491	Failure of intermediate casing hanger packoff
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0081	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.0491	Failure of production casing hanger packoff
0.1653	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.0060	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0049	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connection
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement

Fault Tree with One Penetration	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.2201	Pressure migrates outward from production casing cement
0.0670	Failure of intermediate casing cement
0.1562	Failure of "B" annulus penetration
0.0033	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.0670	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0062	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connections
0.1562	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.1562	Failure of "B" annulus penetration
0.0016	Pressure migrates inward from production casing cement
0.0598	Failure of production casing cement
0.0269	Failure of production casing pipe / connections
0.0117	Failure of surface casing cement
0.0117	Failure of conductor pipe cement

Fault Tree with One Penetration	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.0012	Pressure migrates inward from intermediate casing cement
0.0670	Failure of intermediate casing cement
0.0108	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.2192	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.0491	Failure of production casing hanger packoff
0.0269	Failure of production casing pipe / connections
0.0078	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connections
0.1976	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.0491	Failure of production casing hanger packoff
0.0040	Pressure migrates outward from intermediate casing cement
0.0670	Failure of intermediate casing cement
0.0599	Failure of surface casing pipe / connections

12.4 Appendix D – Fault Tree Details with Two Penetrations

- INABILITY TO
MAINTAIN
PRESSURE



A	UPDATE FROM COMMITTEE MEETING	8/26/2003	YDK	
IR	INITIAL RELEASE			
REV.	DESCRIPTION	DATE	BY	CHK'D.
<p>RECOGNITION</p> <p> This drawing is the property of H&B Engineering Division It is to be used only for the project and for the location and address information from IRB. </p>				
	FAULT TREE ANALYSIS	ISSUED BY	DATE	SCALE
	SUSTAINED CASING PRESSURE	YOK	8/26/03	1" = 1'
	WITH PENETRATIONS	CHKD. BY	DATE	REV.
	API 17D	APP. BY	DATE	IR
		K. YOUNG	8/26/2003	
MATERIALS/STRENGTH				DWG. NO. 111986-09

Fault Tree with Two Penetrations	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
27.26%	Inability to maintain Pressure Barrier
0.0047	Pressure migrates outward from "A" annulus thru production casing pipe / connections
0.0269	Failure of production casing pipe / connection
0.1751	Failure of second barrier
0.1562	Failure of "B" annulus penetration
0.0101	Failure of second flow path
0.0395	Failure of intermediate casing pipe / connections
0.2554	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0125	Failure of third flow path
0.0491	Failure of intermediate casing hanger packoff
0.2554	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0086	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.0491	Failure of production casing hanger packoff
0.1751	Failure of second barrier
0.1562	Failure of "B" annulus penetration
0.0125	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.2554	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0101	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connection
0.2554	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement

Fault Tree with Two Penetrations	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.2326	Pressure migrates outward from production casing cement
0.0670	Failure of intermediate casing cement
0.1562	Failure of "B" annulus penetration
0.0125	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.2554	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0129	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connections
0.3265	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.1562	Failure of "B" annulus penetration
0.0016	Pressure migrates inward from production casing cement
0.0598	Failure of production casing cement
0.0269	Failure of production casing pipe / connections
0.0117	Failure of surface casing cement
0.0117	Failure of conductor pipe cement

Fault Tree with Two Penetrations	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.0012	Pressure migrates inward from intermediate casing cement
0.0670	Failure of intermediate casing cement
0.0185	Failure of secondary flow path
0.0108	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.2192	Failure of secondary flow path
0.1562	Failure of "B" annulus penetration
0.0491	Failure of production casing hanger packoff
0.0269	Failure of production casing pipe / connections
0.0078	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connections
0.1976	Failure of secondary flow path
0.1562	Failure of "B" annulus penetration
0.0491	Failure of production casing hanger packoff
0.0135	Pressure migrates outward from intermediate casing cement
0.0670	Failure of intermediate casing cement
0.2019	Failure of secondary flow path
0.0599	Failure of surface casing pipe / connections
0.1511	Failure of "C" annulus penetration

12.5 Appendix E – Fault Tree Details with ½-inch Penetrations

Fault Tree Analysis of Casing Pressure Subsets

Risk Index	Relative Failure Occurrence	Failure Mode
	27.08%	Failure of B or C Annulus Penetration, 1/2"
	0.1679	False Pressure Reading
6	0.0491	Pressure sensor inoperable
4	0.0249	Pressure sensor lost calibration
2	0.0077	Lost umbilical signal
9	0.0956	Pressure port plugged
	0.0385	Leakage from connections
5	0.0362	Leakage due to vibration
1	0.0024	Leakage due to corrosion
	0.0100	Failure of manual valve to function
2	0.0077	Valve malfunctions closed
1	0.0024	Valve malfunctions open
	0.0000	Wellhead housing integrity
1	0.0024	Higher bending moments due to taller housing
1	0.0024	Stress concentrations due to penetrations
	0.0545	Damage to valves from external forces
4	0.0249	Running / Installation damage
3	0.0153	Damage from ROV contact
2	0.0077	Damage when landing tree
2	0.0077	Dropped equipment

Risk Index	Relative Failure Occurrence	Failure Mode
	2.69%	Failure of Production Casing Pipe / Connections to Maintain a Pressure Barrier
2	0.0077	Corrosion
1	0.0024	Thermal cycling
1	0.0024	Damaged threads
2	0.0077	Damaged sealing surface
1	0.0024	Wear
1	0.0024	Bad / wrong thread compound
1	0.0024	Improper makeup of connection
	3.95%	Failure of Intermediate Casing Pipe / Connections to Maintain a Pressure Barrier
2	0.0077	Corrosion
1	0.0024	Thermal cycling
1	0.0024	Damaged threads
2	0.0077	Damaged sealing surface
3	0.0153	Wear
1	0.0024	Bad / wrong thread compound
1	0.0024	Improper makeup of connection
	5.99%	Failure of Surface Casing Pipe / Connections to Maintain a Pressure Barrier
2	0.0077	Corrosion
1	0.0024	Thermal cycling
1	0.0024	Damaged threads
2	0.0077	Damaged sealing surface
5	0.0362	Wear
1	0.0024	Bad / wrong thread compound
1	0.0024	Improper makeup of connection

Risk Index	Relative Failure Occurrence	Failure Mode
	4.91%	Failure of Casing Hanger Packoff to Maintain a Pressure Barrier
3	0.0153	Damaged sealing surface
2	0.0077	Thermal cycling / axial movement
2	0.0077	Installation anomalies
2	0.0077	Corrosion
1	0.0024	Seal damage from high temperature
1	0.0024	Loss of seal contact pressure
1	0.0024	Seal / fluid incompatibility
1	0.0024	Solids contamination
1	0.0024	Vibration

Risk Index	Relative Failure Occurrence	Failure Mode
	5.98%	Failure of Production Casing Cement to Maintain a Pressure Barrier
3	0.0153	Micro-annulus cracks
3	0.0153	Frac-Pac operations
3	0.0153	Expansion and contraction
2	0.0077	Poor formation / cement bond
2	0.0077	Gas in cement
	6.70%	Failure of Intermediate Casing Cement to Maintain a Pressure Barrier
3	0.0153	Micro-annulus cracks
3	0.0153	Frac-Pac operations
3	0.0153	Expansion and contraction
3	0.0153	Poor formation / cement bond
2	0.0077	Gas in cement
	1.17%	Failure of Surface / Conductor Casing Cement to Maintain a Pressure Barrier
1	0.0024	Micro-annulus cracks
1	0.0024	Frac-Pac operations
1	0.0024	Expansion and contraction
1	0.0024	Poor formation / cement bond
1	0.0024	Gas in cement

Fault Tree with One Penetration	
with 1/2" penetration / valves	
Failure Occurrence	Failure Mode
36.35%	Inability to maintain Pressure Barrier
0.0075	Pressure migrates outward from "A" annulus thru production casing pipe / connections
0.0269	Failure of production casing pipe / connection
0.2788	Failure of secondary barrier
0.2708	Failure of "B" annulus penetration
0.0049	Failure of second flow path
0.0395	Failure of intermediate casing pipe / connections
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0060	Failure of third flow path
0.0491	Failure of intermediate casing hanger packoff
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0137	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.0491	Failure of production casing hanger packoff
0.2788	Failure of secondary barrier
0.2708	Failure of "B" annulus penetration
0.0060	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0049	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connection
0.1229	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement

Fault Tree with One Penetration	
with 1/2" penetration / valves	
Failure Occurrence	Failure Mode
0.3292	Pressure migrates outward from production casing cement
0.0670	Failure of intermediate casing cement
0.2708	Failure of "B" annulus penetration
0.0033	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.0670	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0107	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connections
0.2708	Failure of secondary barrier
0.0599	Failure of surface casing pipe / connections
0.2708	Failure of "B" annulus penetration
0.0016	Pressure migrates inward from production casing cement
0.0598	Failure of production casing cement
0.0269	Failure of production casing pipe / connections
0.0117	Failure of surface casing cement
0.0117	Failure of conductor pipe cement

Fault Tree with One Penetration	
with 1/2" penetration / valves	
Failure Occurrence	Failure Mode
0.0019	Pressure migrates inward from intermediate casing cement
0.0670	Failure of intermediate casing cement
0.0160	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.3253	Failure of secondary barrier
0.2708	Failure of "B" annulus penetration
0.0491	Failure of production casing hanger packoff
0.0269	Failure of production casing pipe / connections
0.0121	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connections
0.3067	Failure of secondary barrier
0.2708	Failure of "B" annulus penetration
0.0491	Failure of production casing hanger packoff
0.0040	Pressure migrates outward from intermediate casing cement
0.0670	Failure of intermediate casing cement
0.0599	Failure of surface casing pipe / connections

Fault Tree with Two Penetrations	
with 1/2" penetration / valves	
Failure Occurrence	Failure Mode
37.95%	Inability to maintain Pressure Barrier
0.0077	Pressure migrates outward from "A" annulus thru production casing pipe / connections
0.0269	Failure of production casing pipe / connection
0.2873	Failure of second barrier
0.2708	Failure of "B" annulus penetration
0.0101	Failure of second flow path
0.0395	Failure of intermediate casing pipe / connections
0.2554	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0125	Failure of third flow path
0.0491	Failure of intermediate casing hanger packoff
0.2554	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0141	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.0491	Failure of production casing hanger packoff
0.2873	Failure of second barrier
0.2708	Failure of "B" annulus penetration
0.0125	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.2554	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0101	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connection
0.2554	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement

Fault Tree with Two Penetrations	
with 1/2" penetration / valves	
Failure Occurrence	Failure Mode
0.3393	Pressure migrates outward from production casing cement
0.0670	Failure of intermediate casing cement
0.2708	Failure of "B" annulus penetration
0.0125	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.2554	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.0670	Failure of intermediate casing cement
0.0165	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connections
0.4181	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0599	Failure of surface casing pipe / connections
0.2708	Failure of "B" annulus penetration
0.0016	Pressure migrates inward from production casing cement
0.0598	Failure of production casing cement
0.0269	Failure of production casing pipe / connections
0.0117	Failure of surface casing cement
0.0117	Failure of conductor pipe cement

Fault Tree with Two Penetrations	
with 1/2" penetration / valves	
Failure Occurrence	Failure Mode
0.0019	Pressure migrates inward from intermediate casing cement
0.0670	Failure of intermediate casing cement
0.0279	Failure of secondary flow path
0.0160	Failure of second flow path
0.0491	Failure of intermediate casing hanger packoff
0.3253	Failure of secondary flow path
0.2708	Failure of "B" annulus penetration
0.0491	Failure of production casing hanger packoff
0.0269	Failure of production casing pipe / connections
0.0121	Failure of third flow path
0.0395	Failure of intermediate casing pipe / connections
0.3067	Failure of secondary flow path
0.2708	Failure of "B" annulus penetration
0.0491	Failure of production casing hanger packoff
0.0135	Pressure migrates outward from intermediate casing cement
0.0670	Failure of intermediate casing cement
0.2019	Failure of secondary flow path
0.0599	Failure of surface casing pipe / connections
0.1511	Failure of "C" annulus penetration

12.6 Appendix F – Sensitivity Analysis Scenario 1

Fault Tree Analysis of Casing Pressure Subsets

Risk Index	Relative Failure Occurrence	Failure Mode
	15.62%	Failure of B or C Annulus Penetration, 2"
	0.0869	False Pressure Reading
6	0.0491	Pressure sensor inoperable
4	0.0249	Pressure sensor lost calibration
2	0.0077	Lost umbilical signal
2	0.0077	Pressure port plugged
	0.0047	Leakage from connections
1	0.0024	Leakage due to vibration
1	0.0024	Leakage due to corrosion
	0.0100	Failure of manual valve to function
2	0.0077	Valve malfunctions closed
1	0.0024	Valve malfunctions open
	0.0000	Wellhead housing integrity
1	0.0024	Higher bending moments due to taller housing
1	0.0024	Stress concentrations due to penetrations
	0.0545	Damage to valves from external forces
4	0.0249	Running / Installation damage
3	0.0153	Damage from ROV contact
2	0.0077	Damage when landing tree
2	0.0077	Dropped equipment

Risk Index	Relative Failure Occurrence	Failure Mode
	0.47%	Failure of Production Casing Pipe / Connections to Maintain a Pressure Barrier
1	0.0024	Corrosion
0	0.0000	Thermal cycling
0	0.0000	Damaged threads
1	0.0024	Damaged sealing surface
0	0.0000	Wear
0	0.0000	Bad / wrong thread compound
0	0.0000	Improper makeup of connection
	1.24%	Failure of Intermediate Casing Pipe / Connections to Maintain a Pressure Barrier
1	0.0024	Corrosion
0	0.0000	Thermal cycling
0	0.0000	Damaged threads
1	0.0024	Damaged sealing surface
2	0.0077	Wear
0	0.0000	Bad / wrong thread compound
0	0.0000	Improper makeup of connection
	2.95%	Failure of Surface Casing Pipe / Connections to Maintain a Pressure Barrier
1	0.0024	Corrosion
0	0.0000	Thermal cycling
0	0.0000	Damaged threads
1	0.0024	Damaged sealing surface
4	0.0249	Wear
0	0.0000	Bad / wrong thread compound
0	0.0000	Improper makeup of connection

Risk Index	Relative Failure Occurrence	Failure Mode
	1.47%	Failure of Casing Hanger Packoff to Maintain a Pressure Barrier
2	0.0077	Damaged sealing surface
1	0.0024	Thermal cycling / axial movement
1	0.0024	Installation anomalies
1	0.0024	Corrosion
0	0.0000	Seal damage from high temperature
0	0.0000	Loss of seal contact pressure
0	0.0000	Seal / fluid incompatibility
0	0.0000	Solids contamination
0	0.0000	Vibration

Risk Index	Relative Failure Occurrence	Failure Mode
	2.75%	Failure of Production Casing Cement to Maintain a Pressure Barrier
2	0.0077	Micro-annulus cracks
2	0.0077	Frac-Pac operations
2	0.0077	Expansion and contraction
1	0.0024	Poor formation / cement bond
1	0.0024	Gas in cement
	3.27%	Failure of Intermediate Casing Cement to Maintain a Pressure Barrier
2	0.0077	Micro-annulus cracks
2	0.0077	Frac-Pac operations
2	0.0077	Expansion and contraction
2	0.0077	Poor formation / cement bond
1	0.0024	Gas in cement
	0.00%	Failure of Surface / Conductor Casing Cement to Maintain a Pressure Barrier
0	0.0000	Micro-annulus cracks
0	0.0000	Frac-Pac operations
0	0.0000	Expansion and contraction
0	0.0000	Poor formation / cement bond
0	0.0000	Gas in cement

Fault Tree without Penetrations	
Failure Occurrence	Failure Mode
3.47%	Inability to Maintain a Pressure Barrier
0.0000	Pressure migrates outward from "A" annulus through the production casing pipe / connections
0.0047	Failure of production casing pipe / connection
0.0017	Failure of secondary barrier
0.0008	Failure of intmd casing flow path
0.0124	Failure of intermediate casing pipe / connections
0.0612	Failure of secondary barrier
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0009	Failure of intmd csg hgr packoff flow path
0.0147	Failure of intermediate casing hanger packoff
0.0612	Failure of secondary barrier
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0000	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.0147	Failure of production casing hanger packoff
0.0017	Failure of secondary barrier
0.0009	Failure of intmd csg hgr packoff flow path
0.0147	Failure of intermediate casing hanger packoff
0.0612	Failure of secondary barrier
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0008	Failure of intmd casing flow path
0.0124	Failure of intermediate casing pipe / connection
0.0612	Failure of secondary barrier
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement

Fault Tree without Penetrations	
Failure Occurrence	Failure Mode
0.0336	Pressure migrates outward from production casing cement
0.0327	Failure of intermediate casing cement
0.0005	Failure of intmd csg hgr packoff flow path
0.0147	Failure of intermediate casing hanger packoff
0.0372	Failure of secondary barrier
0.0047	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0004	Failure of third flow path
0.0124	Failure of intermediate casing pipe / connections
0.0295	Failure of surface casing pipe / connections
0.0001	Pressure migrates inward from production casing cement
0.0275	Failure of production casing cement
0.0047	Failure of production casing pipe / connections
0.0000	Failure of surface casing cement
0.0000	Failure of conductor pipe cement
0.0000	Pressure migrates inward from intermediate casing cement
0.0327	Failure of intermediate casing cement
0.0003	Failure of second flow path
0.0147	Failure of intermediate casing hanger packoff
0.0193	Failure of secondary flow path
0.0147	Failure of production casing hanger packoff
0.0047	Failure of production casing pipe / connections
0.0002	Failure of third flow path
0.0124	Failure of intermediate casing pipe / connections
0.0147	Failure of production casing hanger packoff
0.0010	Pressure migrates outward from intermediate casing cement
0.0327	Failure of intermediate casing cement
0.0295	Failure of surface casing pipe / connections

Fault Tree with One Penetration

with 2" penetration / valves

Failure Occurrence	Failure Mode
18.92%	Inability to maintain Pressure Barrier
0.0007	Pressure migrates outward from "A" annulus thru production casing pipe / connections
0.0047	Failure of production casing pipe / connection
0.1576	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.0008	Failure of second flow path
0.0124	Failure of intermediate casing pipe / connections
0.0612	Failure of secondary barrier
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0009	Failure of third flow path
0.0147	Failure of intermediate casing hanger packoff
0.0612	Failure of secondary barrier
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0023	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.0147	Failure of production casing hanger packoff
0.1576	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.0009	Failure of second flow path
0.0147	Failure of intermediate casing hanger packoff
0.0612	Failure of secondary barrier
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0008	Failure of third flow path
0.0124	Failure of intermediate casing pipe / connection
0.0612	Failure of secondary barrier
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement

Fault Tree with One Penetration	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.1857	Pressure migrates outward from production casing cement
0.0327	Failure of intermediate casing cement
0.1562	Failure of "B" annulus penetration
0.0005	Failure of second flow path
0.0147	Failure of intermediate casing hanger packoff
0.0327	Failure of secondary barrier
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0019	Failure of third flow path
0.0124	Failure of intermediate casing pipe / connections
0.1562	Failure of secondary barrier
0.0295	Failure of surface casing pipe / connections
0.1562	Failure of "B" annulus penetration
0.0001	Pressure migrates inward from production casing cement
0.0275	Failure of production casing cement
0.0047	Failure of production casing pipe / connections
0.0000	Failure of surface casing cement
0.0000	Failure of conductor pipe cement

Fault Tree with One Penetration	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.0002	Pressure migrates inward from intermediate casing cement
0.0327	Failure of intermediate casing cement
0.0025	Failure of second flow path
0.0147	Failure of intermediate casing hanger packoff
0.1725	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.0147	Failure of production casing hanger packoff
0.0047	Failure of production casing pipe / connections
0.0021	Failure of third flow path
0.0124	Failure of intermediate casing pipe / connections
0.1686	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.0147	Failure of production casing hanger packoff
0.0010	Pressure migrates outward from intermediate casing cement
0.0327	Failure of intermediate casing cement
0.0295	Failure of surface casing pipe / connections

Fault Tree with Two Penetrations	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
19.66%	Inability to maintain Pressure Barrier
0.0008	Pressure migrates outward from "A" annulus thru production casing pipe / connections
0.0047	Failure of production casing pipe / connection
0.1608	Failure of second barrier
0.1562	Failure of "B" annulus penetration
0.0025	Failure of second flow path
0.0124	Failure of intermediate casing pipe / connections
0.2030	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0030	Failure of third flow path
0.0147	Failure of intermediate casing hanger packoff
0.2030	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0024	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.0147	Failure of production casing hanger packoff
0.1608	Failure of second barrier
0.1562	Failure of "B" annulus penetration
0.0030	Failure of second flow path
0.0147	Failure of intermediate casing hanger packoff
0.2030	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0025	Failure of third flow path
0.0124	Failure of intermediate casing pipe / connection
0.2030	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement

Fault Tree wiht Two Penetrations	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.1892	Pressure migrates outward from production casing cement
0.0327	Failure of intermediate casing cement
0.1562	Failure of "B" annulus penetration
0.0030	Failure of second flow path
0.0147	Failure of intermediate casing hanger packoff
0.2030	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0295	Failure of surface casing pipe / connections
0.0327	Failure of intermediate casing cement
0.0038	Failure of third flow path
0.0124	Failure of intermediate casing pipe / connections
0.3048	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.0295	Failure of surface casing pipe / connections
0.1562	Failure of "B" annulus penetration
0.0001	Pressure migrates inward from production casing cement
0.0275	Failure of production casing cement
0.0047	Failure of production casing pipe / connections
0.0000	Failure of surface casing cement
0.0000	Failure of conductor pipe cement

Fault Tree with Two Penetrations	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.0002	Pressure migrates inward from intermediate casing cement
0.0327	Failure of intermediate casing cement
0.0046	Failure of secondary flow path
0.0025	Failure of second flow path
0.0147	Failure of intermediate casing hanger packoff
0.1725	Failure of secondary flow path
0.1562	Failure of "B" annulus penetration
0.0147	Failure of production casing hanger packoff
0.0047	Failure of production casing pipe / connections
0.0021	Failure of third flow path
0.0124	Failure of intermediate casing pipe / connections
0.1686	Failure of secondary flow path
0.1562	Failure of "B" annulus penetration
0.0147	Failure of production casing hanger packoff
0.0058	Pressure migrates outward from intermediate casing cement
0.0327	Failure of intermediate casing cement
0.1761	Failure of secondary flow path
0.0295	Failure of surface casing pipe / connections
0.1511	Failure of "C" annulus penetration

12.7 Appendix G – Sensitivity Analysis Scenario 2

Fault Tree Analysis of Casing Pressure Subsets

Risk Index	Relative Failure Occurrence	Failure Mode
	15.62%	Failure of B or C Annulus Penetration, 2"
	0.0869	False Pressure Reading
6	0.0491	Pressure sensor inoperable
4	0.0249	Pressure sensor lost calibration
2	0.0077	Lost umbilical signal
2	0.0077	Pressure port plugged
	0.0047	Leakage from connections
1	0.0024	Leakage due to vibration
1	0.0024	Leakage due to corrosion
	0.0100	Failure of manual valve to function
2	0.0077	Valve malfunctions closed
1	0.0024	Valve malfunctions open
	0.0000	Wellhead housing integrity
1	0.0024	Higher bending moments due to taller housing
1	0.0024	Stress concentrations due to penetrations
	0.0545	Damage to valves from external forces
4	0.0249	Running / Installation damage
3	0.0153	Damage from ROV contact
2	0.0077	Damage when landing tree
2	0.0077	Dropped equipment

Risk Index	Relative Failure Occurrence	Failure Mode
	9.91%	Failure of Production Casing Pipe / Connections to Maintain a Pressure Barrier
4	0.0249	Corrosion
3	0.0153	Thermal cycling
3	0.0153	Damaged threads
4	0.0249	Damaged sealing surface
2	0.0077	Wear
2	0.0077	Bad / wrong thread compound
2	0.0077	Improper makeup of connection
	13.83%	Failure of Intermediate Casing Pipe / Connections to Maintain a Pressure Barrier
4	0.0249	Corrosion
3	0.0153	Thermal cycling
3	0.0153	Damaged threads
4	0.0249	Damaged sealing surface
5	0.0362	Wear
3	0.0153	Bad / wrong thread compound
3	0.0153	Improper makeup of connection
	16.26%	Failure of Surface Casing Pipe / Connections to Maintain a Pressure Barrier
4	0.0249	Corrosion
3	0.0153	Thermal cycling
3	0.0153	Damaged threads
4	0.0249	Damaged sealing surface
7	0.0634	Wear
3	0.0153	Bad / wrong thread compound
3	0.0153	Improper makeup of connection

Risk Index	Relative Failure Occurrence	Failure Mode
	17.26%	Failure of Casing Hanger Packoff to Maintain a Pressure Barrier
5	0.0362	Damaged sealing surface
4	0.0249	Thermal cycling / axial movement
4	0.0249	Installation anomalies
4	0.0249	Corrosion
3	0.0153	Seal damage from high temperature
3	0.0153	Loss of seal contact pressure
3	0.0153	Seal / fluid incompatibility
3	0.0153	Solids contamination
3	0.0153	Vibration

Risk Index	Relative Failure Occurrence	Failure Mode
	14.87%	Failure of Production Casing Cement to Maintain a Pressure Barrier
5	0.0362	Micro-annulus cracks
5	0.0362	Frac-Pac operations
5	0.0362	Expansion and contraction
4	0.0249	Poor formation / cement bond
4	0.0249	Gas in cement
	15.86%	Failure of Intermediate Casing Cement to Maintain a Pressure Barrier
5	0.0362	Micro-annulus cracks
5	0.0362	Frac-Pac operations
5	0.0362	Expansion and contraction
5	0.0362	Poor formation / cement bond
4	0.0249	Gas in cement
	7.42%	Failure of Surface / Conductor Casing Cement to Maintain a Pressure Barrier
3	0.0153	Micro-annulus cracks
3	0.0153	Frac-Pac operations
3	0.0153	Expansion and contraction
3	0.0153	Poor formation / cement bond
3	0.0153	Gas in cement

Fault Tree without Penetrations	
Failure Occurrence	Failure Mode
37.40%	Inability to Maintain a Pressure Barrier
0.0089	Pressure migrates outward from "A" annulus through the production casing pipe / connections
0.0991	Failure of production casing pipe / connection
0.0898	Failure of secondary barrier
0.0409	Failure of intmd casing flow path
0.1383	Failure of intermediate casing pipe / connections
0.2954	Failure of secondary barrier
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0510	Failure of intmd csg hgr packoff flow path
0.1726	Failure of intermediate casing hanger packoff
0.2954	Failure of secondary barrier
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0155	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.1726	Failure of production casing hanger packoff
0.0898	Failure of secondary barrier
0.0510	Failure of intmd csg hgr packoff flow path
0.1726	Failure of intermediate casing hanger packoff
0.2954	Failure of secondary barrier
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0409	Failure of intmd casing flow path
0.1383	Failure of intermediate casing pipe / connection
0.2954	Failure of secondary barrier
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement

Fault Tree without Penetrations	
Failure Occurrence	Failure Mode
0.2118	Pressure migrates outward from production casing cement
0.1586	Failure of intermediate casing cement
0.0418	Failure of intmd csg hgr packoff flow path
0.1726	Failure of intermediate casing hanger packoff
0.2419	Failure of secondary barrier
0.0991	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0225	Failure of third flow path
0.1383	Failure of intermediate casing pipe / connections
0.1626	Failure of surface casing pipe / connections
0.0147	Pressure migrates inward from production casing cement
0.1487	Failure of production casing cement
0.0991	Failure of production casing pipe / connections
0.0742	Failure of surface casing cement
0.0742	Failure of conductor pipe cement
0.0106	Pressure migrates inward from intermediate casing cement
0.1586	Failure of intermediate casing cement
0.0439	Failure of second flow path
0.1726	Failure of intermediate casing hanger packoff
0.2546	Failure of secondary flow path
0.1726	Failure of production casing hanger packoff
0.0991	Failure of production casing pipe / connections
0.0239	Failure of third flow path
0.1383	Failure of intermediate casing pipe / connections
0.1726	Failure of production casing hanger packoff
0.0258	Pressure migrates outward from intermediate casing cement
0.1586	Failure of intermediate casing cement
0.1626	Failure of surface casing pipe / connections

Fault Tree with One Penetration	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
48.71%	Inability to maintain Pressure Barrier
0.0230	Pressure migrates outward from "A" annulus thru production casing pipe / connections
0.0991	Failure of production casing pipe / connection
0.2319	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.0409	Failure of second flow path
0.1383	Failure of intermediate casing pipe / connections
0.2954	Failure of secondary barrier
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0510	Failure of third flow path
0.1726	Failure of intermediate casing hanger packoff
0.2954	Failure of secondary barrier
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0400	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.1726	Failure of production casing hanger packoff
0.2319	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.0510	Failure of second flow path
0.1726	Failure of intermediate casing hanger packoff
0.2954	Failure of secondary barrier
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0409	Failure of third flow path
0.1383	Failure of intermediate casing pipe / connection
0.2954	Failure of secondary barrier
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement

Fault Tree with One Penetration	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.3243	Pressure migrates outward from production casing cement
0.1586	Failure of intermediate casing cement
0.1562	Failure of "B" annulus penetration
0.0274	Failure of second flow path
0.1726	Failure of intermediate casing hanger packoff
0.1586	Failure of secondary barrier
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0216	Failure of third flow path
0.1383	Failure of intermediate casing pipe / connections
0.1562	Failure of secondary barrier
0.1626	Failure of surface casing pipe / connections
0.1562	Failure of "B" annulus penetration
0.0147	Pressure migrates inward from production casing cement
0.1487	Failure of production casing cement
0.0991	Failure of production casing pipe / connections
0.0742	Failure of surface casing cement
0.0742	Failure of conductor pipe cement

Fault Tree with One Penetration	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.0163	Pressure migrates inward from intermediate casing cement
0.1586	Failure of intermediate casing cement
0.0640	Failure of second flow path
0.1726	Failure of intermediate casing hanger packoff
0.3710	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.1726	Failure of production casing hanger packoff
0.0991	Failure of production casing pipe / connections
0.0418	Failure of third flow path
0.1383	Failure of intermediate casing pipe / connections
0.3018	Failure of secondary barrier
0.1562	Failure of "B" annulus penetration
0.1726	Failure of production casing hanger packoff
0.0258	Pressure migrates outward from intermediate casing cement
0.1586	Failure of intermediate casing cement
0.1626	Failure of surface casing pipe / connections

Fault Tree with Two Penetrations	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
53.94%	Inability to maintain Pressure Barrier
0.0256	Pressure migrates outward from "A" annulus thru production casing pipe / connections
0.0991	Failure of production casing pipe / connection
0.2583	Failure of second barrier
0.1562	Failure of "B" annulus penetration
0.0556	Failure of second flow path
0.1383	Failure of intermediate casing pipe / connections
0.4019	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0694	Failure of third flow path
0.1726	Failure of intermediate casing hanger packoff
0.4019	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0446	Pressure migrates outward from "A" annulus thru production casing hanger packoff
0.1726	Failure of production casing hanger packoff
0.2583	Failure of second barrier
0.1562	Failure of "B" annulus penetration
0.0694	Failure of second flow path
0.1726	Failure of intermediate casing hanger packoff
0.4019	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0556	Failure of third flow path
0.1383	Failure of intermediate casing pipe / connection
0.4019	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement

Fault Tree with Two Penetrations	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.3758	Pressure migrates outward from production casing cement
0.1586	Failure of intermediate casing cement
0.1562	Failure of "B" annulus penetration
0.0694	Failure of second flow path
0.1726	Failure of intermediate casing hanger packoff
0.4019	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.1626	Failure of surface casing pipe / connections
0.1586	Failure of intermediate casing cement
0.0554	Failure of third flow path
0.1383	Failure of intermediate casing pipe / connections
0.4001	Failure of second barrier
0.1511	Failure of "C" annulus penetration
0.1626	Failure of surface casing pipe / connections
0.1562	Failure of "B" annulus penetration
0.0147	Pressure migrates inward from production casing cement
0.1487	Failure of production casing cement
0.0991	Failure of production casing pipe / connections
0.0742	Failure of surface casing cement
0.0742	Failure of conductor pipe cement

Fault Tree with Two Penetrations	
with 2" penetration / valves	
Failure Occurrence	Failure Mode
0.0163	Pressure migrates inward from intermediate casing cement
0.1586	Failure of intermediate casing cement
0.1031	Failure of secondary flow path
0.0640	Failure of second flow path
0.1726	Failure of intermediate casing hanger packoff
0.3710	Failure of secondary flow path
0.1562	Failure of "B" annulus penetration
0.1726	Failure of production casing hanger packoff
0.0991	Failure of production casing pipe / connections
0.0418	Failure of third flow path
0.1383	Failure of intermediate casing pipe / connections
0.3018	Failure of secondary flow path
0.1562	Failure of "B" annulus penetration
0.1726	Failure of production casing hanger packoff
0.0458	Pressure migrates outward from intermediate casing cement
0.1586	Failure of intermediate casing cement
0.2891	Failure of secondary flow path
0.1626	Failure of surface casing pipe / connections
0.1511	Failure of "C" annulus penetration

12.8 Appendix H – FMEA Data

FMECA Report Date: 11-Dec-2003 Rev:	Equipment: Subsea Wells in GOM Current Design Configuration without Penetrations Phase: Completed Wells Activity: Sustained Casing Pressure
--	--

Index	Component Identification	Potential Failure Mode(s)	Potential Cause(s) of Failure	Probability Index	Potential Effect(s) of Failure	Severity Index	Current Design Controls	Detection Index	Risk Priority Index
1	Production casing tubing hanger	Leakage of pressure / fluid past the casing hanger into the "B-1" annulus	Corrosion of seal surfaces		High pressure in the intermediate casing annulus				
2	Production casing tubing hanger	Leakage of pressure / fluid past the casing hanger into the "B-1" annulus	Seals not compatible with the high temperatures		High pressure in the intermediate casing annulus				
3	Production casing tubing hanger	Leakage of pressure / fluid past the casing hanger into the "B-1" annulus	Hanging or wear damage to the sealing surfaces		High pressure in the intermediate casing annulus				
4	Production casing tubing hanger	Leakage of pressure / fluid past the casing hanger into the "B-1" annulus	Lack of seal contact pressure		High pressure in the intermediate casing annulus				
5	Production casing tubing hanger	Leakage of pressure / fluid past the casing hanger into the "B-1" annulus	Incompatibility of the seal with the contained fluids		High pressure in the intermediate casing annulus				
6	Production casing tubing hanger	Leakage of pressure / fluid past the casing hanger into the "B-1" annulus	Solids contamination on the sealing surface		High pressure in the intermediate casing annulus				
7	Production casing tubing hanger	Leakage of pressure / fluid past the casing hanger into the "B-1" annulus	Loss of sealability due to vibration		High pressure in the intermediate casing annulus				

FMECA Report Date: 11-Dec-2003 Rev:	Equipment: Subsea Wells in GOM Current Design Configuration without Penetrations Phase: Completed Wells Activity: Sustained Casing Pressure
--	---

Index	Component Identification	Potential Failure Mode(s)	Potential Cause(s) of Failure	Probability Index	Potential Effect(s) of Failure	Severity Index	Current Design Controls	Detection Index	Risk Priority Index
8	Production casing / connections	Leakage of pressure / fluid through the production casing / connections into the "B-1" annulus	Corrosion of the connection sealing surfaces		High pressure in the intermediate casing annulus				
9	Production casing / connections	Leakage of pressure / fluid through the production casing / connections into the "B-1" annulus	Overload of the pipe / connections due to thermal cycling		High pressure in the intermediate casing annulus				
10	Production casing / connections	Leakage of pressure / fluid through the production casing / connections into the "B-1" annulus	Wear of the pipe from drilling operations		High pressure in the intermediate casing annulus				
11	Production casing / connections	Leakage of pressure / fluid through the production casing / connections into the "B-1" annulus	Damaged threads		High pressure in the intermediate casing annulus				
12	Production casing / connections	Leakage of pressure / fluid through the production casing / connections into the "B-1" annulus	Damaged sealing surfaces		High pressure in the intermediate casing annulus				
13	Production casing / connections	Leakage of pressure / fluid through the production casing / connections into the "B-1" annulus	Bad / wrong thread compound		High pressure in the intermediate casing annulus				

FMECA Report Date: 11-Dec-2003 Rev:	Equipment: Subsea Wells in GOM Current Design Configuration without Penetrations Phase: Completed Wells Activity: Sustained Casing Pressure
--	---

Index	Component Identification	Potential Failure Mode(s)	Potential Cause(s) of Failure	Probability Index	Potential Effect(s) of Failure	Severity Index	Current Design Controls	Detection Index	Risk Priority Index
14	Production casing / connections	Leakage of pressure / fluid through the production casing / connections into the "B-1" annulus	Improper thread make-up		High pressure in the intermediate casing annulus				
15	Production casing cement	Leakage of pressure / fluid from formation through the cement into the "B-1" annulus	Micro-annulus cracks in the cement		High pressure in the intermediate casing annulus				
16	Production casing cement	Leakage of pressure / fluid from formation through the cement into the "B-1" annulus	Poor formation / cement bond		High pressure in the intermediate casing annulus				
17	Production casing cement	Leakage of pressure / fluid from formation through the cement into the "B-1" annulus	Frac-Pack operations		High pressure in the intermediate casing annulus				
18	Production casing cement	Leakage of pressure / fluid from formation through the cement into the "B-1" annulus	Expansion / contraction from thermal cycling		High pressure in the intermediate casing annulus				
19	Production casing cement	Leakage of pressure / fluid from formation through the cement into the "B-1" annulus	Mechanical impact loads		High pressure in the intermediate casing annulus				

FMECA Report Date: 11-Dec-2003 Rev:	Equipment: Subsea Wells in GOM Current Design Configuration without Penetrations
	Phase: Completed Wells
	Activity: Sustained Casing Pressure

FMECA Report Date: 11-Dec-2003 Rev:	Equipment: Subsea Wells in GOM Current Design Configuration without Penetrations
	Phase: Completed Wells
	Activity: Sustained Casing Pressure

FMECA Report Date: 11-Dec-2003 Rev:	Equipment: Subsea Wells in GOM Current Design Configuration without Penetrations
	Phase: Completed Wells
	Activity: Sustained Casing Pressure

FMECA Report Date: 11-Dec-2003 Rev:	Equipment: Subsea Wells in GOM Current Design Configuration without Penetrations
	Phase: Completed Wells
	Activity: Sustained Casing Pressure

FMECA Report Date: 11-Dec-2003 Rev:	Equipment: Subsea Wells in GOM Current Design Configuration without Penetrations
	Phase: Completed Wells
	Activity: Sustained Casing Pressure

FMECA Report Date: 11-Dec-2003 Rev:	Equipment: Subsea Wells in GOM Current Design Configuration without Penetrations
	Phase: Completed Wells
	Activity: Sustained Casing Pressure

[illegible]

Additional copies are available through Global Engineering Documents at (800) 854-7179 or (303) 397-7956

Information about API Publications, Programs and Services is available on the World Wide Web at <http://www.api.org>



**American
Petroleum
Institute**

1220 L Street, Northwest
Washington, D.C. 20005-4070
202-682-8000

Product No: G17TR31