# ASME B107.2002

NATIONAL STANDARD

# PLERS: LUGING GLAND AND TUBING PINCE-OFF

# AN AMERICAN



The American Society of Mechanical Engineers

Copyright ASME International Provided by IHS under license with ASME to reproduction or networking permitted without license from IHS



# STA NDARD Α Ν Α Μ Ε RI С Α Ν N ATIONAL PLIERS: LOCKING, CLAMP, AND TUBING **PINCH-NFF** ASME B107.36-2002

This Standard will be revised when the Society approves the issuance of a new edition. There will be no addenda issued to this edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the ASME Web site under the Committee Pages at http://www.asme.org/codes/ as they are issued.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

The American Society of Mechanical Engineers Three Park Avenue, New York, NY 10016-5990

Copyright © 2003 by THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS All rights reserved Printed in U.S.A.

# CONTENTS

For	reword	iv
Sta	indards Committee Roster	v
Co	mmittee Correspondence	vi
1	Scope	1
2	Classification	1
3	Normative References	1
4	Requirements	1
5	Test Procedures	2
6	Type, Class, and Style Provisions	4
7	Designations	4
Fig	Jure	
1	Typical Release Mechanisms for Locking Pliers	1
Та	bles	
1 2 3 4 5	Locking/Load Test For Type I Clamp Pliers Type I, Class 1, Style A, "C" Clamp, Fixed Type I, Class 1, Style B, "C" Clamp, Fixed with Swivel Pads Type I, Class 2, Sheet Metal Clamp Type I, Class 3, Welding Clamp	3 4 5 6 7
0	Type II, Tubing Finch-OH	8

### FOREWORD

The American National Standards Committee B107, Socket Wrenches and Drives, under sponsorship of The American Society of Mechanical Engineers, was reorganized as an ASME Standards Committee, and its title was changed to Hand Tools and Accessories. In 1996, its scope was expanded to include safety considerations.

The purposes of this Standard are to define general and dimensional data and safety considerations specifically applicable to locking clamp and tubing pinch-off pliers and to specify test methods to evaluate performance relating to the defined requirements.

A principal change in this edition of the Standard is the allowance of any material that meets the performance and safety requirements specified.

The format of this standard is in accordance with The ASME Codes & Standards Writing Guide 2000. Requests for interpretations of the technical requirements of this Standard should be expressed in writing to the Secretary, B107 Committee, at the address below.

Suggestions for the improvement of this Standard are welcome. They should be addressed to the American Society of Mechanical Engineers, B107 Standards Committee, Three Park Avenue, New York, NY 10016-5990.

The requirements of this Standard become effective at the time of publication. This Standard was approved as an American National Standard on September 16, 2002.

## ASME STANDARDS COMMITTEE B107 Hand Tools and Accessories

(The following is the roster of the Committee at the time of approval of this Standard.)

#### **OFFICERS**

G. E. Olson, Chair W. T. Pagac, Vice Chair J. R. Bird, Secretary

#### **COMMITTEE PERSONNEL**

- J. R. Bird, The American Society of Mechanical Engineers
- J. D. Davidson, Sears Roebuck & Co.
- J. S. Foote, Trade Association Management, Inc.
- A. Hershkovitz, Consultant
- H. Kimball, Naval Air Warfare Center
- R. R. McCullough, Consultant
- D. S. McKittrick, Western Forge Corp.
- G. E. Olson, Gene Olson, Engineering Consultants, Ltd.
- W. T. Pagac, Snap-on Inc.
- D. Eggert, Alternate, Snap-on Inc.
- J. Ster, General Services Administration
- S. Fjoser, Alternate, General Services Administration
- W. R. Wacker, BAC Associates, Inc.
- R. B. Wright, Wright Tool Co.
- W. Snyder, Alternate, Wright Tool Co.

#### SUBCOMMITTEE 5 - PLIERS

- D. S. McKittrick, Chair, Western Forge Corp.
- J. D. Davidson, Sears Roebuck & Co.
- J. S. Foote, Trade Association Management, Inc.
- R. R. McCullough, Consultant
- J. Ster, General Services Administration

v

## CORRESPONDENCE WITH THE B107 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions, and attending Committee meetings. Correspondence should be addressed to:

Secretary, B107 Standards Committee The American Society of Mechanical Engineers Three Park Avenue New York, NY 10016-5990

*Proposing Revisions.* Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the applications of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Interpretations. Upon request, the B107 Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B107 Standards Committee.

The request for interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his/her request in the following format:

Subject:Cite the applicable paragraph number(s) and the topic of the inquiry.Edition:Cite the applicable edition of the Standard for which the interpretation<br/>is being requested.

Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in this format may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

Attending Committee Meetings. The B107 Standards Committee regularly holds meetings that are open to the public. Persons wishing to attend any meeting should contact the Secretary of the B107 Standards Committee.

## PLIERS: LOCKING, CLAMP, AND TUBING PINCH-OFF

#### **1 SCOPE**

This Standard covers dimensions and functional characteristics of locking clamp pliers and tubing pinchoff pliers suitable for clamping operations in assembly and repair work. Tubing pinch-off pliers are used to pinch off the flow of gas or other material flowing through rubber or soft copper tubing. Inclusion of dimensional and functional data in this Standard is not intended to imply that all products described herein are stock production sizes. Consumers are requested to consult with manufacturers concerning lists of stock production sizes.

#### **2 CLASSIFICATION**

Pliers covered by this Standard shall be of the following types, classes, and styles, as specified.

Type I — Clamp
Class 1 — "C" Clamp
Style A — Fixed
Style B — Fixed, with swivel pads
Class 2 — Sheet metal clamp
Class 3 — Welding clamp
Type II — Tubing Pinch-Off

#### **3 NORMATIVE REFERENCES**

The following documents form a part of this Standard to the extent specified herein. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of the documents indicated here.

- ASME B46.1-1995, Surface Texture (Surface Roughness, Waviness, and Lay)
- ASME B107.25M-1996, Pliers Performance Test Methods
- Publisher: The American Society of Mechanical Engineers (ASME International), Three Park Avenue, New York, NY 10016-5990; Order Department: 22 Law Drive, Box 2300, Fairfield, NJ 07007-2300

#### **4 REQUIREMENTS**

#### 4.1 Illustrations

Illustrations shown herein are descriptive and not restrictive, and are not intended to preclude the manufacture of pliers that are otherwise in accordance with this Standard.

#### 4.2 Material

Materials used in the manufacture of pliers shall be such as to produce pliers conforming to the requirements specified in this Standard.

#### 4.3 Design

Pliers shall be similar to the illustration to which reference is made and shall be proportioned in all parts so as to meet the requirements of this Standard. Pliers shall be provided with a toggle or cam device that has an adjustable mechanism designed so that the jaws can be clamped and locked. Pliers shall be released by hand anywhere within the pliers' capacity by either of the release mechanisms shown in Fig. 1. Test specimens shall withstand applicable test procedures without cracking or breaking.



FIG. 1 TYPICAL RELEASE MECHANISMS FOR LOCKING PLIERS

1

#### 4.4 Handles

Handles of pliers shall be through hardened from 30 to 50 HRC or case hardened from 75 to 86 HR15N, with a case depth of a minimum of 0.010 in. (0.25 mm). Handles shall be so shaped as to afford a comfortable grip and shall be free from rough edges and sharp corners. When the pliers are locked in any position of the jaws, the minimum handle clearance between the fixed and movable handle shall be as specified in the appropriate tables. Outer hand-gripping surfaces of handles shall be smooth, knurled, or impressed.

#### 4.5 Joints

Pliers joints shall have no excessive looseness, play, or any other indications of side play of the two halves of the pliers when opened or closed, which could impair the function of pliers. Joint fasteners shall be through hardened from 25 to 50 HRC. Where fasteners receive a case hardening treatment in addition to the through hardening, a maximum hardness of 60 HRC or equivalent will be permitted.

#### 4.6 Jaws

**4.6.1 Jaw Openings.** Ends of jaws shall open, when adjusted by the screw, to the entire respective clamping range minimum specified in Tables 2 through 5. Pliers shall operate in a smooth and uniform manner.

**4.6.2 Jaw Hardness.** Jaws shall be through hardened from 35 to 50 HRC or case hardened from 83 to 90 HR15N, with a case depth minimum of 0.010 in. (0.25 mm). If provided, swivel pads need not be hardened.

#### 4.7 Adjusting Screw

Adjusting screw located at the end of handle shall have a minimum hardness of 30 HRC.

#### 4.8 Marking

Pliers shall be marked in a plain and permanent manner with the manufacturer's name or with a trademark of such known character that the source of manufacture and country of origin can be readily determined. Marking shall be as permanent as the normal life expectancy of the pliers, providing the surface has not been subjected to a fretting or abrading action, and be capable of withstanding the cleaning normally experienced during its intended use.

#### 4.9 Finish

**4.9.1** Appearance. Surfaces shall be tested in accordance with ASME B46.1. Surfaces shall be free from pits, nodules, burrs, and other conditions that may adversely affect performance or appearance. Ground surfaces shall have a maximum surface roughness of 200  $\mu$ in. (5.1  $\mu$ m) arithmetic average. Measurement of the finish shall be made with a measuring instrument using a cutoff length of 0.03 in. (0.8 mm).

**4.9.2 Coating.** Coating shall be adherent, smooth, continuous, and free of pits, blisters, nodules, oxide scale, and any other conditions that may interfere with the protective value and serviceability of the pliers. Cadmium plate shall not be allowed. Pliers shall be coated with a supplementary rust-preventative treatment.

#### 4.10 Spring

Spring shall be capable of opening the jaws to the maximum value of the respective clamping range minimum dimension as specified in the tables for the individual type and class of pliers.

#### 4.11 Dimensions

Dimensions shall be determined by measuring the pliers with jaws in the closed and locked position. The overall length measurement shall include the adjusting screw.

#### 4.12 Workmanship

Requirements within this Standard are intended to describe the best commercial quality pliers available. Pliers shall conform to the requirements of this Standard.

#### **5 TEST PROCEDURES**

#### 5.1 Safety

WARNING: MANY TESTS REQUIRED HEREIN ARE INHERENTLY HAZARDOUS, AND ADE-QUATE SAFEGUARDS FOR PERSONNEL AND PROPERTY SHALL BE EMPLOYED IN CONDUCT-ING SUCH TESTS.

#### 5.2 Hardness Test

Hardness range specified shall be tested in accordance with ASME B107.25M, para. 5.3.

Classification	Nominal Size, in. (mm)	Maximum Load to Lock Handles, Ibf. (N)	Minimum Test Load on Jaw Tips, Ibf (N)
Class 1	5 (127)	45 (200)	450 (2000)
Class 1	6 (150)	45 (200)	500 (2225)
Class 1	11 (280)	45 (200)	900 (4000)
Class 2	8 (200)	50 (220)	1000 (4450)
Class 3	9 (230)	25 (110)	500 (2225)

TABLE 1 LOCKING/LOAD TEST FOR TYPE I CLAMP PLIERS

#### 5.3 Locking/Load Test - Type I

Pliers shall be tested on a system capable of applying the required minimum test load given in Table 1. The pliers' handles shall be locked, using maximum value shown in Table 1. Test load shall be applied to the jaw tips in a direction to spread the jaw clamping surfaces apart for a minimum of 10 sec. Pliers shall remain locked while the load is applied. Pliers shall have passed the test if the jaw tips close, and all the joints and adjusting screw work properly after removal of the load.

#### 5.4 Pinch-Off Test – Type II

Pliers shall be tested using the following procedure:

**5.4.1** Fit a 0.25 in. (6.4 mm) outside diameter soft copper tube, with a 0.030 in. (0.76 mm) wall thickness, onto an air line having an air pressure of 95 to 100 lb/sq in. gauge (psig) (6.7 to 7.0 kPa).

**5.4.2** Place the copper tube between the jaws of the pliers 0.50 in. (12.7 mm) minimum from free end of the tube. Apply 70 to 75 lb of force (311 to 334 N) to the end of the movable handle to close the pliers. With air pressure of 95 to 100 psig (6.7 to 7.0 kPa) applied to one end of the tube, immerse the other end of the tube and the pliers in water.

**5.4.3** Pliers shall seal the tube by pinching-off the air supply and remain locked on the tube. Pliers shall be considered to have passed the test if no bubbles appear within 1 min.

#### 6 TYPE, CLASS, AND STYLE PROVISIONS

#### 6.1 Type I Clamp

Pliers shall be capable of withstanding the load test specified in para. 5.3. The design of the toggle or cam mechanism for Classes 1, 2, and 3 shall be such that

when the movable handle is released from the closed and locked position, the jaw tips shall move apart a minimum of 1.00 in. (25.4 mm).

**6.1.1 Class 1, "C" Clamp, Style A, Fixed.** Jaws shall have radiused or lightly serrated clamping surfaces. Class 1, Style A pliers shall conform to the dimensions of Table 2 and shall be similar to the illustration accompanying Table 2. With the jaws closed and locked, a rectangular block of a size equal to dimensions B and C shall pass freely through the throat.

**6.1.2 Class 1, "C" Clamp, Style B, Fixed With Swivel Pads.** Jaws shall have smooth clamping surfaces that are movable so as to facilitate parallel clamping throughout adjustment range. Clamp shall conform to the dimensions of Table 3 and shall be similar to the illustration accompanying Table 3. With clamp jaws closed and locked, a rectangular block of a size equal to dimensions B and C shall pass freely through the throat.

**6.1.3 Class 2, Sheet Metal Clamp.** Jaws shall have enlarged clamping surfaces suitable for firmly holding sheet metal. Clamp shall conform to the dimensions in Table 4 and shall be similar to the illustration accompanying Table 4.

**6.1.4 Class 3, Welding Clamp.** Jaws shall be "U" shaped and constructed with an open area in the center to permit welding, soldering, riveting, and similar operations while the work is clamped. Class 3 clamps shall conform to the dimensions in Table 5 and shall be similar to the illustration accompanying Table 5.

#### 6.2 Type II, Tubing Pinch-Off

Pliers shall be capable of withstanding testing in accordance with para. 5.4. With the pliers in the closed and locked position, the jaw tips shall make contact and the remainder of jaw contact surface shall be such that a 0.005-in. (0.13-mm) thickness gage cannot be



TABLE 2 TYPE I, CLASS 1, STYLE A, "C" CLAMP, FIXED

Nominal Size, in. (mm)	Overall Length, A, in. (mm) ±1.00 (25.4)	Min. Throat Width, <i>B</i> , in. (mm)	Min. Throat Depth, <i>C</i> , in. (mm)	Handle Width, <i>D</i> , in. (mm) ±0.25 (6.4)	Min. Handle Clearance, E, in. (mm)	Jaw Width, <i>F</i> , in. (mm) ±0.13 (3.3)	Height, G, in. (mm) ±1.00 (25.4)	Min. Clamping Range, in. (mm)
6	6.50	1.50	1.25	1.50	0.09	0.38	3.50	0 - 2.00
(150)	(165.1)	(38.1)	(31.8)	(38.1)	(2.3)	(9.7)	(88.9)	(0 - 50.8)
11	10.50	3.00	2.25	2.00	0.16	0.50	5.50	0 - 3.38
(280)	(266.7)	(76.2)	(57.2)	(50.8)	(4.1)	(12.7)	(139.7)	(0 - 85.9)

inserted through the closed jaws. The throat depth shall be a minimum of 0.750 in. (19.05 mm). Pliers shall conform to Table 6 and shall be similar to the illustration accompanying Table 6.

- (a) Title, number, and date of this Standard.
- (b) Type, class, and style of pliers required.
- (c) Size of pliers required.
- (d) Type of coating required.

#### **7 DESIGNATIONS**

Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

ASME B107.36-2002



TABLE 3 TYPE I, CLASS 1, STYLE B, "C" CLAMP, FIXED WITH SWIVEL PADS

Nominal Size, in. (mm)	Overall Length, A, in. (mm) ±1.00 (25.4)	Min. Throat Width, <i>B</i> , in. (mm)	Min. Throat Depth, <i>C</i> , in. (mm)	Handle Width, <i>D</i> , in. (mm) ±0.25 (6.4)	Min. Handle Clearance, E, in. (mm)	Pad Width, F, in. (mm) ±0.13 (3.3)	Height, G, in. (mm) ±1.00 (25.4)	Min. Clamping Range, in. (mm)
5	5.25	1.38	0.90	1.31	0.09	0.63	2.75	0 - 1.50
(127)	(133.4)	(35.1)	(22.9)	(33.3)	(2.3)	(16.0)	(69.9)	(0 - 38.1)
6	6.50	1.50	1.13	1.50	0.09	0.88	3.50	0 - 2.00
(150)	(165.1)	(38.1)	(28.7)	(38.1)	(2.3)	(22.4)	(88. <del>9</del> )	(0 - 50.8)
11	10.50	3.00	2.25	2.00	0.16	1.13	5.50	0 - 3.38
(280)	(266.7)	(76.2)	(57.2)	(50.8)	(4.1)	(28.7)	(139.7)	(0 - 85.9)



#### TABLE 4 TYPE I, CLASS 2, SHEET METAL CLAMP

Nominal Size, in. (mm)	Overall Length, A, in. (mm) ±0.63 (16.0)	Clamp Width, B, in. (mm) ±0.13 (3.3)	Height, C, in. (mm) (9.7) ±0.38	Handle Width, D, in. (mm) ±0.38 (9.7)	Min. Handle Clearance, <i>E</i> , in. (mm)	Clamp Depth, <i>F</i> , in. (mm) ±0.50 (12.7)	Min. Clamping Range in. (mm)
8	7.75	3.13	2.25	1.75	0.16	1.75	0 - 0.50
(200)	(196.9)	(79.5)	(57.2)	(44.5)	(4.1)	(44.5)	(0 -12.7)



TABLE 5 TYPE I, CLASS 3, WELDING CLAMP

Nominal Size, in. (mm)	Overall Length, A, in. (mm) ±0.50 (12.7)	Inside Width, B, in. (mm) ±0,13 (3.3)	Inside Height, C, in. (mm) ±0.13 (3.3)	Handle Width, D, in. (mm) ±0.50 (12.7)	Min. Handle Clearance, <i>E</i> , in, (mm)	Inside Depth, F, in. (mm) ±0.50 (12.7)	Outside Width, <i>G</i> , in. (mm) ±0.13 (3.3)	Min. Clamping Range, in. (mm)
9	9.00	1.00	1.00	1.88	0.16	3.00	2.75	0 - 1.63
(230)	(228.6)	(25.4)	(25.4)	(47.8)	(4.1)	(76.2)	(69.9)	(0 -41.4)





TABLE 6 TYPE II, TUBING PINCH-OFF

Nominal Size, in. (mm)	Overall Length, <i>A</i> , in. (mm) ±0.63 (16.0)	Top Jaw Radius, <i>B</i> , in. (mm) ±0.016 (.41)	Bottom Jaw Radius, <i>C</i> , in. (mm) ±0.016 (.41)	Handle Width, <i>D</i> , in. (mm) ±0.38 (9.7)	Min. Handle Clearance, <i>E</i> , in. (mm)	Height, <i>F</i> , in. (mm) ±0.38 (9.7)
7	7.00	0.13	0.06	1.75	0.16	2.25
(180)	(177.8)	(3.3)	(1.5)	(44.5)	(4.1)	(57.2)

# **ASME Services**

ASME is committed to developing and delivering technical information. At ASME's Information Central, we make every effort to answer your questions and expedite your orders. Our representatives are ready to assist you in the following areas:

ASME Press Codes & Standards Credit Card Orders IMechE Publications Meetings & Conferences Member Dues Status Member Services & Benefits Other ASME Programs Payment Inquiries Professional Development Short Courses Publications Public Information Self-Study Courses Shipping Information Subscriptions/Journals/Magazines Symposia Volumes Technical Papers

#### How can you reach us? It's easier than ever!

There are four options for making inquiries\* or placing orders. Simply mail, phone, fax, or E-mail us and an Information Central representative will handle your request.

Mail ASME 22 Law Drive, Box 2900 Fairfield, New Jersey 07007-2900 Call Toll Free US & Canada: 800-THE-ASME (800-843-2763) Mexico: 95-800-THE-ASME (95-800-843-2763) Universal: 973-882-1167 Fax—24 hours 973-882-1717 973-882-5155 E-Mail—24 hours Infocentral@asme.org

\* Information Central staff are not permitted to answer inquiries about the technical content of this code or standard. Information as to whether or not technical inquiries are issued to this code or standard is shown on the copyright page. All technical inquiries must be submitted in writing to the staff secretary. Additional procedures for inquiries may be listed within.

or Resale

#### AMERICAN NATIONAL STANDARDS FOR HAND TOOLS

Socket Wrenches, Hand (Inch Series)	B107.1-2002
Souket Wrenches, Extensions, Adaptors, and Onversal Joints,	B107 2-2002
Fower Direct (mpach) (mon Series)	07 3-1978(R1991)
Socket Wrenches, Fower Drive (Non-Impact) (Inch Series)	07.0-1070(1110017
Driving and Spindle Ends for Portable Hand, impact, Air, and	P107 4M 1005
Electric Tools (Percussion Tools Excluded)	DIU7.4IVI-1990
Socket Wrenches, Hand (Metric Series)	B107.5IVI-2002
Adjustable Wrenches	B107.8IVI-1996
Handles and Attachments for Hand Socket Wrenches – Inch and Metric Series	. B107.10IVI-1996
Pliers: Diagonal Cutting and End Cutting	B107.11-2002
Nut Drivers (Spin Type, Screwdriver Grip) (Inch Series)	B107.12-1997
Pliers – Long Nose, Long Reach	. B107.13M-1996
Hand Torque Tools	. B107.14M-1994
Flat Tip Screwdrivers	B107.15-2002
Shears (Metal Cutting, Hand)	. B107.16M-1998
Gages, Wrench Openings, Reference	. B107.17M-1997
Pliers (Wire Twister)	. B107.18M-1996
Pliers Betaining Bing B10	7.19-1993(R1998)
Pliers (Lineman's Iron Worker's Gas Glass Fence and Battery)	B107.20M-1998
Wrench Crowfoot Attachments	B107 21-1998
	B107 22M-1998
Electronic Guilers,	R107 22M-1007
Filers, Multiple Fosition, Aujustable	D107.25M 1006
Pilers — Performance Fest Methods	D107.20101-1990
Plers, Multiple Position (Electrical Connector)	D107 2014 1007
Electronic Torque Instruments.	. BIU7.28IVI-1997
Electronic Lester, Hand Torque Tools	. B107.29IVI-1998
Cross Tip Screwdrivers.	B107.30-2002
Screwdrivers, Cross Tip Gaging	. B107.31M-1997
Socket Wrenches for Spark Plugs	B107.34M-1997
Nut Drivers (Spin Type, Screwdriver Grip) (Metric Series)	B107.35M-1997
Pliers: Locking, Clamp, and Tubing Pinch-Off	B107.36-2002
Electronic Pliers	B107.38M-1998
Nail Hammers — Safety Requirements	B107.41M-1997
Hatchets: Safety Requirements	B107.42M-1997
Wood-Splitting Wedges: Safety Requirements	B107.43-2002
Glaziers' Chisels and Wood Chisels	B107.44-2002
Bipping Chisels and Flooring/Flectricians' Chisels	B107.45-2002
Stud Screw and Pine Extractors: Safety Bequirements	B107.46M-1998
Metal Chisels: Safety Benuirements	B107.47M-1998
Metal Punches and Drift Pins: Safety Requirements	B107.48M-1998
Nail Sate: Safety Requiremente	B107 49M-1998
Nan Sets. Safety Requirements	B107 50M-1998
Star Drille: Safaty Bequiremente	B107 51-2001
Star Drins, Salety negariements	R107 52M-1008
Nall-ruler bars. Salety nequirements.	0107 52NA 1009
Bail Peen nammers: Salety Requirements.	DIU7.00101-1990
Heavy Striking Loois: Safety Requirements	DIU/.04-2001
Axes: Safety Requirements.	D 107.55IVI-2002
Body Repair Hammers and Dolly Blocks: Safety Requirements	
Bricklayers' Hammers and Prospecting Picks: Safety Requirements	B10/.5/-2001
Riveting, Scaling, and Tinner's Setting Hammers: Safety Requirements	B107.58M-1998
Slugging and Striking Wrenches	B107.59-2002
Wrenches	B107.100-2002

The ASME Publications Catalog shows a complete list of all the Standards published by the Society. For a complimentary catalog, or the latest information about our publications, call 1-800-THE-ASME (1-800-843-2763).

