

AN AMERICAN NATIONAL STANDARD

Inspection and Quality Assurance for High-Volume Machine Assembly Fasteners

ASME/ANSI B18.18.2M-1987

REAFFIRMED 1999

FOR CURRENT COMMITTEE PERSONNEL
PLEASE SEE ASME MANUAL AS-11

SPONSORED AND PUBLISHED BY

THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS

United Engineering Center

345 East 47th Street

New York, N. Y. 10017

Date of Issuance: March 31, 1987

This Standard will be revised when the Society approves the issuance of a new edition. There will be no addenda or written interpretations of the requirements of this Standard issued to this Edition.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Consensus Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment which provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable Letters Patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations issued in accordance with governing ASME procedures and policies which preclude the issuance of interpretations by individual volunteers.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

Copyright © 1987 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All Rights Reserved
Printed in U.S.A.

FOREWORD

(This Foreword is not part of ASME/ANSI B18.18.2M-1987.)

American National Standards Committee B18 for the standardization of bolts, screws, nuts, rivets, and similar fasteners was organized in March 1922 as Sectional Committee B18 under the aegis of the American Engineering Standards Committee (later the American Standards Association, then the United States of America Standards Institute and, as of October 6, 1969, the American National Standards Institute, Inc.) with the Society of Automotive Engineers and the American Society of Mechanical Engineers as joint sponsors.

Subcommittee 18 of Committee B18 was established in September 1978 to develop a document to cover the quality assurance provisions for internally and externally threaded metric fasteners and accessories or associated parts.

At the March 1979 meeting of Subcommittee 18, it was agreed that the quality assurance document should be circulated for subcommittee consideration as a proposed standard. Subcommittee acceptance of the content ensued and the document was approved by letter ballot to the American National Standards Committee B18 on March 21, 1980.

The standard was subsequently approved by the Secretariat and submitted to the American National Standards Institute for designation as an American National Standard; it was designated ANSI B18.18.2M-1982 and approved on September 14, 1982.

A periodic review of the standard, undertaken by the Subcommittee in 1985, resulted in agreement that the document be revised to allow it to be used for inch as well as metric products. This was done by deleting the word "metric" from the title as well as from each place in the standard where it would inhibit the use of the document for inch as well as metric products. By retaining the "M" in the designator, the standard can be used for both inch and metric products without having to change any references made. A proposal containing these changes, as well as editorial corrections, was prepared and balloted by letter ballot to ASME Committee B18. Following approval by ASME, the proposal was submitted to the American National Standards Institute and designated an American National Standard on January 16, 1987.

ASME STANDARDS COMMITTEE B18

Standardization of Bolts, Nuts, Rivets, Screws, Washers, and Similar Fasteners

(The following is the roster of the Committee at the time of approval of this Standard.)

OFFICERS

J. B. Levy, *Chairman*
H. W. Ellison, *Vice Chairman*
E. Schwartz, *Vice Chairman*
R. W. McGinnis, *Secretary*

COMMITTEE PERSONNEL

AMERICAN SOCIETY OF AGRICULTURAL ENGINEERS
E. R. Friesth, Don E. Williams Co., Rock Island, Illinois

AMERICAN SOCIETY OF MECHANICAL ENGINEERS
A. R. Machell, Webster, New York
K. E. McCullough, SPS Technologies Inc., Newtown, Pennsylvania

ENGINE MANUFACTURERS ASSOCIATION
G. A. Russ, Cummins Engine Co., Columbus, Indiana

FARM & INDUSTRIAL EQUIPMENT INSTITUTE
D. A. Clever, Deere & Co., Moline, Illinois

HAND TOOL INSTITUTE
R. B. Wright, Wright Tool Co., Barberton, Ohio

INDUSTRIAL FASTENERS INSTITUTE
D. J. Broomfield, Illinois Tool Works Inc., Elgin, Illinois
D. A. Garrison, Russell, Burdsall & Ward Corp., Rock Falls, Illinois
R. M. Harris, Bethlehem Steel Corp., Lebanon, Pennsylvania
D. Littell, Greensburg, Pennsylvania
J. C. McMurray, *Alternate*, Russell, Burdsall & Ward Inc., Cleveland, Ohio
J. S. Orlando, Bethlehem Steel Corp., Lebanon, Pennsylvania
E. Sterling, Emhart Corp., Cambellsville, Kentucky
J. A. Trilling, Holo-Krome Co., West Hartford, Connecticut
S. Vass, Lake Erie Screw Corp., Cleveland, Ohio
C. J. Wilson, Industrial Fasteners Institute, Cleveland, Ohio

METAL CUTTING TOOL INSTITUTE
D. Emanuel, TRW-Greenfield Tap & Die, Greenfield, Massachusetts

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION
J. B. Levy, General Electric Co., Schenectady, New York
W. F. Montavon, *Alternate*, National Electrical Manufacturers Association, Washington, D.C.
F. F. Weingruber, Westinghouse Electric Corp., Pittsburgh, Pennsylvania

NATIONAL FASTENERS DISTRIBUTORS ASSOCIATION
J. F. Sullivan, Accurate Fasteners, Inc., South Boston, Massachusetts

SOCIETY OF AUTOMOTIVE ENGINEERS

H. W. Ellison, General Motors Corp., Warren, Michigan
R. S. Piotrowski, Mack Trucks Inc., Allentown, Pennsylvania

TUBULAR & MACHINE INSTITUTE

R. M. Byrne, Trade Association Management Inc., Tarrytown, New York
J. G. Zeratsky, National Rivet & Manufacturing Co., Waupun, Wisconsin

U. S. DEPARTMENT OF THE ARMY

M. E. Taylor, U. S. Army Armament, Munitions & Chemical Command, Dover, New Jersey
A. Herskovitz, *Alternate*, U. S. Army Armament, Munitions & Chemical Command, Dover, New Jersey
J. E. Long, *Alternate*, U. S. Army Tank Command, Warren, Michigan

U. S. DEPARTMENT OF DEFENSE

E. Schwartz, Defense Industrial Supply Center, Philadelphia, Pennsylvania
L. Pieninck, *Alternate*, Defense Industrial Supply Center, Philadelphia, Pennsylvania

U. S. DEPARTMENT OF THE NAVY

J. E. Hass, Department of the Navy, Washington, D.C.
M. S. Orysh, *Alternate*, Department of the Navy, Philadelphia, Pennsylvania

INDIVIDUAL MEMBERS

A. R. Breed, Lakewood, Ohio
R. A. Flor, Chrysler Corp., Detroit, Michigan
G. A. Gobb, Ford Motor Co., Dearborn, Michigan
F. E. Graves, F. E. Graves Associates, Fairfield, Connecticut
J. J. Naesset, Clark Equipment Co., Battle Creek, Michigan

PERSONNEL OF SUBCOMMITTEE 18 — INSPECTION AND QUALITY CONTROL

I. N. Kenig, *Chairman*, Defense Industrial Supply Center, Philadelphia, Pennsylvania
R. Flynn, General Motors Corp., Warren, Michigan
K. E. McCullough, SPS Technologies Inc., Newtown, Pennsylvania
I. Park, Steico Co., Ontario, Canada

CONTENTS

Foreword	iii
Standards Committee Roster	iv
1 General Information	1
2 Fasteners for High-Volume Machine Assembly Applications	1
Figure	
1 Basic Plan Outline	2
Tables	
1 Final Inspection — Machine Assembled and Other Special Purpose Fasteners — Nondestructive Tests	5
2 Final Inspection — Machine Assembled and Other Special Purpose Fasteners — Destructive Tests	6
3 Sample Size — Machine Assembled and Other Special Purpose Fasteners	6
Appendices	
I Tables A and B	7
II Ordering Information	9

INSPECTION AND QUALITY ASSURANCE FOR HIGH-VOLUME MACHINE ASSEMBLY FASTENERS

1 GENERAL INFORMATION

1.1 Basic Plan Structure

This Standard outlines a Quality Assurance Plan for internally and externally threaded fasteners and accessories or associated parts. Provisions are included for sampling plans, inspection frequencies, control procedures, and record keeping.

Included in this plan are fasteners such as those where a more detailed inspection would enhance mass assembly operation. The quality assurance plan for these fasteners relies primarily on increased final inspection rather than on documented in-process control.

This Standard will be used in conjunction with other accepted standards for product, testing, gaging, and material and, therefore, those provisions as well as packaging are not included herein.

1.2 Inspection Levels

The substantial difference in importance to the user of various characteristics and the dissimilar degrees of control in manufacture make impractical the subjecting of all characteristics to the same degree of inspection. Therefore, three inspection levels have been provided.

Any additional characteristics deemed applicable by the user that do not appear in the plan shall be explicitly designated by the user, preferably on engineering drawings and related specifications by the appropriate code letter at the time of ordering (see Appendix II). To assist in arriving at the most appropriate inspection level, the Decision Table included in Appendix I is recommended for guidance.

1.3 Lot Sizes

When the acceptance number for sampling by attributes is fixed, variation in sample size results in variation of acceptable quality. Therefore, to avoid this inconsistency, fixed sample sizes are applied for the

greatest range of lot size. Lot sizes are restricted to a maximum of 250,000 pieces.

1.4 Measuring and Testing Equipment

All measuring instruments, gages, and testing equipment used to inspect incoming materials and parts in process and in final inspection shall be calibrated at planned intervals to National Bureau of Standards (NBS) or other equivalent National Standards where applicable. The dates of calibration and fixture checks shall be recorded. Inspection records shall be kept for a minimum of 1 year.

1.5 Basic Plan Outline

The basic plan outline as shown in Fig. 1 is included to enhance understanding and use.

2 FASTENERS FOR HIGH-VOLUME MACHINE ASSEMBLY APPLICATIONS

2.1 Scope

This Section is an Acceptance Sampling Plan for high-volume machine assembly fasteners, accessories, and associated parts. It establishes specific inspection functions that must be performed on the finished product with the objective of ensuring that the accepted product conforms to all the requirements of engineering drawings, related standards, and/or specifications.

This plan does not necessitate in-process control; however, the producer, at his discretion, may apply in-process control. Adherence to the requirements of this plan does not release the contractor from the responsibility of exercising due care in the production of all parts to the requirements established for all characteristics shown on engineering drawings and related specifications.

2.2 Applicable Characteristics

Applicable characteristics include all characteristics of a part that are described by engineering drawings and related specifications. Three levels of inspection — A, B, and C — are provided in the plan. Alternate levels may be designated by the user if required. Refer to the Decision Table in Appendix I to establish alternate levels as required. Any additional characteristic(s) deemed applicable by the user and not appearing in the general plan, or characteristics for which the user requires an inspection level other than that designated in the plan, must be explicitly requested by the user and shown on drawings or specifications by the appropriate code letter at the time of ordering (see Appendix II).

2.3 Lot Definition

A *lot* is a quantity of product of one part number made by the same production process and subsequently submitted for final inspection at one time. Maximum lot size traceable to final inspection shall be no larger than 250,000 pieces.

For lot sizes equal to or less than 5,000 pieces, sample size is reduced to maintain inspection at a practical level.

2.4 Records

The contractor shall maintain logs and records of inspections and tests as required by this plan. Such records shall indicate the nature and number of observations made, the number and type of deficiencies found, the quantities of material or parts approved and rejected, and the nature of the corrective action taken, as appropriate. Records shall also include the disposition of rejected parts in accordance with para. 2.9 and shall be maintained for a minimum of 1 year from the date of shipment of the parts.

2.5 Purchased Accessories and Parts

Accessories, services, and partially fabricated parts (e.g., washers, nuts, blanks, heat treating, plating, etc.) may be purchased by the prime contractor from other suppliers for use in the production of fasteners, provided the following conditions and requirements are met.

(a) The prime contractor shall be completely responsible to the user for the quality of the final product.

(b) The prime contractor shall be responsible for the implementation of all requirements of this plan,




FIG. 1 BASIC PLAN OUTLINE

including records. The prime contractor shall include the requirements of this plan in the purchase order to the subcontractor.

(c) When the accessory, partially fabricated part, or treatment is processed by a subcontractor, the prime contractor shall so identify the subcontracting of the parts or processing in his records

(d) All lots that are heat treated and/or finished by a subcontractor and all lots that are processed by a subcontractor following heat treatment and/or

INSPECTION AND QUALITY ASSURANCE FOR
HIGH-VOLUME MACHINE ASSEMBLY FASTENERS

ASME/ANSI B18.18.2M-1987

finishing operations shall undergo final inspection by the prime contractor. Final inspection may be conducted by the subcontractor upon prior written approval of the customer.

2.6 Raw Material

2.6.1 General. Raw material shall be reviewed to determine that each coil or bundle has a mill identification and that each heat (batch, melt, cast, etc.) is accompanied by a mill certification of analysis or the equivalent. Raw material (rod, wire, or bar) shall be inspected prior to release for fabrication to verify that it conforms to the material requirements specified.

2.6.2 General Quality. One fastener, taken at random from representative coils of rod or wire or from bundles of bars, shall be visually inspected to verify the general quality of the raw material and its condition following the forming process. The part shall be examined for evidence of pipe, cracks, seams, and other surface discontinuities according to applicable specifications.

2.7 Final Inspection

Each lot of fasteners shall be subject to a final inspection. The final inspection is intended to verify lot identification, to check for mechanical property conformance and mixed stock, and to inspect designated characteristics for conformance to related specifications and engineering drawings. Records of final inspection shall be maintained in accordance with para. 2.4. The nondestructive final inspection requirements are given in Table 1, and destructive test requirements are given in Table 2. Sample sizes are then determined in accordance with Table 3.

2.8 Acceptance and Rejection

2.8.1 Basis of Rejection. Any coil of rod or wire or bundle of bars failing to meet the requirements of para. 2.6 shall be held for disposition.

2.8.2 Acceptance Criteria

2.8.2.1 Nondestructive. If a single nonconforming characteristic is found in final inspection, the lot may be resampled for this characteristic with a sample four times the size of the original final acceptance sample. The acceptance criterion will then be zero discrepancies in this larger sample.

2.8.2.2 Destructive. If a single nonconforming characteristic is found in final inspection, the lot may

be resampled for this characteristic with a sample four times the size of the original final acceptance sample. The acceptance criterion will then be zero discrepancies in this larger sample.

2.8.3 Customer Inspection. If on receipt of the material the user discovers a single nonconforming part that functions defectively, he may sample the lot for such nonconforming characteristic(s) in accordance with para. 2.7, using an acceptance number of zero.

2.9 Disposition of Nonconforming Materials or Parts

Records of disposition shall be maintained in accordance with para. 2.4.

2.9.1 Manufacturer's Options. The manufacturer has the choice of the following options in the disposition of those materials or parts that have been found to contain discrepancies within his plant.

(a) They may be scrapped.

(b) They may be 100% sorted and all nonconforming parts removed.

(c) They may be reworked or reprocessed to correct the nonconforming characteristic(s).

(d) The customer may be informed of the rejectable items and his advice requested on their disposition. If the customer considers that the degree to which the characteristic(s) deviates from specified requirements will have no significant effect on the performance of the parts in their service application, the customer may authorize release of the parts or materials for completion of production or for shipment as applicable.

2.9.2 Customer's Options. The customer shall establish agreement with the manufacturer on one of the following options for the disposition of those materials or parts that have been rejected after receipt from the manufacturer.

(a) They may be scrapped.

(b) They may be 100% sorted and all nonconforming parts removed.

(c) They may be reworked or reprocessed to correct the nonconforming characteristic(s).

(d) If the customer considers that the degree to which the characteristic(s) deviates from specified requirements will have no significant effect on the performance of the parts in their service application, the customer may authorize release of the parts or materials for use and advise the manufacturer.

(e) They all may be returned.

ASME/ANSI B18.18.2M-1987

INSPECTION AND QUALITY ASSURANCE FOR
HIGH-VOLUME MACHINE ASSEMBLY FASTENERS

2.9.3 Reinspection. All pieces that have been sorted and/or reworked in accordance with para. 2.9.1 or para. 2.9.2 shall be resubmitted for lot sampling and inspection in accordance with para. 2.7 for the characteristic(s) found nonconforming and all other characteristics that would be affected by the repair or reprocessing operation(s). If no parts in the sample inspected are found nonconforming, the material may reenter the production flow or may be approved for delivery or use as applicable.

**TABLE 1 FINAL INSPECTION — MACHINE ASSEMBLED AND OTHER
SPECIAL PURPOSE FASTENERS — NONDESTRUCTIVE TESTS**

Characteristic		Inspection Level	Internally Threaded Parts	Externally Threaded Parts
1	Body diameter	C	NA	WA
2	Length	B	NA	WA
3	Width across flats	B	WA	WA
4	Width across corners	C	WA	WA
5	Head or nut thickness	C	WA	WA
6	Wrenching height	B	WA	WA
7	Angularity of bearing surface	C	WA	WA
8	Bearing surface diameter	C	WA	WA
9	Head diameter	C	NA	WA
10	Flange diameter	C	WA	WA
11	Flange thickness	C	WA	WA
12	Recess penetration	A	NA	WA
13	Point diameter	B	NA	WA
14	Countersink diameter and depth	C	WA	WA
15	Thread acceptability [Note (1)]	B/C	WA	WA
16	Total thread length	B	NA	WA
17	Grip length	B	NA	WA
18	Slot width	A	WA	WA
19	Slot depth	A	WA	WA
20	Slot alignments and location	B	WA	NA
21	Diameter of undercut	C	NA	WA
22	Depth of undercut	C	NA	WA
23	Washer O.D.	C	WA	WA
24	Washer thickness	C	WA	WA
25	Visual inspection [Note (2)]	A	WA	WA

GENERAL NOTES:

(a) Legend: WA — when applicable

NA — not applicable

(b) Refer to para. 2.8.2 for acceptance criteria. Refer to Table 3 for sample size.

NOTES:

(1) ANSI/ASME B1.3M or other applicable standards and at the appropriate inspection level (B or C).

(2) Visual inspection for grade and source identification, presence of finish, duds, surface discontinuities, head and/or flange eccentricity, flange flatness, radius under head, type of washer, presence of locking feature, closeness of thread to head, and general workmanship.

**TABLE 2 FINAL INSPECTION — MACHINE ASSEMBLED AND OTHER
SPECIAL PURPOSE FASTENERS — DESTRUCTIVE TESTS**

Characteristic	Inspection Level	Internally Threaded Parts	Externally Threaded Parts
1 Proof load — externally threaded	C	NA	WA
2 Proof load — internally threaded	B	WA	NA
3 Tensile strength (wedge or axial)	B	NA	WA
4 Hardness [Note (1)]	A	WA	WA
5 Case depth	B	NA	WA
6 Decarburization	C	WA	WA
7 Torsional strength	B	NA	WA
8 Drive test	B	NA	WA
9 Prevailing torque [Note (2)]	B	WA	WA
10 Washer hardness	B	WA	WA
11 Ductility	A	WA	WA
12 Plating thickness	B	WA	WA
13 Salt spray [Note (3)]	B	WA	WA
14 Hydrogen embrittlement	A	WA	WA

GENERAL NOTE:

Legend: WA — when applicable

NA — not applicable

NOTES:

- (1) Surface, core, or both as appropriate.
 (2) Prevailing torque test includes thread start, all specified torque requirements, and retention of locking feature, when applicable.
 (3) Continuous monitoring of salt spray performance in accordance with the recommendation of Table B in Appendix I constitutes compliance with the requirements for salt spray testing outlined in this table. Refer to Table 3 for sample size.

**TABLE 3 SAMPLE SIZE — MACHINE ASSEMBLED AND OTHER SPECIAL
PURPOSE FASTENERS**

Lot Size	Level of Inspection	Nondestructive Testing	Destructive Testing
5,001–250,000	A	100	8
	B	32	4
	C	8	1
1,000–5,000	A	50	6
	B	16	3
	C	4	1
Up to 1,000 (where sample size exceeds lot size, 100% inspection to be applied)	A	25	4
	B	8	2
	C	2	1

GENERAL NOTE: Refer to para. 2.8.2 for acceptance criteria.

APPENDIX I

TABLE A INSPECTION LEVEL DECISION TABLE

(This Appendix is not part of ASME/ANSI B18.18.2M-1987, and is included here for information purposes only.)




TABLE B SUGGESTED EQUIPMENT AND PROCESSING CONTROL CHECKS

Control Check																		
Finishing Operation	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
	Analysis of Alkali Clean Tank – Log	Analysis of Acid Clean Tank – Log	Analysis of Cyanide Rinse – Log	Ratio of Soluble Oil to Water – Log	Analysis of Chromic Acid Rinse – Log	Analysis of Reverse Current Alkali Solution – Log	Plating Bath Analysis – Log	Analysis of Chromate Finish Solution – Log	Chemical Additives to All Solution Baths – Log	Filtering of Baths – Log	Check for Proper Elec. Contact – Log	Plating Bath Temperatures – Log	Clean Rinse Tanks – Log	Clean and Recharge All Process Tanks – Log	Time Interval Before Baking, Time and Temp. of Bake – Log	Analysis of Lubrication Bath – Log	Coating Weight and/or Thickness – Log	Salt Spray Test – Log
	Daily	Daily	FSTDC	NA	NA	Daily	Daily	Daily	As added to each tank	FSTDC	Daily	Daily	FSTDC	As req'd based on analysis	WA each lot	NA	[Note (1)]	2 pieces per line per shift
	Daily	Daily	FSTDC	NA	NA	NA	Daily	Daily	As added to each tank	FSTDC	Daily	Daily	FSTDC	As req'd based on analysis	WA each lot	NA	[Note (1)]	2 pieces per line per shift
	Daily	Daily	NA	NA	NA	Every 2 days	Daily	NA	As added to each tank	FSTDC	Daily	Daily	FSTDC	As req'd based on analysis	WA each lot	NA	[Note (1)]	NA
	NA	Daily	NA	NA	NA	NA	Daily	NA	As added to each tank	FSTDC	Daily	Daily	FSTDC	As req'd based on analysis	WA each lot	NA	[Note (1)]	WA 2 pieces per line per shift
	NA	Daily	NA	NA	NA	NA	Daily	NA	As added to each tank	FSTDC	Daily	Daily	FSTDC	As req'd based on analysis	WA each lot	NA	[Note (1)]	WA 2 pieces per line per shift
	Daily	Daily	NA	Daily	Daily	NA	Each shift	NA	As added to each tank	NA	NA	Daily	FSTDC	As req'd based on analysis	WA each lot	NA	[Note (2)]	2 pieces per line per shift
7 Post plating lubrication	NA	NA	NA	NA	NA	NA	NA	As added to each tank	NA	NA	Daily	Daily	NA	As req'd based on analysis	NA	Daily	NA	

GENERAL NOTE:

Legend: WA — when applicable

NA — not applicable

FSTDC — frequency sufficient to demonstrate control

NOTES:

(1) For hand line operations, one piece per barrel; for automatic line operations, five pieces at start of each lot.

(2) Check daily coating weight only.

APPENDIX II

ORDERING INFORMATION

(This Appendix is not part of ASME/ANSI B18.18.2M-1987, and is included here for information purposes only.)

Specifications

- (a) Number and title of document
- (b) Exceptions

Example

(a) ASME/ANSI B18.18.2M, Inspection and Quality Assurance for High-Volume Machine Assembly Fasteners

(b) Thread acceptability shall be based on the thread acceptability paragraph in ANSI/ASME B1.3M with an A inspection level.

AMERICAN NATIONAL STANDARDS FOR BOLTS, NUTS, RIVETS, SCREWS, WASHERS, AND SIMILAR FASTENERS

Small Solid Rivets	B18.1.1-1972 (R1983)
Large Rivets	B18.1.2-1972 (R1983)
Metric Small Solid Rivets	B18.1.3M-1983
Square and Hex Bolts and Screws — Inch Series	B18.2.1-1981
Square and Hex Nuts	B18.2.2-1972 (R1983)
Metric Hex Cap Screws	B18.2.3.1M-1979
Metric Formed Hex Screws	B18.2.3.2M-1979
Metric Heavy Hex Screws	B18.2.3.3M-1979
Metric Hex Flange Screws	B18.2.3.4M-1984
Metric Hex Bolts	B18.2.3.5M-1979
Metric Heavy Hex Bolts	B18.2.3.6M-1979
Metric Heavy Hex Structural Bolts	B18.2.3.7M-1979
Metric Hex Lag Screws	B18.2.3.8M-1981
Metric Heavy Hex Flange Screws	B18.2.3.9M-1984
Metric Hex Nuts, Style 1	B18.2.4.1M-1979
Metric Hex Nuts, Style 2	B18.2.4.2M-1979
Metric Slotted Hex Nuts	B18.2.4.3M-1979
Metric Hex Flange Nuts	B18.2.4.4M-1982
Metric Hex Jam Nuts	B18.2.4.5M-1979
Metric Heavy Hex Nuts	B18.2.4.6M-1979
Socket Cap, Shoulder and Set Screws (Inch Series)	B18.3-1986
Socket Head Cap Screws (Metric Series)	B18.3.1M-1986
Metric Series Hexagon Keys and Bits	B18.3.2M-1979 (R1986)
Hexagon Socket Head Shoulder Screws (Metric Series)	B18.3.3M-1986
Hexagon Socket Button Head Cap Screws (Metric Series)	B18.3.4M-1986
Hexagon Socket Flat Countersunk Head Cap Screws (Metric Series)	B18.3.5M-1986
Metric Series Socket Set Screws	B18.3.6M-1986
Round Head Bolts (Inch Series)	B18.5-1978
Metric Round Head Short Square Neck Bolts	B18.5.2.1M-1981
Metric Round Head Square Neck Bolts	B18.5.2.2M-1982
Wood Screws	B18.6.1-1981
Slotted Head Cap Screws, Square Head Set Screws, and Slotted Headless Set Screws	B18.6.2-1972 (R1983)
Machine Screws and Machine Screw Nuts	B18.6.3-1972 (R1983)
Metric Thread Forming and Thread Cutting Tapping Screws	B18.6.5M-1986
Metric Machine Screws	B18.6.7M-1985
Thread Forming and Thread Cutting Tapping Screws and Metallic Drive Screws (Inch Series)	B18.6.4-1981
General Purpose Semi-Tubular Rivets, Full Tubular Rivets, Split Rivets and Rivet Caps	B18.7-1972 (R1980)
Metric General Purpose Semi-Tubular Rivets	B18.7.1M-1984
Clevis Pins and Cotter Pins	B18.8.1-1972 (R1983)
Taper Pins, Dowel Pins, Straight Pins, Grooved Pins, and Spring Pins (Inch Series)	B18.8.2-1978
Plow Bolts	B18.9-1958 (R1977)
Track Bolts and Nuts	B18.10-1982
Miniature Screws	B18.11-1961 (R1983)
Glossary of Terms for Mechanical Fasteners	B18.12-1962 (R1981)
Screw and Washer Assemblies — Sems	B18.13-1965 (R1983)
Forged Eyebolts	B18.15-1985
Mechanical and Performance Requirements for Prevailing-Torque Type Steel Metric Hex Nuts and Hex Flange Nuts	B18.16.1M-1979 (R1986)
Torque-Tension Test Requirements for Prevailing-Torque Type Steel Metric Hex Nuts and Hex Flange Nuts	B18.16.2M-1979 (R1986)
Dimensional Requirements for Prevailing-Torque Type Steel Metric Hex Nuts and Hex Flange Nuts	B18.16.3M-1982
Wing Nuts, Thumb Screws, and Wing Screws	B18.17-1968 (R1983)
Inspection and Quality Assurance for General Purpose Fasteners	B18.18.1M-1987
Inspection and Quality Assurance for High-Volume Machine Assembly Fasteners	B18.18.2M-1987
Inspection and Quality Assurance for Special Purpose Fasteners	B18.18.3M-1987
Inspection and Quality Assurance for Fasteners for Highly Specialized Engineered Applications	B18.18.4M-1987
Lock Washers	B18.21.1-1972 (R1983)
Metric Plain Washers	B18.22M-1981
Plain Washers	B18.22.1-1965 (R1981)
Beveled Washers	B18.23.1-1967 (R1975)



M00126