

ASME B18.2.4.2M-2005
[Revision of ASME B18.2.4.2M-1979 (R1995)]

Metric Hex Nuts, Style 2

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B18.2.4.2M-2005
[Revision of ASME B18.2.4.2M-1979 (R1995)]

Metric Hex Nuts, Style 2

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Three Park Avenue • New York, NY 10016

Date of Issuance: October 7, 2005

This Standard will be revised when the Society approves the issuance of a new edition. There will be no addenda issued to this edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the ASME Web site under the Committee Pages at <http://www.asme.org/codes/> as they are issued.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Three Park Avenue, New York, NY 10016-5990

Copyright © 2005 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	v
Correspondence With the B18 Committee	vi
1 Scope	1
2 Comparison with ISO Standards	1
3 Referenced Standards	1
4 Terminology	1
5 Dimensions	1
6 Width Across Flats	3
7 Thickness	3
8 Tops and Bearing Surface	3
9 Corner Fill	3
10 True Position of Hexagon to the Tapped Hole	3
11 Countersink	3
12 Threads	3
13 Material and Mechanical Properties	3
14 Finish	3
15 Identification Symbols	3
16 Inspection and Quality Assurance	4
17 Dimensional Conformance	4
18 Designation	4
19 Options	4
20 Workmanship	4
Table	
1 Dimensions of Hex Nuts, Style 2	2

FOREWORD

American National Standards Committee B18 for the standardization of bolts, screws, nuts, rivets, and similar fasteners was organized in March 1922 as Sectional Committee B18 under the aegis of the American Engineering Standard Committee (later the American Standards Association, then the United States of America Standards Institute, and, as of October 6, 1969, the American National Standards Institute, Inc.), with the Society of Automotive Engineers and the American Society of Mechanical Engineers as joint sponsors. Subcommittee 2 was subsequently established and charged with the responsibility for technical content of standards covering wrench head bolts and nuts.

At its meeting on December 4, 1974, Committee B18 authorized preparation of a series of standards for metric fasteners. Subcommittee 2 was assigned responsibility for developing standards for metric hex bolts, screws, and nuts.

At a meeting on September 22, 1976, Subcommittee 2 organized the contents of a standard covering six different styles of hex nuts. Actual drafting was postponed until ISO/TC2 could reach final decisions relating to basic dimensions and characteristics of hex bolts, screws, and nuts. At ISO/TC2 meetings held in April 1977, final actions were taken; Committee B18 affirmed the TC2 decisions at a meeting on June 29, 1977; and drafting of this Standard was started.

In February 1978, Committee B18 established a cooperative program with the Department of Defense to draft American National Standards for metric fasteners in such a way that they could be used directly by the government for procurement purposes. The Department of Defense requested that each of the six nut products be covered in separate standards, and Subcommittee 2 accepted this approach at its meeting on June 27, 1978.

The previous edition of the standard was approved by letter ballot of Committee B18 on July 2, 1979 and was subsequently approved by the secretariats and submitted to the American National Standards Institute for designation as an American National Standard. This was granted on December 6, 1979. B18.2.4.2M was last reaffirmed without change in 1995.

This Standard was developed by the American Society of Mechanical Engineers B18 Standards Committee on Fasteners. This Standard was approved by the American National Standards Institute on April 1, 2005.

ASME B18 COMMITTEE

Standardization of Bolts, Nuts, Rivets, Screws, Washers, and Similar Fasteners

(The following is the roster of the Committee at the time of approval of this Standard.)

OFFICERS

D. A. Clever, *Chair*
R. D. Strong, *Vice Chair*
S. W. Vass, *Vice Chair*
R. L. Crane, *Secretary*

COMMITTEE PERSONNEL

J. Altman , Rotor Clip Co.	J. G. Langenstein , <i>Emeritus Member</i> , Consultant
J. H. Slass , <i>Alternate</i> , Rotor Clip Co.	M. Levinson , <i>Alternate</i> , ITW Shakeproof Assembly Components
J. B. Belford , Lawson Products, Inc.	L. L. Lord , <i>Corresponding Member</i> , Consultant
V. Cartina , Aztech Locknut	W. J. Lutkus , Emhart Industrial Heli-Coil
D. A. Clever , Deere and Co.	A. D. McCrindle , Canadian Fasteners Institute
A. P. Cockman , Ford Motor Co.	K. E. McCullough , Consultant
T. Collier , Cam-Tech Industries, Inc.	M. D. Prasad , General Motors Corp.
R. L. Crane , The American Society of Mechanical Engineers	J. A. Roley , <i>Corresponding Member</i> , Caterpillar, Inc.
A. C. DiCola , Wrought Washer Co.	W. L. Sakowski , Account Managers LLC
B. A. Dusina , Federal Screw Works	S. Savoji , ITW Medalist
J. S. Foote , <i>Corresponding Member</i> , Trade Association Management, Inc.	W. Schevey , BGM Fastener Co., Inc.
D. S. George , Ford Motor Co.	W. R. Stevens , Ramco
J. Greenslade , Greenslade and Co.	R. D. Strong , General Motors Corp.
J. J. Grey , Fastener Consulting Services, Inc.	S. W. Vass , Nova Machine Products
B. Hasiuk , Defense Industrial Supply Center Philadelphia	C. B. Wackrow , MNP Corp.
A. Herskovitz , Consultant	R. G. Weber , Fairfield University
J. Hubbard , Rockford Fastener, Inc.	W. K. Wilcox , Consultant
M. Keller , <i>Corresponding Member</i> , Paracad Technology Co.	C. J. Wilson , Industrial Fasteners Institute
J. F. Koehl , Spirol International Corp.	R. B. Wright , Wright Tool Co.
W. H. Kopke , ITW Shakeproof Assembly Components	J. G. Zeratsky , National Rivet and Manufacturing Co.

SUBCOMMITTEE 2—EXTERNALLY DRIVEN FASTENERS

S. W. Vass , <i>Chair</i> , Nova Machine Products	M. Keller , Paracad Technology Co.
R. L. Crane , <i>Secretary</i> , The American Society of Mechanical Engineers	L. L. Lord , <i>Corresponding Member</i> , Caterpillar, Inc.
H. S. Brenner , Almay Research and Testing	A. D. McCrindle , Canadian Fasteners Institute
D. A. Clever , Deere and Co.	K. E. McCullough , Consultant
A. P. Cockman , Ford Motor Co.	J. A. Roley , Caterpillar, Inc.
B. A. Dusina , Federal Screw Works	S. Savoji , ITW Medalist
J. S. Foote , Trade Association Management, Inc.	G. M. Simpson , Semblex Corp.
D. S. George , Ford Motor Co.	W. R. Stevens , RAMCO
J. Greenslade , Greenslade and Co.	R. D. Strong , General Motors Corp.
A. Herskovitz , Consultant	C. B. Wackrow , MNP Corp.
M. W. Holubecki , Electric Boat Corp.	W. K. Wilcox , Naval Sea Systems
J. Hubbard , Rockford Fastener, Inc.	C. J. Wilson , Industrial Fasteners Institute

CORRESPONDENCE WITH THE B18 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions, and attending Committee meetings. Correspondence should be addressed to:

Secretary, B18 Standards Committee
The American Society of Mechanical Engineers
Three Park Avenue
New York, NY 10016-5990

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Interpretations. Upon request, the B18 Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B18 Standards Committee.

The request for interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his/her request in the following format:

Subject:	Cite the applicable paragraph number(s) and the topic of the inquiry.
Edition:	Cite the applicable edition of the Standard for which the interpretation is being requested.
Question:	Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in this format will be rewritten by the Committee prior to being answered, which may inadvertently change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

Attending Committee Meetings. The B18 Standards Committee regularly holds meetings, which are open to the public. Persons wishing to attend any meeting should contact the Secretary of the B18 Standards Committee.

METRIC HEX NUTS, STYLE 2

1 SCOPE

(a) This Standard covers the complete general and dimensional data for metric hex nuts, Style 2, recognized as American National Standard.

(b) The inclusion of dimensional data in this Standard is not intended to imply that all of the nut sizes in conjunction with the various options described herein are stock items. Purchasers should consult with suppliers concerning lists of stock production hex nuts, Style 2.

2 COMPARISON WITH ISO STANDARDS

(a) Hex nuts, Style 2, as covered in this Standard have been coordinated to the extent possible with ISO 4033. The dimensional differences between this Standard and ISO 4033 are very few and relatively minor, except those of the M10 size. None affect the functional interchangeability of nuts manufactured to the requirements of either.

(b) At its meeting in Varna, May 1977, ISO/TC2 studied several technical reports analyzing design considerations influencing determination of the best series of width across flats for hex bolts, screws, and nuts. A primary technical objective was to achieve a logical ratio between underhead (nut) bearing surface area (which determines the magnitude of the compressive stress on the bolted members) and the tensile stress area of the screw thread (which governs the clamping force that can be developed by tightening the fastener). Table 1 lists the sizes selected by ISO/TC2 to be ISO standard.

M10 nuts with 15 mm width across flats are currently being produced and used in the U.S. and many other countries of the world. This size, however, is not an ISO standard.

NOTE: When M10 nuts are ordered, nuts with 16 mm width across flats shall be furnished, unless 15 mm width across flats is specified.

(c) Letter symbols designating dimensional characteristics are in accordance with those used in ISO standards, except where capitals have been used instead of lowercase letters used in ISO standards.

3 REFERENCED STANDARDS

The following is a list of publications referenced in this Standard.

ASME B1.3M, Screw Thread Gaging Systems for Dimensional Acceptability

ASME B1.13M, Metric Screw Threads—M Profile

ASME B18.12, Glossary of Terms for Mechanical Fasteners

ASME B18.18.1, Inspection and Quality Assurance for General Purpose Fasteners

ASME B18.18.2, Inspection and Quality Assurance for High-Volume Machine Assembly Fasteners

ASME B18.24, Part Identifying Number (PIN) Code System Standard for B18 Fastener Products

ASME Y14.5M, Dimensioning and Tolerancing

Publisher: The American Society of Mechanical Engineers (ASME), Three Park Avenue, New York, NY 10016-5990; Order Department: 22 Law Drive, Box 2900, Fairfield, NJ 07007-2900

ASTM A 563M, Carbon and Alloy Steel Nuts [Metric]

ASTM F 467M, Nonferrous Nuts for General Use [Metric]

ASTM F 812/F 812M, Surface Discontinuities of Nuts Inch and Metric Series

ASTM F 836M, Stainless Steel Metric Nuts

Publisher: American Society for Testing and Materials (ASTM), 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959

ISO 4033, Hexagon Nuts, Style 2 – Product Grades A and B

Publisher: International Organization for Standardization (ISO), 1 rue de Varembe, Case Postale 56, CH-1211, Genève 20, Switzerland/Suisse


4 TERMINOLOGY

For definitions of terms relating to fasteners or component features thereof used in this Standard, refer to ASME B18.12.

5 DIMENSIONS

(a) Unless otherwise stated, all dimensions in this Standard are in millimeters and apply before any coating. When plating or coating is specified, the finished product dimensions shall be as agreed upon between supplier and purchaser.

(b) Symbols specifying geometric characteristics are in accord with ASME Y14.5M.

**Table 1 Dimensions of Hex Nuts, Style 2**

Nominal Nut Diameter and Thread Pitch	Width Across Flats, S		Width Across Corners, E		Thickness, M		Bearing Face Diameter, D_W , Min.	Washer Face Thickness, C		Total Runout of Bearing Surface FIM, Max.
	Max.	Min.	Max.	Min.	Max.	Min.		Max.	Min.	
M3 \times 0.5	5.50	5.32	6.35	6.01	2.90	2.65	4.6
M3.5 \times 0.6	6.00	5.82	6.93	6.58	3.30	3.00	5.1
M4 \times 0.7	7.00	6.78	8.08	7.66	3.80	3.50	6.0
M5 \times 0.8	8.00	7.78	9.24	8.79	5.10	4.80	7.0	0.30
M6 \times 1	10.00	9.78	11.55	11.05	5.70	5.40	8.9	0.33
M8 \times 1.25	13.00	12.73	15.01	14.38	7.50	7.14	11.6	0.36
M10 \times 1.5	15.00	14.73	17.32	16.64	10.0	9.6	13.6	0.39
[Note (1)]										
M10 \times 1.5	16.00	15.73	18.48	17.77	9.30	8.94	14.6	0.39
[Note (1)]										
M12 \times 1.75	18.00	17.73	20.78	20.03	12.00	11.57	16.6	0.42
M14 \times 2	21.00	20.67	24.25	23.36	14.10	13.40	19.4	0.45
M16 \times 2	24.00	23.67	27.71	26.75	16.40	15.70	22.4	0.48
M20 \times 2.5	30.00	29.16	34.64	32.95	20.30	19.00	27.9	0.8	0.4	0.56
M24 \times 3	36.00	35.00	41.57	39.55	23.90	22.60	32.5	0.8	0.4	0.64
M30 \times 3.5	46.00	45.00	53.12	50.85	28.60	27.30	42.5	0.8	0.4	0.76
M36 \times 4	55.00	53.80	63.51	60.79	34.70	33.10	50.8	0.8	0.4	0.89
See para.	6		9		7		8	8		8

NOTE:

(1) See para. 2(b). When M10 nuts are ordered, nuts with 16 mm width across flats shall be furnished, unless 15 mm width across flats is specified.

6 WIDTH ACROSS FLATS

(a) The width across flats shall be the distance, measured perpendicular to the axis of the nut, between two opposite wrenching flats.

(b) The minimum width across flats does not apply for 25% of the minimum nut thickness as measured from either face.

(c) On nonferrous products where milled-from-bar material is used, the dimensional specifications outlined may be modified. These dimensional allowances shall be agreed upon between the purchaser and supplier.

7 THICKNESS

The nut thickness shall be the overall distance, measured parallel to the axis of the nut, from the top of the nut to the bearing surface and include the thickness of the washer face where provided but exclude raised identification markings where they are permitted.

8 TOPS AND BEARING SURFACE

(a) M16 and smaller nuts shall be double chamfered. M20 and larger nuts, at the manufacturer's option, shall be either double chamfered or have a washer-faced bearing surface and chamfered top.

(b) The diameter of the bearing surface shall not exceed the width across flats, nor be less than the bearing face diameter specified in Table 1. The measurement of bearing face diameter on washer faced nuts shall be taken at 0.1 mm above the bearing surface (see figure above Table 1).

(c) The bearing surface within a diameter equal to 0.8 times the maximum width across flats shall be flat and perpendicular to the axis of the thread pitch diameter within the total runout limit specified in Table 1.

(d) The tops of washer-faced nuts shall be flat, and the diameter of the chamfer circle shall be equal to the maximum width across flats within a tolerance of -15% .

(e) The length of chamfer at hex corners shall be from 5% to 15% of the nominal thread diameter. The surface of the chamfer may be slightly convex or rounded.

9 CORNER FILL

A rounding or lack of fill at the junction of hex corners with the chamfer shall be permissible, provided the width across corners is within specified limits at and beyond a distance equal to 17.5% of the nominal thread diameter from the chamfered face.

10 TRUE POSITION OF HEXAGON TO THE TAPPED HOLE

At maximum material condition (MMC), the axis of the hexagon shall be located at true position with respect to the axis of the thread pitch diameter within a

tolerance zone having a diameter equivalent to 4% of the maximum width across flats.

11 COUNTERSINK

The tapped hole shall be countersunk on the bearing face(s). The countersink-included reference angle shall be 90 deg to 120 deg. The maximum countersink diameter shall be 1.15 times the nominal thread diameter (major diameter) for nuts M4 and smaller, the nominal thread diameter plus 0.75 mm for nuts M5 through M8, and 1.08 times the nominal thread diameter for M10 and larger nuts. The minimum countersink diameter shall be the nominal thread diameter.

12 THREADS

(a) Threads shall be metric coarse threads with Class 6H tolerances in accordance with ASME B1.13M.

(b) Thread acceptability shall be in accordance with ASME B1.3M System 21.

(c) Nuts intended for use with externally threaded fasteners which are plated or coated with a plating or coating thickness (e.g., hot-dip galvanized) requiring overtapping of the nut thread to permit assembly shall have overtapped threads in conformance with requirements specified in ASTM A 563M.

13 MATERIAL AND MECHANICAL PROPERTIES

(a) Carbon steel nuts without specified heat treatment shall conform to the material and mechanical property requirements specified for Property Class 9 nuts in ASTM A 563M. Carbon steel nuts with specified heat treatment shall conform to the material and mechanical property requirements specified for Property Class 12 nuts in ASTM A 563M.

(b) Stainless steel nuts shall conform to the requirements of ASTM F 836M.

(c) Nonferrous metal nuts shall conform to the requirements of ASTM F 467M.

14 FINISH

Unless otherwise specified, nuts shall be furnished with a natural (as processed) finish, unplated or uncoated.

15 IDENTIFICATION SYMBOLS

(a) Carbon steel nuts shall be marked to identify the property class and manufacturer in accordance with requirements specified in ASTM A 563M.

(b) Stainless steel nuts shall be marked to identify the property class and manufacturer in accordance with the requirements specified in ASTM F 836M.

- (c) Nonferrous nuts shall be marked to identify the property class and manufacturer in accordance with the requirements specified in ASTM F 467M.
- (d) Nuts for which no standard exists shall be marked as agreed between purchaser and manufacturer.

16 INSPECTION AND QUALITY ASSURANCE

Unless otherwise specified by the purchaser in the original inquiry and purchase order, acceptability of nuts shall be determined in accordance with ASME B18.18.1.

17 DIMENSIONAL CONFORMANCE

- (a) Unless otherwise specified, the following designated characteristics shall be inspected in accordance with ASME B18.18.2 and within their specified limits.

Characteristic	Inspection Level
Width across corners	C
Thickness	C
Thread acceptability	C

- If verifiable in-process inspection is used, inspection sample sizes and reporting shall be in accordance with the applicable ASME, ASTM, or SAE quality system consensus standard.
- (b) For nondesignated characteristics, the provisions of ASME B18.18.1 shall apply. Should a nondesignated dimension be determined to be outside its specified limits, it shall be deemed conforming to this Standard if the user, who is the installer, accepts the dimension based on fit, form, and function considerations.

18 DESIGNATION

- (a) Hex nuts, Style 2, shall be designated by the following data, preferably in the sequence shown: product name, designation of standard (ASME B18.2.4.2M), nominal diameter and thread pitch, 15 mm width across flats for size M10, if applicable [see para. 2(b)], steel property class or material identification, and protective coating if required.

NOTE: It is common practice in ISO standards to omit thread pitch from the product designation when screw threads are the metric coarse thread series, e.g., M10 is M10 × 1.5.

EXAMPLES:

- (1) Hex nut, Style 2, ASME B18.2.4.2M, M10 × 1.5, ASTM A 563M Class 9, zinc plated per ASTM F 1941M Fe/Zn5C.
- (2) Hex nut, Style 2, ASME B18.2.4.2M, M20 × 2.5, silicon bronze, ASTM F 467M Grade 651.
- (b) The recommended B18 part identifying numbering system (PIN) for metric hex nuts, Style 2, is included in ASME B18.24. This system may be used by any user needing a definitive part numbering system.

19 OPTIONS

Options, where specified, shall be at the discretion of the manufacturer, unless otherwise agreed between manufacturer and purchaser.

20 WORKMANSHIP

Nuts shall be free of surface irregularities which might affect their serviceability, such as burrs, seams, laps, loose scale, and other irregularities. When control of surface discontinuities is important for the application intended, ASTM F 812/F 812M should be specified.

B18 AMERICAN NATIONAL STANDARDS FOR BOLTS, NUTS, RIVETS, SCREWS, WASHERS, AND SIMILAR FASTENERS

Small Solid Rivets	B18.1.1-1972 (R2001)
Large Rivets	B18.1.2-1972 (R2001)
Metric Small Solid Rivets	B18.1.3M-1983 (R2001)
Square and Hex Bolts and Screws (Inch Series)	B18.2.1-1996
Square and Hex Nuts (Inch Series)	B18.2.2-1987 (R1999)
Metric Hex Cap Screws	B18.2.3.1M-1999
Metric Formed Hex Screws	B18.2.3.2M-2005
Metric Heavy Hex Screws	B18.2.3.3M-1979 (R2001)
Metric Hex Flange Screws	B18.2.3.4M-2001
Metric Hex Bolts	B18.2.3.5M-1979 (R2001)
Metric Heavy Hex Bolts	B18.2.3.6M-1979 (R2001)
Metric Heavy Hex Structural Bolts	B18.2.3.7M-1979 (R2001)
Metric Hex Lag Screws	B18.2.3.8M-1981 (R1999)
Metric Heavy Hex Flange Screws	B18.2.3.9M-2001
Square Head Bolts (Metric Series)	B18.2.3.10M-1996 (R2003)
Metric Hex Nuts, Style 1	B18.2.4.1M-2002
Metric Hex Nuts, Style 2	B18.2.4.2M-2005
Metric Slotted Hex Nuts	B18.2.4.3M-1979 (R2001)
Metric Hex Flange Nuts	B18.2.4.4M-1982 (R1999)
Metric Hex Jam Nuts	B18.2.4.5M-1979 (R2003)
Metric Heavy Hex Nuts	B18.2.4.6M-1979 (R2003)
Fasteners for Use in Structural Applications	B18.2.6-1996 (R2004)
Metric 12-Spline Flange Screws	B18.2.7.1M-2002
Clearance Holes for Bolt, Screws, and Studs	B18.2.8-1999
Socket Cap, Shoulder, and Set Screws, Hex and Spline Keys (Inch Series)	B18.3-2003
Socket Head Cap Screws (Metric Series)	B18.3.1M-1986 (R2002)
Metric Series Hexagon Keys and Bits	B18.3.2M-1979 (R2003)
Hexagon Socket Head Shoulder Screws (Metric Series)	B18.3.3M-1986 (R2002)
Hexagon Socket Button Head Cap Screws (Metric Series)	B18.3.4M-1986 (R2002)
Hexagon Socket Flat Countersunk Head Cap Screws (Metric Series)	B18.3.5M-1986 (R2002)
Metric Series Socket Set Screws	B18.3.6M-1986 (R2002)
Round Head Bolts (Inch Series)	B18.5-1990 (R2003)
Metric Round Head Short Square Neck Bolts	B18.5.2.1M-1996 (R2003)
Metric Round Head Square Neck Bolts	B18.5.2.2M-1982 (R2000)
Round Head Square Neck Bolts With Large Head (Metric Series)	B18.5.2.3M-1990 (R2003)
Wood Screws (Inch Series)	B18.6.1-1981 (R2003)
Slotted Head Cap Screws, Square Head Set Screws, and Slotted Headless Set Screws (Inch Series)	B18.6.2-1998
Machine Screws and Machine Screw Nuts	B18.6.3-2003
Thread Forming and Thread Cutting Tapping Screws and Metallic Drive Screws (Inch Series)	B18.6.4-1998
Metric Thread-Forming and Thread-Cutting Tapping Screws	B18.6.5M-2000
Metric Machine Screws	B18.6.7M-1999
General Purpose Semi-Tubular Rivets, Full Tubular Rivets, Split Rivets and Rivet Caps	B18.7-1972 (R2001)
Metric General Purpose Semi-Tubular Rivets	B18.7.1M-1984 (R2000)
Clevis Pins and Cotter Pins (Inch Series)	B18.8.1-1994 (R2000)
Taper Pins, Dowel Pins, Straight Pins, Grooved Pins, and Spring Pins (Inch Series)	B18.8.2-2000
Spring Pins: Coiled Type, Spring Pins: Slotted, Machine Dowel Pins: Hardened Ground, and Grooved Pins (Metric Series)	B18.8.100M-2000
Cotter Pins, Headless Clevis Pins, and Headed Clevis Pins (Metric Series)	B18.8.200M-2000
Plow Bolts (Inch Series)	B18.9-1996 (R2003)
Track Bolts and Nuts	B18.10-1982 (R2000)
Miniature Screws	B18.11-1961 (R2000)
Glossary of Terms for Mechanical Fasteners	B18.12-2001
Screw and Washer Assemblies — Sems (Inch Series)	B18.13-1996 (R2003)
Screw and Washer Assemblies: Sems (Metric Series)	B18.13.1M-1998 (R2003)

Forged Eyebolts	B18.15-1985 (R2003)
Metric Lifting Eyes	B18.15M-1998 (R2004)
Prevailing-Torque Type Steel Metric Hex Nuts and Hex Flange Nuts	B18.16M-2004
Inspection and Quality Assurance for General Purpose Fasteners	B18.18.1M-1987 (R1999)
Inspection and Quality Assurance for High-Volume Machine Assembly Fasteners	B18.18.2M-1987 (R1999)
Inspection and Quality Assurance for Special Purpose Fasteners	B18.18.3M-1987 (R1999)
Inspection and Quality Assurance for Fasteners for Highly Specialized Engineered Applications	B18.18.4M-1987 (R1999)
Inspection and Quality Assurance Plan Requiring In-Process Inspection and Controls	B18.18.5M-1998 (R2003)
Quality Assurance Plan for Fasteners Produced in a Third Party Accreditation System	B18.18.6M-1998 (R2003)
Quality Assurance Plan for Fasteners Produced in a Customer Approved Control Plan	B18.18.7M-1998 (R2003)
Lock Washers (Inch Series)	B18.21.1-1999
Lock Washers (Metric Series)	B18.21.2M-1999
Metric Plain Washers	B18.22M-1981 (R2000)
Plain Washers	B18.22.1-1965 (R2003)
Part Identifying Number (PIN) Code System for B18 Fastener Products	B18.24-2004
Square and Rectangular Keys and Keyways	B18.25.1M-1996 (R2003)
Woodruff Keys and Keyways	B18.25.2M-1996 (R2003)
Square and Rectangular Keys and Keyways: Width Tolerances and Deviations Greater Than Basic Size	B18.25.3M-1998 (R2003)
Tapered and Reduced Cross Section Retaining Rings (Inch Series)	B18.27-1998
Helical Coil Screw Thread Inserts — Free Running and Screw Locking (Inch Series)	B18.29.1-1993 (R2002)
Helical Coil Screw Thread Inserts — Free Running and Screw Locking (Metric Series)	B18.29.2M-2005
Open-End Blind Rivets With Break Mandrels (Metric Series)	B18.30.1M-2000

The ASME Publications Catalog shows a complete list of all the Standards published by the Society. For a complimentary catalog, or the latest information about our publications, call 1-800-THE-ASME (1-800-843-2763).

ASME B18.2.4.2M-2005

ISBN 0-7918-2962-6



9 780791 829622



M11705