

ASME B29.27-2002

SINGLE-PITCH AND DOUBLE-PITCH HOLLOW PIN CONVEYOR CHAINS AND ATTACHMENTS

AN AMERICAN NATIONAL STANDARD



The American Society of
Mechanical Engineers



The American Society of
Mechanical Engineers

A N A M E R I C A N N A T I O N A L S T A N D A R D

SINGLE-PITCH AND DOUBLE-PITCH HOLLOW PIN CONVEYOR CHAINS AND ATTACHMENTS

ASME B29.27-2002

Date of Issuance: August 7, 2002

This Standard will be revised when the Society approves the issuance of a new edition. There will be no addenda issued to this Edition.

ASME will issue written replies to inquiries concerning interpretation of technical aspects of this Standard.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment which provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with established the ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Three Park Avenue, New York, NY 10016-5990

Copyright © 2002 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All Rights Reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	v
Correspondence With B29 Committee	vi
1 Scope	1
2 Hollow Pin Chains	1
3 Sprockets	3
Figures	
1 Single-Pitch Connecting Link	1
2 Double-Pitch Connecting Link	1
3 Double-Pitch Hollow Pin Chain With Small Rollers	2
4 Double-Pitch Hollow Pin Chain With Large Rollers	2
5 Single-Pitch Hollow Pin Chain	2
6 Single-Pitch Pin Link	3
7 Double-Pitch Pin Link	3
8 Double-Pitch Roller Link With Large Rollers	3
9 Double-Pitch Roller Link With Small Rollers	3
10 Single-Pitch Roller Link	3
11 General Chain Dimensions	5
Table	
1 General Chain Dimensions, Limiting Dimensions for Interchangeability, Measuring Loads, and Ultimate Tensile Strengths	4

FOREWORD

For many years roller chain manufacturers furnished substantial volumes of a limited series of hollow pin chains for specific conveying applications. Such chains usually are rollerless bushing chains having cylindrical pins. The pin bores are essentially the same as the bushing bores for equivalent pitch chains in ASME B29.1 or ASME B29.4. The bushing, or roller, diameters and width are such that the single-pitch chains operate on ASME B29.1 sprockets and the double-pitch chains operate on ASME B29.4 sprockets. These chains are often used in parallel strands with detachable cross-rods fitted through the pin bores of the two parallel strands of chain.

These chains sometimes are assembled with modified design attachment pin link plates or roller link plates to adapt the chains to more versatile use in conveying operations.

Over the years, hollow pin chains became widely used and many manufacturers offered them. About 1990, it was suggested by the ASME B29 Committee that a standard for these chains was needed. In 1995, the Roller Chain Technical Committee of the American Chain Association established a subcommittee to develop such a standard.

Customary inch-pound units were used in tabulating dimensional information in this standard. Additionally, metric conversions of those units, in accordance with ASME Guide SI-1, ASME Orientation and Guide for Use of SI (Metric) Units, are also provided.

This Standard was approved by the American National Standards Institute on March 20, 2002.

ASME B29 COMMITTEE

Chains, Attachments, and Sprockets for Power Transmission and Conveying

(The following is the roster of the Committee at the time of approval of this Standard.)

OFFICERS

J. L. Wright, *Chair*
C. G. Springman, *Vice Chair*
M. Lo, *Secretary*

COMMITTEE PERSONNEL

W. C. Hall, Ramsey Products Corp.
L. E. Hampel, Allied-Locke Industries, Inc.
A. M. McCarty, Emerson Power Transmission
D. Moore, Jeffrey Chain Co.
R. W. Neuhengen, Drives, Inc.
V. D. Petershake, Hitachi Maxco, Ltd.
V. E. Skipper, *Alternate*, Hitachi Maxco, Ltd.
R. A. Reinfried, Conveyor Equipment Manufacturers Association
S. Rhoad, Webster Industries, Inc.
R. J. Rothchild, U.S. Tsubaki, Inc.
K. J. Smith, Drives, Inc.

CORRESPONDENCE WITH B29 COMMITTEE

General. ASME standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions, and attending Committee meetings. Correspondence should be addressed to:

Secretary, B29 Main Committee
The American Society of Mechanical Engineers
Three Park Avenue
New York, NY 10016-5990

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Interpretations. Upon request, the B29 Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B29 Main Committee.

The request for interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his/her request in the following format:

Subject:	Cite the applicable paragraph number(s) and the topic of the inquiry.
Edition:	Cite the applicable edition of the Standard for which the interpretation is being requested.
Question:	Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The inquirer may also include any plans or drawings, which are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in this format will be rewritten in this format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

Attending Committee Meetings. The B29 Main Committee regularly holds meetings, which are open to the public. Persons wishing to attend any meeting should contact the Secretary of the B29 Main Committee.

SINGLE-PITCH AND DOUBLE-PITCH HOLLOW PIN CONVEYOR CHAINS AND ATTACHMENTS

1 SCOPE

This standard covers the dimensional limits required for chain interchangeability on sprockets. It does not provide for interconnectability of chains or individual links from different manufacturers.

2 HOLLOW PIN CHAINS

2.1 Definitions and Nomenclature

connecting link: an outside link consisting of a pin link plate, *E*, two hollow pins, *G-G*, a detachable pin link plate, *D*, and two retainers, *H-H* (see Figs. 1 and 2).

hollow pin chain, double-pitch: a series of alternately assembled roller links and pin links in which the hollow pins articulate inside the bushings. The pitch of the link plates is twice that of the link plates of the base series chain. Pin link plates and roller link plates have identical straight-edged contours. Chains may have large rollers that are intended for use when the conveyed load is carried by the rollers (see Figs. 3 and 4).

hollow pin chain, single-pitch: a series of alternately assembled roller links and pin links in which the hollow pins articulate inside the bushings (see Fig. 5).

pin link: an outside link consisting of two pin link plates, *E-E*, and two hollow pins, *F-F* (see Figs. 6 and 7).

roller link, double-pitch, large roller series: an inside link consisting of two roller link plates, *A-A*, two bushings, *B-B*, and two rollers of the large roller series, *C_L-C_L* (see Fig. 8).




FIG. 1 SINGLE-PITCH CONNECTING LINK

roller link, double-pitch, small roller series: an inside link consisting of two roller link plates, *A-A*, and two bushings, *B-B* (see Fig. 9).

roller link, single-pitch: an inside link consisting of two roller link plates, *A-A*, and two bushings, *B-B* (see Fig. 10).

2.2 General Proportions

2.2.1 Single-Pitch

(a) The roller diameter approximately equals $0.625 \times P$ (P = pitch).

(b) The chain width is defined as the distance between roller link plates and approximately equals $0.625 \times P$.

(c) The bore of the hollow pin approximately equals $0.312 \times P$.

(d) The thickness of link plates approximately equals $0.125 \times P$.

(e) The maximum height of pin and roller link plates equals $0.95 \times P$.

2.2.2 Double-Pitch

(a) The roller diameter for the small roller series approximately equals $0.312 \times P$ and for the large roller series approximately equals $0.625 \times P$.

(b) The chain width is defined as the distance between roller link plates and approximately equals $0.312 \times P$.

(c) The bore of the hollow pin approximately equals $0.156 \times P$.




FIG. 2 DOUBLE-PITCH CONNECTING LINK




FIG. 3 DOUBLE-PITCH HOLLOW PIN CHAIN WITH SMALL ROLLERS




FIG. 4 DOUBLE-PITCH HOLLOW PIN CHAIN WITH LARGE ROLLERS




FIG. 5 SINGLE-PITCH HOLLOW PIN CHAIN

(d) The thickness of link plates approximately equals $0.062 \times P$.

(e) The maximum height of pin and roller link plates equals $0.475 \times P$.

(c) *The tensile test is a destructive test.* Even though the chain may not visibly fail when subjected to the *minimum ultimate tensile force*, it will have been damaged and will be unfit for service.

2.3 Numbering System

Single-pitch hollow pin chains are identified by the same basic chain number as in ASME B29.1 followed by the suffix *HP*.

Double-pitch hollow pin chains are identified by the same basic chain number as in ASME B29.4 followed by the suffix *HP*.

2.4 Minimum Ultimate Tensile Strength

Single strand hollow pin chains, conforming to this standard, shall have a minimum ultimate tensile strength, or breaking strength, equal to or exceeding the values listed in Table 1.

The minimum ultimate tensile strength (M.U.T.S.) for chains covered by this standard is the minimum force at which an unused, undamaged chain could fail when subjected to a single tensile loading test.

(a) **WARNING:** *The minimum ultimate tensile strength is NOT a "working load."* The M.U.T.S. greatly exceeds the maximum force that may be applied to the chain.

(b) **Test Procedure.** A tensile force is slowly applied, in uniaxial direction, to the ends of the chain sample.

2.5 Chain Length Accuracy

2.5.1 Chain Length Tolerance. An unused, undamaged chain, with standard measuring load applied, shall not be underlength. An unused, undamaged chain, with standard measuring load applied, shall not exceed the overlength shown in the following tabulation.

Base Chain Numbers	Overlength Limit	
	in./ft	mm/m
40, C2040, C2042	+0.038	3.17
50, C2050, C2052	+0.036	3.00
60, C2060, C2062	+0.034	2.83
80, C2080, C2082	+0.032	2.67

2.5.2 Standard Measuring Load and Length. Measuring load is the load that shall be applied to the chain while it is measured for length. Measuring load is equal to 1% of the M.U.T.S., with a minimum of 31 lb (138 N).

Chain length measurements shall be taken over a length of at least 12 in. (300 mm).




FIG. 6 SINGLE-PITCH PIN LINK




FIG. 7 DOUBLE-PITCH PIN LINK




FIG. 8 DOUBLE-PITCH ROLLER LINK WITH
LARGE ROLLERS




FIG. 9 DOUBLE-PITCH ROLLER LINK WITH
SMALL ROLLERS




FIG. 10 SINGLE-PITCH ROLLER LINK

2.5.3 Chain Length Matching for Parallel Operation. Chains intended to operate in parallel may be matched to closer tolerances.

2.6 Chain Dimensions

See Fig. 11 and Table 1.

2.7 Attachment Link Plates for Hollow Pin Chains

Attachment link plates and limiting dimensions for attachment link plates for single-pitch hollow pin chains are listed in ASME B29.1.

Attachment link plates and limiting dimensions for attachment link plates for double-pitch hollow pin chains are listed in ASME B29.4.

Extended pins normally are not offered for hollow pin chains.

3 SPROCKETS

Sprocket types, tooth forms, and tooth section profiles are as shown in ASME B29.1.

For single-pitch hollow pin chains, sprocket diameters are as listed in ASME B29.1.

For double-pitch hollow pin chains, sprocket diameters are as listed in ASME B29.4.

**TABLE 1 GENERAL CHAIN DIMENSIONS, LIMITING DIMENSIONS FOR INTERCHANGEABILITY, MEASURING LOADS, AND
ULTIMATE TENSILE STRENGTHS**

Standard Chain Number	Dimensions, in. (mm)											
	40HP			50HP			60HP			80HP		
	in.	(mm)		in.	(mm)		in.	(mm)		in.	(mm)	
Chain Pitch, <i>P</i>	0.500	(12.70)		0.625	(15.875)		0.750	(19.05)		1.000	(25.40)	
Roller Diameter Small, <i>D_s</i> , Max.	0.312	(7.92)		0.400	(10.16)		0.469	(11.91)		0.625	(15.88)	
Large, <i>D_L</i> , Max.	
Width Between Roller Link Plates, <i>W</i> , Min.	0.309	(7.85)		0.370	(9.40)		0.495	(12.57)		0.620	(15.75)	
Roller Link Width, Max.	0.440	(11.18)		0.545	(13.84)		0.699	(17.75)		0.890	(22.61)	
Distance Between Pin Link Plates, Min.	0.442	(11.23)		0.547	(13.89)		0.701	(17.81)		0.892	(22.66)	
Hollow Pin Bore Diameter, <i>D_b</i> , Min.	0.1567	(4.00)		0.2004	(5.12)		0.2346	(5.98)		0.3126	(7.96)	
Measuring Load, <i>l_b</i> (N)	31	(138)		31	(138)		51	(227)		92	(409)	
Min. Ultimate Tensile Strength, <i>l_b</i> (N)	1,750	(7 784)		2,500	(11 120)		5,100	(22 686)		9,200	(40 924)	
Width Over Regular Pin, <i>B</i> , Max.	0.66	(16.76)		0.82	(20.83)		1.02	(25.91)		1.30	(33.02)	
Add to <i>B</i> for Conn. Pin, Max.	0.05	(1.27)		0.06	(1.52)		0.06	(1.52)		0.06	(1.52)	




FIG. 11 GENERAL CHAIN DIMENSIONS

AMERICAN NATIONAL STANDARDS –CHAINS, ATTACHMENTS, AND SPROCKETS FOR POWER TRANSMISSION AND CONVEYING

Precision Power Transmission Roller Chains, Attachments, and Sprockets	B29.1M-1993(R1999)
Inverted Tooth (Silent) Chains and Sprockets	B29.2M-1982(R1994)
Double-Pitch Power Transmission Roller Chains and Sprockets	B29.3M-1994(R1999)
Double-Pitch Conveyor Roller Chains, Attachments, and Sprockets	B29.4M-1994(R1999)
Leaf Chains, Clevises, and Sheaves	B29.8-2002
Heavy Duty Offset Sidebar Power Transmission Roller Chains and Sprocket Teeth	B29.10M-1997
Combination Chains, Attachments, and Sprocket Teeth	B29.11M-1994
Steel Bushed Rollerless Chains, Attachments, and Sprocket Teeth	B29.12M-1997
“H” Type Mill Chains, Attachments, and Sprocket Teeth	B29.14M-1996
Steel Roller Type Conveyor Chains, Attachments, and Sprocket Teeth	B29.15M-1997
Welded Steel Type Mill Chains, Attachments, and Sprocket Teeth	B29.16M-1995
Hinge Type Flat Top Conveyor Chains and Sprocket Teeth	B29.17M-1998
Welded Steel-Type Drag Chains, Attachments, and Sprocket Teeth	B29.18M-1994
700 Class Welded Steel and Cast Chains, Attachments, and Sprockets for Water and Sewage Treatment Plants	B29.21M-1996
Drop Forged Rivetless Chains, Sprocket Teeth Drive Chain/Drive Dogs	B29.22-2001
Flexible Chain Couplings	B29.23M-1985(R1995)
Roller Load Chains for Overhead Hoists	B29.24-2002
Fatigue Testing Power Transmission Roller Chain	B29.26-2001
Single-Pitch and Double-Pitch Hollow Pin Conveyor Chains and Attachments	B29.27-2002
Agricultural, Detachable, and Pintle Chains, Attachments, and Sprockets	B29.300-1998

The ASME Publications Catalog shows a complete list of all the Standards published by the Society. For a complimentary catalog, or the latest information about our publications, call 1-800-THE-ASME (1-800-843-2763).

ISBN 0-7918-2758-5



9 780791 827581



K15002