

ASME B32.100-2016

[Revision of ASME B32.100-2005 (R2011)]

Preferred Metric Sizes for Flat, Round, Square, Rectangular, and Hexagonal Metal Products

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B32.100-2016
(Revision of ASME B32.100-2005)

Preferred Metric Sizes for Flat, Round, Square, Rectangular, and Hexagonal Metal Products

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: October 14, 2016

This Standard will be revised when the Society approves the issuance of a new edition. This Standard will become effective 1 year after the Date of Issuance.

Periodically certain actions of the ASME B32 Committee may be published as Cases. Cases are published on the ASME Web site under the B32 Committee Page at go.asme.org/B32committee as they are issued.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The B32 Committee Page can be found at go.asme.org/B32committee. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting “Errata” in the “Publication Information” section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2016 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Acknowledgement	v
Committee Roster	vi
Correspondence With the B32 Committee	vii
1 Scope	1
2 General	1
3 Use of Tables	1
4 Basis of Tables	1
5 Tolerances	1
Nonmandatory Appendix	
A Related Standards	9
Tables	
1 Preferred Thickness for All Flat Metal Products, mm	3
2 Preferred Widths for Flat Metal Products, mm	3
3 Preferred Lengths for Flat Metal Products, mm	3
4 Preferred Diameters, <i>D</i> , of Round Metal Products, mm	4
5 Preferred Across Flat Sizes, <i>D</i> , of Square Metal Products, mm	5
6 Preferred Across Flat Sizes, <i>D</i> , of Hexagonal Metal Products, mm	5
7 Preferred Lengths of Round, Square, Rectangular, and Hexagonal Metal Products, mm	5
8 Preferred Across Flat Sizes of Rectangular Metal Products, mm	6
9 Thickness Tolerances for Hot-Rolled Steel Sheet of Structural Qualities (ISO-4995, ISO 5002), mm	6
10 Thickness Tolerances for Cold-Rolled Steel Sheet of Structural Qualities (ISO 4997), mm	7
11 Tolerance for Hot-Rolled, Round, Square, and Hex Steel Bars (ISO 1035-4), mm	7
12 Tolerances for Hot-Rolled Flat Bars (ISO 1035-4), mm	7
13 Tolerance for Cold-Finished, Round, Square, Rectangular, and Hex Steel Bars (ANSI B4.2), mm ..	8

FOREWORD

The U.S. Department of Commerce, in its July 1971 report to Congress, titled “A Metric America — A Decision Whose Time Has Come,” recommended that the United States should change to the metric system of measurement through a coordinated national program. This action, along with subsequent increased metric activity in industry, resulted in a number of requests from producers and users that the B32 Committee develop preferred series of metric sizes for the various forms of wrought metal mill products.

The B32.100 standard is based on the previously published standards B32.3M-1984 and B32.4M-1980. Development of these standards was started in 1973. The proposal received Standards Committee B32 approval on June 4, 1974. It was subsequently approved by the sponsor and submitted to the American National Standards Institute (ANSI) for designation as an American National Standard. This was granted on July 9, 1974. The last edition was approved by ANSI on September 24, 1984 and reaffirmed in 1994.

The sizes in this Standard are derived from a list of preferred metric sizes in which each number is approximately 60% greater than the number preceding it (ANSI B4.2 or ISO 497 Series R5'). Second Choice sizes are in increments of 25% (Series R10') and Third Choice sizes in increments of 12% (Series R20'). Some deviations from this principle occur as the result of minor rounding. The selected sizes also reflect standard material sizes in ISO and national standards in traditional metric countries.

In 2002, the B32 Committee established a task force to draft a new metric standard for the product group: ASME B32.100-200X Preferred Metric Sizes for Flat, Round, Square, Rectangular, and Hexagonal Metal Products.

Material tolerances must be included in order to fully define the size of a product. International or leading national metric standards data were used as the basis for the tolerance data included in this Standard. References to the sources of these tolerances have been made, and a list of related standards are shown in [Nonmandatory Appendix A](#).

The 2005 edition was approved by ANSI on February 11, 2005.

The present edition deleted obsolete references, the year date of the referenced standards have been deleted, and some corrections were made to [Nonmandatory Appendix A](#). The present edition also includes additional data and clarification related to [para. 5.8](#) and [Table 13](#).

The present edition was approved by ANSI on June 29, 2016.

ACKNOWLEDGEMENT

Data shown in this Standard were developed with the help of the global standards material published in the book, *Metric Standards for Worldwide Manufacturing*, with the permission of the publishers, ASME Press and *GOmetricUSA.org*.

ASME B32 COMMITTEE

Metal and Metal Alloy Wrought Mill Product Nominal Sizes

(The following is the roster of the Committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

J. A. Gruber, *Chair*
A. R. Amaral, *Secretary*

STANDARDS COMMITTEE PERSONNEL

A. R. Amaral, The American Society of Mechanical Engineers
D. O. Bankston, Jr., Bechtel National, Inc.
D. Frikken, Becht Engineering Co.
J. A. Gruber, J A Gruber & Associates, LLC
R. A. McLeod, General Electric Co.

A. P. Rangus, Bechtel
R. Reamey, Turner Industries Group, LLC
F. W. Tatar, FM Global
M. L. Nayyar, *Alternate*, NICE

CORRESPONDENCE WITH THE B32 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions or a case, and attending Committee meetings. Correspondence should be addressed to:

Secretary, B32 Standards Committee
The American Society of Mechanical Engineers
Two Park Avenue
New York, NY 10016-5990
<http://go.asme.org/Inquiry>

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Proposing a Case. Cases may be issued to provide alternative rules when justified, to permit early implementation of an approved revision when the need is urgent, or to provide rules not covered by existing provisions. Cases are effective immediately upon ASME approval and shall be posted on the ASME Committee Web page.

Requests for Cases shall provide a Statement of Need and Background Information. The request should identify the Standard and the paragraph, figure, or table number(s), and be written as a Question and Reply in the same format as existing Cases. Requests for Cases should also indicate the applicable edition(s) of the Standard to which the proposed Case applies.

Interpretations. Upon request, the B32 Standards Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B32 Standards Committee.

Requests for interpretation should preferably be submitted through the online Interpretation Submittal Form. The form is accessible at <http://go.asme.org/InterpretationRequest>. Upon submittal of the form, the Inquirer will receive an automatic e-mail confirming receipt.

If the Inquirer is unable to use the online form, he/she may mail the request to the Secretary of the B32 Standards Committee at the above address. The request for an interpretation should be clear and unambiguous. It is further recommended that the Inquirer submit his/her request in the following format:

Subject:	Cite the applicable paragraph number(s) and the topic of the inquiry in one or two words.
Edition:	Cite the applicable edition of the Standard for which the interpretation is being requested.
Question:	Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. Please provide a condensed and precise question, composed in such a way that a "yes" or "no" reply is acceptable.
Proposed Reply(ies):	Provide a proposed reply(ies) in the form of "Yes" or "No," with explanation as needed. If entering replies to more than one question, please number the questions and replies.
Background Information:	Provide the Committee with any background information that will assist the Committee in understanding the inquiry. The Inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in the format described above may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

Attending Committee Meetings. The B32 Standards Committee regularly holds meetings and/or telephone conferences that are open to the public. Persons wishing to attend any meeting and/or telephone conference should contact the Secretary of the B32 Standards Committee. Future Committee meeting dates and locations can be found on the Committee Page at go.asme.org/B32committee.

PREFERRED METRIC SIZES FOR FLAT, ROUND, SQUARE, RECTANGULAR, AND HEXAGONAL METAL PRODUCTS

1 SCOPE

This Standard establishes a preferred series of metric thicknesses, widths, and lengths for flat metal products of rectangular cross section. The thicknesses and widths shown in this Standard are also applicable to base metals that may be coated in later operations. This Standard also establishes a preferred series of metric sizes for round, square, rectangular, and hexagonal metal products.

2 GENERAL

The sizes in this Standard provide an orderly series of thicknesses for all flat metal products and widths for rectangular cross-section metal products. The series was developed to provide a reasonable selection of metal thicknesses from 0.050 mm to 300 mm and of metal widths from 10 mm to 5 000 mm. In each case, the series provides for some second, third, and sometimes fourth choice sizes (thicknesses and widths) to cover instances where selection from the primary preferred sizes may be inadequate. Sufficient coverage in logical steps is presented in the tables to adequately serve most of the general purpose requirements of industry for flat metal products. This Standard provides an orderly series of lengths for flat metal products.

This Standard also provides a series of sizes for each of round, square, rectangular, and hexagonal forms of metal products used for general applications. The series was developed to provide a reasonable selection of metal diameters from 0.020 mm to 320 mm for rounds and distance-across-flats from 3 mm to 300 mm for squares, various cross-section sizes from 1.6 mm by 2 mm to 100 mm by 200 mm for rectangles, and from 1.5 mm to 150 mm for hexagons. The series provides for some second, third, and fourth choice diameters for rounds and second and third choice distance-across-flats for squares and hexagons, where selection from the primary preferred sizes may be inadequate. The series also provides for preferred lengths of rounds, squares, rectangles, and hexagons. Sufficient coverage in logical steps is presented in the tables to adequately serve most of the general purpose requirements of industry for round, square, rectangular, and hexagonal metal products.

It is recognized that for some applications, particularly large-volume requirements in some metals for specific end uses, precise engineering requirements dictate a need for sizes other than those presented in this

Standard. This Standard is in no way meant to preclude the use of such sizes where they are required. However, for general purpose applications or where requirements permit some latitude in the selection of thickness or thickness/width/length combinations, the simplified preferred sizes given in this Standard should facilitate interchangeability of metals in design, reduce inventories, and increase the availability of warehouse stocks of those sizes commonly used for general purpose applications. In such instances, the use of sizes listed in this Standard is to be encouraged.

All of the sizes included in this Standard are not necessarily produced in all metals and grades. Producers or distributors should be consulted to determine availability of a particular thickness or thickness/width combination for a given metal product.

3 USE OF TABLES

Wherever possible, sizes should be selected from the columns headed "First Choice." Only if no size in the preferred list is suitable should a selection be made from the columns headed "Second Choice" or "Third Choice." Lengths should be selected from the preferred list.

4 BASIS OF TABLES

The sizes in this Standard are derived from a list of preferred metric sizes in which each number is approximately 60% greater than the number preceding it [ANSI B4.2 (Preferred Metric Limits and Fits) or ISO 497 (Guide to the choice of series of preferred numbers and series containing more rounded values of preferred numbers) Series R5']. Second Choice sizes are in increments of 25% (Series R10') and Third Choice sizes in increments of 12% (Series R20'). Some deviations from this principle occur as the result of minor rounding. The selected sizes also reflect standard material sizes in ISO and national standards in traditional metric countries.

5 TOLERANCES

Material product tolerances are shown in applicable international or national product standards. Normal tolerances shown in international standards are generally larger and could be up to twice as large for metric material compared with customary inch tolerances used in the U.S. Only a few major product groups will be covered by this Standard, and they are specified in [paras. 5.1 through 5.8](#).

5.1 Hot-Rolled Steel Sheets

Preferred sizes for hot-rolled steel sheets are shown in [Tables 1](#) through [3](#). Tolerances for hot-rolled steel sheets are specified in ISO 4995 (Hot-rolled steel sheet of structural quality) and ISO 5002 (Hot-rolled and cold-reduced electrolytic zinc-coated carbon steel sheet of commercial and drawing qualities) and shown in [Table 9](#).

5.2 Cold-Rolled Steel Sheets

Preferred sizes for cold-rolled steel sheets are shown in [Tables 1](#) through [3](#). Tolerances for cold-rolled steel sheets are specified in ISO 4997 (Cold-reduced carbon steel sheet of structural quality) and shown in [Table 10](#).

5.3 Hot-Rolled Steel Bars

Preferred sizes for hot-rolled steel bars are shown in [Tables 4](#) through [8](#). Note that in [Tables 4](#), [5](#), [6](#), and [13](#), D is the Basic Size, which is defined as the size to which limits and tolerances are assigned. Tolerances for hot-rolled steel bars are specified in ISO 1035-4 (Hot-rolled steel bars — Part 4: Tolerances) and shown in [Table 11](#).

5.4 Cold-Finished Round Steel Bars

Preferred sizes for cold-finished round steel bars are shown in [Tables 4](#) and [7](#). Cold-finished round steel bars held to the ISO tolerances h11, h9, h7, and h6 are listed in [Table 13](#).

5.5 Cold-Finished Square Steel Bars

Preferred sizes for cold-finished square steel bars are shown in [Tables 5](#) and [7](#). Cold-finished square steel bars held to the ISO tolerances h11 up to and including 65 mm and h12 for larger sizes are listed in [Table 13](#).

5.6 Cold-Finished Hex Steel Bars

Preferred sizes for cold-finished hex steel bars are shown in [Tables 6](#) and [7](#). Cold-finished hex steel bars held to the ISO tolerances h11 up to and including 65 mm and h12 for larger sizes are listed in [Table 13](#).

5.7 Hot-Rolled Rectangular Steel Bars

Preferred sizes for hot-rolled rectangular steel bars are shown in [Tables 7](#) and [8](#). Tolerances for hot-rolled steel bars are specified in ISO 1035-4 and shown in [Table 12](#).

5.8 Cold-Finished Rectangular Steel Bars

Preferred sizes for cold-finished rectangular steel bars are shown in [Tables 7](#) and [8](#). Cold-finished rectangular steel bars are held to the ISO tolerances specified in [Table 13](#) with the following limitations. For thicknesses (B) from 1.5 mm to 30 mm and widths (A) from 5 mm to 100 mm, ISO h11 tolerances are specified. For thicknesses over 30 mm, ISO h13 tolerances are specified. For widths over 100 mm, consult supplier.

Table 1 Preferred Thickness for All Flat Metal Products, mm

First Choice	Second Choice	Third Choice	First Choice	Second Choice	Third Choice
...	0.05	...	4
0.06	4.5
...	0.08	5	...
0.1	5.5
...	...	0.11	6
...	0.12	7
...	...	0.14	7.5
0.16	8	...
...	...	0.18	9
...	0.2	...	10
...	...	0.22	11
0.25	12	...
...	...	0.28	14
...	0.3	15
...	...	0.35	16
0.4	18
...	...	0.45	...	20	...
...	0.5	22
...	...	0.55	25
0.6	28
...	...	0.65	...	30	...
...	...	0.7	32
...	...	0.75	35
...	0.8	38
...	...	0.9	40
1	45
...	...	1.1	...	50	...
...	1.2	55
...	...	1.4	60
...	...	1.5	70
1.6	80	...
...	...	1.7	90
...	...	1.8	100
...	2	110
...	...	2.2	...	120	...
...	...	2.3	130
2.5	140
...	...	2.6	150
...	...	2.8	160
...	3	180
...	...	3.2	...	200	...
...	...	3.5	250
...	...	3.8	...	300	...

Table 2 Preferred Widths for Flat Metal Products, mm

First Choice	Second Choice	Third Choice	First Choice	Second Choice	Third Choice
...	2	130
2.5	140	...
...	3	150
4	160
...	5	180
6	200	...
...	8	225
10	250
...	12	280
16	300	...
...	20	...	400
25	500	...
...	30	...	600
...	...	35	700
40	800	...
...	...	45	900
...	50	...	1 000
...	...	55	...	1 200	...
60	1 600	...	1 500
...	...	70	...	2 000	...
...	80	...	2 500
...	...	90	...	3 000	...
100	3 500
...	...	110	4 000
...	120	5 000	...

Table 3 Preferred Lengths for Flat Metal Products, mm

First Choice	Second Choice	Third Choice
...	2 000	...
2 500
...	3 000	...
...	...	3 500
4 000
...	...	4 500
...	5 000	...
6 000
...	8 000	...
10 000
...	12 000	...
...	...	14 000
16 000
...	...	18 000

Table 4 Preferred Diameters, *D*, of Round Metal Products, mm

First Choice	Second Choice	Third Choice	First Choice	Second Choice	Third Choice	First Choice	Second Choice	Third Choice
...	0.02	2.4	45
...	...	0.022	2.5	48
0.025	2.6	...	50	...
...	...	0.028	2.8	55
...	0.03	3	56
...	...	0.035	3.2	60
0.04	3.5	63
...	...	0.045	3.8	65
...	0.05	...	4	70
...	...	0.055	4.5	75
0.06	4.8	...	80	...
...	...	0.065	...	5	85
...	...	0.07	5.5	90
...	0.08	...	6	95
...	...	0.09	6.5	100
0.1	7	105
...	...	0.11	7.5	110
...	0.12	8	120	...
...	...	0.14	8.5	125
0.16	9	130
...	...	0.18	9.5	140
...	0.2	...	10	150
...	...	0.22	11	160
0.25	12	170
...	...	0.28	13	180
...	0.3	14	190
...	...	0.35	15	...	200	...
0.4	16	220
...	...	0.45	17	240
...	0.5	18	250
...	...	0.55	19	260
0.6	20	280
...	21	...	300	...
...	...	0.7	22	320
...	0.8	23	340
...	...	0.9	24	350
1	25	360
...	...	1.1	26	380
...	1.2	28	400
...	30	420
...	...	1.4	32	440
1.6	35	450
...	...	1.8	36	460
...	2	38	480
...	40	500	...
...	...	2.2	42

GENERAL NOTE: Hot-finished round material sizes made to this Standard are interchangeable with those made to ISO 1035-1 (Hot-rolled steel bars — Part 1: Dimensions of round bars).

Table 5 Preferred Across Flat Sizes, *D*, of Square Metal Products, mm

First Choice	Second Choice	Third Choice	First Choice	Second Choice	Third Choice
...	3	45
4	50	...
...	5	55
6	60
...	8	70
10	80	...
...	12	90
...	...	14	100
16	110
...	...	18	...	120	...
...	20	140
...	...	22	160
25	180
...	...	28	...	200	...
...	30	220
...	...	35	250
40	300	...

GENERAL NOTE: Hot-finished square material sizes made to this Standard are interchangeable with those made to ISO 1035-2 (Hot-rolled steel bars — Part 2: Dimensions of square bars).

Table 6 Preferred Across Flat Sizes, *D*, of Hexagonal Metal Products, mm

First Choice	Second Choice	Third Choice	First Choice	Second Choice	Third Choice
...	1.5	...	30
...	2	32	...
...	2.5	...	34
3	36
...	3.2	...	41
4	46
5	50
...	5.5	...	55
6	60
...	7	...	65
8	70
10	75
12	80
...	13	...	85
14	90
...	15	...	95
16	100
...	17	...	105
18	110
...	19	...	115
21	120
...	22	...	130
24	135
27	145
...	150

Table 7 Preferred Lengths of Round, Square, Rectangular, and Hexagonal Metal Products, mm

First Choice	Second Choice	Third Choice
1 000
...	2 000	...
2 500
...	3 000	...
...	...	3 500
...	...	3 700
4 000
...	...	4 500
...	5 000	...
6 000
...	8 000	...
10 000
...	12 000	...
...	...	14 000
16 000
...	...	18 000

Table 8 Preferred Across Flat Sizes of Rectangular Metal Products, mm

Choice of Width, <i>A</i>			Thickness, <i>B</i>																			
			First Choice										Second Choice									
First	Second	Third	1.6	2.5	4	6	10	16 (1)	25	40	60	100	2	3	5	8	12	20	30	50	80	
...	2	
2.5	
...	3	
4	
...	5	C	C	C	
6	C	C	C	C	
...	8	...	C	C	X	C	C	X	C	
10	C	C	X	X	C	X	C	
...	12	...	C	C	X	X	C	X	C	
16	C	C	X	X	X	C	X	C	X	
...	20	...	C	C	X	X	X	C	C	X	X	X	X	
25	C	X	X	X	C	C	X	X	X	X	C	
...	30	C	X	X	X	X	C	C	X	X	X	X	X	
...	...	35	...	C	C	X	X	X	C	C	C	X	X	X	X	
40	C	X	X	X	X	C	C	X	X	X	X	C	
...	...	45	C	X	X	X	X	C	C	X	X	X	X	C	
...	50	C	X	X	X	X	C	C	X	X	X	X	X	
60	C	X	X	X	X	C	C	X	X	X	X	X	
...	...	70	X	X	X	X	C	X	X	X	X	X	
...	80	X	X	X	X	X	X	X	X	X	X	X	...	
...	...	90	X	X	X	X	X	X	X	X	X	X	X	...	
100	X	X	X	X	X	X	X	X	X	X	X	...	
...	...	110	H	H	H	H	H	H	H	H	H	H	H	...	
...	120	H	H	H	H	H	H	H	H	H	H	H	...	
...	...	130	H	H	H	H	H	H	H	H	H	H	H	...	
...	...	140	H	H	H	H	H	H	H	H	H	H	H	...	
...	...	150	H	H	H	H	H	H	H	H	H	H	H	...	
160	
...	...	180	
...	200	

GENERAL NOTES:

- (a) Hot-finished rectangular material sizes made to this Standard are interchangeable with those made to ISO 1035-3 (Hot-rolled steel bars — Part 3: Dimensions of flat bars).
- (b) X = hot and cold finished, C = cold finished, and H = hot finished.

NOTE: (1) The ISO 1035-3 standard specifies the 15-mm thickness.

Table 9 Thickness Tolerances for Hot-Rolled Steel Sheet of Structural Qualities (ISO-4995, ISO 5002), mm

Width	Thickness					
	Over 1.6 to 2	Over 2 to 2.5	Over 2.5 to 3	Over 3 to 4	Over 4 to 5	Over 5 to 6
Over 600 to 1200	0.17	0.18	0.20	0.22	0.24	0.26
Over 1200 to 1500	0.19	0.21	0.22	0.24	0.26	0.28
Over 1500 to 1800	0.21	0.23	0.24	0.26	0.28	0.29
Over 1800	...	0.25	0.26	0.27	0.29	0.31

Table 10 Thickness Tolerances for Cold-Rolled Steel Sheet of Structural Qualities (ISO 4997), mm

Width	Thickness								
	Over 0.36 to 0.4	Over 0.4 to 0.6	Over 0.6 to 0.8	Over 0.8 to 1	Over 1 to 1.2	Over 1.2 to 1.6	Over 1.6 to 2	Over 2 to 2.5	Over 2.5 to 3
Over 600 to 1200	0.05	0.06	0.08	0.09	0.10	0.12	0.14	0.17	0.20
Over 1200 to 1500	0.06	0.07	0.09	0.10	0.11	0.13	0.15	0.18	0.21
Over 1500 to 1800	...	0.09	0.10	0.11	0.13	0.15	0.18	0.20	0.23

Table 11 Tolerances for Hot-Rolled, Round, Square, and Hex Steel Bars (ISO 1035-4), mm

Nominal Sizes [Note (1)]		Tolerances on Size for Classes		
Over	Up to and Including	N	F	S [Note (2)]
...	15	±0.4	±0.3	±0.2
15	25	±0.5	±0.4	±0.25
25	35	±0.6	±0.5	±0.3
35	50	±0.8	±0.6	±0.4
50	80	±1	±0.8	±0.5 [Note (3)]
80	100	±1.3	±1	...
100	120	±1.6	±1.3	...
120	160	±2	±1.6	...
160	200	±2.5	±2	...
200	...	±1.5% of size	±1.2 of size	...

NOTES:

(1) Diameter of round bars, distance-across-flats of square and hex bars.

(2) Applicable to round bars only.

(3) Applicable only to sizes up to and including 65 mm. For larger sizes, the tolerances should be agreed on at the time of ordering.

Table 12 Tolerances for Hot-Rolled Flat Bars (ISO 1035-4), mm

Nominal Widths			Nominal Thickness		Tolerances on Thicknesses for Nominal Widths, <i>b</i> , mm	
Over	Up to and Including	Tolerances on Width	Over	Up to and Including	<i>b</i> ≤ 50	50 < <i>b</i> < 150
...	50	±0.8	...	20	±0.4	±0.5
50	75	±1.2	20	40	±0.8	±1
70	100	±1.5	40	±1.5
100	125	±2
125	150	±2.5

Table 13 Tolerances for Cold-Finished, Round, Square, Rectangular, and Hex Steel Bars (ANSI B4.2), mm

Basic Size, <i>D</i>	h13	h12	h11	h9	h7	h6
Over 0 to 3	+0.000, -0.140	+0.000, -0.100	+0.000, -0.060	+0.000, -0.025	+0.000, -0.010	+0.000, -0.006
Over 3 to 6	+0.000, -0.180	+0.000, -0.120	+0.000, -0.075	+0.000, -0.030	+0.000, -0.012	+0.000, -0.008
Over 6 to 10	+0.000, -0.220	+0.000, -0.150	+0.000, -0.090	+0.000, -0.036	+0.000, -0.015	+0.000, -0.009
Over 10 to 14	+0.000, -0.270	+0.000, -0.180	+0.000, -0.110	+0.000, -0.043	+0.000, -0.018	+0.000, -0.011
Over 14 to 18	+0.000, -0.270	+0.000, -0.180	+0.000, -0.110	+0.000, -0.043	+0.000, -0.018	+0.000, -0.011
Over 18 to 24	+0.000, -0.330	+0.000, -0.210	+0.000, -0.130	+0.000, -0.052	+0.000, -0.021	+0.000, -0.013
Over 24 to 30	+0.000, -0.330	+0.000, -0.210	+0.000, -0.130	+0.000, -0.052	+0.000, -0.021	+0.000, -0.013
Over 30 to 40	+0.000, -0.390	+0.000, -0.250	+0.000, -0.160	+0.000, -0.062	+0.000, -0.025	+0.000, -0.016
Over 40 to 50	+0.000, -0.390	+0.000, -0.250	+0.000, -0.160	+0.000, -0.062	+0.000, -0.025	+0.000, -0.016
Over 50 to 65	+0.000, -0.460	+0.000, -0.300	+0.000, -0.190	+0.000, -0.074	+0.000, -0.030	+0.000, -0.019
Over 65 to 80	+0.000, -0.460	+0.000, -0.300	+0.000, -0.190	+0.000, -0.074	+0.000, -0.030	+0.000, -0.019
Over 80 to 100	+0.000, -0.540	+0.000, -0.350	+0.000, -0.220	+0.000, -0.087	+0.000, -0.035	+0.000, -0.022
Over 100 to 120	+0.000, -0.540	+0.000, -0.350	+0.000, -0.220	+0.000, -0.087	+0.000, -0.035	+0.000, -0.022
Over 120 to 140	+0.000, -0.630	+0.000, -0.400	+0.000, -0.250	+0.000, -0.100	+0.000, -0.040	+0.000, -0.025
Over 140 to 160	+0.000, -0.630	+0.000, -0.400	+0.000, -0.250	+0.000, -0.100	+0.000, -0.040	+0.000, -0.025
Over 160 to 180	+0.000, -0.630	+0.000, -0.400	+0.000, -0.250	+0.000, -0.100	+0.000, -0.040	+0.000, -0.025
Over 180 to 200	+0.000, -0.720	+0.000, -0.460	+0.000, -0.290	+0.000, -0.115	+0.000, -0.046	+0.000, -0.029
Over 200 to 225	+0.000, -0.720	+0.000, -0.460	+0.000, -0.290	+0.000, -0.115	+0.000, -0.046	+0.000, -0.029
Over 225 to 250	+0.000, -0.720	+0.000, -0.460	+0.000, -0.290	+0.000, -0.115	+0.000, -0.046	+0.000, -0.029
Over 250 to 280	+0.000, -0.810	+0.000, -0.520	+0.000, -0.320	+0.000, -0.130	+0.000, -0.052	+0.000, -0.032
Over 280 to 315	+0.000, -0.810	+0.000, -0.520	+0.000, -0.320	+0.000, -0.130	+0.000, -0.052	+0.000, -0.032
Over 315 to 355	+0.000, -0.890	+0.000, -0.570	+0.000, -0.360	+0.000, -0.140	+0.000, -0.057	+0.000, -0.036
Over 355 to 400	+0.000, -0.890	+0.000, -0.570	+0.000, -0.360	+0.000, -0.140	+0.000, -0.057	+0.000, -0.036
Over 400 to 450	+0.000, -0.970	+0.000, -0.630	+0.000, -0.400	+0.000, -0.155	+0.000, -0.063	+0.000, -0.040
Over 450 to 500	+0.000, -0.970	+0.000, -0.630	+0.000, -0.400	+0.000, -0.155	+0.000, -0.063	+0.000, -0.040

GENERAL NOTE: For cold-finished rectangular bars, the basic size dimensions, *A* (width) and *B* (thickness), are used to determine tolerance in lieu of *D*.

NONMANDATORY APPENDIX A

RELATED STANDARDS

The following is a list of standards and specifications that may be applicable to various products mentioned in this Standard:

- ISO 3: Preferred numbers—Series of preferred numbers
- ISO 17: Guide to the use of preferred numbers and series of preferred numbers
- ISO 286-1: Geometrical product specifications (GPS) – ISO code system for tolerances on linear sizes—Part 1: Basis of tolerances, deviations, and fits
- ISO 286-2: Geometrical product specifications (GSP) – ISO code system for tolerances on linear sizes—Part 2: Tables of standard tolerance classes and limit deviations for holes and shafts
- ISO 657-1: Hot-rolled steel sections—Part 1: Equal-leg angles — Dimensions
- ISO 657-2: Hot-rolled steel sections—Part 2: Unequal-leg angles — Dimensions
- ISO 657-5: Hot-rolled steel sections—Part 5: Equal-leg angles and unequal-leg angles—Tolerances for metric and inch series
- ISO 657-11: Hot-rolled steel sections—Part 11: Sloping flange channel sections (Metric series)—Dimensions and sectional properties
- ISO 657-15: Hot-rolled steel sections—Part 15: Sloping flange beam sections (Metric series)—Dimensions and sectional properties
- ISO 657-16: Hot-rolled steel sections—Part 16: Sloping flange column sections (metric series)—Dimensions and sectional properties
- ISO 657-18: Hot-rolled steel sections—Part 18: L sections for shipbuilding (metric series)—Dimensions, sectional properties, and tolerances
- ISO 657-21: Hot-rolled steel sections—Part 21: T-sections with equal depth and flange width—Dimensions
- ISO 1127: Stainless steel tubes—Dimensions, tolerances, and conventional masses per unit length
- ISO 2937: Plain-end seamless steel tubes for mechanical application
- ISO 2938: Hollow steel bars for machining
- ISO 3573: Hot-rolled carbon steel sheet of commercial and drawing qualities
- ISO 3574: Cold-reduced carbon steel sheet of commercial and drawing qualities
- ISO 3575: Continuous hot-dip, zinc-coated carbon steel sheet of commercial and drawing qualities
- ISO 4200: Plain-end steel tubes, welded and seamless — General tables of dimensions and masses per unit length
- ISO 4960: Cold-reduced carbon steel strip with a mass fraction of carbon over 0.25%
- ISO 4996: Hot-rolled steel sheet of high-yield stress structural quality
- ISO 4998: Continuous hot-dip, zinc-coated and zinc-iron alloy-coated carbon steel sheet of structural quality
- ISO 5000: Continuous hot-dip aluminum-silicon-coated, cold-reduced carbon steel sheet of commercial and drawing qualities
- ISO 5001: Cold-reduced carbon steel sheet for vitreous enameling
- ISO 5252: Steel tubes—Tolerance systems
- ISO 5950: Electrolytic tin-coated, cold-reduced carbon steel sheet of commercial and drawing qualities
- ISO 5951: Hot-rolled steel sheet of higher yield strength with improved formability
- ISO 5952: Continuously hot-rolled steel sheet of structural quality with improved atmospheric corrosion resistance
- ISO 5954: Cold-reduced carbon steel sheet according to hardness requirements
- ISO 6316: Hot-rolled steel strip of structural quality
- ISO 6317: Hot-rolled carbon steel strip of commercial and drawing qualities
- ISO 6932: Cold-reduced carbon steel strip with a maximum carbon content of 0.25%
- ISO 7452: Hot-rolled steel plates—Tolerances on dimensions and shape
- ISO 8458-1: Steel wire for mechanical springs—Part 1: General requirements
- ISO 8458-2: Steel wire for mechanical springs—Part 2: Patented cold-drawn non-alloy steel wire
- ISO 9034: Hot-rolled structural steel wide flats—Tolerances on dimensions and shape
- ISO 9364: Continuous hot-dip 55% aluminum/zinc alloy-coated steel sheet of commercial, drawing, and structural qualities
- ISO 10384: Hot-rolled carbon steel sheet as defined by chemical composition
- ISO 13887: Cold-reduced steel sheet of higher yield strength with improved formability
- ISO 13976: Hot-rolled steel sheet in coils of structural quality and heavy thickness

ISO 14590: Cold-reduced steel sheet of high tensile strength and low-yield point with improved formability

ISO 14788: Continuous hot-dip zinc-5% aluminum alloy-coated steel sheet

ISO 16160: Hot-rolled steel sheet products—Dimensional and shape tolerances

ISO 16162: Cold-rolled steel sheet products—Dimensional and shape tolerances

ISO 16163: Continuously hot-dipped coated steel sheet products—Dimensional and shape tolerances

Publisher: International Organization for Standardization (ISO), Central Secretariat, Chemin de Blandonnet 8, Case postale 401, 1214 Vernier, Geneva Switzerland (www.iso.org)

ASME Services

ASME is committed to developing and delivering technical information. At ASME's Customer Care, we make every effort to answer your questions and expedite your orders. Our representatives are ready to assist you in the following areas:

ASME Press	Member Services & Benefits	Public Information
<i>Codes & Standards</i>	Other ASME Programs	Self-Study Courses
Credit Card Orders	Payment Inquiries	Shipping Information
IMechE Publications	Professional Development	Subscriptions/Journals/Magazines
Meetings & Conferences	Short Courses	Symposia Volumes
Member Dues Status	Publications	Technical Papers

How can you reach us? It's easier than ever!

There are four options for making inquiries* or placing orders. Simply mail, phone, fax, or E-mail us and a Customer Care representative will handle your request.

<i>Mail</i>	<i>Call Toll Free</i>	<i>Fax—24 hours</i>	<i>E-Mail—24 hours</i>
ASME	US & Canada: 800-THE-ASME	973-882-1717	customercare@asme.org
150 Clove Road, 6th Floor	(800-843-2763)	973-882-5155	
Little Falls, New Jersey	Mexico: 95-800-THE-ASME		
07424-2139	(95-800-843-2763)		

*Customer Care staff are not permitted to answer inquiries about the technical content of this code or standard. Information as to whether or not technical inquiries are issued to this code or standard is shown on the copyright page. All technical inquiries must be submitted in writing to the staff secretary. Additional procedures for inquiries may be listed within.

ASME B32.100-2016

ISBN 978-0-7918-7115-7



9 780791 871157



L 0 8 2 1 Q