

STD • ASME B56.11.7-ENGL 1998 ■ 0759670 0608428 401 ■



The American Society of
Mechanical Engineers

LIQUID PROPANE GAS (LPG) FUEL CYLINDERS (HORIZONTAL OR VERTICAL) MOUNTING—LIQUID WITHDRAWAL—FOR POWERED INDUSTRIAL TRUCKS

AN AMERICAN NATIONAL STANDARD

ASME B56.11.7-1998



The American Society of
Mechanical Engineers

A N A M E R I C A N N A T I O N A L S T A N D A R D

LIQUID PROPANE GAS (LPG) FUEL CYLINDERS (HORIZONTAL OR VERTICAL) MOUNTING—LIQUID WITHDRAWAL—FOR POWERED INDUSTRIAL TRUCKS

ASME B56.11.7-1998

POWERED AND NONPOWERED INDUSTRIAL TRUCKS

Date of Issuance: November 13, 1998

The 1998 edition of this Standard is being issued with an automatic addenda subscription service. The use of an addenda allows revisions made in response to public review comments or committee actions to be published on a regular yearly basis; revisions published in addenda will become effective 1 year after the Date of Issuance of the addenda. The next edition of this Standard is scheduled for publication in 2003.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. The interpretations will be included with the above addenda service. Interpretations are not part of the addenda to the Standard.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment which provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable Letters Patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations issued in accordance with governing ASME procedures and policies which preclude the issuance of interpretations by individual volunteers.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Three Park Avenue, New York, NY 10016-5990

Copyright © 1998 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All Rights Reserved
Printed in U.S. A.

FOREWORD

(This Foreword is not part of ASME B56.11.7-1998.)

On December 9, 1993, the ASME B56.11 Subcommittee began work on this Standard at the direction of the B56 Committee. Following a number of meetings, it was approved by the Subcommittee and submitted to the ASME B56 Committee on Powered and Nonpowered Industrial Trucks.

After several B56 Committee ballots and public review, the standard was approved by the B56 Committee, by ASME, and by the American National Standards Institute on June 2, 1998.

Safety codes and standards are intended to enhance public health and safety. Revisions result from committee consideration of factors such as technological advances, new data, and changing environmental and industry needs. Revisions do not imply that previous editions were inadequate.

ASME STANDARDS COMMITTEE B56 Powered and Nonpowered Industrial Trucks

(The following is the roster of the Committee at the time of approval of this Standard.)

OFFICERS

E. B. Gutta, *Chair*
G. H. Ritterbusch, *Vice Chair*
U. D'Urso, *Secretary*

COMMITTEE PERSONNEL*

ALLIANCE OF AMERICAN INSURERS

D. A. Greer, Liberty Mutual Insurance Co.

AMERICAN TRUCKING ASSOCIATION, INC.

N. Darmstadter, American Trucking Associations, Inc.

J. M. Dandrea, *Alternate*, American Trucking Associations, Inc.

BATTERY COUNCIL INTERNATIONAL

K. S. Sanders, East Penn Manufacturing Co., Inc.

W. N. Ritchie, *Alternate*, East Penn Manufacturing Co., Inc.

INDUSTRIAL TRUCK ASSOCIATION, THE

W. J. Montweiler, The Industrial Truck Association

INTERNATIONAL ASSOCIATION OF MACHINISTS AND AEROSPACE WORKERS

E. W. Sprang, International Association of Machinists and Aerospace Workers

G. W. Meyer, *Alternate*, International Association of Machinists and Aerospace Workers

MOTOR VEHICLE MANUFACTURERS ASSOCIATION

D. M. Graham, Ford Motor Group

INDIVIDUAL MEMBERS

L. R. Berke, Safety Solutions of America

L. J. Churches, Churches & Associates, Inc.

J. N. Eavenson, Commercial Turf Products, Ltd.

R. C. Fuller, Consultant

C. R. Herron, ACS Industries, Inc.

D. E. Hupp, Aluminum Company of America

J. E. Johnson, Johnson Engineering Services, Inc.

A. C. Karelus, Eastman Kodak Co.

R. A. Klebes, Universal Health Services

D. T. Labelle, Industrial Tires, Ltd.

R. R. Lasecki, Consultant

E. J. Ramsey, Major Equipment Co., Inc.

G. H. Ritterbusch, Caterpillar, Inc.

R. N. Rogers, Raymond Corp.

S. J. Simpson, Simpson Machine Corp.

E. R. Sirotak, Consultant

F. E. Steinberger, General Motors Corp.

* The members listed, except for those listed under the heading of individual members, were nominated by their respective organizations.

**SUBCOMMITTEE B56.11 — STANDARDIZATION OF POWERED AND
NONPOWERED INDUSTRIAL TRUCKS**

S. Simpson, *Chair*, Simpson Machine Corp.
J. E. Johnson, *Vice Chair*, Johnson Engineering Services, Inc.
U. D'Urso, *Secretary*, The American Society of Mechanical Engineers
F. L. Clason, Daewoo Equipment Co.
W. J. Girardi, Girardi Consulting
D. H. Graham, Ford Motor Co.
D. A. Greer, Liberty Mutual Group
A. C. Karelus, Eastman Kodak Co.
R. D. McAdam, Hyster Co.
W. J. Montwieler, Industrial Truck Association
R. Niblock, GM-LAD UAW
R. N. Rogers, Raymond Corp.
J. D. Schell, Consultant
R. E. Steinberger, General Motors Corp.

CONTENTS

Foreword	iii
Committee Roster	v
1 Scope	1
2 Purpose	1
3 Interpretation	1
3.1 Mandatory and Advisory Rules	1
3.2 Requests for Interpretation	1
4 Design and Construction Standards	1
5 Markings	1
6 Dimensional Detail	1
Figure	
1 Dimensional Detail	2
Table	
1 Weight and Volume Specifications	3

LIQUIFIED PETROLEUM GAS (LPG) FUEL CYLINDERS (HORIZONTAL OR VERTICAL) MOUNTING — LIQUID WITHDRAWAL — FOR POWERED INDUSTRIAL TRUCKS

1 SCOPE

This Standard establishes dimensions for LPG fuel cylinders used on powered industrial trucks.

2 PURPOSE

The purpose of this Standard is to promote the interchangeability of 20#, 33.5#, and 43.5# LP-Gas cylinders used on powered industrial trucks.

3 INTERPRETATION

3.1 Mandatory and Advisory Rules

To carry out the provisions of this Standard, all items are mandatory except those including the word *should*, which are recommendations.

3.2 Requests for Interpretation

The B56 Committee will render an interpretation of any requirement of this Standard. The interpretations will be rendered only in response to a written request sent to the Secretary of the B56 Committee, ASME, Three Park Avenue, New York, NY 10016-5990. The request for interpretation shall be in the following format:

- Subject: Cite the applicable paragraph number(s) and provide a concise description.
- Edition: Cite the applicable edition of the pertinent standard for which the interpretation is being requested.
- Question: Phrase the questions as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for approval of a proprietary design or situation. The inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

4 DESIGN AND CONSTRUCTION STANDARDS

(a) LP-Gas fuel cylinders shall be constructed of steel or aluminum and shall conform to the appropriate ASME, Department of Transportation (DOT), and Transport Canada (TC) Standards. DOT and TC cylinders shall have a minimum service pressure rating of 240 psi (16 bar).

NOTE: Newly constructed cylinders used in Canada require TC markings. Cylinders manufactured to TC standards contain metric markings. Cylinders used in the United States require DOT markings. Some cylinders are manufactured and dual marked to allow filling and use in both countries (e.g., DOT-4BA240 — TC4BAM16).

(b) LPG fuel cylinders shall be constructed to engage a substantial positioning pin or an equivalent means to provide for intended positioning of the cylinder. (See Fig. 1, G.)

(c) LPG fuel cylinders shall be filled (see Table 1) by weight only or by either weight or volume.

(d) LPG fuel cylinders, which can be filled by either weight or volume, shall have a fixed liquid level gauge.

5 MARKINGS

Cylinders shall be marked in accordance with NFPA 58.

6 DIMENSIONAL DETAIL (See Fig. 1)

(a) Pressure relief device with captive rain cap shall discharge at 45 deg. from horizontal with cylinder in

ASME B56.11.7-1998

LIQUID PROPANE GAS (LPG) FUEL CYLINDERS —
FOR POWERED INDUSTRIAL TRUCKS

NOTE:
All dimensions are in mm.
All pipe threads are tapered.




FIG. 1 DIMENSIONAL DETAIL

LIQUID PROPANE GAS (LPG) FUEL CYLINDERS —
FOR POWERED INDUSTRIAL TRUCKS

ASME B56.11.7-1998

TABLE 1 WEIGHT AND VOLUME SPECIFICATIONS

Type	Method of Fill	Fixed Dip Lube	LPG Cap lbs / kg	Min Water Cap lbs / kg	Approx. Tare Wgt lbs / kg ⁽¹⁾	Conforms to Specifications
1-HV	Wgt only	Not req'd	20.00 / 9.1	47.62 / 21.6	24 - 35 / 10.9 - 15.9 Steel 16 - 19 / 7.2 - 8.6 Alum	TC4BAM16 DOT 4B240 4BA240
2-HV	Wgt or vol	Req'd	20.00 / 9.1	47.62 / 21.6	24 - 35 / 10.9 - 15.9 Steel 16 - 19 / 7.2 - 8.6 Alum	4BW240 or 4E240
3-HV	Vol only	Req'd	20.00 / 9.1	47.62 / 21.6	80 / 36.3	ASME Code for U.P.V. Section VIII
4-HV	Wgt or vol	Req'd	20.00 / 9.1	47.62 / 21.6	80 / 36.3	ASME Code for U.P.V. Section VIII
1-HV	Wgt only	Not req'd	33.50 / 15.22	79.8 / 36.3	35 - 43 / 15.9 - 19.5 Steel 21 - 23 / 9.5 - 10.4 Alum	TC4BAM16 DOT 4B240 4BA240
2-HV	Wgt or vol	Req'd	33.50 / 15.22	79.8 / 36.3	35 - 43 / 15.9 - 19.5 Steel 21 - 23 / 9.5 - 10.4 Alum	4BW240 or 4E240
3-HV	Vol only	Req'd	33.50 / 15.22	79.8 / 36.3	100 / 45.4	ASME Code for U.P.V. Section VIII
4-HV	Wgt or vol	Req'd	33.50 / 15.22	79.8 / 36.3	100 / 45.4	ASME Code for U.P.V. Section VIII
1-HV	Wgt only	Not req'd	43.50 / 19.77	103.6 / 47.1	41 - 49 / 18.6 - 22.2 Steel 25.5 - 11.6 Alum	TC4BAM16 DOT 4B240 4BA240
2-HV	Wgt or vol	Req'd	43.50 / 19.77	103.6 / 47.1	41 - 49 / 18.6 - 22.2 Steel 25.5 / 11.6 Alum	4BW240 or 4E240
3-HV	Vol only	Req'd	43.50 / 19.77	103.6 / 47.1	120 / 54.5	ASME Code for U.P.V. Section VIII
4-HV	Wgt or vol	Req'd	43.50 / 19.77	103.6 / 47.1	120 / 54.5	ASME Code for U.P.V. Section VIII

NOTE:

(1) Weights vary based on cylinder design, manufacturing construction, and valving configuration.

horizontal or vertical position. Relief valve discharge shall be provided with clear passage without impinging on head ring. Relief valve inlet shall contact vapor space of filled cylinder when mounted horizontally or vertically.

(b) Hand hole may be enlarged from point of contact with the cylinder to curl on top side to maintain a 1-in. (25-mm) clearance for liquid service shut-off device extended centerline within window area.

(c) A liquid service shut-off valve shall be installed and it shall have a flow check valve. The valve handle shall be marked "liquid shut-off valve," with "close" and "open" directions denoted by arrows. Location of this valve shall provide free hand clearance with head

ring and adjacent fittings. Liquid withdrawal tube shall be located to allow maximum practical emptying of tank in horizontal or vertical position.

(d) Universal cylinder float gauge position shall be optional.

(e) Fixed liquid level gauge and identification shall be required for volume filling (location optional).

(f) Quick fill valve (optional), when provided, shall terminate fill tube in upper 20% of the cylinder. Position and tube contour shall be optional.

(g) Cylinder positioning pin hole.

(h) Vapor withdrawal port, not used for powered industrial trucks.

AMERICAN NATIONAL STANDARDS ON MATERIAL HANDLING EQUIPMENT

Safety Code for Elevators and Escalators.....	A17.1-1990
Safety Standard for Conveyors and Related Equipment	B20.1-1990
Safety Standard for Low Lift and High Lift Trucks	B56.1-1988
Safety Standard for Guided Industrial Vehicles	B56.5-1988
Safety Standard for Rough Terrain Forklift Trucks	B56.6-1987
Safety Standard for Industrial Crane Trucks	B56.7-1987
Safety Standard for Personnel and Burden Carriers	B56.8-1988
Safety Standard for Operator Controlled Industrial Tow Tractors	B56.9-1991
Double Race or Bi-Level Swivel and Rigid Industrial Casters.....	B56.11.1-1991
Load Handling Symbols for Powered Industrial Trucks	B56.11.3-1988
Hook-Type Forks and Fork Carriers for Powered Industrial Forklift Trucks	B56.11.4-1988
Measurement of Sound Emitted by Low Lift, High Lift, and Rough Terrain Powered Industrial Trucks	B56.11.5-1989
Liquid Propane Gas (LPG) Fuel Cylinders (Horizontal or Vertical) Mounting — Liquid Withdrawal — for Powered Industrial Trucks.....	B56.11.7-1998
Definitions and Terminology Covering Pallets and Related Structures.....	MH1.1.2-1989
Pallet Sizes	MH1.2.2M-1989
Specifications for Identification and Marking of Cargo Containers.....	MH5.3M-1982

The ASME Publications Catalog shows a complete list of all the Standards published by the Society. For a complementary catalog, or the latest information about our publications, call 1-800-THE-ASME (1-800-843-2763.)