

Designation: D6707/D6707M – 06 (Reapproved 2016) $^{\epsilon 1}$ 

# Standard Specification for Circular-Knit Geotextile for Use in Subsurface Drainage Applications<sup>1</sup>

This standard is issued under the fixed designation D6707/D6707M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\varepsilon$ ) indicates an editorial change since the last revision or reapproval.

 $\epsilon^1$  NOTE—Designation was changed to dual and units information was corrected editorially in January 2016.

## 1. Scope

1.1 This specification covers circular-knit geotextiles for use on the outside of perforated pipes and Class B geocomposites per Specification D7001 in drainage applications.

1.2 The tests used to characterize the geotextile are intended to ensure good workmanship and quality, and are not necessarily adequate for design purposes in view of the importance of environmental factors and specific performance objectives. Tests have been selected with essentially neutral aqueous systems in mind. Other tests may be necessary to establish chemical resistance and durability under the conditions of a particular application.

1.3 The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

1.4 This standard may involve hazardous materials, operations, and equipment. This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.

# 2. Referenced Documents

2.1 ASTM Standards:<sup>2</sup>
D123 Terminology Relating to Textiles
D4439 Terminology for Geosynthetics
D4491/D4491M Test Methods for Water Permeability of

Geotextiles by Permittivity

- D4751 Test Method for Determining Apparent Opening Size of a Geotextile
- D6241 Test Method for Static Puncture Strength of Geotextiles and Geotextile-Related Products Using a 50-mm Probe
- D7001 Specification for Geocomposites for Pavement Edge Drains and Other High-Flow Applications

#### 3. Terminology

3.1 Definitions of Terms Specific to This Standard:

3.1.1 *circular knit*—a structure produced by interlooping one or more ends of yarn or comparable material in a continuously circular orientation around the fabric.

3.1.2 *filtration*—the equilibrium soil to geotextile system that allows for adequate liquid flow with limited soil loss across the plane of the geotextile over the service lifetime compatible with the application under consideration.

3.2 Definitions in this specification are in accordance with Terminologies D123 and D4439, unless otherwise specified.

## 4. Classification

4.1 The circular-knit geotextiles covered by this specification are classified as follows:

- 4.1.1 Type A: fabric
- 4.1.2 Type H: fabric

4.2 The characteristics of the two types of geotextile are given in 8.1 below.

## 5. Significance and Use

5.1 Circular knit geotextiles have been used extensively for many years as filtration geotextiles in combination with subsurface drainage pipes.

5.2 The test procedures and recommendations referred to in this standard are considered adequate to determine the acceptable performance properties of these geotextiles and are recommended to specifiers and users of these products for acceptance testing.

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdiction of ASTM Committee D35 on Geosynthetics and is the direct responsibility of Subcommittee D35.03 on Permeability and Filtration.

Current edition approved Jan. 1, 2016. Published June 2016. Originally approved in 2001. Last previous edition approved in 2011 as D6707–06(2011). DOI: 10.1520/D6707\_D6707M-06R16E01.

<sup>&</sup>lt;sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.



## 6. Materials and Manufacture

6.1 The geotextile shall be manufactured from polymeric materials.

6.2 The geotextiles are manufactured by a circular knit process to ensure a consistent, continuous fabric without seams along its machine direction in order to envelope the perforated pipe without flaws.

## 7. Fabrication Procedures

7.1 The circular knit geotextiles, when applied to the perforated tubing, fit snugly and uniformly over the entire exterior surface of the pipe.

7.2 If for any reason the circular knitted geotextile fabric becomes damaged, repair of damaged area may be conducted in the field prior to installation, by wrapping or overlaying the damaged area with similar knitted fabric and attaching the fabric either by tying or with suitable adhesive tape.

7.3 The overlaid fabric must be secured in such a manner so as to prevent the patch from moving or shifting during normal installation procedures.

7.4 The overlaid fabric must cover an area extending a minimum of 45 cm [18 in.] on either side of the damaged area

and must cover the entire circumference of the wrapped pipe in the area where the repair is being made.

## 8. Physical Requirements

8.1 Table of Values:

Test Method	Туре А	Туре Н
D4491/D4491M Water Permittivity	2.4 s (-1) min	2.75 s (-1) min
D4751 AOS	0.60 mm max	0.425 mm max
D6241 Puncture strength (N)	800 min	800 min

8.1.1 The physical values provided in this standard are not intended to address all soil conditions which may be encountered.

8.1.2 Specialty circular knit geotextiles may be available for other soil conditions.

8.1.3 Fabric designed to fit nominal O.D. of pipe.

## 9. Quality Assurance

9.1 When specified in the contract or purchase order, or when requested by the purchaser, the supplier shall affirm that the geotextile was manufactured, inspected and tested in accordance with this specification and that it has been found to meet the requirements of this specification.

## 10. Keywords

10.1 circular-knit; drainage pipe; fabric; filter; geocomposite; geotextile; perforated pipe

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/