

INTERNATIONAL STANDARD

IEC
60384-24-1

First edition
2006-06

Fixed capacitors for use in electronic equipment –

Part 24-1:

Blank detail specification –

**Surface mount fixed tantalum electrolytic
capacitors with conductive polymer solid
electrolyte – Assessment level EZ**



Reference number
IEC 60384-24-1:2006(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC
60384-24-1

First edition
2006-06

Fixed capacitors for use in electronic equipment –

Part 24-1:

Blank detail specification –

Surface mount fixed tantalum electrolytic capacitors with conductive polymer solid electrolyte – Assessment level EZ

© IEC 2006 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

N

For price, see current catalogue

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –**Part 24-1: Blank detail specification – Surface mount fixed tantalum electrolytic capacitors with conductive polymer solid electrolyte –
Assessment level EZ**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60384-24-1 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
40/1732/FDIS	40/1755/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 60384 consists of the following parts, under the general title *Fixed capacitors for use in electronic equipment*:

- Part 1: Generic specification
- Part 2: Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors
- Part 3: Sectional specification: Fixed tantalum chip capacitors
- Part 4: Sectional specification: Aluminium electrolytic capacitors with solid and non- solid electrolyte
- Part 5: Sectional specification: Fixed mica dielectric d.c. capacitors with a rated voltage not exceeding 3 000 V – Selection of methods of test and general requirements
- Part 6: Sectional specification: Fixed metallized polycarbonate film dielectric d.c. capacitors
- Part 7: Sectional specification: Fixed polystyrene film dielectric metal foil d.c. capacitors
- Part 8: Sectional specification: Fixed capacitors of ceramic dielectric, Class 1
- Part 9: Sectional specification: Fixed capacitors of ceramic dielectric, Class 2
- Part 11: Sectional specification: Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors
- Part 12: Sectional specification: Fixed polycarbonate film dielectric metal foil d.c. capacitors
- Part 13: Sectional specification: Fixed polypropylene film dielectric metal foil d.c. capacitors
- Part 14: Sectional specification: Fixed capacitors for electromagnetic interference suppression and connection to the supply mains
- Part 15: Sectional specification: Fixed tantalum capacitors with non-solid or solid electrolyte
- Part 16: Sectional specification: Fixed metallized polypropylene film dielectric d.c. capacitors
- Part 17: Sectional specification: Fixed metallized polypropylene film dielectric a.c. and pulse capacitors
- Part 18: Sectional specification: Fixed aluminium electrolytic chip capacitors with solid and non-solid electrolyte
- Part 19: Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric chip d.c. capacitors
- Part 20: Sectional specification: Fixed metallized polyphenylene sulphide film dielectric chip d.c. capacitors
- Part 21: Sectional specification: Fixed surface mount multilayer capacitors of ceramic dielectric, Class 1
- Part 22: Sectional specification: Fixed surface mount multilayer capacitors of ceramic dielectric, Class 2
- Part 23: Sectional specification: Fixed surface mount metallized polyethylene naphthalate film dielectric d.c. capacitors
- Part 24: Sectional specification: Surface mount fixed tantalum electrolytic capacitors with conductive polymer solid electrolyte
- Part 25: Sectional specification: Surface mount fixed aluminium electrolyte capacitors with conductive polymer solid electrolyte

All sectional specifications mentioned above do have one or more blank detail specifications being a supplementary document, containing requirements for style, layout and minimum content of detail specifications.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT

Part 24-1: Blank detail specification – Surface mount fixed tantalum electrolytic capacitors with conductive polymer solid electrolyte – Assessment level EZ

Blank detail specification

A blank detail specification is a supplementary document to the sectional specification and contains requirements for style and layout and minimum content of detail specifications. Detail specifications not complying with these requirements may not be considered as being in accordance with IEC specifications nor shall they so be described.

In the preparation of detail specifications the content of 1.4 of the sectional specification shall be taken into account.

The numbers between square brackets on the first page of the detail specification correspond to the following information, which shall be inserted in the position indicated.

Identification of the detail specification

- [1] The “International Electrotechnical Commission” or the National Standards Organization under whose authority the detail specification is drafted.
- [2] The IEC or National Standards number of the detail specification, date of issue and any further information required by the national system.
- [3] The number and issue number of the IEC or national generic specification.
- [4] The IEC number of the blank detail specification.

Identification of the capacitor

- [5] A short description of the type of capacitor.
- [6] Information on typical construction (when applicable).
- [7] Outline drawing with main dimensions which are of importance for interchangeability and/or reference to the national or international documents for outlines. Alternatively, this drawing may be given in an annex to the detail specification.
- [8] Application or group of applications covered and/or assessment level.
- [9] Reference data on the most important properties, to allow comparison between the various capacitor types.

	[1]		[2]
ELECTRONIC COMPONENTS OF ASSESSED QUALITY IN ACCORDANCE WITH :	[3]	IEC 60384-24-1	[4]
Outline drawing : (see Table 1) (...angle projection)	[7]	Surface mount fixed tantalum electrolytic capacitors with conductive polymer solid electrolyte	[5]
			[6]
		Assessment level(s): EZ	[8]

Information on the availability of components qualified to this detail specification is given in IEC QC 001005.

(9)

1 General data

1.1 Recommended method(s) of mounting (to be inserted)

(See 1.4.2 of IEC 60384-24).

1.2 Dimensions

Table 1 – Case size reference and dimensions

Case size reference	Dimension						
	mm						
	<i>L</i>	<i>W</i>	<i>H</i>				

NOTE 1 When there is no case size reference, Table 1 may be omitted and the dimensions should be given in Table 2, which then becomes Table 1.

NOTE 2 The dimensions should be given as maximum dimensions or as nominal dimensions with a tolerance.

1.3 Ratings and characteristics

Rated capacitance range (see Table 2)

Tolerance on rated capacitance

Rated voltage (see Table 2)

Category voltage (see Table 2)

Climatic category

Rated temperature

Variation of capacitance with temperature (see Table 3)

Tangent of loss angle (see Table 3)

Leakage current (see Table 3)

Equivalent series resistance (see Table 3)

Surge voltage (see Table 2)

Table 2 – Values of capacitance and of voltage related to case sizes

Rated voltage V					
Category voltage V					
Surge voltage V	Rated temperature				
	Upper category temperature				
		Case sizes	Case sizes	Case sizes	Case sizes
Rated capacitance μF					

Table 3 – Characteristics

Case size	U_R V	C_R μF	Capacitance change %			Maximum values							
						Tangent of loss angle $\tan \delta$ at 120 Hz				Leakage current μA			Equivalent series resistance at 100 kHz m Ω
			-55 °C	Rated temperature	Upper category temperature	-55 °C	20 °C	Rated temperature	Upper category temperature	20 °C	Rated temperature	Upper category temperature	20 °C

1.4 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60384-1:1999, *Fixed capacitors for use in electronic equipment – Part 1: Generic specification*

IEC 60384-24:2006, *Fixed capacitors for use in electronic equipment – Part 24: Sectional specification – Surface mount fixed tantalum electrolytic capacitors with conductive polymer solid electrolyte*

1.5 Marking

The marking of the capacitor and the package shall be in accordance with the requirements of 1.6 of IEC 60384-24.

NOTE The details of the marking of the component and package should be given in full in the detail specification.

1.6 Ordering information

Orders for capacitors covered by this specification shall contain, in clear or in coded form, the following minimum information:

- a) rated capacitance;
- b) tolerance on rated capacitance;
- c) rated d.c. voltage;
- d) number and issue reference of the detail specification and style reference;
- e) packaging instructions.

1.7 Certified records of released lots

Required/not required.

1.8 Additional information (not for inspection purposes)

1.9 Additional or increased severities or requirements to those specified in the generic and/or sectional specification

NOTE Additions or increased requirements should be specified only when essential.

Table 4 – Other characteristics

<p>This table is to be used for defining characteristics which are additional to, or more severe than, those given in the sectional specification.</p>
--

2 Inspection requirements

2.1 Procedures

2.1.1 For qualification approval, the procedures shall be in accordance with 3.4 of IEC 60384-24.

2.1.2 For quality conformance inspection, the test schedule (Table 5) includes sampling, periodicity, severities and requirements. The formation of inspection lots is covered by 3.5.1 of IEC 60384-24.

Table 5 – Test schedule for quality conformance inspection

Subclause number and test ^a	D or ND ^b	Conditions of test ^a	Number of specimens and number of non-conforming items ^b			Performance requirements ^a
			<i>IL</i>	<i>n</i>	<i>c</i>	
Group A inspection (lot-by-lot) Subgroup A0 4.18 High surge current (if applicable) 4.5.1 Leakage current 4.5.2 Capacitance 4.5.3 Tangent of loss angle ($\tan \delta$) 4.5.4 Equivalent series resistance (ESR) (if applicable)	ND	Protective resistor: 1 000 Ω Frequency: 120 Hz Frequency: 120 Hz Frequency: 100 kHz	100 % ^c			As in Table 3 Within specified tolerance As in Table 3 As in Table 3
Subgroup A1 4.4 Visual examination	ND		S-3	^d	0	As in 4.4.2 Legible marking (if required) and as specified in the detail specification
Subgroup A2 4.4 Dimension (detail) ^e	ND		S-3	^d	0	As specified in Table 1 of this specification
Group B inspection (lot-by-lot) 4.7 Solderability 4.7.1 Test 4.7.2 Final measurement	D	See detail specification for the method Visual examination	S-3	^d	0	As in 4.7.2

Table 5 – Test schedule for quality conformance inspection (*continued*)

Subclause number and test ^a	D or ND ^b	Conditions of test ^a	Number of specimens and number of non-conforming items ^b			Performance requirements ^a
			<i>p</i>	<i>n</i>	<i>c</i>	
Group C inspection (Periodic) Subgroup C1 4.6 Resistance to soldering heat 4.6.1 Initial measurement 4.6.2 Test 4.6.3 Final measurement	D	Capacitance Method: ... Deflection: ...s Reflow profile: ... Recovery: 24 h ± 2 h Visual examination Leakage current Capacitance Tangent of loss angle (tan δ) Equivalent series resistance (ESR)	3	12	0 f	For use as reference value As in 4.6.3 As in Table 3 See detail specification As in Table 3 See detail specification
Sub group C2 4.9 Substrate bending test 4.9.1 Initial measurement 4.9.3 Final inspection	D	Capacitance Capacitance (with printed board in bent position)	3	12	0 f	For use as reference value See detail specification
Sub group C3 4.3 Mounting 4.3.1 Initial measurement 4.3.3 Final inspection	D	Substrate material: ... Capacitance (the value obtained in 4.5.2 may be used) Visual examination Leakage current Capacitance Tangent of loss angle (tan δ) Equivalent series resistance (ESR)	g			No visible damage As in Table 3 $\Delta C/C \leq 8 \%$ As in Table 3 See detail specification

Table 5 – Test schedule for quality conformance inspection (*continued*)

Subclause number and test ^a	D or ND ^b	Conditions of test ^a	Number of specimens and number of non-conforming items ^b			Performance requirements ^a
			<i>p</i>	<i>n</i>	<i>c</i>	
Sub group C3.1			6	18	0	
4.8 Shear test		Visual examination			f	No visible damage
4.10 Rapid change of temperature						
4.10.1 Initial measurement		Capacitance (the value obtained in Group 3 may be used)				
4.10.2 Test		T_A = Lower category temperature T_B = Upper category temperature Five cycles Duration t_1 = 30 min Recovery: 1 h to 2 h				
4.10.3 Final measurements		Leakage current Capacitance Tangent of loss angle ($\tan \delta$)				As in Table 3 $\Delta C/C \leq 10$ % of value measured in 4.10.1 As in Table 3
4.11 Climatic sequence						
4.11.1 Initial measurement		Capacitance (the value obtained in 4.10.3 may be used)				
4.11.2 Dry heat		Temperature: upper category temperature Duration: 16 h				
4.11.3 Damp heat, cyclic, test Db, first cycle						
4.11.4 Cold		Temperature: lower category temperature Duration: 2h				
4.11.5 Damp heat, cyclic, test Db, remaining cycles						
4.11.6 Final measurements		Visual examination Leakage current Capacitance Tangent of loss angle				No visible damage Legible marking As in Table 3 $\Delta C/C < \pm 20$ % of the value measured in 4.11.1 $\leq 1,2$ times the limit of Table 3

Table 5 – Test schedule for quality conformance inspection *(continued)*

Subclause number and test ^a	D or ND ^b	Conditions of test ^a	Number of specimens and number of non-conforming items ^b			Performance requirements ^a
			<i>p</i>	<i>n</i>	<i>c</i>	
Subgroup C3.2 4.12 Damp heat, steady state 4.12.1 Initial measurement 4.12.3 Final measurements	D	Recovery: 1 h to 2 h Capacitance (the value obtained in Group 3 may be used) Visual examination Leakage current Capacitance Tangent of loss angle	6	12	0 f	No visible damage Legible marking $\leq 5 \times$ initial limit $-20 \% \leq \Delta C/C \leq 40 \%$ of the value measured in 4.12.1 $\leq 1,2$ times the limit of Table 3
Sub group C3.3 4.13 Characteristics at high and low temperature	D	The capacitors shall be measured at each temperature step Step 1: 20 °C Leakage current Capacitance Tangent of loss angle Step 2: lower category temperature Capacitance (if applicable) Tangent of loss angle (if applicable) Step 3 : 20 °C Leakage current Capacitance Tangent of loss angle Step 4 : rated temperature Leakage current Capacitance Tangent of loss angle Step 5 : upper category temperature Leakage current Capacitance Tangent of loss angle	6	15	0 f	As in Table 3 For use as reference value As in Table 3 As in Table 3 As in Table 3 As in Table 3 $\Delta C/C \leq 5 \%$ of value measured in Step 1 As in Table 3 As in Table 3 As in Table 3 As in Table 3 As in Table 3 As in Table 3 As in Table 3

Table 5 – Test schedule for quality conformance inspection (*continued*)

Subclause number and test ^a	D or ND ^b	Conditions of test ^a	Number of specimens and number of non-conforming items ^b			Performance requirements ^a
			<i>p</i>	<i>n</i>	<i>c</i>	
4.14 Surge		Step 6 :20 °C Leakage current Capacitance Tangent of loss angle Number of cycles: 1 000 Test temperature: ...°C Voltage: 1,15 U_R Protective resistor: 1 000 Ω Duration of charge: 30 s Duration of no load: 5 min 30 s	6	15	0	As in Step 3 As in Step 3 As in Step 3
4.14.3 Final measurements		Visual examination Leakage current Capacitance Tangent of loss angle				No visible damage As in Table 3 $\Delta C/C < \pm 20$ % of the value measured in 4.13 Step 6 $\leq 1,5$ times the limit of Table 3
Subgroup C3.4	D		3	24	0	
4.15 Endurance		Duration: 1 000 h Test temperature: ... °C Voltage: ... V Recovery: 1 h to 2 h			f	
4.15.1 Initial measurement		Capacitance				No visible damage
4.15.3 Final measurements		Visual examination Leakage current Capacitance Tangent of loss angle Equivalent series resistance (if required by the detail specification)				Legible marking ≤ 2 times the limit of Table 3 $\Delta C/C \leq 20$ % of value measured in 4.15.1 $\leq 1,5$ times the limit of Table 3 ≤ 2 times the limit of Table 3

Table 5 – Test schedule for quality conformance inspection (*continued*)

Subclause number and test ^a	D or ND ^b	Conditions of test ^a	Number of specimens and number of non-conforming items ^b			Performance requirements ^a
			<i>p</i>	<i>n</i>	<i>c</i>	
Sub group C3.5	D		6	12	0	
4.19 Storage at high temperature		Test temperature: upper category temperature				
		Duration: 96 h ± 4 h				
		Recovery: 16 h min				
4.19.1 Initial measurement		Capacitance (the value obtained in Group 3 may be used)				
4.19.3 Final measurements		Visual examination				No visible damage
		Leakage current				≤ 5 times the limit of Table 3
		Capacitance				$\Delta C/C \leq \pm 10\%$ of the value measured in 4.19.1
		Tangent of loss angle				As in Table 3
<p>^a Subclause numbers of tests and performance requirements refer to IEC 60384-24 and Clause 1 of this specification.</p> <p>^b In this table <i>p</i> = periodicity (in months), <i>n</i> = sample size, <i>c</i> = acceptance criterion (permitted number of non-conforming items), D = destructive, ND = non-destructive, <i>IL</i> = inspection level.</p> <p>^c 100 % testing shall be followed by reinspection by sampling in order to monitor outgoing quality level by non-conforming items per million (ppm). The sampling level shall be established by the manufacturer. For the calculation of ppm values, any parametric failure shall be counted as a non-conforming item. If one or more non-conforming items occur in a sample, this lot shall be rejected.</p> <p>^d Inspection Levels are selected from IEC 60410.</p> <p>^e This test may be replaced by in-production testing if the manufacturer installs Statistical Process Control (SPC) on dimensional measurements or other mechanisms to avoid parts exceeding the limits.</p> <p>^f If one non-conforming item is obtained, all the tests of the subgroup shall be repeated on a new sample and then no further non-conforming items are permitted. The release of the product may continue during repeat testing.</p> <p>^g The capacitors which found non-conformances after mounting shall not be taken into account when calculating the non-conformances for the following tests. They shall be replaced by spare capacitors.</p>						



Standards Survey

The IEC would like to offer you the best quality standards possible. To make sure that we continue to meet your needs, your feedback is essential. Would you please take a minute to answer the questions overleaf and fax them to us at +41 22 919 03 00 or mail them to the address below. Thank you!

Customer Service Centre (CSC)

International Electrotechnical Commission

3, rue de Varembe
1211 Genève 20
Switzerland

or

Fax to: **IEC/CSC** at +41 22 919 03 00

Thank you for your contribution to the standards-making process.

A Prioritaire

Nicht frankieren
Ne pas affranchir



Non affrancare
No stamp required

RÉPONSE PAYÉE

SUISSE

Customer Service Centre (CSC)
International Electrotechnical Commission
3, rue de Varembe
1211 GENEVA 20
Switzerland



Q1 Please report on **ONE STANDARD** and **ONE STANDARD ONLY**. Enter the exact number of the standard: (e.g. 60601-1-1)

.....

Q2 Please tell us in what capacity(ies) you bought the standard (tick all that apply). I am the/a:

- purchasing agent ☐
 librarian ☐
 researcher ☐
 design engineer ☐
 safety engineer ☐
 testing engineer ☐
 marketing specialist ☐
 other.....

Q3 I work for/in/as a:
(tick all that apply)

- manufacturing ☐
 consultant ☐
 government ☐
 test/certification facility ☐
 public utility ☐
 education ☐
 military ☐
 other.....

Q4 This standard will be used for:
(tick all that apply)

- general reference ☐
 product research ☐
 product design/development ☐
 specifications ☐
 tenders ☐
 quality assessment ☐
 certification ☐
 technical documentation ☐
 thesis ☐
 manufacturing ☐
 other.....

Q5 This standard meets my needs:
(tick one)

- not at all ☐
 nearly ☐
 fairly well ☐
 exactly ☐

Q6 If you ticked NOT AT ALL in Question 5 the reason is: (tick all that apply)

- standard is out of date ☐
 standard is incomplete ☐
 standard is too academic ☐
 standard is too superficial ☐
 title is misleading ☐
 I made the wrong choice ☐
 other

Q7 Please assess the standard in the following categories, using the numbers:

- (1) unacceptable,
 (2) below average,
 (3) average,
 (4) above average,
 (5) exceptional,
 (6) not applicable

- timeliness.....
 quality of writing.....
 technical contents.....
 logic of arrangement of contents
 tables, charts, graphs, figures.....
 other

Q8 I read/use the: (tick one)

- French text only ☐
 English text only ☐
 both English and French texts ☐

Q9 Please share any comment on any aspect of the IEC that you would like us to know:

.....



ISBN 2-8318-8703-8



ICS 31.060.40; 31.060.50
