INTERNATIONAL STANDARD

IEC 60384-9-1

QC 300701

Second edition 2005-05

Fixed capacitors for use in electronic equipment -

Part 9-1: Blank detail specification: Fixed capacitors of ceramic dielectric, Class 2 – Assessment level EZ



Reference number IEC 60384-9-1:2005(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

IEC Web Site (<u>www.iec.ch</u>)

Catalogue of IEC publications

The on-line catalogue on the IEC web site (<u>www.iec.ch/searchpub</u>) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

• IEC Just Published

This summary of recently issued publications (<u>www.iec.ch/online_news/justpub</u>) is also available by email. Please contact the Customer Service Centre (see below) for further information.

• Customer Service Centre

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: <u>custserv@iec.ch</u> Tel: +41 22 919 02 11 Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 60384-9-1

QC 300701

Second edition 2005-05

Fixed capacitors for use in electronic equipment -

Part 9-1: Blank detail specification: Fixed capacitors of ceramic dielectric, Class 2 – Assessment level EZ

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale International Electrotechnical Commission Международная Электротехническая Комиссия



For price, see current catalogue

- 2 -

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT -

Part 9-1: Blank detail specification: Fixed capacitors of ceramic dielectric, Class 2 – Assessment level EZ

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60384-9-1 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment

This second edition cancels and replaces the first edition published in 1988. This second edition is a result of maintenance activities related to the previous edition. All changes that have been agreed upon can be categorized as minor revisions.

The text of this standard is based on the following documents:

FDIS	Report on voting
40/1531/FDIS	40/1551/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 60384 consists of the following parts, under the general title Fixed capacitors for use in electronic equipment:

- Part 1: Generic specification
- Part 2: Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors
- Part 3: Sectional specification: Fixed tantalum chip capacitors
- Part 4: Sectional specification: Aluminium electrolytic capacitors with solid and non-solid electrolyte
- Part 5: Sectional specification: Fixed mica dielectric d.c. capacitors with a rated voltage not exceeding 3000 V Selection of methods of test and general requirements
- Part 6: Sectional specification: Fixed metallized polycarbonate film dielectric d.c. capacitors
- Part 7: Sectional specification: Fixed polystyrene film dielectric metal foil d.c. capacitors
- Part 8: Sectional specification: Fixed capacitors of ceramic dielectric, Class 1
- Part 9: Sectional specification: Fixed capacitors of ceramic dielectric, Class 2
- Part 11: Sectional specification: Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors
- Part 12: Sectional specification: Fixed polycarbonate film dielectric metal foil d.c. capacitors
- Part 13: Sectional specification: Fixed polypropylene film dielectric metal foil d.c. capacitors
- Part 14: Sectional specification: Fixed capacitors for electromagnetic interference suppression and connection to the supply mains
- Part 15: Sectional specification: Fixed tantalum capacitors with non-solid or solid electrolyte
- Part 16: Sectional specification: Fixed metallized polypropylene film dielectric d.c. capacitors
- Part 17: Sectional specification: Fixed metallized polypropylene film dielectric a.c. and pulse capacitors
- Part 18: Sectional specification: Fixed aluminium electrolytic chip capacitors with solid and non-solid electrolyte
- Part 19: Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric chip d.c. capacitors
- Part 20: Sectional specification: Fixed metallized polyphenylene sulfide film dielectric chip d.c. capacitors
- Part 21: Sectional specification: Fixed surface mount multilayer capacitors of ceramic dielectric, Class 1
- Part 22: Sectional specification: Fixed surface mount multilayer capacitors of ceramic dielectric, Class 2
- Part 23: Sectional specification: Fixed surface mount metallized polyethylene naphthalate film dielectric d.c. capacitors¹
- Part 24: Sectional specification Surface mount fixed tantalum electrolytic capacitors with conductive polymer solid electrolyte①
- Part 25: Sectional specification Surface mount fixed aluminium electrolytic capacitors with conductive polymer solid electrolyte①

¹ To be published.

The QC number that appears on the front cover of this publication is the specification number in the IECQ Quality Assessment System for Electronic Components.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- · replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT -

Part 9-1: Blank detail specification: Fixed capacitors of ceramic dielectric, Class 2 – Assessment level EZ

Blank detail specification

A blank detail specification is a supplementary document to the sectional specification and contains requirements for style and layout and minimum content of detail specifications. Detail specifications not complying with these requirements may not be considered as being in accordance with IEC specifications nor shall they be so described.

In the preparation of detail specifications, the content of 1.4 of the sectional specification shall be taken into account.

The numbers between brackets on the first page correspond to the following information, which shall be inserted in the position indicated:

Identification of the detail specification

- [1] The "International Electrotechnical Commission" or the National Standards Organization under whose authority the detail specification is drafted.
- [2] The IEC or National Standards number of the detail specification, date of issue and any further information required by the national system.
- [3] The number and issue number of the IEC or national generic specification.
- [4] The IEC number of the blank detail specification.

Identification of the capacitor

- [5] A short description of the type of capacitor.
- [6] Information on typical construction (when applicable).

When the capacitor is not designed for use in printed board applications, this shall be clearly stated in the detail specification in this position.

- [7] Outline drawing with main dimensions, which are of importance for interchangeability and/or reference to the national or international documents for outlines. Alternatively, this drawing may be given in an appendix to the detail specification.
- [8] Application or group of applications covered and/or assessment level.

The assessment level(s) to be used in a detail specification shall be selected from the sectional specification, 3.5.4. This implies that one blank detail specification may be used in combination with several assessment levels provided the grouping of the tests does not change.

[9] Reference data on the most important properties, to allow comparison between the various capacitor types.

[1]	IEC 60384-9-1-XXX QC 300701-XXX	[2]
ELECTRONIC COMPONENTS OF ASSESSED QUALITY IN ACCORDANCE WITH:	IEC 60384-9-1 QC 300701	[4]
[3]	FIXED CAPACITORS OF CERAMIC DIELECTRIC, CLASS 2	[5]
Outline drawing: (see Table 1) (angle projection)		
[7]		[6]
(Other shapes are permitted within the dimensions given)	Assessment level(s): EZ	[8]

Information on the availability of components qualified to this detail specification is given in the IEC QC 001005.

[9]

LICENSED TO MECON Limited. - RANCHI/BANGALORE FOR INTERNAL USE AT THIS LOCATION ONLY, SUPPLIED BY BOOK SUPPLY BUREAU.

1 General data

1.1 Recommended method(s) of mounting (to be inserted)

(See IEC 60384-9, 1.4.2).

1.2 Dimensions

Table 1 – Case size reference and dimensions

Case size reference	Dimensions (in mm)							
	Ø	L	Н	d				

1.3 Ratings and characteristics

Rated capacitance range (see Table 2) Tolerance on rated capacitance Rated voltage Climatic category Rated temperature Tangent of loss angle Insulation resistance

Temperature characteristic of capacitance

Table 2 – Values of capacitance and of voltage related to case sizes

Rated voltage					
Rated capacitance (in pF and/or nF)	Tolerance %	Case size	Case size	Case size	Case size

Table 3 – Temperature characteristic of capacitance

Temperature	Permissible capacitance variation						
range	With no voltage applied	With U _R applied					
°C/ + °C	+ % / – %	+ % / – %					

1.4 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60384-9:200X, Fixed capacitors for use in electronic equipment. Part 9: Sectional specification: Fixed capacitors of ceramic dielectric, Class 2

IEC 60410:1973, Sampling plans and procedures for inspection by attributes

1.5 Marking

The marking of the capacitor and the packing shall be in accordance with the requirements of IEC 60384-9, 1.6.

The details of the marking of the component and packing shall be given in full in the detail specification.

1.6 Ordering information

Orders for capacitors covered by this specification shall contain, in clear or in coded form, the following minimum information:

- a) rated capacitance;
- b) tolerance on rated capacitance;
- c) rated d.c. voltage;
- d) temperature characteristic of capacitance;
- e) number and issue reference of the detail specification and style reference.

1.7 Certified records of released lots

Required/not required.

1.8 Additional information (not for inspection purposes)

1.9 Additional or increased severities or requirements to those specified in the generic and/or sectional specification

NOTE Additions or increased requirements should be specified only when essential.

Table 4 – Other characteristics

- 8 -

This table is to be used for defining characteristics which are additional to or more severe than those given in the sectional specification.

2 Inspection requirements

2.1 Procedures

2.1.1 For qualification approval, the procedures shall be in accordance with the sectional specification, IEC 60384-9, 3.4.

2.1.2 For quality conformance inspection the test schedule (Table 5) includes sampling, periodicity, severities and requirements. The formation of inspection lots is covered by 3.5.1 of the sectional specification IEC 60384-9.

Subclause number and test ^a	D or ND	Conditions of test ^a	Number of specimens (<i>n</i>) and number of non- conforming items (<i>c</i>)		n-	Performance requirements ^a
			IL	n	С	
Group A inspection (lot-by-lot)						
Subgroup A0	ND			100 % °		
4.3.1 Capacitance		Frequency: kHz Measuring Voltage: V				Within specified tolerance
4.3.2 Tangent of loss angle		Frequency and measuring voltage same as in 4.3.1				As in 4.3.2.3
4.3.3 Insulation resistance (Test A)		Method:				As in 4.3.3.2
4.3.4 Voltage proof (Test A)		Method:				No breakdown or flashover
Subgroup A1 4.2 Visual examination	ND		S-4	d	0	As in 4.2 Legible marking and as specified in 1.5 of this specification
Subgroup A2	ND		S-3	d	0	
4.2 Dimensions (gauging) ^e						As specified in Table 1 of this specification

Table 5 – Test schedule for qualification conformance inspection

Sub	oclause number and test ª	D or ND	Conditions of test ^a	nu	Number cimens (/ umber of oforming (c)	n) and non-	Performance requirements ^a
				IL	n	с	
(lot-b	p B inspection y-lot) roup B1	D		S-	d)	0	
4.7	Solderability		Method:	3			Good tinning as evidenced by free flowing of the solder with wetting of the terminations or solder shall flow within s, as applicable
4.16	Solvent resistance of the marking (if applicable)		Solvent: Solvent temperature: Method 1 Rubbing material: cotton wool Recovery:				Legible marking
Subg	roup B2 ^{g)}	ND		S-	d)	0	
4.4	Temperature characteristic of capacitance		Special preconditioning as in 4.1 Capacitance	2			$\Delta C/C$ as in 4.4.3

- 9 -

_	1	0	-
---	---	---	---

Subclause number and test a	D or ND	Conditions of test ^a	Number of specimens (<i>n</i>) and number of non- conforming items (<i>c</i>)		n) and non-	Performance requirements ^a
			р	n	с	
Group C inspection (periodic)						
Subgroup C1A	D		6	9	0 ^{f)}	
Part of sample of subgroup C1						
4.2 Dimensions (detail)						As specified in Table 1 of this specification
4.5 Robustness of terminations		Visual examination				No visible damage
4.6.2 Initial measurement		Capacitance				
4.6 Resistance to soldering heat		Special preconditioning as in 4.1 Method:				
4.6.4 Final measurements		Visual examination				No visible damage Legible marking
4.15 Component solvent resistance (if applicable)		Capacitance Solvent: Solvent temperature: Method 2 Recovery: 24 h ± 2 h				$\Delta \tilde{C}/C$ as in 4.6.4
Subgroup C1B	D		6	18	0 ^{f)}	
Other part of sample of subgroup C1						
4.8 Rapid change of temperature		Special preconditioning as in 4.1				
4.8.2 Initial measurement		Capacitance T_A = Lower category temperature T_B = Upper category temperature Five cycles Duration t_1 = 30 min Recovery: 24 h ± 2 h				
Ι	I	Visual examination				No visible damage

Subcla	use number and test ª	D or ND	Conditions of test ^a	Number of specimens (<i>n</i>) and number of non- conforming items (<i>c</i>)		(n) and f non-	Performance requirements ^a
				p	n	с	
4.9 Vi	bration		Method of mounting: see 1.1 of this specification				
			Frequency range: Hz to Hz				
			Amplitude 0,75 mm or acceleration 100 m/s ² (whichever is the less severe)				
			Total duration: 6 h				
	termediate spection		Visual examination				No visible damage
	ump (or shock, ee 4.11)		Method of mounting: see 1.1 of this specification Acceleration: m/s ² Duration of pulse: ms				
	nock (or bump, ee 4.10)		Method of mounting: see 1.1 of this specification Acceleration: m/s ² Duration of pulse: ms				
	nal measurements		Visual examination				No visible damage
or 4.11.3							Legible marking
			Capacitance				$\Delta C/C$ as in 4.11.3
Subgrou	ıp C1	D		6	27	0 ^{f)}	
specimer	d sample of ns of os C1A and C1B						
4.12	Climatic sequence		Special preconditioning as in 4.1				
4.12.1.1	Initial measurement		Capacitance				
4.12.2	Dry heat		Temperature: upper category temperature Duration: 16 h				
4.12.3	Damp heat, cyclic, Test Db, first cycle						
4.12.4	Cold		Temperature: lower category temperature Duration: 2 h				
			Visual examination				No visible damage
4.12.5	Low air pressure (if required by the detail specification)		Air pressure: 8 kPa				
4.12.5.3	Intermediate inspection		Visual examination				No breakdown or flashover
4.12.6	Damp heat, cyclic, Test Db, remaining cycles		Recovery: 24 h ± 2 h				

Subcla	Subclause number and test ª		Conditions of test ^a			s (n) er of rming	Performance requirements ^a	
				р	n	с		
4.12.6.3	Final measurements		Visual examination				No visible damage Legible marking	
			Capacitance				∆C/C as in 4.12.6.3	
			Tangent of loss angle				As in 4.12.6.3	
			Insulation resistance				As in 4.12.6.3	
Subgrou	ıp C2	D		6	15	0 ^{f)}		
4.13	Damp heat, steady state		Special preconditioning as in 4.1					
4.13.2	Initial measurements		Capacitance Recovery: 24 h ± 2 h					
4.13.5	Final measurements		Visual examination				No visible damage Legible marking	
			Capacitance				∆C/C as in 4.13.5	
			Tangent of loss angle				As in 4.13.5	
			Insulation resistance				As in 4.13.5	
Subgrou	ір СЗ	D		3	21	0 ^{f)}		
4.14	Endurance		Special preconditioning as in 4.1					
			Voltage: V					
			Duration: h					
4.14.2	Initial measurement		Capacitance Recovery: 24 h ± 2 h					
4.14.5	Final measurements		Visual examination				No visible damage Legible marking	
			Capacitance				Δ C/C as in 4.14.5	
			Tangent of loss angle				As in 4.14.5	
			Insulation resistance				As in 4.14.5	
Subgrou	ıp C4	ND		12	9	0 ^{f)}		
4.4	Temperature characteristic		Special preconditioning as in 4.1					
	of capacitance		Capacitance				$\Delta C/C$ as in 4.4.3	

^a Subclause numbers of tests and performance requirements refer to the sectional specification, IEC 60384-9 and Clause 1 of this specification.

^b In this table: *p* = periodicity (in months), *n* = sample size, *c* = acceptance criterion (permitted number of non-conforming items), D = destructive, ND = non-destructive, *IL* = inspection level.

^c 100 % testing shall be followed by re-inspection by sampling in order to monitor outgoing quality level by non-conforming items per million (10⁻⁶). The sampling level shall be established by the manufacturer. For the calculation of 10⁻⁶ values any parametric failure shall be counted as a non-conforming item. In case one or more non-conforming items occur in a sample, this lot shall be rejected.

^d Inspection levels are selected from IEC 60410: Sampling plans and procedures for inspection by attributes.

^e This test may be replaced by in-production testing if the manufacturer installs Statistical Process Control (SPC) on dimensional measurements or other mechanisms to avoid parts exceeding the limits.

^f If one non-conforming item is obtained, all the tests of the subgroup shall be repeated on a new sample and then no further non-conforming items are permitted. Release of product may continue during repeat testing.

^g This subgroup may be omitted if a corresponding test is carried out on each manufacturing batch of dielectric material.



The IEC would like to offer you the best quality standards possible. To make sure that we continue to meet your needs, your feedback is essential. Would you please take a minute to answer the questions overleaf and fax them to us at +41 22 919 03 00 or mail them to the address below. Thank you!

Customer Service Centre (CSC)

International Electrotechnical Commission 3, rue de Varembé 1211 Genève 20 Switzerland

or

Fax to: IEC/CSC at +41 22 919 03 00

Thank you for your contribution to the standards-making process.



Nicht frankieren Ne pas affranchir



Non affrancare No stamp required

RÉPONSE PAYÉE SUISSE

Customer Service Centre (CSC) International Electrotechnical Commission 3, rue de Varembé 1211 GENEVA 20 Switzerland

Q1	Please report on ONE STANDARD ar ONE STANDARD ONLY . Enter the ex number of the standard: (e.g. 60601-1	act	Q6	If you ticked NOT AT ALL in Question & the reason is: (tick all that apply)				
		,		standard is out of date				
		••••		standard is incomplete				
				standard is too academic				
Q2	Please tell us in what capacity(ies) yo		standard is too superficial					
	bought the standard (tick all that apply I am the/a:	y).		title is misleading				
				I made the wrong choice				
	purchasing agent			other				
	librarian							
	researcher							
	design engineer		Q7	Please assess the standard in the				
	safety engineer		Q (1	following categories, using				
	testing engineer			the numbers:				
	marketing specialist			(1) unacceptable,				
	other			(2) below average, (3) average,				
				(4) above average,				
Q3	l work for/in/as a:			(5) exceptional,				
43	(tick all that apply)			(6) not applicable				
				timeliness				
	manufacturing			quality of writing				
	consultant			technical contents				
	government			logic of arrangement of contents				
	test/certification facility			tables, charts, graphs, figures				
	public utility			other				
	education							
	military							
	other		Q8	I read/use the: (tick one)				
Q4	This standard will be used for:			French text only				
44	(tick all that apply)			English text only				
				both English and French texts				
	general reference							
	product research							
	product design/development							
	specifications		Q9	Please share any comment on any				
	tenders			aspect of the IEC that you would like us to know:				
	quality assessment							
	certification							
	technical documentation	<u> </u>						
	thesis	<u> </u>						
	manufacturing	L						
	other							
Q5	This standard meets my needs:							
	(tick one)							
	not at all							
	nearly							
	fairly well							
	exactly							

LICENSED TO MECON Limited. - RANCHI/BANGALORE FOR INTERNAL USE AT THIS LOCATION ONLY, SUPPLIED BY BOOK SUPPLY BUREAU.



ICS 31.060.20