LICENSED TO MECON Limited. - RANCHI/BANGALORE FOR INTERNAL USE AT THIS LOCATION ONLY, SUPPLIED BY BOOK SUPPLY BUREAU.

INTERNATIONAL STANDARD

IEC 60873-2

First edition 2004-01

Electrical and pneumatic analogue chart recorders for use in industrial process control systems –

Part 2: Guidance for inspection and routine testing



Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

IEC Web Site (<u>www.iec.ch</u>)

Catalogue of IEC publications

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

IEC Just Published

This summary of recently issued publications (www.iec.ch/online_news/"justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

• Customer Service Centre

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

LICENSED TO MECON Limited. - RANCHI/BANGALORE FOR INTERNAL USE AT THIS LOCATION ONLY, SUPPLIED BY BOOK SUPPLY BUREAU.

INTERNATIONAL STANDARD

IEC 60873-2

First edition 2004-01

Electrical and pneumatic analogue chart recorders for use in industrial process control systems –

Part 2: Guidance for inspection and routine testing

© IEC 2004 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



PRICE CODE

F

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRICAL AND PNEUMATIC ANALOGUE CHART RECORDERS FOR USE IN INDUSTRIAL PROCESS CONTROL SYSTEMS –

Part 2: Guidance for inspection and routine testing

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60873-2 has been prepared by subcommittee 65B: Devices, of IEC technical committee 65: Industrial-process measurement and control.

The text of this standard is based on the following documents:

FDIS	Report on voting
65B/513/FDIS	65B/520/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until 2009. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

ELECTRICAL AND PNEUMATIC ANALOGUE CHART RECORDERS FOR USE IN INDUSTRIAL PROCESS CONTROL SYSTEMS –

Part 2: Guidance for inspection and routine testing

1 Scope and object

This part of IEC 60873 applies to electrical and pneumatic analogue chart recorders (for use in industrial-process control systems), operating from a standardized signal which may be used in process control. It is intended that continuous and dotted line traces, and multiple pen and multiple-channel instruments should be covered. Some tests may not apply to all instruments and additional tests may be required for certain types of recorders.

The object of this standard is to provide technical guidance for inspection and routine testing of electrical and pneumatic analogue chart recorders, for instance, as acceptance tests or after repair. For a full evaluation, or where a recorder is to be used under arduous conditions, (for example, high temperatures), IEC 60873-1 should be used. Whenever possible any tests carried out are to be in accordance with IEC 61298, and the person carrying out the tests needs to have a copy of it to hand and be familiar with it.

Quantitative criteria for acceptable performance should be established by agreement between manufacturer and user, and the report on the tests shall make clear which tests were carried out. The requirements of this standard shall be effective when agreed by the manufacturer and the user.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60410:1973, Sampling plans and procedures for inspection by attributes

IEC 60873-1, Electrical and pneumatic analogue chart recorders for use in industrial-process control systems – Part 1: Methods for performance evaluation¹

IEC 61010-1:2001, Safety requirements for electrical equipment for measurement, control, and laboratory use – Part 1: General requirements

IEC 61298 (all parts), Process measurement and control devices – General methods and procedures for evaluating performance

¹ To be published.

3 Terms and definitions

For the purposes of this document, the terms and definitions of IEC 60873-1, together with the following, apply.

3.1

acceptance test

test which intends to prove to the user that the device complies with certain conditions of its requirements as they appear in the contract

4 Sampling for test

If, by agreement between user and manufacturer, tests are to be performed on a sample lot, it is recommended that a sampling method such as that presented in IEC 60410 be selected.

When sampling is used, recorders to be tested may be chosen by the user's inspector.

5 Performance test

Environmental conditions at the location of testing shall be recorded (see 5.1 of IEC 60873-1).

Adjustments: For zero, span and damping, the routine tests shall be carried out with the final manufacturing adjustments (for example, as an acceptance test) or with the adjustments determined by the user (for example, after repair).

The following tests shall be performed unless another series of tests is agreed between user and manufacturer.

NOTE Ink and paper should be in accordance with the manufacturer's specifications. A chart speed of approximately 20 mm/h should preferably be used.

5.1 Measured error and hysteresis (see Clause 6 of IEC 60873-1)

Prior to recording observations, the device under test shall be exercised by three full-range traverses in each direction. The input-output characteristic under reference conditions shall be measured in one measurement cycle traversing full range in each direction. For this, at least five points of measurements should be distributed over the range, for example, in steps of 25 % from 0 % to 100 % and then from 100 % to 0 %. Tapping or vibrating the instrument under test is not allowed, unless otherwise stated.

Adjust the input to bring the output to the required value. Measure the input at this level and determine the difference between this input and the specified input to give this output value. As the result, report the difference as "measured error including hysteresis" expressed in per cent of input span.

NOTE For this test, measured error is defined as the greatest positive or negative error in the measuring cycle. Hysteresis (including deadband) is defined as the greatest difference between upscale and downscale readings which are determined at each value of output.

5.2 Effects of influence quantities

5.2.1 Power supply variations (see 12.1 of IEC 61298-3)

Adjust the input signal to bring the output to approximately 95 % of span. Measure and report the change of input that is necessary to bring the output level to its original value in % of span at the following variations in power supply or at the manufacturer's stated limits, if smaller:

- voltage variation = +10 %, -15 % of nominal a.c. or +20 %, -15 % of nominal d.c. voltage;
- supply pressure variation = +10 % -15 % of nominal supply pressure (see 12.8 of IEC 61298-3)

5.2.2 Over-range (see Clause 10 of IEC 61298-3)

With the input adjusted to bring the output first to approximately 5 % and then to approximately 95 % span, note the input levels.

The input shall then be increased gradually to the maximum overrange specified by the manufacturer. After the over-range has been applied for 1 min, the input shall be reduced to the nominal lower range value. After a further 5 min have elapsed, using the same output values as before, determine the changes required in input values to bring the output back to the originally used values.

The changes in input determined after over-ranging shall be reported, expressed as per cent input span.

NOTE If over-ranging produces significant thermal effects, the duration of application should be increased accordingly.

5.3 Recording quality

The instrument shall be connected as for normal operation and an alternating input applied with a peak-to-peak amplitude equal to half the span and centred at the mean of the upper and lower range input values. The frequency selected shall be such that all recorded traces can be clearly distinguished (not more than 1 cycle per millimeter chart travel).

After an appropriate number of traverses it shall be noted

- a) whether all traces are without interruption of the ink flow;
- b) whether the widths of the recorded lines change during the test;
- c) for multi-channel recorders, whether the ink colours change over a longer distance than 5 mm after crossing different colour traces.

5.4 Paper speed

With the chart-drive operating as normal, check by observing over a suitable period of time that the paper speed is within specification.

5.5 Step response

With the chart being driven at its fastest selectable speed, apply a suitably large step change of input signal and check that the step response of the pen mechanism is within specification.

6 Safety

The instrument shall be checked against the requirements of IEC 61010-1.

The IEC would like to offer you the best quality standards possible. To make sure that we continue to meet your needs, your feedback is essential. Would you please take a minute to answer the questions overleaf and fax them to us at +41 22 919 03 00 or mail them to the address below. Thank you!

Customer Service Centre (CSC)

International Electrotechnical Commission

3, rue de Varembé 1211 Genève 20 Switzerland

or

Fax to: IEC/CSC at +41 22 919 03 00

Thank you for your contribution to the standards-making process.

A Prioritaire

Nicht frankieren Ne pas affranchir



Non affrancare No stamp required

RÉPONSE PAYÉE SUISSE

Customer Service Centre (CSC)
International Electrotechnical Commission
3, rue de Varembé
1211 GENEVA 20
Switzerland



Q1	Please report on ONE STANDARD and ONE STANDARD ONLY . Enter the exact number of the standard: (e.g. 60601-1-1)		Q6	If you ticked NOT AT ALL in Question 5 the reason is: (tick all that apply)	
	, 3	,		standard is out of date	
				standard is incomplete	
				standard is too academic	
Q2	Please tell us in what capacity(ies) you bought the standard (tick all that apply). I am the/a:			standard is too superficial	
				title is misleading	
				I made the wrong choice	
	purchasing agent			other	
	librarian				
	researcher				
	design engineer		Q7	Diagon access the atomicand in the	
	safety engineer			Please assess the standard in the following categories, using the numbers:	
	testing engineer				
	marketing specialist			(1) unacceptable,	
	other	_		(2) below average,	
				(3) average,	
				(4) above average,(5) exceptional,	
Q3	I work for/in/as a:			(6) not applicable	
	(tick all that apply)			(o) not applicable	
	manufacturing			timeliness	
	consultant			quality of writing	
		_		technical contents	
	government			logic of arrangement of contents	
	test/certification facility			tables, charts, graphs, figuresother	
	public utility				
	education				
	military				
	other		Q8	I read/use the: (tick one)	
~ 4	T1 12 - 44 - 4 - 4 - 1 - 20 1 - 4 - 4 - 4 - 4 - 4			Franch tout only	
Q4	This standard will be used for: (tick all that apply)			French text only	
	(non an mai apply)			English text only both English and French texts	
	general reference			both English and French texts	_
	product research				
	product design/development				
	specifications		Q9	Please share any comment on any aspect of the IEC that you would like us to know:	
	tenders				
	quality assessment				
	certification				
	technical documentation				
	thesis				
	manufacturing \Box				
	other				
05	This standard mosts my needs:				
Q5	This standard meets my needs: (tick one)				
	,				
	not at all				
	nearly				
	fairly well				
	exactly				



ISBN 2-8318-7356-8



ICS 25.040.40