

INTERNATIONAL STANDARD

IEC
60939-2-1

First edition
2004-11

**Complete filter units for radio
interference suppression –**

**Part 2-1:
Blank detail specification –
Passive filter units for electromagnetic
interference suppression –
Filters for which safety tests are required
(assessment level D/DZ)**



Reference number
IEC 60939-2-1:2004(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC
60939-2-1

First edition
2004-11

Complete filter units for radio interference suppression –

Part 2-1: Blank detail specification – Passive filter units for electromagnetic interference suppression – Filters for which safety tests are required (assessment level D/DZ)

© IEC 2004 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

P

For price, see current catalogue

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMPLETE FILTER UNITS FOR RADIO INTERFERENCE SUPPRESSION –

Part 2-1: Blank detail specification – Passive filter units for electromagnetic interference suppression – Filters for which safety tests are required (assessment level D/DZ)

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60939-2-1 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
40/1466/FDIS	40/1487/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 60939 consists of the following parts under the general title *Complete filter units for radio interference suppression*:

Part 1: Generic specification

Part 2: Sectional specification

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

INTRODUCTION

Blank detail specification

A blank detail specification is a supplementary document to the sectional specification and contains requirements for style and layout and minimum content of detail specifications. In the preparation of detail specifications, the content of 1.4 of the sectional specification shall be taken into account.

The use of IEC 60939-2-2 may be more appropriate for components where approval and requalification tests contribute considerably to the cost of the product, whereas the employment of this specification may be necessary for components manufactured in mass production. This specification offers the assessment levels D and DZ (Zero defect).

Identification of the detail specification and of the component

The first page of the detail specification should have the layout recommended on the next page of this blank detail specification. The numbers between square brackets correspond to the following information which shall be inserted at the position indicated:

- [1] The name of the National Standards Organization under whose authority the detail specification is published and, if applicable, the organization from which the detail specification is available.
- [2] The IECQ symbol and the number allotted to the detail specification by the IECQ General Secretariat.
- [3] The number and issue number of the IECQ generic or sectional specification as relevant; also national reference if different.
- [4] If different from the IECQ number, the national number of the detail specification, date of issue and any further information required by the national system, together with any amendment numbers.
- [5] A brief description of the component or range of components.
- [6] Information on typical construction (when applicable).

For [5] and [6] the text to be given in the detail specification should be suitable for an entry in the IECQ Register of Approvals.

- [7] Outline drawing with main dimensions which are of importance for interchangeability and/or reference to the appropriate national or international documents for outlines. Alternatively the drawing may be given in an annex to the detail specification, but [7] should always contain an illustration of the general outer appearance of the component.
- [8] The level(s) of quality assessment covered by the detail specification, as appropriate.
- [9] Reference data giving information on the most important properties of the component which allow comparison between the various component types intended for the same or similar applications.

[1]	IEC 60939-2-1-XXX [2] QC XXXXXXXXXX
ELECTRONIC COMPONENTS OF ASSESSED QUALITY IN ACCORDANCE WITH: IEC 60939-1 IEC 60939-2 [3]	[4]
Outline and dimensions: (... angle projection) [7] (Other shapes are permitted within the dimensions given, see Table 1)	PASSIVE FILTER UNITS FOR ELECTROMAGNETIC INTERFERENCE SUPPRESSION AND FOR CONNECTION TO THE SUPPLY MAINS – FILTERS FOR WHICH SAFETY TESTS ARE REQUIRED [5]
	TYPICAL CONSTRUCTION: cylindrical/rectangular non-metallic/metallic case insulated/non-insulated axial/radial/screwed terminations contains capacitors of subclasses X and Y [6]
	Assessment level D / DZ [8]
NOTE For [1] to [9], see preceding page.	
REFERENCE DATA: Rated voltages, current range, climatic category, frequency range, insertion loss range, functional circuit diagram. [9]	

Information on the availability of components qualified to this detail specification is given in the IEC QC 001005.

COMPLETE FILTER UNITS FOR RADIO INTERFERENCE SUPPRESSION –

Part 2-1: Blank detail specification – Passive filter units for electromagnetic interference suppression – Filters for which safety tests are required (assessment level D/DZ)

1 General data

1.1 Method of mounting for vibration, bump and shock tests

See 1.3.2 of IEC 60939-2.

1.2 Dimensions

Table 1 – Dimensions related to case size

Case size reference	Dimensions								
	mm								
	<i>L</i>	<i>W</i>	<i>H</i>

When there is no case size reference, Table 1 may be omitted and the dimensions shall be given in Table 2, which then becomes Table 1.

The dimensions shall be given as maximum dimensions or as nominal dimensions with a tolerance.

1.3 Ratings and characteristics

Rated voltages (see Table 2a)

Category voltage (if applicable) (see Table 2a)

Rated current (see Table 2b)

DC line resistance or d.c. voltage drop at rated current

Maximum current at upper category temperature and derating curve (if applicable)

Maximum internal and external temperatures for temperature rise test (if applicable)

Climatic category

Rated temperature

Insertion loss, no load/room temperature (see Table 2a)

Insertion loss, load/temperature (see Table 2b)

Insulation resistance

Discharge resistance (if applicable)

Category of passive flammability (if applicable)

Table 2a – Insertion loss at no load

Case size or type designation	Rated voltage	Category voltage	Minimum insertion loss dB						
			kHz	kHz	MHz	MHz	MHz	GHz	GHz

Table 2b – Insertion loss at specified current and temperature

Case size or type designation	Rated current	Test current	Test temp. °C	Minimum insertion loss dB						
				kHz	kHz	MHz	MHz	MHz	GHz	GHz

1.4 Normative references

IEC 60384-1, *Fixed capacitors for use in electronic equipment – Part 1: Generic specification*

IEC 60410, *Sampling plans and procedures for inspection by attributes*

IEC 60939-1, *Complete filter units for radio interference suppression – Part 1: Generic specification*¹

IEC 60939-2, *Complete filter units for radio interference suppression – Part 2: Sectional specification*²

1.5 Marking

The marking of the filter, if any, and the packing shall be in accordance with 1.5 of IEC 60939-2.

The details of the marking of the filter and the packing shall be given in full in the detail specification.

¹ To be published.

1.6 Ordering information

Orders for filters covered by this specification shall contain, in clear or in coded form, the following information:

- (a) type designation;
- (b) rated voltage;
- (c) number and issue reference of this detail specification.

1.7 Certified test records

Required/not required.

1.8 Additional information (not for inspection purposes)

1.9 Additional or increased severities or requirements to those specified in the generic and/or sectional specification

NOTE Additional or increased requirements should be specified only when essential.

Table 3 – Other characteristics

This table is to be used for defining characteristics which are additional to or more severe than those given in the sectional specification

2 Inspection requirements

2.1 Procedures

2.1.1 For Qualification Approval the procedures shall be in accordance with 3.4.2 of IEC 60939-2.

2.1.2 For Quality Conformance inspection the test schedule (Table 4) includes sampling, periodicity, severities and requirements. The formation of inspection lots is covered by 3.5.1 of IEC 60939-2.

**Table 4a – Test schedule for lot-by-lot tests (Group A and Group B inspection) –
Assessment level D / DZ**

Assessment level D				
Clause number and test¹⁾	Conditions of test¹⁾	IL²⁾	AQL	Performance requirements¹⁾
Group A1 4.2 Visual examination 4.2 Marking 4.2 Dimensions (gauging)	Non-destructive	S-4	2,5 %	As in 4.2 Any marking on the filter shall be legible and correct See Table 1 of this specification
Group A2 4.5 DC line resistance or voltage drop 4.6 Insertion loss 4.3 Voltage proof (Test A only) 4.4 Insulation resistance (Test A only) 4.7 Discharge resistance ⁴⁾	Non-destructive See Annex A of this specification Method: ... ⁶⁾ Method: ... ⁶⁾	II	1,0 %	See 1.3 of this specification See Table 2 of this specification No breakdown or flashover See 4.4.2 See Table 2a of this specification
Group B1 4.10 Solderability ⁴⁾ 4.10.2 Requirements	Non destructive⁵⁾ Method: ... ⁶⁾ Specify ageing if none or other than 4 h 155 °C dry heat: ... ⁶⁾ Visual examination Wetting time	S-3	2,5 %	Methods 1 and 2: good tinning Method 3: < 3 s

Assessment level DZ				
Clause number and test ¹⁾	Conditions of test ¹⁾	IL ²⁾	AN ⁶⁾	Performance requirements ¹⁾
Group A1	Non-destructive	S-3	0	
4.2 Visual examination				As in 4.2
4.2 Marking				Any marking on the filter shall be legible and correct
4.2 Dimensions (gauging)				See Table 1 of this specification
Group A2	Non-destructive	S-4	0	
4.5 DC line resistance or voltage drop				See 1.3 of this specification
4.6 Insertion loss	See Annex A of this specification			See Table 2 of this specification
4.3 Voltage proof (Test A only)	Method: ... ⁴⁾			No breakdown or flashover
4.4 Insulation resistance (Test A only)	Method: ... ⁴⁾			See 4.4.2
4.7 Discharge resistance ³⁾				See Table 2a of this specification
Group B1	Non destructive ⁵⁾	S-3	0	
4.10 Solderability ³⁾	Method: ... ⁴⁾ Specify ageing if none or other than 4 h 155 °C dry heat: ... ⁴⁾			
4.10.2 Requirements	Visual examination Wetting time			Methods 1 and 2: good tinning Method 3: < 3 s
¹⁾ Clause numbers of tests and performance requirements refer to Clause 4 of IEC 60939-2. ²⁾ Inspection Levels (IL) and Acceptance Quality Levels (AQL) are selected from IEC 60410. ³⁾ If applicable. ⁴⁾ To be required in the detail specification. ⁵⁾ Filters which have been submitted to the tests of Group B1 may be released provided they have not been submitted to ageing and are resubmitted to the tests of Group A and pass those tests. It is permitted to submit electrically defective filters or detached terminations instead of completed filters to this test provided they have been subjected to the same process treatments as a completed filter. ⁶⁾ Acceptance number.				

**Table 4b – Test schedule for periodic tests (Group C inspection) –
Assessment level D / DZ**

Clause number and test ¹⁾	Conditions of test ¹⁾	p	n	²⁾ c		Performance requirements ¹⁾
				D	DZ	
Group C1A	Destructive	6	2 1 1	0 0 0	0 0 0	
4.2 Dimensions (detail)						See Table 1 of this specification
4.2.1 Creepage distances and clearances						See Table 6
4.8 Robustness of terminations	Severity: ... ⁶⁾					
4.9 Resistance to soldering heat ⁴⁾	Visual examination No pre-drying Method 1A or 1B: ... ⁶⁾					No visible damage
4.24 Solvent resistance of marking ³⁾						Marking legible
4.9.2 Intermediate measurements	Visual examination DC line resistance or voltage drop					No visible damage See 1.3 of this specification
Group C1B	Destructive	6	4 1 1	0 0 0	0 0 0	
4.25 Component solvent resistance ³⁾						
4.11 Rapid change of temperature	T_A = Lower category temperature T_B = Upper category temperature Five cycles Duration t = ... ⁶⁾					
4.11.1 Intermediate inspection	Visual examination					No visible damage
4.12 Vibration	Mounting as 1.1 of this specification Severity: ... ⁶⁾					
4.12.2 Intermediate inspection	Visual examination					No visible damage
4.13 Bump or 4.14 Shock	Mounting as 1.1. of this specification Severity: ... ⁶⁾					
4.13.2 Intermediate inspection or 4.14.2	Visual examination DC line resistance or voltage drop					No visible damage See 1.3 of this specification

Table 4b (continued)

Clause number and test ¹⁾	Condition of test ¹⁾	2)				Performance requirements ¹⁾
		p	n	c		
				D	DZ	
Group C1	Destructive	6	6 2 2	1 1 0	0 0 0	No evidence of leakage
4.15 Container sealing ³⁾	Test Qc or Test Qd as required					
4.16 Climatic sequence						
4.16.1 Initial measurements	Measurements made in 4.9.2, 4.13.2 or 4.14.2 as appropriate					
4.16.2 Dry heat	No measurements					
4.16.3 Damp heat, cyclic, first cycle						
4.16.4 Cold	No measurements					
4.16.5 Low air pressure ³⁾	Severity: ... ⁶⁾ if non-standard: see 4.16.5 for applied voltage	No permanent breakdown or flashover or harmful deformation of the case				
4.16.6 Damp heat, cyclic, remaining cycles	Recovery 18 h to 26 h					
4.16.7 Final inspection	Visual examination					
	Voltage proof at 66 % of value in Table 7					
	Insulation resistance	> 50 % of limit given in Table 8				
	DC line resistance or voltage drop	See 1.3 of this specification				
	Insertion loss (no load)	See 4.6 and Table 2a of this specification				

Table 4b (continued)

Clause number and test ¹⁾	Conditions of test ¹⁾	2)				Performance requirements ¹⁾
		p	n	c		
				D	DZ	
Group C2	Destructive	12	4	0	0	
			2	0	0	
			1	0	0	
4.17 Damp heat, steady state						
4.17.1 Test conditions	Specify if applied voltage is required ⁶⁾ If so for half the sample U_R applied, for other half no voltage applied Recovery: 18 h to 26 h					
4.17.2 Final inspection	Visual examination Voltage proof at 66 % of value in Table 7 Insulation resistance or voltage drop DC line resistance or voltage drop Insertion loss (no load)					No visible damage Any marking shall be legible No permanent breakdown or flashover ≥ 3,5 MΩ See 1.3 of this specification See 4.6 and Table 2a of this specification
Group C3A	Destructive	3	2	0	0	
			2	0	0	
			2	0	0	
			1	0	0	
4.18 Temperature rise ⁷⁾						
4.18.2 Final measurements	Internal temperature Temperature of case					See 4.18.2 Requirement: ... ⁶⁾
4.20.1 Endurance current ⁸⁾ ⁹⁾	Duration: 1 000 h Current and temperature: see 4.20.1					See 4.20.5
Group C3B	Destructive	3	2	0	0	
			2	0	0	
			2	0	0	
			1	0	0	
4.19 Impulse voltage	3 impulses, full wave Crest voltage: see Tables 1a and 1b					
4.20.2 Endurance voltage, line terminations to case ⁴⁾	Duration: 1 000 h Voltage and temperature: see 4.20.2					See 4.20.5

Table 4b (continued)

Clause number and test ¹⁾	Conditions of test ¹⁾	2)				Performance requirements ¹⁾
		p	n	c		
				D	DZ	
Group C3C	Destructive	3	4	0	0	See 4.19.3
4.19	Impulse voltage		2	0	0	
4.20.3	Endurance voltage, between line terminations ⁹⁾		1	0	0	
4.20.4	Endurance combined voltage current ^{3) 9)}					
4.20.3	Endurance voltage, between line terminations ⁹⁾					See 4.20.5
4.20.4	Endurance combined voltage current ^{3) 9)}					See 4.20.5
<hr/>						
Group C3						
4.20.5	Final inspection and measurements for all endurance tests					No visible damage Any marking shall be legible No permanent breakdown or flashover > 50 % of limit in Table 8 See 1.3 of this specification See 4.6 and Table 2a of this specification
Group C4	Destructive	12	2	0	0	Recorded for reference Recorded for reference
4.21	Charge and discharge ⁴⁾		2	0	0	
4.21.1	Initial measurements		1	0	0	
4.21.3	Finale measurements					
4.21.1	Initial measurements					See Table 10
4.21.3	Finale measurements					See Table 10
						See Table 10

Table 4b (continued)

Clause number and test ¹⁾	Conditions of test ¹⁾	2)				Performance requirements ¹⁾
		p	n	c		
				D	DZ	
Group C5	Non-destructive	12	2	0	0	See Table 2b of this specification
4.6 Insertion loss (load/temperature) ³⁾	See Annex A of this specification		2 1	0 0 0		
Group C6	Destructive	12	2	0	0	Requirements: ... ⁶⁾
4.23 Current overload ³⁾			2 1	0 0 0		
Group C 7	Destructive	12	⁵⁾	0	0	See 4.22 requirements: ... ⁶⁾ according to specified category (see 1.3 of this specification)
4.22 Passive flammability ⁴⁾						
Group C 9	Destructive	12	¹⁰⁾	0	0	See 4.26 requirements: ... ⁶⁾
4.26 Active flammability ⁴⁾						

¹⁾ Clause numbers of tests and performance requirements refer to Clause 4 of IEC 60939-2.

²⁾ *p* = periodicity (in months); *n* = sample size, *c* = acceptance criteria. The three numbers in the table columns „*n*“ and „*c*“ indicate in descending order the sample sizes and acceptance criteria applicable for specimens within the following current limits:

< 16 A

≥ 16 A ... ≤ 80 A

> 80 A

„Current“ in this context is the sum of the rated current(s) carried by the leads for the individual phases, N excluded.

Where filters manufactured in the period fall within more than one of the current classifications listed above, the number of specimens selected shall be that for the classification in which the majority of the filters manufactured in the period fall. The specimens selected shall be representative of the whole current range manufactured in the period.

The numbers required for the passive flammability test (Group C7), are calculated on a different basis as described in IEC 60384-1.

³⁾ If required in the detail specification.

⁴⁾ If applicable.

⁵⁾ Number of specimens: see 4.22 of IEC 60939-2.

⁶⁾ To be required in the detail specification.

⁷⁾ For filters with rated current > 0,5 A.

⁸⁾ For filters with a rated current ≤ 0,5 A.

⁹⁾ See 4.20.4 of IEC 60939-1 for the option of combining the test of Groups C3A and C3C.

¹⁰⁾ Number of specimens: see 4.26 of IEC 60939-2.

Except for Group C7, when in a given group zero non-conforming items are required and one non-conforming item is obtained, all the tests of the group shall be repeated on a fresh sample and then no further non-conforming items are permitted.

The tests of Groups 3B and 3C and Group 4 may be omitted if the capacitors in the filter across which the test voltages will appear are separately encapsulated and have been qualified to a detail specification under IEC 60384-14.

Annex A (normative)

Measurement method for insertion loss

Details of method for no-load conditions and for load/temperature conditions (if applicable) shall be specified in the detail specification.



Standards Survey

The IEC would like to offer you the best quality standards possible. To make sure that we continue to meet your needs, your feedback is essential. Would you please take a minute to answer the questions overleaf and fax them to us at +41 22 919 03 00 or mail them to the address below. Thank you!

Customer Service Centre (CSC)

International Electrotechnical Commission

3, rue de Varembé
1211 Genève 20
Switzerland

or

Fax to: **IEC/CSC** at +41 22 919 03 00

Thank you for your contribution to the standards-making process.

A Prioritaire

Nicht frankieren
Ne pas affranchir



Non affrancare
No stamp required

RÉPONSE PAYÉE

SUISSE

Customer Service Centre (CSC)
International Electrotechnical Commission
3, rue de Varembé
1211 GENEVA 20
Switzerland



Q1 Please report on **ONE STANDARD** and **ONE STANDARD ONLY**. Enter the exact number of the standard: (e.g. 60601-1-1)

.....

Q2 Please tell us in what capacity(ies) you bought the standard (tick all that apply). I am the/a:

- purchasing agent ☐
 librarian ☐
 researcher ☐
 design engineer ☐
 safety engineer ☐
 testing engineer ☐
 marketing specialist ☐
 other.....

Q3 I work for/in/as a:
(tick all that apply)

- manufacturing ☐
 consultant ☐
 government ☐
 test/certification facility ☐
 public utility ☐
 education ☐
 military ☐
 other.....

Q4 This standard will be used for:
(tick all that apply)

- general reference ☐
 product research ☐
 product design/development ☐
 specifications ☐
 tenders ☐
 quality assessment ☐
 certification ☐
 technical documentation ☐
 thesis ☐
 manufacturing ☐
 other.....

Q5 This standard meets my needs:
(tick one)

- not at all ☐
 nearly ☐
 fairly well ☐
 exactly ☐

Q6 If you ticked NOT AT ALL in Question 5 the reason is: (tick all that apply)

- standard is out of date ☐
 standard is incomplete ☐
 standard is too academic ☐
 standard is too superficial ☐
 title is misleading ☐
 I made the wrong choice ☐
 other

Q7 Please assess the standard in the following categories, using the numbers:

- (1) unacceptable,
 (2) below average,
 (3) average,
 (4) above average,
 (5) exceptional,
 (6) not applicable

- timeliness.....
 quality of writing.....
 technical contents.....
 logic of arrangement of contents
 tables, charts, graphs, figures.....
 other

Q8 I read/use the: (tick one)

- French text only ☐
 English text only ☐
 both English and French texts ☐

Q9 Please share any comment on any aspect of the IEC that you would like us to know:

.....



ISBN 2-8318-7699-0



ICS 31.190; 33.160
