

INTERNATIONAL STANDARD

IEC 61029-2-1

1993

AMENDMENT 1
1999-02

Amendment 1

Safety of transportable motor-operated electric tools –

Part 2-1: Particular requirements for circular saws

Amendement 1

Sécurité des machines-outils électriques semi-fixes –

Partie 2.1: Règles particulières pour les scies circulaires

© IEC 1999 — Copyright - all rights reserved

International Electrotechnical Commission 3, rue de Varembé Geneva, Switzerland
Telefax: +41 22 919 0300 e-mail: inmail@iec.ch IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

C

For price, see current catalogue

FOREWORD

This amendment has been prepared by subcommittee 61F: Safety of hand-held motor-operated electric tools, of IEC technical committee 61: Safety of household and similar electrical appliances.

The text of this amendment is based on the following documents:

FDIS	Report on voting
61F/257/FDIS	61F/263/RVD

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

Page 7

2 Definitions

Subclause 2.21

Replace the third dashed item with the following:

- $0,13 \leq \sqrt{n_0}$ for other saws designed for cutting depths from 20 mm to 55 mm and for circular saw components of combined machines;

Add the following new fourth dashed item:

- $0,10 \leq \sqrt{n_0}$ for other saws designed for cutting depths not exceeding 20 mm.

Page 13

18 Stability and mechanical hazards

Subclause 18.1.104.1

Replace, on page 17, the table of figure 102 by the following:

Maximum diameters of saw blade Dimensions of the saw table	≤60 **	>60 and ≤100 *	>100 and ≤200	>200
L ≥	175	300	500	$\frac{5D}{2}$
l ≥	150	200	335	400
a ≥	87,5	150	250	$\frac{5D}{4}$
b ≥	75	75	110	$\frac{5D}{9}$
* Maximum depth of cut: 15 mm. ** Maximum depth of cut: 10 mm.				

Figure 102 – Dimensions of the saw table in millimetres

ISBN 2-8318-4690-0



ICS 25.140.20
