

INTERNATIONAL STANDARD

**Coaxial communication cables –
Part 10-1: Blank detail specification for semi-rigid cables with
polytetrafluoroethylene (PTFE) dielectric**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



IEC 61196-10-1

Edition 1.0 2014-09

INTERNATIONAL STANDARD

**Coaxial communication cables –
Part 10-1: Blank detail specification for semi-rigid cables with
polytetrafluoroethylene (PTFE) dielectric**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

J

ICS 33.120.10

ISBN 978-2-8322-1863-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
1 Scope	5
2 Normative references	5
3 Guidance for the preparation of detail specifications	5
4 Blank detail specification	6
Annex A (normative) Maximum attenuation	9

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COAXIAL COMMUNICATION CABLES –

**Part 10-1: Blank detail specification for semi-rigid cables
with polytetrafluoroethylene (PTFE) dielectric**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61196-10-1 has been prepared by subcommittee 46A: Coaxial cables, of IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

The text of this standard is based on the following documents:

FDIS	Report on voting
46A/1214/FDIS	46A/1233/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This publication is to be used in conjunction with IEC 61196-1:2005 and IEC 61196-10:2014.

A list of all parts in the IEC 61196 series, published under the general title *Coaxial communication cables*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

COAXIAL COMMUNICATION CABLES –

Part 10-1: Blank detail specification for semi-rigid cables with polytetrafluoroethylene (PTFE) dielectric

1 Scope

This part of IEC 61196 applies to coaxial communication cables described in IEC 61196-10. It specifies the requirements for semi-rigid radio frequency and coaxial cables with solid dielectric and semi-airspace dielectric. These cables are intended for use in microwave and wireless equipment or other signal transmission equipment or units at frequencies above 500 MHz.

This part of IEC 61196 is to be read in conjunction with IEC 61196-1 and IEC 61196-10. The blank detail specification determines the layout and style for detail. Detail specifications, based on the blank detail specification, may be prepared by a national organization, a manufacturer or a user.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61196-1:2005, *Coaxial communication cables – Part 1: Generic specification – General, definitions and requirements*

IEC 61196-10:2014, *Coaxial communication cables – Part 10: Sectional specification for semi-rigid cables with polytetrafluoroethylene (PTFE) dielectric*

NOTE Documents which are needed to achieve the tests according to Clause 4, item [9] or item [10], respectively, are listed in IEC 61196-10.

3 Guidance for the preparation of detail specifications

The detail specification shall be written in accordance with the layout of the blank detail specification, which forms part of this standard.

NOTE 1 When a characteristic does not apply, then NA (for not applicable) is entered in the appropriate space.

NOTE 2 When a characteristic applies but a specific value is not considered necessary, then NS (for not specified) is entered.

The numbers shown in brackets in this and the following pages correspond to the following items of required information, which should be entered in the space provided.

- [1] Name and address of the organization that has prepared the document
- [2] IEC document number and date of issue
- [3] Address of the organization from which the document is available
- [4] Related documents
- [5] Any other references to the cable, national reference, trade name, etc.
- [6] Complete description of the cable

- [7] Cable construction
- [8] Engineering information
- [9] Parameter to be verified
- [10] Reference to the relevant subclause of the sectional specification
- [11] Minimum requirements, the values entered shall meet as a minimum the requirements of sectional specification IEC 61196-10
- [12] Remarks

4 Blank detail specification

Title			
[1] Prepared by:	[2] Document No.: Issue: Date:		
[3] Available from:	[4] Generic specification	IEC 61196-1	
	Sectional specification	IEC 61196-10	
[5] Additional references:			
[6] Cable description: a) Cable variant b) Material of inner conductor c) Material of dielectric d) Outer conductor e) Material of sheath (if any)			
[7] Cable construction: a) Inner conductor Material Diameter (mm) nominal Tolerance (mm): ± ... b) Dielectric Material Diameter (mm) nominal Tolerance (mm): ± ... c) Outer conductor Material Diameter (mm) nominal Tolerance (mm): ± ... d) Sheath (if any) Material Minimum thickness (mm) Diameter (mm) Tolerance (mm): ± ...			

[8] Engineering information (reference only): <ul style="list-style-type: none"> a) Operating temperature range b) Installation temperature range c) Storage temperature range d) Maximum operating frequency e) Nominal characteristic impedance f) Maximum continue working voltage g) Minimum bending radius (static state) h) Minimum bending radius (dynamic state) i) Nominal weight j) Power rating 			
[9] Parameter	[10] Subclause of IEC 61196-10:2014	[11] Value	[12] Remarks
Electrical characteristics	7.2		
Continuity	7.2.1	pass	
Conductor direct current resistance	7.2.2	$\leq \dots \Omega/\text{km}$	
Withstand voltage of dielectric	7.2.3	$\geq \dots \text{ kV r.m.s.}$	40 Hz to 60 Hz
Withstand voltage of sheath	7.2.4	$\geq \dots \text{ kV r.m.s.}$	40 Hz to 60 Hz
Insulation resistance	7.2.5	$\geq \dots \text{ M}\Omega \cdot \text{km}$	$\geq 5\,000 \text{ M}\Omega \cdot \text{km}$ according to IEC 61196-10
Capacitance	7.2.6	Frequency: $\leq \text{ pF/m}$	
Mean characteristic impedance	7.2.7	$(\dots \pm \dots) \Omega$	200 MHz
Regularity of impedance	7.2.8	Test procedure: Regularity $\geq 40 \text{ dB}$ resp. $\leq 1 \% ^a$	
Relative propagation velocity (velocity ratio)	7.2.9	Frequency: $(\dots \pm \dots) \%$	
Return loss	7.2.10	at $\dots \text{ MHz} \geq \dots \text{ dB}$	If necessary, refer to a table or graph at the end of the detail specification
Attenuation	7.2.11	at $\dots \text{ MHz} \leq \dots \text{ dB/100 m}$	If necessary, refer to a table or graph at the end of the detail specification
Attenuation stability	7.2.12		
Intermodulation (IM3)	7.2.13	$\geq \dots \text{ dBm}$	$f_1 = \dots \text{ MHz} ^a$ $f_2 = \dots \text{ MHz} ^a$ Input power: $W \dots$ Only applicable to 50Ω cable variants
Environmental characteristics	7.3		
Dimensional stability	7.3.1	ns	See IEC 61196-10
Heat behaviour	7.3.2	ns	See IEC 61196-10

Ageing	7.3.3	NS	See IEC 61196-10
Solderability	7.3.4	NS	See IEC 61196-10
Resistance to soldering	7.3.5	NS	See IEC 61196-10
Mechanical characteristics	7.4		
Visual examination	7.4.1	NS	See IEC 61196-10
Dimensional examination	7.4.2		
Ovality of dielectric	7.4.3	≤ ... %	≤ 7 % according to IEC 61196-10
Eccentricity of dielectric	7.4.4	≤ ... %	≤ 10 % according to IEC 61196-10
Ovality of sheath	7.4.5	≤ ... %	≤ 7 % according to IEC 61196-10
Adhesion testing	7.4.6	≥ ... N	
Bendability (single bend) ^b	7.4.7	1 cycle No cracks or longitudinal splits in outer conductor Transmission characteristics shall remain within specified tolerances	
Thermal cycling	7.4.8	Low temperature ... °C min. High temperature ... °C max. Rate of temperature change ... s Number of cycles Duration of cycle Details of sample placement	
Quality assessment	Annex A	NS	See IEC 61196-10
NS: not specified, i.e. the appropriate requirement in the sectional specification shall apply.			
^a Mark NA, if not applicable			
^b Frequencies are not always fixed frequencies and can be a swept over a range.			

Annex A
(normative)

Maximum attenuation

Frequency specified MHz	Maximum attenuation: dB/100 m at 20 °C
–	–
–	–
–	–
200	–
–	–
–	–
–	–
800	–
–	–
1 000	–
–	–
–	–

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

3, rue de Varembé
PO Box 131
CH-1211 Geneva 20
Switzerland

Tel: + 41 22 919 02 11
Fax: + 41 22 919 03 00
info@iec.ch
www.iec.ch