

INTERNATIONAL STANDARD

IEC
61332

Second edition
2005-09

Soft ferrite material classification



Reference number
IEC 61332:2005(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 61332

Second edition
2005-09

Soft ferrite material classification

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

G

For price, see current catalogue

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SOFT FERRITE MATERIAL CLASSIFICATION

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61332 has been prepared IEC technical committee 51: Magnetic components and ferrite materials.

This second edition cancels and replaces the first edition published in 1995. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) the scope has been reviewed;
- b) the column of temperature coefficient of SP class ferrite material has been omitted;
- c) the measuring frequency for relative loss factor of SP class has been specified;
- d) the parameters of SP class has been coordinated with IEC 60401-3.

The text of this standard is based on the following documents:

FDIS	Report on voting
51/832/FDIS	51/838/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

SOFT FERRITE MATERIAL CLASSIFICATION

1 Scope

This International Standard specifies classification rules for soft ferrite materials used in inductive components (inductors and transformers) fulfilling the requirements of the electronic industries.

This standard addresses the following purposes for ferrite suppliers and users:

- cross-reference between materials from multiple suppliers;
- assistance to customers in understanding the published technical data in catalogues when comparing multiple suppliers;
- guidance to customers in selecting the most applicable material for each application;
- setting of nomenclature for IEC standards relating to ferrite;
- establishing uniform benchmarks for suppliers for performance in new development of materials.

The numerical values given in this standard are typical values of parameters (properties) of the related materials. Direct translation from the material specification into the core specification is not always easy or possible.

Every detailed material and core specification should be agreed upon between the user and the manufacturer.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-221:1990, *International Electrotechnical Vocabulary (IEV) – Chapter 221: Magnetic materials and components*

IEC 60401-3: 2003, *Terms and nomenclature for cores made of magnetically soft ferrites – Part 3: Guidelines on the format of data appearing in manufacturers' catalogues of transformer and inductor cores*

3 Terms and definitions

For the purposes of this document, the terms and definitions in Tables 1, 2 and 3 are defined in IEC 60050-221.

4 Classification

4.1 Material classification

Soft ferrite materials may be classified by the following basic parameters:

- initial permeability and the relevant operation frequency and/or applicable maximum frequency;
- initial permeability as a function of the temperature;
- applicable maximum flux density and/or amplitude permeability;
- power loss at a given frequency, temperature and flux density;
- normalized impedance at a given frequency.

4.2 Main classes

Soft ferrite materials may be divided into three main classes identified by two letters as follows:

- class IS materials are for use at a.c. low flux density as impedances in interference suppression (EMI) applications;
- class SP materials are for use at low flux density in signal processing applications;
- class PW materials are for use at high flux density (power application).

4.3 Subclasses

Each main class is divided into subclasses identified by two letters and a serial number.

Ferrite manufacturers' catalogues may indicate more than one class into which a material grade can fall, where desired.

5 Soft ferrite material classes

5.1 Materials used as impedances in interference suppression applications (IS class)

These materials are mainly used in the shape of rods, tubes, beads, wide band chokes, bobbin cores and rings. The relevant subclasses are given in Table 1.

Table 1 – IS class ferrite materials

Subclasses	Frequency ^{a)} MHz	Normalized impedance ^{b)} Z_N Ω/mm	Initial permeability ^{c)} μ_i	Curie temperature T_C °C
IS1	300	≥ 50	< 100	> 300
IS2a IS2b	300	≥ 50 ≥ 40	100 - 2 000	200 - 300
IS3a IS3b	100	≥ 40 ≥ 30	100 - 2 000	100 - 250
IS4a IS4b	30	≥ 30 ≥ 20	100 - 2 000	100 - 250
IS5a IS5b	10	≥ 30 ≥ 20	2 000 - 6 000	100 - 250
IS6a IS6b	3	≥ 30 ≥ 20	2 000 - 6 000	100 - 150
IS7a IS7b	1	≥ 20 ≥ 10	2 000 - 6 000	100 - 150
IS8a IS8b	1	≥ 20 ≥ 10	6 000 - 10 000	100 - 150
IS9a IS9b	0,5	≥ 10 ≥ 5	10 000 - 15 000	> 100
^{a)} The frequency is the measuring frequency of the normalized impedance. ^{b)} Measured on a bead $\phi 5 \text{ mm} \times \phi 2 \text{ mm} \times 10 \text{ mm}$ and at temperature of 25°C. ^{c)} μ_i is measured at $\leq 10 \text{ kHz}$, $\leq 0,5 \text{ mT}$. μ_i is for reference only, indicating typical values seen. μ_i is not a fundamental parameter for class IS materials.				

5.2 Materials used mainly in low flux density applications ($B \leq 5$ mT) (SP class)

These materials are mainly used in the shape of ring-cores, pot-cores, EP-cores, RM-cores and E-cores. The relevant subclasses are given in Table 2.

Table 2 – SP class ferrite materials

Subclasses	Initial permeability ^{a)} μ_i	Relative loss factor ^{a)} $\tan\delta/\mu_i$ $\times 10^{-6}$	Frequency ^{b)} MHz	Curie temperature T_C °C
SP1	< 100	50 - 150	10	> 300
SP2	100 - 400	20 - 30	1	> 250
SP3	400 - 800	15 - 50	0,1	> 150
SP4	800 - 1 200	1 - 10	0,1	> 120
SP5	1 200 - 2 000	1 - 10	0,1	> 120
SP6	1 200 - 2 500	2 - 7	0,1	> 150
SP7	1 500 - 2 500	3 - 5	0,1	> 150
SP8	2 500 - 3 500	2 - 10	0,1	> 130
SP9	3 500 - 6 000	≤ 15	0,1	> 120
SP10a	6 000 - 8 000	≤ 3	0,01	> 120
SP10b	6 000 - 8 000	≤ 10	0,01	> 120
SP11a	8 000 - 12 000	≤ 3	0,01	> 100
SP11b	8 000 - 12 000	≤ 10	0,01	> 100
SP12a	12 000 - 16 000	≤ 6	0,01	> 100
SP12b	12 000 - 16 000	≤ 20	0,01	> 100
SP13	16 000 - 20 000	≤ 20	0,01	> 100
^{a)} μ_i and $\tan\delta/\mu_i$ are measured at 25°C.				
^{b)} The frequency is the measuring frequency for $\tan\delta/\mu_i$.				
NOTE Size of the test core is $\phi 10$ mm \times $\phi 6$ mm \times 4 mm.				

5.3 Materials used mainly in high flux density applications (PW class)

These materials are mainly used in the shape of RM-cores, EFD-cores, ER-cores, ETD-cores, EER-cores, E-cores, PQ-cores, ring-cores and cores for planar applications. The relevant subclasses are given in Table 3.

Table 3 – PW class ferrite materials

Subclasses	$f_{\max}^{a)}$ kHz	$f^{c)d)}$ kHz	$B^{b)}$ mT	$\mu_a^{c)}$	Performance factor ($B \times f$) mT \times kHz	Power loss (volume) density ^{d) e) f)} kW/m ³	$\mu_i^{g)}$
PW1a PW1b PW1c	100	15	300	2 500	4 500 (300 \times 15)	≤ 100 ≤ 200 ≤ 300	3 500 - 2 000
PW2a PW2b PW2c	200	25	200	2 500	5 000 (200 \times 25)	≤ 60 ≤ 150 ≤ 300	3 500 - 2 000
PW3a PW3b PW3c	300	100	100	3 000	10 000 (100 \times 100)	≤ 60 ≤ 150 ≤ 300	3 500 - 2 000
PW4a PW4b PW4c	500	300	50	3 000	15 000 (50 \times 300)	≤ 100 ≤ 150 ≤ 300	2 000 - 1 400
PW5a PW5b PW5c	1 000	500	50	2 000	25 000 (50 \times 500)	≤ 100 ≤ 150 ≤ 300	2 000 - 1 400
PW6a PW6b PW6c	2 000	1 000	25	1 000	25 000 (25 \times 1 000)	≤ 100 ≤ 150 ≤ 300	1 400 - 800
PW7a PW7b PW7c	3 000	2 000	15	1 000	30 000 (15 \times 2 000)	≤ 100 ≤ 150 ≤ 300	1 400 - 800
PW8a PW8b PW8c	5 000	3 000	10	400	30 000 (10 \times 3 000)	≤ 100 ≤ 200 ≤ 300	800 - 400
PW9a PW9b	10 000	5 000	10	40	50 000 (10 \times 5 000)	≤ 200 ≤ 300	400 - 40
<p>a) f_{\max} is the guide of the applicable maximum frequency relevant to a given material subclass.</p> <p>b) B is the applicable a.c. peak flux density relevant to a given material subclass. These levels of B are normally resulting in power losses in the ranges of ≤ 300 kW/m³. In these ranges a wide variety of sizes in the common shapes can be used in open-air conditions without forced cooling. The use of higher flux densities in these subclasses will result in higher power losses, which may often require additional cooling, or will be limited in open air with no forced cooling to the use of only smaller sizes from the common core shapes.</p> <p>c) μ_a is the amplitude permeability at 100 °C, B and f in Table 3. μ_a is for reference only.</p> <p>d) Power loss should be measured at 100 °C, B and f in Table 3. These combinations of B and f are different from the preferred combinations according to IEC 60401-3, Table 2, where power losses higher than 300 kW/m³ are assumed as well (see also b)).</p> <p>e) Power loss only refers to B as an a.c. peak flux density and does not apply for situations where there is a combination of a.c. and d.c. flux density applicable in which power losses may be different. In these cases, it is usual that a critical parameter used for core selection is either</p> <ol style="list-style-type: none"> 1) saturation flux density at the intended maximum operating temperature (typically 100 °C to 120 °C); or 2) maximum decrease in inductance with a specified d.c. flux density, a.c. flux density, temperature, and air gap in the core structure (the gap is defined by dimension or by inductance factor). <p>f) Power loss only refers to the temperature of 100 °C, although there are some power ferrites available which are optimised for lower or higher operating temperatures than approximately 100 °C.</p> <p>g) μ_i is measured at ≤ 10 kHz, $\leq 0,5$ mT. μ_i is for reference only, indicating typical values seen. μ_i is not a fundamental parameter for class PW materials.</p>							
NOTE Size of the test core is $\phi 25$ mm \times $\phi 15$ mm \times 10 mm.							



Standards Survey

The IEC would like to offer you the best quality standards possible. To make sure that we continue to meet your needs, your feedback is essential. Would you please take a minute to answer the questions overleaf and fax them to us at +41 22 919 03 00 or mail them to the address below. Thank you!

Customer Service Centre (CSC)

International Electrotechnical Commission

3, rue de Varembé
1211 Genève 20
Switzerland

or

Fax to: **IEC/CSC** at +41 22 919 03 00

Thank you for your contribution to the standards-making process.

A Prioritaire

Nicht frankieren
Ne pas affranchir



Non affrancare
No stamp required

RÉPONSE PAYÉE

SUISSE

Customer Service Centre (CSC)
International Electrotechnical Commission
3, rue de Varembé
1211 GENEVA 20
Switzerland



Q1 Please report on **ONE STANDARD** and **ONE STANDARD ONLY**. Enter the exact number of the standard: (e.g. 60601-1-1)

.....

Q2 Please tell us in what capacity(ies) you bought the standard (tick all that apply). I am the/a:

- purchasing agent ☐
 librarian ☐
 researcher ☐
 design engineer ☐
 safety engineer ☐
 testing engineer ☐
 marketing specialist ☐
 other.....

Q3 I work for/in/as a:
(tick all that apply)

- manufacturing ☐
 consultant ☐
 government ☐
 test/certification facility ☐
 public utility ☐
 education ☐
 military ☐
 other.....

Q4 This standard will be used for:
(tick all that apply)

- general reference ☐
 product research ☐
 product design/development ☐
 specifications ☐
 tenders ☐
 quality assessment ☐
 certification ☐
 technical documentation ☐
 thesis ☐
 manufacturing ☐
 other.....

Q5 This standard meets my needs:
(tick one)

- not at all ☐
 nearly ☐
 fairly well ☐
 exactly ☐

Q6 If you ticked NOT AT ALL in Question 5 the reason is: (tick all that apply)

- standard is out of date ☐
 standard is incomplete ☐
 standard is too academic ☐
 standard is too superficial ☐
 title is misleading ☐
 I made the wrong choice ☐
 other

Q7 Please assess the standard in the following categories, using the numbers:

- (1) unacceptable,
 (2) below average,
 (3) average,
 (4) above average,
 (5) exceptional,
 (6) not applicable

- timeliness.....
 quality of writing.....
 technical contents.....
 logic of arrangement of contents
 tables, charts, graphs, figures.....
 other

Q8 I read/use the: (tick one)

- French text only ☐
 English text only ☐
 both English and French texts ☐

Q9 Please share any comment on any aspect of the IEC that you would like us to know:

.....



ISBN 2-8318-8218-4



9 782831 882185

ICS 29.100.10
