

# INTERNATIONAL STANDARD

**Fibre optic interconnecting devices and passive components – Performance standard –**

**Part 031-2: Non-connectorized single-mode 1×N and 2×N non-wavelength-selective branching devices for Category C – Controlled environment**



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).



IEC 61753-031-2

Edition 1.0 2014-09

# INTERNATIONAL STANDARD

**Fibre optic interconnecting devices and passive components – Performance standard –**

**Part 031-2: Non-connectorized single-mode 1×N and 2×N non-wavelength-selective branching devices for Category C – Controlled environment**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

R

ICS 33.180.20

ISBN 978-2-8322-1818-1

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references .....	5
3 Test.....	6
4 Test report.....	7
5 Performance requirements .....	7
5.1 Dimensions .....	7
5.2 Sample size .....	7
5.3 Test details and requirements .....	7
Annex A (normative) A and U requirements of $1 \times N$ and $2 \times N$ NWBDs .....	14
A.1 Attenuation and uniformity requirements of $1 \times N$ and $2 \times N$ NWBDs calculated by the equations of Tests No.1 and 2 .....	14
A.2 Minimum requirements at room temperature of attenuation values for balanced bidirectional $1 \times N$ and $2 \times N$ NWBD .....	15
Annex B (normative) Sample size .....	17
Bibliography.....	18
Table 1 – Test details and requirements ( <i>1 of 6</i> ).....	8
Table A.1 – Attenuation and uniformity requirements of balanced bidirectional NWBD having the most common port configurations for Class A, with the underlying formulas as specified in the Tests 1 and 2 of Table 1 .....	14
Table A.2 – Attenuation and uniformity requirements of balanced bidirectional NWBD having the most common port configurations for Class B, with the underlying formulas as specified in Tests 1 and 2 of Table 1 .....	15
Table A.3 – Attenuation requirements of $1 \times 2$ and $2 \times 2$ unbalanced NWBD having the most common port configurations, with the underlying formula as specified in Test 1 of Table 1 .....	15
Table A.4 – Minimum requirements at room temperature of attenuation values for Class A balanced bidirectional NWBD.....	16
Table A.5 – Minimum requirements at room temperature of attenuation values for Class B balanced bidirectional NWBD.....	16
Table B.1 – Sample size for each test.....	17

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

# **FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –**

## **Part 031-2: Non-connectorized single-mode 1×N and 2×N non-wavelength-selective branching devices for Category C – Controlled environment**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61753-031-2 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

The text of this standard is based on the following documents:

FDIS	Report on voting
86B/3791/FDIS	86B/3823/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 61753 consists of the following parts, under the general title *Fibre optic interconnecting devices and passive components – Performance standard*:

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

# **FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –**

## **Part 031-2: Non-connectorized single-mode 1×N and 2×N non-wavelength-selective branching devices for Category C – Controlled environment**

### **1 Scope**

This part of IEC 61753 contains the minimum initial tests and measurement requirements and severities which a non-wavelength selective branching device (NWBD) should satisfy in order to be categorized as meeting the requirement of this IEC standard.

The requirements cover balanced bidirectional non-connectorized single-mode 1 × N and 2 × N non wavelength-selective branching devices for use in an IEC Category C environment (N is the number of branching ports), especially but not exclusively used for PON application. For balanced NWBD two attenuation and uniformity performance classes are considered: class A (premium class) which meets more restrictive requirements (i.e. for extended reach PON application) and class B (standard class) for standard application (i.e. normal reach PON application).

The requirements also cover unbalanced bidirectional non-connectorized single-mode, non-wavelength-selective branching devices; however, the specifications of unbalanced branching devices are limited to 1 × 2 and 2 × 2 devices because they are the most commonly used.

### **2 Normative references**

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-2-50:2012, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre/cable retention*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock*

IEC 61300-2-14, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – High optical power*

IEC 61300-2-17, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-17: Tests – Cold*

IEC 61300-2-18, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-18: Tests – Dry heat – High temperature endurance*

IEC 61300-2-19, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-19: Tests – Damp heat (steady state)*

IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature*

IEC 61300-2-42, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-42: Tests – Static side load for connectors*

IEC 61300-2-44, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-44: Tests – Flexing of the strain relief of fibre optic devices*

IEC 61300-3-2:2009, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examination and measurements – Polarization dependent loss in a single-mode fibre optic device*

IEC 61300-3-3:2009, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-3: Examinations and measurements – Active monitoring of changes in attenuation and return loss*

IEC 61300-3-6:2008, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-6: Examinations and measurements – Return loss*

IEC 61300-3-7:2009, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-7: Examinations and measurements – Wavelength dependence of attenuation and return loss of single mode components*

IEC 61300-3-20, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-20: Examinations and measurements – Directivity of fibre optic branching devices*

IEC 61300-3-28, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-28: Examinations and measurements – Transient loss*

### 3 Test

All test methods are selected within the IEC 61300 series.

The samples for tests shall be terminated onto single-mode fibres according to category B1.1, B1.3, or B.6 of IEC 60793-2-50:2012 in either coated fibres (primary and secondary) or reinforced cable format.

All tests shall be carried out to validate performance over one of the spectral bands listed below:

- 1) Spectral bands I:
  - 1 260 nm to 1 360 nm
  - 1 480 nm to 1 625 nm
- 2) Spectral bands II:
  - 1 260 nm to 1 360 nm
  - 1 480 nm to 1 660 nm



## **4 Test report**

Fully documented test reports and supporting evidence shall be prepared and be available for inspection as evidence that the tests have been carried out and complied with.

## **5 Performance requirements**

### **5.1 Dimensions**

Dimensions shall comply with those given in appropriate manufacturer's drawings.

### **5.2 Sample size**

Sample sizes for the tests are defined in Annex B.

### **5.3 Test details and requirements**

Performance requirements and details are specified in Table 1.

All optical performances are given only for non-connectorized NWBD. During the environmental tests where monitoring of the NWBD is needed, all ports of the device shall be monitored.

In Annex A some numerical values of attenuation and uniformity requirements of Tests No.1 and 2 for the most commonly used NWBD are shown in Tables A.1, A.2 and A.3.

In Tables A.4 and A.5 the minimum attenuation requirements at room temperature are described by way of equations on the top of column, with the calculated values of the most commonly used NWBD listed below.

Table 1 – Test details and requirements (1 of 6)

No.	Tests	Requirements						Details		
1	Attenuation (A) (Insertion loss) IEC 61300-3-7:2009 (Method A)	Balanced NWBD							Launch patchcord length	≥ 2 m
		Configuration							Source type	Unpolarized
		Performance class	A		B		2 × N		Launch conditions	The wavelength of the source shall be longer than the cut-off wavelength of the fibre.  ≤ ± 0,05 dB  The measurement should be performed with all combination of input/output ports  See Tables A.1, A.2 and A.3 for example  ≥ 2 m
		Spectral band I	≤ 0,5 + 3,3log <sub>2</sub> N (dB)	≤ 0,5 + 3,4log <sub>2</sub> N (dB)	≤ 0,7 + 3,4log <sub>2</sub> N (dB)	≤ 0,7 + 3,5log <sub>2</sub> N (dB)	≤ 0,7 + 3,5log <sub>2</sub> N (dB)	≤ 0,7 + 3,6log <sub>2</sub> N (dB)		
		Spectral band II	≤ 0,5 + 3,4log <sub>2</sub> N (dB)	≤ 0,5 + 3,5log <sub>2</sub> N (dB)	≤ 0,7 + 3,5log <sub>2</sub> N (dB)	≤ 0,7 + 3,6log <sub>2</sub> N (dB)				
		Unbalanced NWBD								
		Spectral band I Spectral band II	≤ 22 – 10,5log <sub>10</sub> P (dB)  where P is the nominal percentage of power associated with one port						Uncertainty	
2	Uniformity (U) IEC 61300-3-7:2009 (Method A)	Balanced NWBD							Launch patchcord length	≥ 2 m
		Configuration							Source type	Unpolarized
		Performance class	A		B		2 × N		Launch conditions	The wavelength of the source shall be longer than the cut-off wavelength of the fibre.  ≤ ± 0,05 dB  The measurement should be performed with all combination of input/output ports.  See Tables A.1 and A.2 for example
		Spectral band I	≤ 0,1 + 0,3log <sub>2</sub> N (dB)	≤ 0,2 + 0,3log <sub>2</sub> N (dB)	≤ 0,4 + 0,4log <sub>2</sub> N (dB)	≤ 0,5 + 0,4log <sub>2</sub> N (dB)	≤ 0,5 + 0,5log <sub>2</sub> N (dB)			
		Spectral band II	≤ 0,1 + 0,4log <sub>2</sub> N (dB)	≤ 0,2 + 0,4log <sub>2</sub> N (dB)	≤ 0,4 + 0,5log <sub>2</sub> N (dB)	≤ 0,5 + 0,5log <sub>2</sub> N (dB)				
		Uncertainty								

**Table 1** (2 of 6)

No.	Tests	Requirements	Details	
3	Directivity IEC 61300-3-20	$\geq 55$ dB	Launch patchcord length	$\geq 2$ m
			Source type	LD
			Launch conditions	The wavelength of the source shall be longer than the cut-off wavelength of the fibre.
			Uncertainty	$\leq \pm 1$ dB  The measurement should be made between all pairs of Input/output ports. All ports not under test shall be terminated to avoid unwanted reflections contributing to the measurement
4	Return loss (RL) IEC 61300-3-6:2008 (Method 1, OCWR)	$\geq 55$ dB	Launch patchcord length	$\geq 2$ m
			Source type	LD
			Launch conditions	The wavelength of the source shall be longer than the cut-off wavelength of the fibre.
			Uncertainty	$\leq \pm 1$ dB  The measurement should be performed with all combination of input/output ports. All ports not under test shall be terminated to avoid unwanted reflections contributing to the measurement
5	Polarization dependent loss (PDL) IEC 61300-3-2	For balanced NWBD:  $\begin{array}{ccc} & 1 \times N & 2 \times N \\ N \leq 4 & \leq 0,2 \text{ dB} & \leq 0,3 \text{ dB} \\ 4 < N \leq 16 & \leq 0,3 \text{ dB} & \leq 0,4 \text{ dB} \\ N > 16 & \leq 0,4 \text{ dB} & \leq 0,5 \text{ dB} \end{array}$ For unbalanced $1 \times 2$ and $2 \times 2$ NWBD and for any pair of input and output ports: $\leq 0,7 - 0,25 \log_{10} P \text{ (DB)}$ where P is the nominal percentage of the power associated with one port	Launch patchcord length	$\geq 2$ m
			Source type	LD
			Uncertainty	$\leq \pm 0,05$ dB  The measurement should be performed with all combination of input/output ports

**Table 1 (3 of 6)**

No.	Tests	Requirements	Details	
6	High optical power  IEC 61300-2-14	<p><math>P_{\max}</math> = 500 mW (+27 dBm) per port only one at the time.</p> <p>During the test the change in A shall be within <math>\pm 0,5</math> dB of the original value under ambient conditions, while on completion of the test the change in A shall be within <math>\pm 0,3</math> dB of the original value.</p> <p>During and on completion of the test the RL limit of test No. 4 shall be met</p>	<p>Launch patchcord length</p> <p>Source type</p> <p>Launch conditions</p> <p>Uncertainty A test</p> <p>Uncertainty RL test</p> <p>Test wavelength Spectral band I</p> <p>Test wavelength Spectral band II</p> <p>Duration of the optical power exposure at the each level</p>	<p><math>\geq 2</math> m</p> <p>Unpolarized.</p> <p>The wavelength of the source shall be longer than the cut-off wavelength of the fibre</p> <p><math>\leq \pm 0,05</math> dB</p> <p><math>\leq \pm 1</math> dB</p> <p>1 310 nm <math>\pm</math> 20 nm 1 550 nm <math>\pm</math> 20 nm</p> <p>1 310 nm <math>\pm</math> 20 nm 1 625 nm <math>\pm</math> 20 nm</p> <p>30 min</p> <p>The measurement shall be performed between the common port (input port) and the output ports</p>
7	Cold  IEC 61300-2-17	<p>For balanced and unbalanced NWBD before and on completion of the test the A limits of Test No. 1 shall be met.</p> <p>In addition during the test the change in A of balanced NWBD shall be within <math>\pm 0,3</math> dB for <math>N \leq 4</math> and within <math>\pm 0,5</math> dB for <math>N &gt; 4</math> of the original value under ambient conditions. For unbalanced NWBD the change in A during the test shall be within <math>\pm 0,3</math> dB for <math>P \% &gt; 2</math> % and <math>\pm 0,5</math> dB for <math>P \% \leq 2</math> % of the original value.</p> <p>During and after the test the RL limit of test No. 4 shall be met</p>	<p>Temperature</p> <p>Duration of exposure</p>	<p><math>-10</math> °C <math>\pm</math> 2 °C</p> <p>96 h</p> <p>Specimens shall be optically functioning.</p> <p>A and RL shall be measured before the test, during the test at a maximum interval of 1 h and after the test by the Method 3 of IEC 61300-3-3:2009</p>
8	Dry heat – High temperature endurance  IEC 61300-2-18	<p>For balanced and unbalanced NWBD before and on completion of the test the A limits of Test No. 1 shall be met.</p> <p>In addition, during the test the change in A of balanced NWBD shall be within <math>\pm 0,3</math> dB for <math>N \leq 4</math> and within <math>\pm 0,5</math> dB for <math>N &gt; 4</math> of the original value under ambient conditions. For unbalanced NWBD the change in A during the test shall be within <math>\pm 0,3</math> dB for <math>P \% &gt; 2</math> % and <math>\pm 0,5</math> dB for <math>P \% \leq 2</math> % of the original value.</p> <p>During and after the test the RL limit of test No. 4 shall be met</p>	<p>Temperature</p> <p>Duration of exposure</p>	<p>+ 60 °C <math>\pm</math> 2 °C.</p> <p>96 h</p> <p>Specimens shall be optically functioning.</p> <p>A and RL shall be measured before the test, during the test at a maximum interval of 1 h and after the test by the Method 3 of IEC 61300-3-3:2009</p>

**Table 1** (4 of 6)

No.	Tests	Requirements	Details	
9	Damp heat (steady state)  IEC 61300-2-19	For balanced and unbalanced NWBD before and on completion of the test the A limits of Test No. 1 shall be met.  In addition during the test the change in A of balanced NWBD shall be within $\pm 0,3$ dB for $N \leq 4$ and within $\pm 0,5$ dB for $N > 4$ of the original value under ambient conditions. For unbalanced NWBD the change in A during the test shall be within $\pm 0,3$ dB for $P \% > 2$ % and $\pm 0,5$ dB for $P \% \leq 2$ % of the original value.  During and after the test the RL limit of Test No. 4 shall be met	Temperature  Relative humidity  Duration of exposure	$+ 40\text{ °C} \pm 2\text{ °C}$  $93\text{ \%} + 2\text{ \%}$ to $-3\text{ \%}$  96 h  Specimens shall be optically functioning.  A and RL shall be measured before the test, during the test at a maximum interval of 10 min and after the test by the Method 3 of IEC 61300-3-3:2009
10	Change of temperature  IEC 61300-2-22	For balanced and unbalanced NWBD before and on completion of the test the A limits of Test No. 1 shall be met.  In addition during the test the change in A of balanced NWBD shall be within $\pm 0,3$ dB for $N \leq 4$ and within $\pm 0,5$ dB for $N > 4$ of the original value under ambient conditions. For unbalanced NWBD the change in A during the test shall be within $\pm 0,3$ dB for $P \% > 2$ % and $\pm 0,5$ dB for $P \% \leq 2$ % of the original value.  During and after the test the RL limit of Test No. 4 shall be met.	High temperature  Low temperature  Duration at extreme temperature  Temperature rate of change  Number of cycles	$+ 60\text{ °C} \pm 2\text{ °C}$  $-10\text{ °C} \pm 2\text{ °C}$  1 h  $1\text{ °C/min}$  5  Specimens shall be optically functioning. A and RL shall be measured before the test, during the test at a maximum interval of 10 min and after the test by the Method 3 of IEC 61300-3-3:2009

**Table 1** (5 of 6)

No.	Tests	Requirements	Details	
11	Vibration (sinusoidal)  IEC 61300-2-1	For balanced and unbalanced NWBD before and on completion of the test the A limits of Test No. 1 shall be met.  In addition during the test the change in A of balanced NWBD shall be within $\pm 0,3$ dB for $N \leq 4$ and within $\pm 0,5$ dB for $N > 4$ of the initial value. For unbalanced NWBD the change in A during the test shall be within $\pm 0,3$ dB for $P \% > 2$ % and within $\pm 0,5$ dB for $P \% \leq 2$ % of the initial value.  During and after the test the RL limit of Test No. 4 shall be met	Frequency range  Number of axes  Rate of change  Number of sweeps  Vibration amplitude	10 Hz to 55 Hz  3 orthogonal  1 octave/min  (10 Hz to 55 Hz to 10 Hz): 15  0,75 mm  NWBD shall be optically functioning. A and RL shall be measured before and after the test by means the set-ups defined in Test No. 1 and No. 4.  In addition during the test the change in A shall be measured by the IEC 61300-3-28 (Transient loss) at 1 550 nm $\pm$ 25 nm
12	Flexing of strain relief of fibre optic devices  IEC 61300-2-44	For balanced and unbalanced NWBD before and on completion of the test the A limits of Test No. 1 shall be met.  In addition on completion of the test the change in A of balanced NWBD shall be within $\pm 0,3$ dB for $N \leq 4$ and within $\pm 0,5$ dB for $N > 4$ of the initial value. For unbalanced NWBD the change in A after the test shall be within $\pm 0,3$ dB for $P \% > 2$ % and within $\pm 0,5$ dB for $P \% \leq 2$ % of the initial value.  After the test the RL limit of Test No. 4 shall be met	Magnitude of the load    Number of cycles	2 N for reinforced cable. For primary and secondary coated fibre the test can be omitted.  30 at $\pm 90^\circ$  NWBD shall be optically functioning. A and RL shall be measured before and after the test by means the setups defined in Tests No. 1 and No. 4

**Table 1** (6 of 6)

No.	Tests	Requirements	Details	
13	Fibre/cable retention IEC 61300-2-4	<p>For balanced and unbalanced NWBD before and on completion of the test the A limits of Test No. 1 shall be met.</p> <p>In addition on completion of the test the change in A of balanced NWBD shall be within <math>\pm 0,3</math> dB for <math>N \leq 4</math> and within <math>\pm 0,5</math> dB for <math>N &gt; 4</math> of the initial value. For unbalanced NWBD the change in A after the test shall be within <math>\pm 0,3</math> dB for <math>P \% &gt; 2</math> % and within <math>\pm 0,5</math> dB for <math>P \% \leq 2</math> % of the initial value.</p> <p>After the test the RL limit of Test No. 4 shall be met</p>	<p>Magnitude and rate of application of the tensile load</p> <p>Point of application of tensile load</p> <p>Duration of the test (maintaining the load)</p>	<p>10 N <math>\pm</math> 1 N at a speed of 5 N/s for reinforced cable; 5 N <math>\pm</math> 0,5 N at a speed of 0,5 N/s for secondary coated fibres; 2 N <math>\pm</math> 0,2 N at a speed of 0,5 N/s for primary coated fibres.</p> <p>0,3 m from the end of the NWBD</p> <p>120 s at 10 N; 60 s at 2 N and 5 N</p> <p>NWBD shall be optically functioning. A and RL shall be measured before and after the test by means the setups defined in Tests No. 1 and No. 4</p>
14	Static side load IEC 61300-2-42	<p>For balanced and unbalanced NWBD before and on completion of the test the A limits of Test No. 1 shall be met.</p> <p>In addition on completion of the test the change in A of balanced NWBD shall be within <math>\pm 0,3</math> dB for <math>N \leq 4</math> and within <math>\pm 0,5</math> dB for <math>N &gt; 4</math> of the initial value. For unbalanced NWBD the change in A after the test shall be within <math>\pm 0,3</math> dB for <math>P \% &gt; 2</math> % and within <math>\pm 0,5</math> dB for <math>P \% \leq 2</math> % of the initial value.</p> <p>After the test the RL limit of Test No. 4 shall be met</p>	<p>Magnitude of the load</p>	<p>1 N for 1 h for reinforced cables; 0,2 N for 5 min for secondary coated fibres. For primary coated fibre the test can be omitted.</p> <p>The test shall be applied in two mutually perpendicular directions as permitted by the device design. NWBD shall be optically functioning.</p> <p>A and RL shall be measured before and after the test by means the setups defined in Tests No. 1 and No. 4.</p>
15	Shock IEC 61300-2-9	<p>For balanced and unbalanced NWBD before and on completion of the test the A limits of Test No. 1 shall be met.</p> <p>In addition on completion of the test the change in A of balanced NWBD shall be within <math>\pm 0,3</math> dB for <math>N \leq 4</math> and within <math>\pm 0,5</math> dB for <math>N &gt; 4</math> of the initial value. For unbalanced NWBD the change in A after the test shall be within <math>\pm 0,3</math> dB for <math>P \% &gt; 2</math> % and within <math>\pm 0,5</math> dB for <math>P \% \leq 2</math> % of the initial value.</p> <p>After the test the RL limit of Test No. 4 shall be met</p>	<p>Acceleration forces</p> <p>Nominal duration</p> <p>No. of shocks</p>	<p>Components: 5 000 m/s<sup>2</sup> for mass <math>\leq 0,125</math> kg</p> <p>Modules: 2 000 m/s<sup>2</sup> for: 0,125 kg &lt; mass <math>\leq 0,225</math> kg; 500 m/s<sup>2</sup> for: 0,225 Kg &lt; mass <math>\leq 1</math> kg.</p> <p>1 ms, half sine pulse</p> <p>3 axes in 2 directions, 2 shocks per axis, 12 shocks total.</p> <p>NWBD shall be optically functioning. A and RL shall be measured before and after the test by means the setups defined in Tests No. 1 and No. 4</p>

## Annex A (normative)

### A and U requirements of $1 \times N$ and $2 \times N$ NWBDs

#### A.1 Attenuation and uniformity requirements of $1 \times N$ and $2 \times N$ NWBDs calculated by the equations of Tests No.1 and 2

Tables A.1, A.2 and A.3 show the attenuation and uniformity requirements for different classes with the underlying formulas as specified in the Tests 1 and 2 of Table 1.

**Table A.1 – Attenuation and uniformity requirements of balanced bidirectional NWBD having the most common port configurations for Class A, with the underlying formulas as specified in the Tests 1 and 2 of Table 1**

N	$1 \times N$				$2 \times N$			
	Spectral band I		Spectral band II		Spectral band I		Spectral band II	
	$A_{\max}$ (dB)	$U_{\max}$ (dB)	$A_{\max}$ (dB)	$U_{\max}$ (dB)	$A_{\max}$ (dB)	$U_{\max}$ (dB)	$A_{\max}$ (dB)	$U_{\max}$ (dB)
	$0,5+3,3\log_2 N$	$0,1+0,3\log_2 N$	$0,5+3,4\log_2 N$	$0,1+0,4\log_2 N$	$0,7+3,4\log_2 N$	$0,4+0,4\log_2 N$	$0,7+3,5\log_2 N$	$0,4+0,5\log_2 N$
2	3,8	0,4	3,9	0,5	4,1	0,8	4,2	0,9
3	5,7	0,6	5,9	0,7	6,1	1,0	6,2	1,2
4	7,1	0,7	7,3	0,9	7,5	1,2	7,7	1,4
6	9,0	0,9	9,3	1,1	9,5	1,4	9,7	1,7
8	10,4	1,0	10,7	1,3	10,9	1,6	11,2	1,9
12	12,3	1,2	12,7	1,5	12,9	1,8	13,2	2,2
16	13,7	1,3	14,1	1,7	14,3	2,0	14,7	2,4
24	15,6	1,5	16,1	1,9	16,3	2,2	16,7	2,7
32	17,0	1,6	17,5	2,1	17,7	2,4	18,2	2,9
64	20,3	1,9	20,9	2,5	21,1	2,8	21,7	3,4
128	23,6	2,2	24,3	2,9	24,5	3,2	25,2	3,9
NOTE N is the number of branching ports.								



**Table A.2 – Attenuation and uniformity requirements of balanced bidirectional NWBD having the most common port configurations for Class B, with the underlying formulas as specified in Tests 1 and 2 of Table 1**

N°	1 × N				2 × N			
	Spectral band I		Spectral band II		Spectral band I		Spectral band II	
	$A_{\max}$ (dB)	$U_{\max}$ (dB)	$A_{\max}$ (dB)	$U_{\max}$ (dB)	$A_{\max}$ (dB)	$U_{\max}$ (dB)	$A_{\max}$ (dB)	$U_{\max}$ (dB)
	$0,5+3,4\log_2 N$	$0,2+0,3\log_2 N$	$0,5+3,5\log_2 N$	$0,2+0,4\log_2 N$	$0,7+3,5\log_2 N$	$0,5+0,4\log_2 N$	$0,7+3,6\log_2 N$	$0,5+0,5\log_2 N$
2	3,9	0,5	4,0	0,6	4,2	0,9	4,3	1,0
3	5,9	0,7	6,0	0,8	6,2	1,1	6,4	1,3
4	7,3	0,8	7,5	1,0	7,7	1,3	7,9	1,5
6	9,3	1,0	9,5	1,2	9,7	1,5	10,0	1,8
8	10,7	1,1	11,0	1,4	11,2	1,7	11,5	2,0
12	12,7	1,3	13,0	1,6	13,2	1,9	13,6	2,3
16	14,1	1,4	14,5	1,8	14,7	2,1	15,1	2,5
24	16,1	1,6	16,5	2,0	16,7	2,3	17,2	2,8
32	17,5	1,7	18,0	2,2	18,2	2,5	18,7	3,0
64	20,9	2,0	21,5	2,6	21,7	2,9	22,3	3,5
128	24,3	2,3	25,0	3,0	25,2	3,3	25,9	4,0
NOTE N is the number of branching ports.								

**Table A.3 – Attenuation requirements of 1 × 2 and 2 × 2 unbalanced NWBD having the most common port configurations, with the underlying formula as specified in Test 1 of Table 1**

Coupling ratio ( $P_1$ %/ $P_2$ %)	$A_{1\max}/A_{2\max}$ dB
	$(22 - 10,5\log_{10} P_1)/(22 - 10,5\log_{10} P_2)$
40/60	5,2 / 3,3
30/70	6,5 / 2,6
20/80	8,3 / 2,0
10/90	11,5 / 1,5
5/95	14,7 / 1,2
2/98	18,8 / 1,1
1/99	22,0 / 1,0

## A.2 Minimum requirements at room temperature of attenuation values for balanced bidirectional 1 × N and 2 × N NWBD

Tables A.4 and A.5 show the minimum requirements at room temperature of attenuation values for different classes.

**Table A.4 – Minimum requirements at room temperature of attenuation values for Class A balanced bidirectional NWBD**

N°	1 × N		2 × N	
	Spectral band I	Spectral band II	Spectral band I	Spectral band II
	$A_{\max}$ (dB) $0,5+3,2\log_2 N$	$A_{\max}$ (dB) $0,5+3,3\log_2 N$	$A_{\max}$ (dB) $0,7+3,3\log_2 N$	$A_{\max}$ (dB) $0,7+3,4\log_2 N$
2	3,7	3,8	4,0	4,1
3	5,6	5,7	5,9	6,1
4	6,9	7,1	7,3	7,5
6	8,8	9,0	9,2	9,5
8	10,1	10,4	10,6	10,9
12	12,0	12,3	12,5	12,9
16	13,3	13,7	13,9	14,3
24	15,2	15,6	15,8	16,3
32	16,5	17,0	17,2	17,7
64	19,7	20,3	20,5	21,1
128	22,9	23,6	23,8	24,5
NOTE N is the number of branching ports.				

**Table A.5 – Minimum requirements at room temperature of attenuation values for Class B balanced bidirectional NWBD**

N°	1 × N		2 × N	
	Spectral band I	Spectral band II	Spectral band I	Spectral band II
	$A_{\max}$ (dB) $0,5+3,3\log_2 N$	$A_{\max}$ (dB) $0,5+3,4\log_2 N$	$A_{\max}$ (dB) $0,7+3,4\log_2 N$	$A_{\max}$ (dB) $0,7+3,5\log_2 N$
2	3,8	3,9	4,1	4,2
3	5,7	5,9	6,1	6,2
4	7,1	7,3	7,5	7,7
6	9,0	9,3	9,5	9,7
8	10,4	10,7	10,9	11,2
12	12,3	12,7	12,9	13,2
16	13,7	14,1	14,3	14,7
24	15,6	16,1	16,3	16,7
32	17,0	17,5	17,7	18,2
64	20,3	20,9	21,1	21,7
128	23,6	24,3	24,5	25,2
NOTE N is the number of branching ports.				

## Annex B (normative)

### Sample size

As shown in Table B.1, all samples shall be subjected to Tests 1 – 5. All other tests shall be carried out in any of the following order. Consecutive testing on the same optical sample is allowed, but in case of failure during the consecutive testing, a new sample shall be prepared and the failed test shall be redone.

**Table B.1 – Sample size for each test**

Test number	Test	Sample size
1	Attenuation (insertion loss)	12
2	Uniformity	12
3	Directivity	12
4	Return loss	12
5	Polarization dependent loss	12
6	High optical power	4
7	Cold	4
8	Dry heat – High temperature endurance	4
9	Damp heat (steady state)	4
10	Change of temperature	4
11	Vibration	4
12	Flexing of the strain relief of fibre optic devices	4
13	Fibre/cable retention	4
14	Static side load	4
15	Shock	4

## Bibliography

IEC 60875-1, *Fibre optic interconnecting devices and passive optical components – Non-wavelength-selective fibre optic branching devices – Part 1: Generic specification*

IEC 61753-1, *Fibre optic interconnecting devices and passive components performance standard – Part 1: General and guidance for performance standard*

Recommendation ITU-T G.671, *Transmission characteristics of optical components and subsystems*

---



INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

3, rue de Varembé  
PO Box 131  
CH-1211 Geneva 20  
Switzerland

Tel: + 41 22 919 02 11  
Fax: + 41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)