# INTERNATIONAL STANDARD



Second edition 2004-08

Consumer audio/video equipment – Digital interface –

Part 4: MPEG2-TS data transmission



Reference number IEC 61883-4:2004(E)

#### **Publication numbering**

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

#### **Consolidated editions**

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

#### Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

IEC Web Site (<u>www.iec.ch</u>)

#### Catalogue of IEC publications

The on-line catalogue on the IEC web site (<u>www.iec.ch/searchpub</u>) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

• IEC Just Published

This summary of recently issued publications (<u>www.iec.ch/online\_news/justpub</u>) is also available by email. Please contact the Customer Service Centre (see below) for further information.

#### • Customer Service Centre

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: <u>custserv@iec.ch</u> Tel: +41 22 919 02 11 Fax: +41 22 919 03 00

# INTERNATIONAL STANDARD



Second edition 2004-08

Consumer audio/video equipment – Digital interface –

Part 4: MPEG2-TS data transmission

© IEC 2004 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale International Electrotechnical Commission Международная Электротехническая Комиссия



For price, see current catalogue

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

## CONSUMER AUDIO/VIDEO EQUIPMENT – DIGITAL INTERFACE –

### Part 4: MPEG2-TS data transmission

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61883-4 has been prepared by technical area 4: Digital system interfaces and protocols, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This second edition of IEC 61883-4 cancels and replaces the first edition published in 1998. This edition contains the following significant technical changes with respect to the previous edition:

Updated IEC 61834-9, IEC 61834-10 and added IEC 61834-1 in Bibliography.

The text of this standard is based on the following documents:

CDV	Report on voting
100/729/CDV	100/818/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 61883 consists of the following parts under the general title *Consumer audio/video* equipment – Digital interface:

Part 1: General

Part 2: SD-DVCR data transmission

Part 3: HD-DVCR data transmission

- Part 4: MPEG2-TS data transmission
- Part 5: SDL-DVCR data transmission

Part 6: Audio and music data transmission protocol

Part 7: Transmission of ITU-R BO.1294 System B

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this document may be issued at a later date.

## CONSUMER AUDIO/VIDEO EQUIPMENT – DIGITAL INTERFACE –

## Part 4: MPEG2-TS data transmission

### 1 Scope

This part of IEC 61883 describes the packetization and the transmission timing for MPEG2 transport streams for the IEEE 1394 digital interface. It describes the specifications for the IEEE 1394 packet, the CIP header and the transmission timing for use with the transport stream as specified in prETS 300 468. This explanation is based on the transport stream as specified in DVB.

### 2 Normative reference

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61883-1, Consumer audio/video equipment – Digital interface – Part 1: General

ISO/IEC 13818-1, Information technology – Generic coding of moving pictures and associated audio information: Systems

ISO/IEC 13818-2, Information technology – Generic coding of moving pictures and associated audio information: Video

ISO/IEC 13818-3, Information technology – Generic coding of moving pictures and associated audio information – Part 3: Audio

ISO/IEC 13818-9, Information technology – Generic coding of moving pictures and associated audio information – Part 9: Extension for real time interface for system decoders

prETS 300 468, Digital broadcasting systems for television, sound and data services – Specification for Service Information (SI) in digital video broadcasting (DVB) systems

#### 3 Terms, definitions, and abbreviations

For the purposes of this document, the following abbreviations apply:

CIP	Common Isochronous Packet
CTR	Cycle Time Register
DVB	Digital Video Broadcasting (in Europe)
SI	Service Information
ETS	European Telecommunication Standard
MPEG	Moving Picture Experts Group
RTI	Real Time Interface
TS	Transport Stream
TSP	Transport Stream Packet
IEEE 1394 packet	IEEE 1394 isochronous packet defined in IEC 61883-1

#### 4 Construction of IEEE 1394 packet

#### 4.1 Structure of the MPEG2-TS data stream

The length of the source packet is 192 bytes (see Figure 1). The source packet consists of one MPEG2-TSP with a length of 188 bytes and a source packet header of 4 bytes. The source packet header contains a time stamp.

MPEG2-TS packets shall comply with ISO/IEC 13818 series.

#### 4.2 Packetization of source packet of the MPEG2-TS data stream

A source packet is split into 8 data blocks with a length of 6 quadlets. Zero or more data blocks are packed in an IEEE 1394 isochronous packet. A receiver of the isochronous packets shall collect the data blocks of one source packet and combine them in order to reconstruct the source packet before sending this source packet to the application. There are restrictions on the transmission of fractions (see 5.2).

Active transmitters shall send an isochronous packet in every cycle. If not enough data is available to transmit in the isochronous packet, then an empty packet shall be transmitted.

#### 4.3 Time stamp

The time stamp in the source packet header is used by isochronous data receivers for reconstructing a correct timing of the TSPs at their output. The time stamp indicates the intended delivery time of the first bit/byte of the TSP from the receiver output to the transport stream target decoder. The time stamp represents the 25 bits of the IEEE 1394 CYCLE\_TIME register (CTR) at the moment the first bit/byte of the TSP arrives from the application, plus some offset. The offset is equal to the constant overall delay of the TSP between the moment of arriving (of the first bit) and the moment the TSP (first bit) is delivered by the receiver to the application.

#### 5 CIP header

#### 5.1 Structure of CIP header

The structure of the CIP header (see Figure 2) for the MPEG2-TS is compliant with the two quadlet CIP header format explained in IEC 61883-1, 6.2.1. The static values of the CIP header components are as follows.

SID		(depends on configuration)
DBS	00000110 <sub>2</sub>	(6 quadlets)
FN	112	(8 data blocks in one source packet)
QPC	0002	(no padding)
SPH	1	(source packet header is present)
DBC	0 255	(see 5.2)
FMT	100000 <sub>2</sub>	(format type of MPEG2-TS)
FDF		(see 5.3)

### 5.2 DBC values

The first data block of a source packet (data block containing the source packet header) corresponds to a DBC value from which the three LSBs are '000'.

An isochronous packet contains 0, 1, 2 or 4 data blocks or an integer number of source packets.

Where the isochronous packet contains

- one data block, then the DBC value increments with 1;
- two data blocks, then the DBC value is a multiple of 2, the LSB is '0';
- four data blocks, then the DBC value is a multiple of 4, the two LSBs are '00'.

Where the isochronous packet contains n source packets (n is an integer) then the DBC value is a multiple of 8. The three LSBs are '000'.

### 5.3 FDF area

The structure of the FDF area is shown in Figure 3. The definitions of the fields are as follows:

- TSF (time shift flag) indicates a time-shifted data stream:
  - 0 = the stream is not time-shifted.
  - 1 = the stream is time-shifted.
- Res: reserved for future extension and shall be zeros.

#### 6 Transmission of isochronous packets

#### 6.1 Steps in transmission

An MPEG2-TS consists of TSPs with a length of 188 bytes. In Figure 4, an example is given of a TS which consists of several programmes. Very often only one or a few programs have to be transmitted. If a programme selection is carried out, then only those TSPs from that particular TS are transmitted. In this situation, the occupied bandwidth on the 1394 interface can be reduced. Reduction of the bit rate is carried out in a smoothing buffer. As a result of the smoothing operation, the TSPs will be shifted in time.

The TSPs at the output of the smoothing buffer are transmitted over the interface. During transmission this interface will introduce some jitter on the arrival time of the TSPs in the receiver.

In the MPEG2-TS there are strong requirements on the timing of the TSPs. The jitter introduced by the smoothing buffer and the transmitter of the interface shall be compensated. To do this, a time stamp is added to the TSP at the moment it arrives at the input of the smoothing buffer or, if smoothing is not applied, at the input of the digital interface. The receiver of the interface contains a receiver buffer. In this receiver buffer, the jitter introduced is compensated.

#### 6.2 Late packets

The time stamp in the transmitted source packet header shall point to a value in future. If for some reason the delay in the transmitter is too long, resulting in a time stamp which points in the past (late packet), then this source packet is not transmitted.

A late packet occurs if the actual value of the CTR becomes equal to the value represented in the time stamp from the source packet header, before the isochronous packet(s) that contain the source packet (including CRC), has been transmitted.

In the case of transmission of one source packet/cycle, the interval needed to transmit the complete isochronous packet can be calculated (the clock frequency and the number of bits is known). If a late packet occurs, then an empty packet or the next valid packet should be sent and the late packet is discarded.

In the case of transmission of more than one source packet /cycle, then the same procedure is followed. It is allowed to discard all source packets from the isochronous packet if one source packet turns out to be a late packet.

In the case of transmission of fractions, it is recommended to first collect a complete source packet in the transmitter. If a late packet occurs, then the complete source packet should be discarded.

If a late packet occurs when some data blocks of the source packet have already been transmitted (for example, at a bus reset), then data blocks remaining in the transmitting buffer are removed.

#### 7 Buffering in the receiver

Buffering in the receiver is needed to compensate jitter introduced by smoothing buffer and transmitter. It is expected that, at the moment of arriving in the receiver, the source packets or fractions of source packets are stored in the receiving buffer with the bus clock frequency (S100, S200 or S400 mode). The MPEG2 TSPs are read out of the receiver buffer and sent to the application at the intended delivery time of the first bit(byte) of the TSP. The intended delivery time is represented by the time stamp in the source packet header. The clock frequency used for reading the bytes from the TSP may be high.

Buffering needed for compensating jitter from the transmitter only is given in Table A.1 and buffering needed for compensating the jitter introduced by smoothing of the TS is given in Table A.2.

For the transmission of an MPEG2-TS as specified in DVB, it is expected that the buffer size in the receiver is 3 264 bytes.

Source packet header (4 bytes)





Figure 1b – Source packet header

Figure 1 – Structure of a source packet

0	0	SID								D	BS	;				F	N		QP	C		HRes				DBC													
												I				L										"											Ι		
1	0			I	FN	т																	FD	F															
			I	I			L	I			L	I	I		I	I	I	Т					T	I	I	Т		I	I	I		L	I	I		I	T	I	
										SII DE FN QF SP Re DE FM FD					: () () () () () () () () () () () () ()	ira ira gui sol ires dat ior	uro ta cti ad uro ser ta ma ma	ce blo on let ce ve blo at at-	no oc i r pa ed oc ID de	ode k s nun bad ack k c b epe	e II size nbe dir cet con	) er ig h tii	in q co eac nuit nt f	iua un ty ïel	t cc	let	s	ər											

Figure 2 – CIP header for MPEG2-TS



Figure 3 – Structure of FDF area

61883-4 © IEC:2004(E)



- 9 -

a) Complete transport stream with multiplex of programmes (A,B,C,D) and SI information b) source packets of the selected programme A with relevant SI information

- c) source packets at the output of the smoothing buffer
- d) source packets at the input of the 1394 receiver
- e) reconstructed timing for the TS
- b-c: Delay in smoothing buffer
- c-d: Delay from transmitter
- d-e: Delay in receiver buffer

The clock frequency for transferring the bytes of a TSP may be different in every situation.



### – 10 –

## Annex A (informative)

## Buffering

## A.1 Buffer needed to compensate jitter introduced by the transmitter

The TSP packet can be sent to the application by the receiver as soon as the CRC of the isochronous packet is carried out. The buffer size needed to compensate jitter introduced by the transmitter is given by the following relation:

buf\_size = (R\_bus) \* (max\_jitter ) + (B\_granularity)

where

R\_bus is the allocated data rate on the interface;

Max\_jitter is the maximum 1394\_jitter (~ 311  $\mu$ s) minus the minimum time needed to transmit one bus packet;

B\_granularity is the size of one bus packet.

The necessary buffer size will be largest with high transmission rates (several TSPs per cycle) and high clock frequencies of the bus (400 Mbit/s).

In Table A.1, the buffer size is given for some transmission rates.

## A.2 Buffer needed to compensate jitter introduced by smoothing

The buffer needed to compensate jitter from the smoothing buffer is calculated with the following assumptions:

- the smoothing\_buffer\_descripter has a default value of 1 536 bytes;
- maximum jitter from the RTI is 50  $\mu$ s (p-p);
- contribution of auxiliary data (SI) is restricted to one source packet.

In Table A.2, the buffer size is given for some transmission rates.

### A.3 Default buffer size in the receiver

The default value of the buffer size in the IEEE 1394 receiver is

328 bytes (tentative)	for low bit rate applications;
3 264 bytes	for MPEG2-TS as specified in DVB;
32 kbytes (tentative)	where >3 264 bytes are needed.

With the default value of 3 264 bytes for MPEG2-TS transmission, a complete TS (without smoothing) with a bit rate of at least 60 Mbit/s can be transmitted or a single programme with a bit rate of up to 24 Mbit/s (with smoothing).

Note that 17 source packets can be stored in 3 264 bytes.

Transmission rate TSP/cycle	Transmission rate Mbit/s	Minimum buffer size bytes
1/8	1,504	82
1/4	3,008	165
1/2	6,016	328
1	12,032	654
2	24,064	1 296
3	36,096	1 927
4	48,128	2 547
5	60,160	3 154

# Table A.1 – Minimum buffer size needed to compensate jitter originating from the IEEE 1394 transmitter

- 11 -

NOTE 1 The buffer size above does not include the size which depends on the reading out data rate.

NOTE 2 The clock frequency on the bus is 400 MHz.

# Table A.2 – Minimum buffer size needed to compensate jitter originating from the smoothing buffer (including RTI and AUX packet)

Transmission rate TSP/cycle	Transmission rate Mbit/s	Minimum buffer size bytes
1/8	1,504	1 733
1/4	3,008	1 743
1/2	6,016	1 762
1	12,032	1 799
2	24,064	1 874
3	36,096	1 950
4	48,128	2 025
5	60,160	2 100

## **Bibliography**

The following documents contain additional information related to this standard:

- [1] IEC 61834-1, Recording Helical-scan digital video cassette recording system using 6,35 mm magnetic tape for consumer use (525-60, 625-50, 1125-60 and 1250-50 systems) Part 1: General specifications
- [2] IEC 61834-9, Recording Helical-scan digital video cassette recording system using 6,35 mm magnetic tape for consumer use (525-60, 625-50, 1125-60 and 1250-50 systems) – Part 9: DVB format
- [3] IEC 61834-10, Recording Helical-scan digital video cassette recording system using 6,35 mm magnetic tape for consumer use (525-60, 625-50, 1125-60 and 1250-50 systems) Part 10: DTV format
- [4] DVB document A001, August 1994, *Implementation guidelines for the use of MPEG2 systems, Video and Audio in Satellite and Cable Broadcasting applications in Europe*



Standards Survey

The IEC would like to offer you the best quality standards possible. To make sure that we continue to meet your needs, your feedback is essential. Would you please take a minute to answer the questions overleaf and fax them to us at +41 22 919 03 00 or mail them to the address below. Thank you!

Customer Service Centre (CSC)

International Electrotechnical Commission 3, rue de Varembé 1211 Genève 20 Switzerland

or

L

Fax to: IEC/CSC at +41 22 919 03 00

Thank you for your contribution to the standards-making process.



Nicht frankieren Ne pas affranchir



Non affrancare No stamp required

RÉPONSE PAYÉE

SUISSE

Customer Service Centre (CSC) International Electrotechnical Commission 3, rue de Varembé 1211 GENEVA 20 Switzerland

Q1	Please report on <b>ONE STANDARD</b> at <b>ONE STANDARD ONLY</b> . Enter the enumber of the standard: (e.g. 60601-	nd xact 1-1)	Q6	If you ticked NOT AT ALL in Questic the reason is: <i>(tick all that apply)</i>	on 5					
		,		standard is out of date						
				standard is incomplete						
				standard is too academic						
Q2	Please tell us in what capacity(ies) yo		standard is too superficial							
	bought the standard (tick all that appl	ly).		title is misleading						
				I made the wrong choice						
	purchasing agent			other						
	librarian									
	researcher									
	design engineer		07	Please assess the standard in the						
	safety engineer		ч.	following categories, using						
	testing engineer			the numbers:						
	marketing specialist			(1) unacceptable,						
	other			(2) below average, (3) average						
				(4) above average,						
Q3	l work for/in/as a:			(5) exceptional,						
	(tick all that apply)			(6) not applicable						
		_		timeliness						
	manufacturing			quality of writing						
	consultant			technical contents						
	government			logic of arrangement of contents						
	test/certification facility			tables, charts, graphs, figures						
	public utility	U 		other						
	education									
	military									
	otner		Q8	I read/use the: (tick one)						
Q4	This standard will be used for:			French text only						
	(tick all that apply)			English text only						
		~		both English and French texts						
	general reference			-						
	product research									
	product design/development		~~							
	specifications		Qa	Please snare any comment on any aspect of the IEC that you would lik	۵					
				us to know:	C					
	technical documentation									
	thesis									
	manufacturing									
	other									
Q5	This standard meets my needs:									
	(lick Ulle)									
	not at all									
	nearly									
	fairly well									
	exactly									

French text only	
English text only	
both English and French texts	

- nt on any would like
  - ..... ..... ..... ..... ..... ..... ..... .....

LICENSED TO MECON Limited. - RANCHI/BANGALORE FOR INTERNAL USE AT THIS LOCATION ONLY, SUPPLIED BY BOOK SUPPLY BUREAU.



ICS 35.200; 33.160.01