



Edition 1.0 2014-04

Copyrighted material licensed to BR Demo by Thomson Reuters (Scientific), Inc., subscriptions.techstreet.com, downloaded on Nov-27-2014 by James Madison. No further reproduction or distribution is permitted. Uncontrolled when print

INTERNATIONAL STANDARD

Multimedia systems and equipment – Colour measurement and management – Part 12-2: Simple metadata format for identification of colour gamut





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office	Tel.: +41 22 919 02 11
3, rue de Varembé	Fax: +41 22 919 03 00
CH-1211 Geneva 20	info@iec.ch
Switzerland	www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.





Edition 1.0 2014-04

INTERNATIONAL STANDARD

Multimedia systems and equipment – Colour measurement and management – Part 12-2: Simple metadata format for identification of colour gamut

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

ICS 17.180.20; 33.160

ISBN 978-2-8322-1481-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

- 2 -

FOR	EWORD	3
INTF	RODUCTION	5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Simple description of gamut	7
5	Relationship with IEC 61966-12-1	9
Anno	ex A (informative) Conversion from IEC 61966-12-2 to IEC 61966-12-1 simple profile	11
Ann	ex B (informative) Example of simple metadata format and conversion to IEC 61966-12-1 simple profile	13
Bibli	ography	17
Figu	re 1 – The colour gamut of additive three primary colours type display	8
Figu	re 2 – IEC 61966-12-1 full/medium profile	9
Figu	re 3 – IEC 61966-12-1 simple profile and IEC 61966-12-2	9
Tabl	le 1 – Simple metadata format for identification of colour gamut	7
Tabl	e 2 – Differences of IEC 61966-12-1 simple profile and IEC 61966-12-2	10
Tabl	le B.1 – Colour gamut for IEC 61966-2-5 opRGB	13
Tabl	le B.2 – Encoded simple metadata format	13
Tabl	le B.3 – Conversion result to CIE-XYZ values for five colour vertices	14
Tabl	e B.4 – Example for the header	14
Tabl	e B.5 – Example for the header of description of gamut geometry	14
Tabl	e B.6 – Example of definition of vertices	15
Tabl	e B.7 – Example of encoded colour space coordinates for vertices	15

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MULTIMEDIA SYSTEMS AND EQUIPMENT – COLOUR MEASUREMENT AND MANAGEMENT –

Part 12-2: Simple metadata format for identification of colour gamut

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61966-12-2 has been prepared by technical area 2: Colour measurement and management, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

CDV	Report on voting
100/2129/CDV	100/2276/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

A list of all parts of the IEC 61966 series, published under the general title *Multimedia* systems and equipment – Colour measurement and management, can be found on the IEC website.

- 4 -

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

New technologies in capturing and displaying wide-gamut colour images enable a new market of wide-gamut video colour content creation. Recent video standards for wide gamut colour space encoding such as IEC 61966-2-4 (xvYCC) were developed in order to be able to distribute content with a colour gamut that is extended with respect to classical colour gamuts such as defined by standards ITU-R BT.601 (standard definition television) and ITU-R BT.709 (high definition television). With the increasing popularity of wide gamut and high dynamic range contents and displays, the variety of colour gamuts of displays is expected to increase. This issue can be an obstacle to adoption of wide-gamut video colour contents in professional content creation since the compatibility of the contents to the employed displays, as well as the compatibility among different displays, is not ensured. The term display includes here any video colour reproduction equipment, such as direct view displays and projectors. Thanks to improvements in technology, the variety of colour gamuts and colour reproduction capacities of displays increases while the colour gamut and the colour encoding rules of existing colour space encoding standards are fixed.

To address this issue, IEC 61966-12-1: "Metadata for identification of colour gamut (Gamut ID)" specifies a colour gamut metadata scheme for video systems including information for colour reproduction. This metadata can apply to video content or displays. More specifically, improvements can be achieved if the wide-gamut colour content is created with the knowledge of the display colour gamut as well as if the colour reproduction in the display is done with the knowledge of the colour gamut of the pictorial content.

IEC 61966-12-1 has the capability to describe arbitrary 3D colour gamuts in a given colour space and include the full/medium profile for professional use and the simple profile for consumer use with easier product implementation. This approach is effective, but some ambiguities can occur in practical use. For example, if typical CE devices are able to decode the simple profile only, due to CPU and software limitations.

In this case, even if a sender device and a receiver device are "based on IEC 61966-12-1 standard",

- a) the receiver device cannot handle the Gamut ID of incoming contents, if the sender device sends only full or medium profile.
- b) the sender device should convert a full profile to a simple one for CE-devices, if the receiver can receive the simple profile only. But the conversion is not possible for all the cases.

Therefore, a simple Gamut ID profile standard of this standard has been developed to address this problem.

For published parts of this series of standards refer to the IEC website.

MULTIMEDIA SYSTEMS AND EQUIPMENT – COLOUR MEASUREMENT AND MANAGEMENT –

Part 12-2: Simple metadata format for identification of colour gamut

1 Scope

This part of IEC 61966 specifies the colour gamut metadata format for video systems intended for use in CE (Consumer Electronics) devices. The metadata specified in this part of IEC 61966 is limited to the gamut description of additive three primary colours type displays whose white and black points have the same chromaticity. It is fundamentally based on the conventional VESA-EDID format.

When associated with content, the simple metadata format defines the gamut for which the content was created. It can be used by the display for controlled colour reproduction even if the display's colour gamut is different from that of the content.

When associated with a display, the simple metadata format defines the display colour gamut. It can be used during content creation to enable improved colour reproduction.

This standard provides the simplest, but unambiguous solution for typical CE devices that are based on colour gamut information communication.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-845, International Electrotechnical Vocabulary – Part 845: Lighting

IEC 61966-12-1:2011, Multimedia systems and equipment – Colour measurement and management – Part 12-1: Metadata for identification of colour gamut (Gamut ID)

IEC 61966-2-4, Multimedia systems and equipment – Colour measurement and management – Part 2-4: Colour management – Extended-gamut YCC colour space for video applications – xvYCC

ISO 15076-1:2005, Image technology colour management – Architecture, profile format and data structure – Part 1: Based on ICC.2010

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-845, as well as the following apply.

3.1

content

set of video signals in production, post-production or consumption

3.2

colour gamut

range of colours achievable on a given colour reproduction medium (or present in an image of that medium) under a given set of viewing conditions

Note 1 to entry: It is a volume in colour space.

3.3

gamut mapping

mapping of the colour-space coordinates of the elements of a source image to colour-space coordinates of the elements of a reproduction to compensate for differences in the source and output medium colour gamut capability

4 Simple description of gamut

Additive three primary colours gamut can be specified by four combinations of CIE-xy chromaticity values of red, green, blue and white. The gamut is assumed to have the characteristic that combining equal amounts of the three primaries (red, green, blue) produces the chromaticity of white. These values can be encoded according to the gamut CIE-xy chromaticity values used in VESA ENHANCED EXTENDED DISPLAY IDENTIFICATION DATA STANDARD (Defines EDID Structure Version 1, Revision 4). The description includes eight values (CIE-xy chromaticity values for each red, green, blue and white) with 10-bit fixed point form in the range of 0.0-1.0. These display primary and the white point CIE-xy chromaticity values should be measured in such a way as to minimize the contribution from the display black. In addition to VESA-EDID format, the information of White Absolute Luminance (WAL) and Black Level Ratio (BLR) are included. WAL value is defined in cd/m² and denoted as Y_w , and encoded into 16-bit unsigned integer form. BLR is defined as Equation (1), and encoded into 16-bit fixed point form in the range of 0.0-1.0.

$$BLR = \left(Y_K / Y_W\right) \tag{1}$$

where

 Y_{κ} is the luminance of black shown in Figure 1;

 Y_w is the luminance of white shown in Figure 1.

Table 1 shows the total metadata which includes the VESA-EDID compatible CIE-xy chromaticity values of red, green, blue and white and BLR and WAL value. The total size of this format is 14 B.

Byte# hex	Size B	Colour characteristic		Description							
			7	6	5	4	3	2	1	0	
00	1	Red_x, Red_y, Green_x, Green_y bits1 & bits0	Rx1	Rx0	Ry1	Ry0	Gx1	Gx0	Gy1	Gy0	
01	1	Blue_x, Blue_y, White_x, White_y bits1 & bits0	Bx1	Bx0	By1	By0	Wx1	Wx0	Wy1	Wy1	
02	1	Red_x bit9 - bit2	Rx9	Rx8	Rx7	Rx6	Rx5	Rx4	Rx3	Rx2	
03	1	Red_y bit9 - bit2	Ry9	Ry8	Ry7	Ry6	Ry5	Ry4	Ry3	Ry2	

 Table 1 – Simple metadata format for identification of colour gamut

Byte# hex	Size B	Colour characteristic	Description							
			7	6	5	4	3	2	1	0
04	1	Green_x bit9 – bit2	Gx9	Gx8	Gx7	Gx6	Gx5	Gx4	Gx3	Gx2
05	1	Green_y bit9 – bit2	Gy9	Gy8	Gy7	Gy6	Gy5	Gy4	Gy3	Gy2
06	1	Blue_x bit9 – bit2	Bx9	Bx8	Bx7	Bx6	Bx5	Bx4	Bx3	Bx2
07	1	Blue_y bit9 – bit2	Ву9	By8	By7	By6	By5	By4	By3	By2
08	1	White_x bit9 – bit2	Wx9	Wx8	Wx7	Wx6	Wx5	Wx4	Wx3	Wx2
09	1	White_y bit9 – bit2	Wy9	Wy8	Wy7	Wy6	Wy5	Wy4	Wy3	Wy2
		White Absolute Luminance								
0A	1	bit15 – bit8	WAL15	WAL14	WAL13	WAL12	WAL11	WAL10	WAL9	WAL8
		(16 bit unsigned integer)								
		White Absolute Luminance								
0B	1	bit7 – bit0	WAL7	WAL6	WAL5	WAL4	WAL3	WAL2	WAL1	WAL0
		(16 bit unsigned integer)								
0C	1	Black Level Ratio bit15 - bit8 (16 bit fixed point)	BLR15	BLR14	BLR13	BLR12	BLR11	BLR10	BLR9	BLR8
0D	1	Black Level Ratio bit7 - bit0 (16 bit fixed point)	BLR7	BLR6	BLR5	BLR4	BLR3	BLR2	BLR1	BLR0

- 8 -



Figure 1 – The colour gamut of additive three primary colours type display

IEC 61966-12-2:2014 © IEC 2014 - 9 -

5 Relationship with IEC 61966-12-1

A content gamut is usually smaller than a colour encoding gamut of today's extended-gamut colour space such as IEC 61966-2-4 xvYCC. If there is no description of an actual colour gamut for some content, it is possible that gamut mapping will use the colour encoding gamut as the content gamut, which can cause some problems. IEC 61966-12-1: "The Gamut ID metadata" solves this problem by associating an explicit description of an actual content gamut to contents. IEC 61966-12-1 has a full, medium and simple profile.

The full profile and the medium profile have high flexibility for describing 3D-shapes of complicated content gamuts in a colour space as shown in Figure 2. As a consequence IEC 61966-12-1 full / medium profiles are well suited for some professional use. In addition, the IEC 61966-12-1 provides simple profile formats that are limited to three primary type colour gamuts, as shown in Figure 3.

However, the IEC 61966-12-1 simple profile is 77 B and still large for the CE devices. This standard is therefore limited to the CIE-xy chromaticity values of additive three primary colour gamuts and has a reduced size of 14 B.



Figure 2 – IEC 61966-12-1 full/medium profile



Figure 3 – IEC 61966-12-1 simple profile and IEC 61966-12-2

	IEC 61966-12-1 simple profile	IEC 61966-12-2
Size	77 B (Header: 17 B + Gamut description: 60 B)	14 B (Gamut description only)
Coordinate's format	 CIE-XYZ tristimulus values of 5 colours (red, green, blue, white, black) 	 CIE-xy chromaticity values of four colours (red, green, blue, white)
	- s15Fixed16Number	 VESA-EDID compatible
	(see ICC profiles in ISO 15076-1:2005)	 16-bit unsigned integer form
		 16-bit fixed point form in the range of 0.0-1.0

Table 2 – Differences of IEC 61966-12-1 simple profile and IEC 61966-12-2

- 10 -

Annex A

(informative)

Conversion from IEC 61966-12-2 to IEC 61966-12-1 simple profile

IEC 61966-12-2 can be converted to the IEC 61966-12-1 simple profile. This annex shows an example of the conversion method. The conversion equations calculate five CIE-XYZ tristimulus values of red, green, blue, white and black colour vertices from four CIE-xy chromaticity values of the red, green, blue and white colour vertices, WAL and BLR values. It should be noted that the inverse conversion cannot be uniquely defined when the additivity rule of the three primary colours mixture is not guaranteed.

 x_i and y_i are xy coordinates of colours described in IEC 61966-12-2. X_i , Y_i and Z_i are XYZ coordinates of IEC 61966-12-1 simple profile. In both coordinate systems, i = R,G,B,W, or K which denotes red, green, blue, white or black colour vertices.

The conversion process has the following four steps:

a) In the first step, (XYZ) values for white colour are calculated. Here, absolute Y_w value information from IEC 61966-12-2 should be used. We can calculate (XYZ) values using Yw value and xy chromaticity coordinates for white colour as Equation (A.1).

$$\begin{bmatrix} X_W \\ Y_W \\ Z_W \end{bmatrix} = Y_W \begin{bmatrix} \frac{x_W}{y_W} \\ 1 \\ \frac{1 - x_W - y_W}{y_W} \end{bmatrix}$$
(A.1)

b) In the second step, (XYZ) values for black colour are calculated. First, Y_K can be obtained from Y_W and BLR values as Equation (A.2).

$$Y_{K} = BLR \times Y_{W} \tag{A.2}$$

Then, (XYZ) values of black can be Y_K and xy chromaticity coordinates can be calculated as Equation (A.3) for we assume black colour has the same chromaticity as white.

$$\begin{bmatrix} X_K \\ Y_K \\ Z_K \end{bmatrix} = Y_K \begin{bmatrix} \frac{x_W}{y_W} \\ 1 \\ \frac{1 - x_W - y_W}{y_W} \end{bmatrix}$$
(A.3)

c) Then in the third step, assuming additive three primary colours, Y values for red, green and blue colours without the offset value by black are estimated using the calculated value of white and black colours as Equation (A.4). Here, -1 denotes the inverse of the 3 x 3 matrix.

IEC 61966-12-2:2014 © IEC 2014

$$\begin{bmatrix} Y_R - Y_K \\ Y_G - Y_K \\ Y_B - Y_K \end{bmatrix} = \begin{bmatrix} \frac{x_R}{y_R} & \frac{x_G}{y_G} & \frac{x_B}{y_B} \\ 1 & 1 & 1 \\ \frac{1 - x_R - y_R}{y_R} & \frac{1 - x_G - y_G}{y_G} & \frac{1 - x_B - y_B}{y_B} \end{bmatrix}^{-1} \begin{bmatrix} X_W - X_K \\ Y_W - Y_K \\ Z_W - Z_K \end{bmatrix}$$
(A.4)

d) In the last step, (XYZ) values of red, green and blue colours are calculated using the estimated luminance of each colour in step two, and then black offset values are added as shown in Equations (A.5), (A.6) and (A.7).

- 12 -

$$\begin{bmatrix} X_R \\ Y_R \\ Z_R \end{bmatrix} = \begin{bmatrix} \frac{X_R}{y_R} \\ 1 \\ \frac{1 - x_R - y_R}{y_R} \end{bmatrix} (Y_R - Y_K) + \begin{bmatrix} X_K \\ Y_K \\ Z_K \end{bmatrix}$$
(A.5)

$$\begin{bmatrix} X_G \\ Y_G \\ Z_G \end{bmatrix} = \begin{bmatrix} \frac{x_G}{y_G} \\ 1 \\ \frac{1 - x_G - y_G}{y_G} \end{bmatrix} (Y_G - Y_K) + \begin{bmatrix} X_K \\ Y_K \\ Z_K \end{bmatrix}$$
(A.6)

$$\begin{bmatrix} X_B \\ Y_B \\ Z_B \end{bmatrix} = \begin{bmatrix} \frac{X_B}{y_B} \\ 1 \\ \frac{1 - x_B - y_B}{y_B} \end{bmatrix} (Y_B - Y_K) + \begin{bmatrix} X_K \\ Y_K \\ Z_K \end{bmatrix}$$
(A.7)

At this step, all five CIE-XYZ tri-stimulus values of red, green, blue, white and black colour vertices which are needed in the IEC 61966-12-1 simple profile are defined. Each (XYZ) value should be encoded into s15Fixed16Number format.

Annex B

(informative)

Example of simple metadata format and conversion to IEC 61966-12-1 simple profile

This annex provides an example of the simple metadata format. This example describes the theoretical gamut of IEC 61966-2-5 opRGB and the encoded data. Table B.1 shows the CIE-xy chromaticity coordinates for four colour vertices: white, red, green, blue of opRGB colour space.

	CIE-x	CIE-y
White	0,312 7	0,329 0
Red	0,640 0	0,330 0
Green	0,210 0	0,710 0
Blue	0,150 0	0,060 0

Table B.1 – Colour gamut for IEC 61966-2-5 opRGB

White absolute luminance values of white and black level are160 cd/m² and 0,4 cd/m².

The simple metadata format calculated from the chromaticity values CIE-xy coordinates for the above four colour vertices is shown in Table B.2. The xy chromaticity values for red, green, blue and white colour vertices are encoded into fixed 10 bit values. The white absolute luminance is encoded into a 16-bit unsigned integer form and the black level ratio is encoded into a 16-bit fixed point form in the range of 0.0-1.0.

Tab	e B.	2 –	Encod	led s	simple	e met	tada	ita f	format	
-----	------	-----	-------	-------	--------	-------	------	-------	--------	--

Byte# hex	Size B	Colour characteristic	Description							
			7	6	5	4	3	2	1	0
00	1	Red/Green bits1 and bits0	1	1	1	0	1	1	1	1
01	1	Blue/White bits1 and bits0	1	0	0	1	0	0	0	1
02	1	Red_x bit9 to bit2	1	0	1	0	0	0	1	1
03	1	Red_y bit9 to bit2	0	1	0	1	0	1	0	0
04	1	Green_x bit9 to bit2	0	0	1	1	0	1	0	1
05	1	Green_y bit9 to bit2	1	0	1	1	0	1	0	1
06	1	Blue_x bit9 to bit2	0	0	1	0	0	1	1	0
07	1	Blue_y bit9 to bit2	0	0	0	0	1	1	1	1
08	1	White_x bit9 to bit2	0	1	0	1	0	0	0	0
09	1	White_y bit9 to bit2	0	1	0	1	0	1	0	0
0A	1	White absolute luminance bit15 - bit8 (16-bit unsigned integer)	0	0	0	0	0	0	0	0
0B	1	White absolute luminance bit7 - bit0 (16-bit unsigned integer)	1	0	1	0	0	0	0	0
0C	1	Black level ratio bit15 - bit8 (16-bit fixed point)	0	0	0	0	0	0	0	0
0D	1	Black level ratio bit7 - bit0 (16-bit fixed point)	1	0	1	0	0	1	0	0

The XYZ tristimulus values for five colour vertices: white, black, red, green, blue of opRGB colour space can be decoded according to Annex A (see Table B.3).

	CIE-X	CIE-Y	CIE-Z
White	151,928 783	160,000 000	174,243 323
Black	0,380 193	0,400 391	0,436 034
Red	92,156 976	47,760 013	4,779 668
Green	30,047 025	100,715 680	11,750 826
Blue	30,485 168	12,325 089	158,584 898

Table B.3 – Conversion	result to CIE-XYZ values	for five colour vertices
------------------------	--------------------------	--------------------------

The resultant converted Gamut ID metadata in the simple profile of IEC 61966-12-1 format is shown below. This format includes three headers described in Table B.4, Table B.5, and Table B.6 and CIE XYZ tristimulus values of five colours in Table B.7. These XYZ values are basically the same values as in Table B.3, and encoded into s15Fixed 16Number format.

Byte # hex	Size B	Symbols			Values						
			7	6	5	4	3	2	1	0	
00	1	N, P	0	1	0	0	0	0	1	1	
			R	ID_PROFILE		ID_PRECISION		ID_GBD_SPACE			
01	1		Byte	# of st	art of	the des	criptior	n of gar	nut		0h00
02	1	10_0	geom	etry							0h09
03	1		Byte	# of st	art of	the des	criptior	n of col	our		0h00
04	1		repro	ductio	n						0h00
05	1		Deee	much (0h00
06	1		Rese	Keservea. Shall de zero.							0h00
07	1		Deee	much (0h00
08	1	1	Rese	ivea. S	snall D	e zero.					0h00

Table B.4 – Example for the header

Table B.5 – Example for the header of description of gamut geometry

Byte # hex	Size B	Symbol	Description	Values
09	1		Dute # of start of varians	0h00
0A	1	10_1	Byte # of start of vertices	0h0D
0B	1		Reserved	0h00
0C	1		Reserved	0h00

Byte # hex	Size B	Symbol	Description	Values
0D	1	V	Total number of vertices	0h00
0E	1	V		0h05
0F	1	P	Shall be zero	0h00
10	1	K		0h00
11	$\left\lceil 3VN/8 \right\rceil = 60$		3V encoded colour space coordinates defining V vertices	See Table D.5 of IEC 61966- 1:2011

Table B.6 – Example of definition of vertices

Table B.7 – Example of encoded colour space coordinates for vertices

Byte # hex	Value hex	Description	
11	00		
12	97	White X	
13	ED		
14	C4		
15	00		
16	A0		
17	00	vvnite Y	
18	00	1	
19	00		
1A	AE	- White Z	
1B	3E		
1C	4A		
1D	00	Black X	
1E	00		
1F	61		
20	54		
21	00		
22	00	Dia sk V	
23	66	DIACK	
24	80	1	
25	00		
26	00		
27	6F	DIACK Z	
28	9F		
29	00		
2A	5C	Ded Y	
2B	28	Ked X	
2C	2F		
2D	00		
2E	2F	Red Y	
2F	C2		

Copyrighted material licensed to BR Demo by Thomson Reuters (Scientific), Inc., subscriptions.techstreet.com, downloaded on Nov-27-2014 by James Madison. No further reproduction or distribution is permitted. Uncontrolled when print

Byte # hex	Value hex	Description	
30	90		
31	00		
32	04	Red Z	
33	C7		
34	98		
35	00		
36	1E	Croop X	
37	0C	Green X	
38	09		
39	00	Green Y	
ЗA	64		
3B	B7		
3C	36		
3D	00		
3E	0B	Green Z	
3F	C0	Gieen Z	
40	36		
41	00		
42	1E	Blue X	
43	7C	Dide X	
44	33		
45	00		
46	0C	Blue Y	
47	53	Dide i	
48	39		
49	00		
4A	9E	Blue 7	
4B 95			
4C	BB		

Bibliography

IEC 61966-2-5, Multimedia systems and equipment – Colour measurement and management – Part 2-5: Colour management – Optional RGB colour space – opRGB

ISO 22028-1, Photography and graphic technology – Extended colour encodings for digital image storage, manipulation and interchange – Part 1: Architecture and requirements

ITU-R BT.601, Studio encoding parameters of digital television for standard 4:3 and wide screen 16:9 aspect ratios

ITU-R BT.709, Parameter values for the HDTV standards for production and international programme exchange

VESA ENHANCED EXTENDED DISPLAY IDENTIFICATION DATA STANDARD (Defines EDID Structure Version 1, Revision 4)

Copyrighted material licensed to BR Demo by Thomson Reuters (Scientific), Inc., subscriptions.techstreet.com, downloaded on Nov-27-2014 by James Madison. No further reproduction or distribution is permitted. Uncontrolled when print

Copyrighted material licensed to BR Demo by Thomson Reuters (Scientific), Inc., subscriptions.techstreet.com, downloaded on Nov-27-2014 by James Madison. No further reproduction or distribution is permitted. Uncontrolled when print

INTERNATIONAL ELECTROTECHNICAL COMMISSION

3, rue de Varembé PO Box 131 CH-1211 Geneva 20 Switzerland

Tel: + 41 22 919 02 11 Fax: + 41 22 919 03 00 info@iec.ch www.iec.ch