

INTERNATIONAL STANDARD



Audio, video and related equipment – Determination of power consumption – Part 4: Video recording equipment



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



IEC 62087-4

Edition 1.0 2015-06

INTERNATIONAL STANDARD



**Audio, video and related equipment – Determination of power consumption –
Part 4: Video recording equipment**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.160.10

ISBN 978-2-8322-2684-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| | |
|--|----|
| FOREWORD..... | 3 |
| INTRODUCTION..... | 5 |
| 1 Scope..... | 6 |
| 2 Normative references | 6 |
| 3 Terms, definitions and abbreviations | 6 |
| 3.1 Terms and definitions..... | 6 |
| 3.2 Abbreviations..... | 7 |
| 4 Specification of operating modes and functions | 7 |
| 4.1 General..... | 7 |
| 4.2 Auto power down function | 8 |
| 5 Measuring conditions for video recorders..... | 9 |
| 5.1 Input signal | 9 |
| 5.1.1 General | 9 |
| 5.1.2 RF test signal | 9 |
| 5.1.3 Broadband input signal | 9 |
| 5.2 Input terminals..... | 9 |
| 5.2.1 Analogue terrestrial input terminal | 9 |
| 5.2.2 Cable television input terminal..... | 10 |
| 5.2.3 Digital terrestrial input terminal | 10 |
| 5.2.4 Satellite input terminal | 10 |
| 5.3 Measurement procedure | 10 |
| 5.3.1 General measuring conditions | 10 |
| 5.3.2 Stabilization..... | 10 |
| 5.3.3 Environmental conditions..... | 10 |
| 5.3.4 Setup..... | 10 |
| 5.3.5 Power measurements | 11 |
| Bibliography..... | 15 |
| Figure 1 – Auto power down function | 14 |
| Table 1 – Operating modes and functions | 8 |
| Table 2 – Matrix for multituner VRs | 12 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**AUDIO, VIDEO AND RELATED EQUIPMENT –
DETERMINATION OF POWER CONSUMPTION –****Part 4: Video recording equipment****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62087-4 has been prepared by technical area 12: AV energy efficiency and smart grid applications, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This first edition of IEC 62087-4 cancels and replaces Clause 7 of IEC 62087:2011. This standard together with IEC 62087-1 to IEC 62087-3 and IEC 62087-5 to IEC 62087-6 cancels and replaces IEC 62087:2011. This International Standard constitutes a technical revision.

This edition includes significant technical changes with respect to Clause 7 of IEC 62087:2011. The changes include fundamental and extensive revisions to cover video recorders such as DVD and BD types as well as recorders with removable solid state memory. Clause 7 has been revised in its entirety.

The text of this standard is based on the following documents:

| FDIS | Report on voting |
|---------------|------------------|
| 100/2469/FDIS | 100/2499/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62087 series, published under the general title *Audio, video, and related equipment – Determination of power consumption*, can be found on the IEC website.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

This part of IEC 62087 specifies methods of measurement for the power consumption of video recording equipment for consumer use.

IEC 62087:2011 revises methods for measuring power consumption of set top boxes mainly in the modes of On mode and Standby-active, high mode. These modes correspond to the active modes which are defined in IEC 62542:2013.

This standard has been divided into multiple parts. At the time of publication of this part, the following parts are planned or published:

- Part 1: General
- Part 2: Signals and media
- Part 3: Television sets
- Part 4: Video recording equipment
- Part 5: Set-top boxes (STB)
- Part 6: Audio equipment

AUDIO, VIDEO AND RELATED EQUIPMENT – DETERMINATION OF POWER CONSUMPTION –

Part 4: Video recording equipment

1 Scope

This part of IEC 62087 specifies methods of measurement for the power consumption of video recording equipment with removable media. It specifies the different modes of operation which are relevant for measuring power consumption.

The methods of measurement are applicable only for equipment which can be connected to the mains.

The measuring conditions in this standard represent the normal use of the equipment and may differ from specific conditions, as specified, for example, in safety standards.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60107-1:1997, *Methods of measurement on receivers for television broadcast transmissions – Part 1: General considerations – Measurements at radio and video frequencies*

IEC 62087-1:2015, *Audio, video, and related equipment – Methods of measurement for power consumption – Part 1: General*

IEC 62216:2009, *Digital terrestrial television receivers for the DVB-T system*

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62087-1:2015, as well as the following apply.

3.1.1

additional functions

functions that are not required for the basic operation of the equipment

3.1.2

buffering

temporary storage of video and audio streams in some form of memory in order to perform time shifting functions

3.1.3

hard disk drive

non removable media with a spinning disk for recording video and audio

3.1.4**removable media**

write-once or rewritable device to store audio, video or other data via a standardized read/write interface usable in all devices with the respective interface

Note 1 to entry: Examples include optical discs (DVD, BD), memory cards, video tape cassettes.

3.1.5**television set****TV**

equipment for the reception and display of television broadcast and similar services for terrestrial, cable, satellite and broadband network transmission of analogue and/or digital signals

Note 1 to entry: A television set may include additional functions that are not required for its basic operation.

3.1.6**time shifting**

capability of a device to allow playback type functions with real time broadcast

Note 1 to entry: Such functions may include fast forward, review (rewind), pause and slow motion.

3.1.7**video recording equipment**

equipment for the recording and reproduction of video and audio signals on a recording medium

Note 1 to entry: Equipment with only playback function are included as well.

Note 2 to entry: Examples are video cassette recorder (VCR) or a digital versatile disc (DVD) player or recorder.

3.2 Abbreviations

| | |
|-----|-----------------------------------|
| ' | Prime |
| BD | Blu-ray Disc™ ¹ |
| DVD | Digital Versatile Disc |
| EPG | Electronic Program Guide |
| IP | Internet Protocol |
| HD | High Definition (720 p or better) |
| LNB | Low Noise Block converter |
| PF | Picture Failure point |
| RF | Radio Frequency |
| SD | Standard Definition |
| TV | TeleVision set |
| VCR | Video Cassette Recorder |
| VR | Video Recorder |

4 Specification of operating modes and functions**4.1 General**

Table 1 contains the operating modes and functions for video recorders.

¹ Blu-ray Disc™ is a trade mark of the Blue-ray Disc Association. This information is given for the convenience of users of this document and does not constitute an endorsement by IEC of the product named.

4.2 Auto power down function

An auto power down feature may be implemented on a VR to power down into a Partial On mode after a predetermined time and possibly predetermined conditions. Such a feature should be referred to as auto power down.

Table 1 – Operating modes and functions

| Power | Mode | Sub-mode | Function(s) | Description |
|-------|--------------|----------------------|--|---|
| 0 W | Disconnected | Disconnected | Disconnect | The equipment is disconnected from all external power sources. |
| ≥0 W | Off | Off | Off | The equipment is connected to an external power source and provides no functions that depend on a power source. The equipment cannot be switched into any other mode with the remote control unit, or an external or internal signal. Note that some power may be consumed if an EMC filter or other components exist on the source side of the power switch. |
| >0 W | Partial On | Standby-passive | <ul style="list-style-type: none"> – Wake on – remote control – internal signal | The equipment is connected to an external power source and does not provide its primary functions. The equipment can be switched into another mode with the remote control unit or an internal signal, but not with an external signal. |
| | | Standby-active, low | <ul style="list-style-type: none"> – Wake on – remote control – internal signal – external signal | The equipment is connected to an external power source and does not provide its primary functions. The equipment can be switched into another mode with the remote control unit, an internal signal, or an external signal. |
| | | Standby-active, high | <ul style="list-style-type: none"> – Wake on – remote control – internal signal – external signal – Data communications | The equipment is connected to an external power source and does not provide its primary functions. The equipment can be switched into another mode with the remote control unit, an internal signal, or an external signal. Additionally, the equipment is exchanging/receiving data with/from an external source. |
| | On | On-play | Playing a programme | Playing content from a build in storage device, from removable media or streamed via a device port. |
| | | On-broadcast | Pictures and sound from a broadcast | The equipment is performing the function of providing a viewer with video and audio from a broadcast. |
| | | On-record | Recording a programme from a broadcast | The equipment is connected to a power source and records a signal from an external or internal source. |
| | | On-multifunction | Recording Playing back | The equipment is performing multifunction “On-play” and/or “On-record” simultaneously. |

5 Measuring conditions for video recorders

5.1 Input signal

5.1.1 General

In general terms, input signals shall be of the strength and quality for the type of broadcast system on which the VR is intended to be used. Where a VR supports multiple broadcast systems, it shall be tested for each broadcast system in which it operates. Each measured result shall be described in the report.

5.1.2 RF test signal

5.1.2.1 General

For digital terrestrial, satellite and cable VRs, the test signal shall be a signal representative of those present in the typical environment in which the VR is intended to be used. The video and audio components of the transport stream shall be as described in 5.1.2.2 and 5.1.2.3. For analogue terrestrial, satellite and cable VRs, the signal should be typical of the type of signal the VR is designed to receive.

5.1.2.2 Video test signal

The VR shall be tested using an appropriate input signal. This signal should be at the highest resolution that the VR is capable of decoding using the most processing intensive advanced decoding standard of the intended broadcast system(s) that the VR will be used on. A description of the signal used for the test shall be included in the test report. This description shall include at a minimum, resolution, frame rate and bit rate.

If the VR under test is an HD decoder, additional testing may also be conducted with an SD input signal.

Where the VR is operating in a download or recording mode, the input signal should contain content that simulates material that would typically be downloaded or recorded.

Where a VR has a conditional access system, it should be tested whilst decoding encrypted content.

Where a VR can record other services than the one being watched, the test signal should contain sufficient services to enable this feature to be tested.

5.1.2.3 Audio test signal

The VR shall be tested using an appropriate input signal. The audio test signal should have the maximum data rate (bit/s).

The audio format used during the power measurement shall be described in the report.

5.1.3 Broadband input signal

An input signal that provides the equivalent multiplexed transport stream as an appropriate internet protocol (IP) broadband signal conforming to 5.1.2.2 and 5.1.2.3.

5.2 Input terminals

5.2.1 Analogue terrestrial input terminal

If the VR is being tested with an analogue terrestrial RF input signal, the signals used shall conform to IEC 60107-1:1997, 3.3, and shall have the input signal level set at –39 dB(mW)

when terminated with a $75\ \Omega$ resistor or at a level to provide a perceptually noise free or error free picture.

NOTE 39 dB(mW) corresponds to 70 dB(μ V).

5.2.2 Cable television input terminal

If the VR is being tested with a cable television RF input signal, the signals used shall conform to the cable television specifications for the region, and shall have the input signal level set at -49 dB(mW) with a termination of $75\ \Omega$ resistor or at a level to provide better than the picture failure point (PF) as defined in IEC 62216 for digital signals or a perceptually noise free picture or error free for analogue signals.

NOTE 49 dB(mW) corresponds to 60 dB(μ V).

5.2.3 Digital terrestrial input terminal

If the VR is being tested with a digital terrestrial RF input signal, the signals used shall conform to the broadcast specifications for the region, and shall have the input signal level set at -49 dB(mW) with a termination of $75\ \Omega$ resistor or at a level to provide better than the picture failure point (PF) as defined in IEC 62216 or a perceptually noise free picture.

5.2.4 Satellite input terminal

If the television set is being tested with a satellite input signal, the input signal level shall be set at -49 dB(mW) with a termination of $75\ \Omega$ resistor or at a level to provide better than the picture failure point (PF) as defined in IEC 62216 for digital signals or a perceptually noise free picture or error free for analogue signals.

5.3 Measurement procedure

5.3.1 General measuring conditions

The general measuring conditions including the type of power meters to be used is as per IEC 62087-1:2015 except where conditions are otherwise specified in this subclause.

5.3.2 Stabilization

The measurements shall be performed after the VR has achieved a stable condition with respect to power consumption. Refer also to IEC 62087-1:2015.

NOTE There are several ways to consider a VR stable. For example, a VR can be considered stable between 15 min and 30 min after entering into each operation mode. In this case, the time used to stabilize the VR shall be recorded in the test report. A VR can be also considered stable when any of the results of the same test repeated are within 2 %.

5.3.3 Environmental conditions

The ambient temperature shall be $23\ ^\circ\text{C} \pm 5\ ^\circ\text{C}$. Refer also to IEC 62087-1:2015.

5.3.4 Setup

The VR shall be set up in a manner to simulate a normal operating environment. In this condition, the measurement shall be made without optional peripheral devices attached to the device. The input signals to the VRs may be either live signals or generated test streams that simulate live signals that the VR is designed to receive and decode.

Where a VR can power an LNB of an antenna amplifier this power shall not be included in the measurement. Where possible this power supply should be disabled. Where it cannot be disabled isolation connectors should be used to isolate the power supply.

If required the LNB or antenna amplifier should be powered from an external power source to the VR.

If possible, any function which may work in background of any On mode function should be disabled (turned off). If possible, any function which may cause the interruption of any On mode function should also be disabled (turned off). If they cannot be disabled the measurement should be scheduled so as to avoid working such background functions during the measurement.

NOTE Examples of background and/or interrupt functions for any On mode function are:

- background software download/install;
- timer recording;
- automatic deletion of an old TV programme which was recorded.

5.3.5 Power measurements

5.3.5.1 General

The VR under test shall be measured in each applicable mode as specified below. In the case of HD VRs, testing shall be with an HD input signal. Testing with an SD input signal may also be conducted. Where the SD test is conducted on an HD VR, the result shall be recorded as $P_{AV_ON_SD}$. If possible disable the time shifting function.

Unless the power measurement is being made with removable media any other removable media not being used shall be removed.

5.3.5.2 On-broadcast

Measure the average power consumed for at least 2 min. Record this as P_{AV_ON} . Record the time used to measure the average power.

5.3.5.3 On-play

Start a playback of a previously recorded programme on the VR and measure the average power consumed for at least 2 min. Record this as P_{PL} . Record the time used to measure the average power.

Start a playback of a programme on the removable media inserted into the VR and measure the average power consumed for at least 2 min. Record this as P_{RPL} . Record the time used to measure the average power.

5.3.5.4 On-record

Start or schedule a recording. With the VR recording the programme, measure the average power consumed for at least 2 min. Record this as P_{REC_ON} . Record the time used to measure the average power.

Start or schedule a recording. With the VR recording the programme to the inserted removable media measure the average power consumed for at least 2 min. Record this as $P_{REC_RM_ON}$. Record the time used to measure the average power.

5.3.5.5 On-multifunction with a single tuner

Set the VR to record a programme while simultaneously playing back a previously recorded programme and measure the average power consumed for at least 2 min. Record this as P_{MF_ST} . Record the time used to measure the average power. Time shifting is covered in this measurement as this is the case when the VR is playing back the same program as it is recording.

NOTE The mechanism for multifunction with a single tuner is the same as for time shift or recording.

5.3.5.6 On-multifunction with a multituner

Table 2 shows the matrix that shall be used to characterize a multituner VR.

Table 2 – Matrix for multituner VRs

| | Tuner | Viewing | Add 2 nd tuner recording HD or SD | Add 3 rd tuner recording HD or SD ^a | Add 4 th tuner recording HD or SD ^a | Add <i>n</i> th tuner recording HD or SD ^a |
|-------------------------|------------------|---------|---|--|--|---|
| Sequence 1 | $P_{MFA_SD_n}$ | SD | $P_{MFA_SD_2}$ | $P_{MFA_SD_3}$ | $P_{MFA_SD_4}$ | $P_{MFA_SD_n}$ |
| Sequence 2 | $P_{MFA_HD_n}$ | HD | $P_{MFA_HD_2}$ | $P_{MFA_HD_3}$ | $P_{MFA_HD_4}$ | $P_{MFA_HD_n}$ |
| ^a If fitted. | | | | | | |

Measure the average power for at least 2 min for each of the modes in the matrix. Record the time used to measure the average power.

For SD VRs, only sequence 1 shall be performed. For HD VRs, both sequence 1 and sequence 2 shall be performed.

5.3.5.7 Standby-active, high

If possible, activate a download mode from the primary service and measure the average power consumed for at least 2 min. This measurement may require information from the manufacturer and/or service provider to ensure the transport stream contains a suitable download and instructions on how to set the VR to receive the download. Record this value as P_{SAH} . Record the time used to measure the average power.

NOTE It may not be possible to place the VR into this mode. If this is the case and the value is still required, it may have to be provided by a manufacturer's declaration.

5.3.5.8 Standby-active, low

To ensure that the VR is in standby active and not performing any downloading or recording function, the following procedure should be used.

- Put the VR into its on mode.
- If the VR is capable of scheduling a recording then schedule a recording 2 or more hours in the future.
- After 5 min in this mode, press the standby or off button on the remote control.
- Leave the VR for a minimum of 30 min or until higher power mode maintenance activities within the UUT have been completed.

Measure the average power consumed for at least 2 min. Record this as P_{SAL} . Record the time used to measure the average power. Record the time taken to switch to standby active, low.

5.3.5.9 Standby-passive

To ensure that the VR is in standby passive, the following procedure should be used.

- a) Put the VR into its On mode.
- b) If the VR is capable of scheduling a recording then schedule a recording 2 or more hours in the future.
- c) After 5 min in this mode, press the standby or off button on the remote control.
- d) Leave the VR for a minimum of 30 min or until higher power mode maintenance activities within the UUT activities have been completed.

Measure the average power consumed for at least 2 min. Record this as P_{SP} . Record the time used to measure the average power. Record the time taken to switch to Standby- passive.

NOTE The method for determining standby-active, low and standby-passive are identical as the switching into either one of these modes is the same. Which mode the VR actually switches to is actually determined by the platform in which the VR is operating. A VR with a terrestrial tuner will be more likely to be in a passive mode and a VR with a cable or satellite tuner will be more likely to be in a standby-active, low mode. Both methods are specified here to be consistent with the definitions in Table 1.

5.3.5.10 Off

Turn the VR off using the power switch, if available, and measure the average power consumed for at least 2 min. Record this as P_{OFF} . Record the time used to measure the average power.

5.3.5.11 Auto power down

If the UUT includes an auto power down feature, use the following procedure to determine the auto power down interval and the power consumption after auto power down is completed. (See Figure 1.)

- a) Place the UUT in the On mode with the auto power down function enabled. The auto power down interval is specified by the manufacturer. The auto power down interval should be reported.
- b) Stop any main functions of the UUT and start a timer to determine the auto power down interval.
- c) Allow the UUT to automatically power down.
- d) Monitor the power consumption of the UUT until the power consumption stabilizes.
- e) Stop the timer and report the auto power down interval.
- f) Measure the average power consumed for a 2 min. Record this as P_{APD} .




Figure 1 – Auto power down function

Bibliography

IEC 61938:2013, *Multimedia systems – Guide to the recommended characteristics of analogue interfaces to achieve interoperability*

IEC 62087 (all parts), *Audio, video, and related equipment – Determination of power consumption*

IEC 62087-2:2015, *Audio, video, and related equipment – Methods of measurement for power consumption – Part 2: Signals and media*

IEC 62301:2011, *Household electrical appliances – Measurement of standby power*

IEC 62542:2013, *Environmental standardization for electrical and electronic products and systems – Glossary of terms*

EN 50049-1:1998, *Domestic and Similar Electronic Equipment Interconnection Requirements: Peritelevision Connector*

SMPTE EG 1-1990 (Archived 2004), *Alignment Color Bar Test Signal for Television Picture Monitors*

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

3, rue de Varembé
PO Box 131
CH-1211 Geneva 20
Switzerland

Tel: + 41 22 919 02 11
Fax: + 41 22 919 03 00
info@iec.ch
www.iec.ch