

TECHNICAL REPORT

Semiconductor die products – Part 7: XML schema for data exchange





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00



TECHNICAL REPORT

Semiconductor die products – Part 7: XML schema for data exchange

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

U

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references.....	6
3 Definitions	6
4 General	7
5 Data exchange	7
Annex A (normative) XML schema.....	8
Annex B (informative) XML example.....	19
Bibliography.....	26

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SEMICONDUCTOR DIE PRODUCTS –**Part 7: XML schema for data exchange**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 62258-7, which is a technical report, has been prepared by IEC technical committee 47: Semiconductor devices.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
47/1887/DTR	47/1897/RVC

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62258 series, under the general title *Semiconductor die products*, can be found on the IEC website. Further parts may be added as required.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

This technical report is based on the work carried out in the ESPRIT 4th Framework project GOODDIE which resulted in the publication of the ES 59008 series of European specifications. Organizations that helped prepare this report included the ESPRIT ENCAST and IST ENCASIT projects, the Die Products Consortium, JEITA, JEDEC and ZVEI.

SEMICONDUCTOR DIE PRODUCTS –

Part 7: XML schema for data exchange

1 Scope

IEC/TR 62258-7, which is a technical report, has been developed to facilitate the production, supply and use of semiconductor die products, including:

- wafers;
- singulated bare die;
- die and wafers with attached connection structures;
- minimally or partially encapsulated die and wafers.

This report contains an XML schema that describes the elements needed for data exchange and that will allow the implementation of the requirements of IEC 62258-1, IEC 62258-5 and IEC 62258-6, as well as providing an exchange structure that is complementary to those defined in IEC 62258-2. It is also complementary to and compatible with the questionnaire in IEC/TR 62258-4.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050 (all parts), *International Electrotechnical Vocabulary*

IEC 62258-1: *Semiconductor die products – Part 1: Requirements for procurement and use*

IEC 62258-2: *Semiconductor die products – Part 2: Exchange data formats*

IEC/TR 62258-4: *Semiconductor die products – Part 4: Questionnaire for die users and suppliers*

IEC 62258-5: *Semiconductor die products – Part 5 Requirements for information concerning electrical simulation*

IEC 62258-6: *Semiconductor die products – Part 6 Requirements for information concerning thermal simulation*

3 Terms and definitions

For the purposes of this document, relevant terms, which are defined in IEC 60050, together with additional terms and acronyms as given in IEC 62258-1, apply.

4 General

The schema given in this technical report complies with Version 1.0 (Third edition) of the Extensible Markup Language (XML) as defined by the World Wide Web Consortium (W3C). Links to the XML standard are given in the bibliography.

To comply with IEC 62258-1, that standard requires that suppliers of die devices shall furnish information that is necessary and sufficient for users of die devices at all stages of design, procurement, manufacture and test of products containing them. The schema in Annex A defines an exchange mechanism for structuring such information using an XML representation and as such is intended as an aid to compliance with the standard.

Whilst it is expected that much of the information supplied will be in the public domain and available from such sources as manufacturers' data sheets, neither the standard nor the schema places an obligation on a supplier to make information public. Any information that a supplier considers to be proprietary or commercially sensitive may be supplied under the terms of a non-disclosure agreement.

5 Data exchange

The schema in Annex A implements all the entities as defined by IEC 62258-2 for the DDX format. In addition, it includes additional entities extending the range of that data as follows:

- expansion of data on organisations (manufacturer, supplier etc.) to include addresses and contacts;
- sub-division of some entities to make their values clearer.

Annex B contains an example of an XML file based on the schema using a fictitious example similar to that employed in IEC 62258-2, and extended to cover additional data requirements. It is possible that software may be available for conversion of data produced using the spreadsheet associated with IEC/TR 62258-4 into this format. In any case, a wide range of tools is available commercially for handling and processing XML files.

The electronic form of the schema contained in this technical report may be downloaded from the IEC website. The copyright conditions applying to the use of the electronic file are those that apply to IEC database standards, which permit the use of such information in electronic form for bona-fide e-commerce but do not permit its sale to third parties or other commercial use.

Annex A (normative)

XML schema

In electronic form, for use by the example file shown in Annex B, the file containing this schema is assumed to have the name DDXschema.xsd

```
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema">
<!-- Declaration of simple types -->
<xs:simpleType name="NAME_Type">
  <xs:restriction base="xs:string"/>
</xs:simpleType>
<xs:simpleType name="LIST_Type">
  <xs:list itemType="xs:string"/>
</xs:simpleType>
<xs:simpleType name="DATE_Type">
  <xs:restriction base="xs:date"/>
</xs:simpleType>
<xs:simpleType name="COUNT_Type">
  <xs:restriction base="xs:integer">
    <xs:minInclusive value="1"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="LENGTH_Type">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="NEGATIVE_LENGTH_Type">
  <xs:restriction base="xs:decimal">
    <xs:maxInclusive value="0"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ANGLE_Type">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0"/>
    <xs:maxInclusive value="360"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="TEMPERATURE_Type">
  <xs:restriction base="xs:decimal"/>
</xs:simpleType>
<xs:simpleType name="TIME_Type">
  <xs:restriction base="xs:decimal"/>
</xs:simpleType>
<xs:simpleType name="POWER_Type">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0"/>
  </xs:restriction>
</xs:simpleType>
```

```
<xs:simpleType name="DEVICE_FORM_Type">
  <xs:restriction base="xs:string">
    <xs:enumeration value="bare_die"/>
    <xs:enumeration value="bumped_die"/>
    <xs:enumeration value="lead_frame_die"/>
    <xs:enumeration value="minimally_packaged_device"/>
    <xs:enumeration value="MPD"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="SIGNAL_TYPE_Type">
  <xs:restriction base="xs:string">
    <xs:enumeration value="I"/>
    <xs:enumeration value="O"/>
    <xs:enumeration value="B"/>
    <xs:enumeration value="G"/>
    <xs:enumeration value="V"/>
    <xs:enumeration value="A"/>
    <xs:enumeration value="N"/>
    <xs:enumeration value="U"/>
    <xs:enumeration value="T"/>
    <xs:enumeration value="X"/>
    <xs:enumeration value="H"/>
    <xs:enumeration value="L"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="CONNECTION_REQUIREMENT_Type">
  <xs:restriction base="xs:string">
    <xs:enumeration value="CONN"/>
    <xs:enumeration value="ISOL"/>
    <xs:enumeration value="OPT"/>
    <xs:enumeration value="N/A"/>
    <xs:enumeration value="N/K"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="VIEW_Type">
  <xs:restriction base="xs:string">
    <xs:enumeration value="top"/>
    <xs:enumeration value="bottom"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="GEOMETRIC_UNIT_Type">
  <xs:restriction base="xs:string">
    <xs:enumeration value="metre"/>
    <xs:enumeration value="millimetre"/>
    <xs:enumeration value="micrometre"/>
    <xs:enumeration value="micron"/>
    <xs:enumeration value="mil"/>
    <xs:enumeration value="mm"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="MIRROR_Type">
  <xs:restriction base="xs:string">
    <xs:enumeration value="MX"/>
    <xs:enumeration value="MY"/>
    <xs:enumeration value="MXMY"/>
    <xs:enumeration value="MYMX"/>
  </xs:restriction>
</xs:simpleType>
```

```

<xs:simpleType name="WAFER_UNIT_Type">
  <xs:restriction base="xs:string">
    <xs:enumeration value="inch"/>
    <xs:enumeration value="millimetre"/>
    <xs:enumeration value="mm"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="INDEX_Type">
  <xs:restriction base="xs:string">
    <xs:enumeration value="flat"/>
    <xs:enumeration value="notch"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="MOISTURE_SENSITIVITY_LEVEL_Type">
  <xs:restriction base="xs:string">
    <xs:enumeration value="1"/>
    <xs:enumeration value="2"/>
    <xs:enumeration value="2a"/>
    <xs:enumeration value="3"/>
    <xs:enumeration value="4"/>
    <xs:enumeration value="5"/>
    <xs:enumeration value="5a"/>
    <xs:enumeration value="6"/>
  </xs:restriction>
</xs:simpleType>

<!-- Declaration of complex types -->

<xs:complexType name="REFERENCE">
  <xs:attribute name="REF" type="xs:string" use="required"/>
</xs:complexType>

<xs:complexType name="SIZE_VALUE_Type" abstract="false">
  <xs:attribute name="X_SIZE" type="LENGTH_Type" use="required"/>
  <xs:attribute name="Y_SIZE" type="LENGTH_Type" use="required"/>
</xs:complexType>

<xs:complexType name="TOLERANCE_Type" abstract="false">
  <xs:attribute name="NEG" type="NEGATIVE_LENGTH_Type" use="required"/>
  <xs:attribute name="POS" type="LENGTH_Type" use="required"/>
</xs:complexType>

<xs:complexType name="CIRCLE_Type" abstract="false">
  <xs:attribute name="RADIUS" type="LENGTH_Type" use="required"/>
</xs:complexType>

<xs:complexType name="POSITION_Type" abstract="false">
  <xs:attribute name="X" type="xs:decimal" use="required"/>
  <xs:attribute name="Y" type="xs:decimal" use="required"/>
</xs:complexType>

<xs:complexType name="TEMPERATURE_RANGE_Type" abstract="false">
  <xs:attribute name="MIN" type="TEMPERATURE_Type" use="required"/>
  <xs:attribute name="MAX" type="TEMPERATURE_Type" use="required"/>
</xs:complexType>

<xs:complexType name="POLYGON_Type" abstract="false">
  <xs:sequence>
    <xs:element name="VERTEX" type="POSITION_Type" minOccurs="3"
      maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="ORIENTATION_Type" abstract="false">
  <xs:attribute name="ANGLE" type="ANGLE_Type" use="required"/>
  <xs:attribute name="MIRROR" type="MIRROR_Type"/>
</xs:complexType>

<xs:complexType name="WAFER_SIZE_Type" abstract="false">
  <xs:attribute name="DIAMETER" type="LENGTH_Type" use="required"/>
  <xs:attribute name="UNITS" type="WAFER_UNIT_Type" use="required"/>
</xs:complexType>

<xs:complexType name="WAFER_INDEX_Type" abstract="false">
  <xs:attribute name="INDEX" type="INDEX_Type" use="required"/>
  <xs:attribute name="ORIENTATION" type="ANGLE_Type" use="required"/>
</xs:complexType>

<xs:complexType name="MANUFACTURERS_Type" abstract="false">
  <xs:sequence>
    <xs:element name="MANUFACTURER" type="ORGANISATION_Type"/>
    <xs:element name="WAFER_FAB" type="ORGANISATION_Type" minOccurs="0"/>
    <xs:element name="TESTING_FACILITY" type="ORGANISATION_Type"
      minOccurs="0"/>
    <xs:element name="PACKING_FACILITY" type="ORGANISATION_Type"
      minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="MATERIAL_Type" abstract="false">
  <xs:sequence>
    <xs:element name="TECHNOLOGY" type="xs:string" minOccurs="0"/>
    <xs:element name="SEMICONDUCTOR_MATERIAL" type="xs:string"
      minOccurs="0"/>
    <xs:element name="SUBSTRATE_MATERIAL" type="xs:string" minOccurs="0"/>
    <xs:element name="METALLISATION" type="xs:string" minOccurs="0"/>
    <xs:element name="PASSIVATION" type="xs:string" minOccurs="0"/>
    <xs:element name="BACKSIDE_DETAIL" type="xs:string" minOccurs="0"/>
    <xs:element name="TERMINAL_MATERIAL" type="xs:string" minOccurs="0"/>
    <xs:element name="TERMINAL_STRUCTURE" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="BUMP_DATA_Type" abstract="false">
  <xs:sequence>
    <xs:element name="BUMP_MATERIAL" type="xs:string"/>
    <xs:element name="SHAPE" type="xs:string" minOccurs="0"/>
    <xs:element name="SIZE" type="SIZE_VALUE_Type" minOccurs="0"/>
    <xs:element name="HEIGHT" type="LENGTH_Type"/>
    <xs:element name="HEIGHT_TOLERANCE" type="TOLERANCE_Type"
      minOccurs="0"/>
    <xs:element name="BUMP_SPECIFICATION_DRAWING"
      type="DOCUMENT_OR_GRAPHICS_Type" minOccurs="0"
      maxOccurs="unbounded"/>
    <xs:element name="BUMP_ATTACHMENT_METHOD" type="xs:string"
      minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="MPD_DATA_Type" abstract="false">
  <xs:sequence>
    <xs:element name="SEATED_HEIGHT" type="LENGTH_Type" minOccurs="0"/>
    <xs:element name="PACKAGE_MATERIAL" type="xs:string" minOccurs="0"/>
    <xs:element name="MOISTURE_SENSITIVITY_LEVEL"
      type="MOISTURE_SENSITIVITY_LEVEL_Type" minOccurs="0"/>
    <xs:element name="PACKAGE_STYLE" type="xs:string" minOccurs="0"/>
    <xs:element name="OUTLINE_DRAWING" type="DOCUMENT_OR_GRAPHICS_Type"
      minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="DOCUMENT_OR_GRAPHICS_Type" abstract="false">
  <xs:sequence>
    <xs:element name="DOCUMENT_NAME" type="NAME_Type" minOccurs="0"/>
    <xs:element name="FILE_NAME" type="NAME_Type" minOccurs="0"/>
    <xs:element name="VERSION" type="NAME_Type" minOccurs="0"/>
    <xs:element name="DATE" type="xs:date" minOccurs="0"/>
    <xs:element name="FILE_TYPE" type="NAME_Type" minOccurs="0"/>
    <xs:element name="MIME_TYPE" type="NAME_Type" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="RATING_Type" abstract="false">
  <xs:sequence>
    <xs:element name="MAX_TEMP" type="TEMPERATURE_Type" minOccurs="0"/>
    <xs:element name="MAX_TEMP_TIME" type="TIME_Type" minOccurs="0"/>
    <xs:element name="POWER_RANGE" type="POWER_Type" minOccurs="0"/>
    <xs:element name="TEMPERATURE_RANGE" type="TEMPERATURE_RANGE_Type"
      minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="WAFER_Type" abstract="false">
  <xs:sequence>
    <xs:element name="WAFER_SIZE" type="WAFER_SIZE_Type" minOccurs="0"/>
    <xs:element name="WAFER_THICKNESS" type="LENGTH_Type" minOccurs="0"/>
    <xs:element name="WAFER_DIE_STEP_SIZE" type="SIZE_VALUE_Type"
      minOccurs="0"/>
    <xs:element name="WAFER_GROSS_DIE_COUNT" type="COUNT_Type"
      minOccurs="0"/>
    <xs:element name="WAFER_INDEX" type="WAFER_INDEX_Type" minOccurs="0"/>
    <xs:element name="WAFER_RETICULE_STEP_SIZE" type="SIZE_VALUE_Type"
      minOccurs="0"/>
    <xs:element name="WAFER_RETICULE_GROSS_DIE_COUNT" type="COUNT_Type"
      minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="QUALITY_Type" abstract="false">
  <xs:sequence>
    <xs:element name="OUTGOING_QUALITY_LEVEL" type="OUTGOING_QUALITY_Type"/>
    <xs:element name="STANDARDS_COMPLIANCE" type="xs:string" minOccurs="0"/>
    <xs:element name="ADDITIONAL_SCREENING" type="xs:string" minOccurs="0"/>
    <xs:element name="PRODUCT_STATUS" type="xs:string" minOccurs="0"/>
    <xs:element name="TESTABILITY_FEATURES" type="xs:string" minOccurs="0"/>
    <xs:element name="ADDITIONAL_TEST_REQUIREMENTS" type="xs:string"
      minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="OUTGOING_QUALITY_Type" abstract="false">
  <xs:sequence>
    <xs:element name="DESCRIPTION" type="xs:string"/>
    <xs:element name="ELECTRICAL_PARAMETER_CONDITIONS" type="xs:string"/>
  </xs:sequence>
  <xs:attribute name="VALUE" type="xs:decimal" use="required"/>
  <xs:attribute name="UNITS" type="xs:string" use="required"/>
</xs:complexType>

<xs:complexType name="RELIABILITY_Type" abstract="false">
  <xs:sequence>
    <xs:element name="CONDITIONS" type="xs:string"/>
    <xs:element name="RELIABILITY_CALCULATION"
      type="DOCUMENT_OR_GRAPHICS_Type" minOccurs="0"/>
  </xs:sequence>
  <xs:attribute name="VALUE" type="xs:decimal" use="required"/>
  <xs:attribute name="UNITS" type="xs:string" use="required"/>
</xs:complexType>

<xs:complexType name="ASSEMBLY_AND_STORAGE_Type" abstract="false">
  <xs:sequence>
    <xs:element name="ATTACH_METHODS" type="xs:string" minOccurs="0"/>
    <xs:element name="ATTACH_MATERIALS" type="xs:string" minOccurs="0"/>
    <xs:element name="BONDING_METHODS" type="xs:string" minOccurs="0"/>
    <xs:element name="BONDING_MATERIALS" type="xs:string" minOccurs="0"/>
    <xs:element name="ASSEMBLY_LIMITATIONS" type="xs:string" minOccurs="0"/>
    <xs:element name="PROCESS_LIMITATIONS" type="xs:string" minOccurs="0"/>
    <xs:element name="STORAGE_LIMITATIONS" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="SUBSTRATE_CONNECTION_Type" abstract="false">
  <xs:sequence>
    <xs:element name="REQUIREMENT" type="CONNECTION_REQUIREMENT_Type"/>
    <xs:element name="CONNECTED_TO" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="DIE_DIMENSIONS_Type" abstract="false">
  <xs:sequence>
    <xs:element name="GEOMETRIC_UNITS" type="GEOMETRIC_UNIT_Type"/>
    <xs:element name="GEOMETRIC_ORIGIN" type="POSITION_Type"/>
    <xs:element name="GEOMETRIC_VIEW" type="VIEW_Type"/>
    <xs:element name="DIE_SIZE" type="SIZE_VALUE_Type"/>
    <xs:element name="DIE_THICKNESS" type="LENGTH_Type"/>
    <xs:element name="LENGTH_TOLERANCE" type="TOLERANCE_Type"
      minOccurs="0"/>
    <xs:element name="WIDTH_TOLERANCE" type="TOLERANCE_Type" minOccurs="0"/>
    <xs:element name="THICKNESS_TOLERANCE" type="TOLERANCE_Type"
      minOccurs="0"/>
    <xs:element name="TERMINAL_LENGTH_TOLERANCE" type="TOLERANCE_Type"
      minOccurs="0"/>
    <xs:element name="TERMINAL_WIDTH_TOLERANCE" type="TOLERANCE_Type"
      minOccurs="0"/>
    <xs:element name="TERMINAL_X_POSITION_TOLERANCE" type="TOLERANCE_Type"
      minOccurs="0"/>
    <xs:element name="TERMINAL_Y_POSITION_TOLERANCE" type="TOLERANCE_Type"
      minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="ORGANISATION_Type" abstract="false">
  <xs:sequence>
    <xs:element name="NAME" type="NAME_Type"/>
    <xs:element name="INTERNAL_LOCATION" type="xs:string" minOccurs="0"/>
    <xs:element name="STREET_NUMBER" type="xs:string" minOccurs="0"/>
    <xs:element name="STREET" type="xs:string" minOccurs="0"/>
    <xs:element name="POSTAL_BOX" type="xs:string" minOccurs="0"/>
    <xs:element name="TOWN" type="xs:string" minOccurs="0"/>
    <xs:element name="REGION" type="xs:string" minOccurs="0"/>
    <xs:element name="POSTAL_CODE" type="xs:string" minOccurs="0"/>
    <xs:element name="COUNTRY" type="xs:string" minOccurs="0"/>
    <xs:element name="ISO_COUNTRY_CODE" type="xs:string"
      minOccurs="0"/>
    <xs:element name="FACSIMILE_NUMBER" type="xs:string" minOccurs="0"/>
    <xs:element name="TELEPHONE_NUMBER" type="xs:string" minOccurs="0"/>
    <xs:element name="ELECTRONIC_MAIL_ADDRESS" type="xs:string"
      minOccurs="0"/>
    <xs:element name="TELEX_NUMBER" type="xs:string" minOccurs="0"/>
    <xs:element name="CONTACT" type="CONTACT_Type" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="CONTACT_Type" abstract="false">
  <xs:sequence>
    <xs:element name="NAME" type="NAME_Type"/>
    <xs:element name="DEPARTMENT" type="NAME_Type" minOccurs="0"/>
    <xs:element name="TELEPHONE_NUMBER" type="xs:string" minOccurs="0"/>
    <xs:element name="ELECTRONIC_MAIL_ADDRESS" type="xs:string"
      minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="TERMINAL_OR_GROUP_Type" abstract="false">
  <xs:sequence>
    <xs:choice>
      <xs:element name="TERMINAL_REF" type="REFERENCE"/>
      <xs:element name="TERMINAL_GROUP_REF" type="REFERENCE"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="PERMUTABLE_Type" abstract="false">
  <xs:sequence>
    <xs:choice>
      <xs:element name="TERMINAL_REF" type="REFERENCE" minOccurs="2"
        maxOccurs="unbounded"/>
      <xs:element name="TERMINAL_GROUP_REF" type="REFERENCE" minOccurs="2"
        maxOccurs="unbounded"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>

```

```

<!-- Declaration of global elements -->

<xs:element name="TERMINAL">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="TERMINAL_IDENTIFIER" type="xs:string"/>
      <xs:element name="TERMINAL_NUMBER" type="xs:string" minOccurs="0"/>
      <xs:element name="TERMINAL_TYPE_NAME">
        <xs:complexType>
          <xs:sequence>
            <xs:element name="TERMINAL_TYPE_REF" type="REFERENCE"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="TERMINAL_POSITION" type="POSITION_Type"/>
      <xs:element name="ORIENTATION" type="ORIENTATION_Type"/>
      <xs:element name="SIGNAL_NAME" type="xs:string" minOccurs="0"/>
      <xs:element name="SIGNAL_TYPE" type="SIGNAL_TYPE_Type" minOccurs="0"/>
    </xs:sequence>
    <xs:attribute name="TERMINID" type="xs:string" use="required"/>
  </xs:complexType>
</xs:element>

<xs:element name="TERMINAL_GROUP">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="GROUP_NAME" type="NAME_Type"/>
      <xs:element name="TERMINAL_OR_GROUP" type="TERMINAL_OR_GROUP_Type"
        minOccurs="2" maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:attribute name="GROUPLD" type="xs:string" use="required"/>
  </xs:complexType>
</xs:element>

<xs:element name="TERMINAL_TYPE">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="TERMINAL_TYPE_NAME" type="xs:string"/>
      <xs:choice>
        <xs:element name="RECTANGLE" type="SIZE_VALUE_Type"/>
        <xs:element name="CIRCLE" type="CIRCLE_Type"/>
        <xs:element name="POLYGON" type="POLYGON_Type"/>
        <xs:element name="ELLIPSE" type="SIZE_VALUE_Type"/>
      </xs:choice>
    </xs:sequence>
    <xs:attribute name="PADID" type="xs:string" use="required"/>
  </xs:complexType>
</xs:element>

<xs:element name="SIMULATOR">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="MODEL_FILE" type="NAME_Type"/>
      <xs:element name="MODEL_FILE_DATE" type="xs:date"/>
      <xs:element name="SIMULATOR_NAME" type="NAME_Type"/>
      <xs:element name="SIMULATOR_VERSION" type="NAME_Type"/>
      <xs:element name="SIMULATOR_COMPLIANCE" type="NAME_Type"/>
      <xs:element name="TERMINAL_OR_GROUP" type="TERMINAL_OR_GROUP_Type"
        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:attribute name="SIMID" type="xs:string" use="required"/>
  </xs:complexType>
</xs:element>

```

```

<xs:element name="FIDUCIAL">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="FIDUCIAL_IDENTIFIER" type="NAME_Type"/>
      <xs:element name="FIDUCIAL_TYPE_NAME">
        <xs:complexType>
          <xs:sequence>
            <xs:element name="FIDUCIAL_TYPE_REF" type="REFERENCE"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="FIDUCIAL_POSITION" type="POSITION_Type"/>
      <xs:element name="ORIENTATION" type="ORIENTATION_Type"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

<xs:element name="FIDUCIAL_TYPE">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="FIDUCIAL_FILE" type="DOCUMENT_OR_GRAPHICS_Type"/>
      <xs:element name="FIDUCIAL_SIZE" type="SIZE_VALUE_Type"/>
    </xs:sequence>
    <xs:attribute name="FIDID" type="xs:string" use="required"/>
  </xs:complexType>
</xs:element>

<xs:element name="DEVICES">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="DEVICE" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

<xs:element name="DEVICE">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="BLOCK_CREATION_DATE" type="DATE_Type"/>
      <xs:element name="BLOCK_VERSION" type="NAME_Type"/>
      <xs:element name="VERSION" type="NAME_Type"/>
      <xs:element name="DATA_SOURCE" type="ORGANISATION_Type"/>
      <xs:element name="DATA_VERSION" type="NAME_Type"/>
      <xs:element name="DEVICE_FORM" type="DEVICE_FORM_Type"/>
      <xs:element name="DIE_NAME" type="NAME_Type"/>
      <xs:element name="DIE_MASK_REVISION" type="xs:string" minOccurs="0"/>
      <xs:element name="MANUFACTURERS" type="MANUFACTURERS_Type"/>
      <xs:element name="SUPPLIER" type="ORGANISATION_Type" minOccurs="0"/>
      <xs:element name="TYPE_NUMBER" type="NAME_Type"/>
      <xs:element name="PACKAGED_PART_NAME" type="NAME_Type" minOccurs="0"/>
      <xs:element name="FUNCTION" type="xs:string"/>
      <xs:element name="DIMENSIONS" type="DIE_DIMENSIONS_Type"/>
      <xs:element name="DIE_PICTURE" type="DOCUMENT_OR_GRAPHICS_Type"
        minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="DEVICE_DATA_FILE" type="DOCUMENT_OR_GRAPHICS_Type"
        minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="MATERIALS" type="MATERIAL_Type"/>
      <xs:element name="BUMP_DATA" type="BUMP_DATA_Type" minOccurs="0"/>
      <xs:element name="MPD_DATA" type="MPD_DATA_Type" minOccurs="0"/>
      <xs:element name="RATINGS" type="RATING_Type" minOccurs="0"/>
      <xs:element name="DIE_DELIVERY_FORM" type="LIST_Type" minOccurs="0"/>
      <xs:element name="PACKING_CODE" type="xs:string" minOccurs="0"/>
      <xs:element name="WAFER_DATA" type="WAFER_Type" minOccurs="0"/>
      <xs:element name="SUBSTRATE_CONNECTION"
        type="SUBSTRATE_CONNECTION_Type"/>
      <xs:element name="TERMINAL_TYPES">
        <xs:complexType>

```

```

    <xs:sequence>
      <xs:element name="TERMINAL_TYPE_COUNT" type="COUNT_Type"/>
      <xs:element ref="TERMINAL_TYPE" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="TERMINALS">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="TERMINAL_COUNT" type="COUNT_Type"/>
      <xs:element ref="TERMINAL" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="TERMINAL_GROUPS" minOccurs="0">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="TERMINAL_GROUP" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="PERMUTABLE" type="PERMUTABLE_Type" minOccurs="0"
  maxOccurs="unbounded"/>
<xs:element name="SIMULATORS" minOccurs="0">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="SIMULATOR" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="FIDUCIAL_TYPES" minOccurs="0">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="FIDUCIAL_TYPE" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="FIDUCIALS" minOccurs="0">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="FIDUCIAL" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="QUALITY" type="QUALITY_Type"/>
<xs:element name="RELIABILITY" type="RELIABILITY_Type"/>
<xs:element name="ASSEMBLY_AND_STORAGE"
  type="ASSEMBLY_AND_STORAGE_Type" minOccurs="0"/>
</xs:sequence>
<xs:attribute name="NAME" type="xs:string" use="required"/>
<xs:attribute name="TYPE" type="xs:string" use="required"/>
</xs:complexType>

```

```

<!-- Key declarations -->

<xs:key name="TERMINAL_Key">
  <xs:selector xpath="."/TERMINAL"/>
  <xs:field xpath="@TERMID"/>
</xs:key>
<xs:keyref name="TERMINAL_KeyRef" refer="TERMINAL_Key">
  <xs:selector xpath="."/TERMINAL_REF"/>
  <xs:field xpath="@REF"/>
</xs:keyref>
<xs:key name="TERMINAL_TYPE_Key">
  <xs:selector xpath="."/TERMINAL_TYPE"/>
  <xs:field xpath="@PADID"/>
</xs:key>
<xs:keyref name="TERMINAL_TYPE_KeyRef" refer="TERMINAL_TYPE_Key">
  <xs:selector xpath="."/TERMINAL_TYPE_REF"/>
  <xs:field xpath="@REF"/>
</xs:keyref>
<xs:key name="TERMINAL_GROUP_Key">
  <xs:selector xpath="."/TERMINAL_GROUP"/>
  <xs:field xpath="@GROUPID"/>
</xs:key>
<xs:keyref name="TERMINAL_GROUP_KeyRef" refer="TERMINAL_GROUP_Key">
  <xs:selector xpath="."/TERMINAL_GROUP_REF"/>
  <xs:field xpath="@REF"/>
</xs:keyref>
<xs:key name="SIMULATOR_Key">
  <xs:selector xpath="."/SIMULATOR"/>
  <xs:field xpath="@SIMID"/>
</xs:key>
<xs:keyref name="SIMULATOR_KeyRef" refer="SIMULATOR_Key">
  <xs:selector xpath="."/SIMULATOR_REF"/>
  <xs:field xpath="@REF"/>
</xs:keyref>
<xs:key name="FIDUCIAL_TYPE_Key">
  <xs:selector xpath="."/FIDUCIAL_TYPE"/>
  <xs:field xpath="@FIDID"/>
</xs:key>
<xs:keyref name="FIDUCIAL_TYPE_KeyRef" refer="FIDUCIAL_TYPE_Key">
  <xs:selector xpath="."/FIDUCIAL_TYPE_REF"/>
  <xs:field xpath="@REF"/>
</xs:keyref>
</xs:element>

</xs:schema>

```

Annex B (informative)

XML example

Annex B is based on a fictitious example for a quad two-input NAND gate and illustrates many of the features of the schema.

```
<?xml version="1.0" encoding="UTF-8"?>
<DEVICES xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:noNamespaceSchemaLocation="DDXschema.xsd">
  <DEVICE NAME = "74ACT00" TYPE = "bare_die">
    <BLOCK_CREATION_DATE>2006-02-13</BLOCK_CREATION_DATE>
    <BLOCK_VERSION>DDXconvert version 4.0</BLOCK_VERSION>
    <VERSION>1.2</VERSION>
    <DATA_SOURCE>
      <NAME>GOOD-DIE database</NAME>
    </DATA_SOURCE>
    <DATA_VERSION>Initial issue A</DATA_VERSION>
    <DEVICE_FORM>bare_die</DEVICE_FORM>
    <DIE_NAME>74ACT00</DIE_NAME>
    <DIE_MASK_REVISION>Mask T</DIE_MASK_REVISION>
    <MANUFACTURERS>
      <MANUFACTURER>
        <NAME>Fuzziwuzz Logic Ltd</NAME>
      </MANUFACTURER>
    </MANUFACTURERS>
    <TYPE_NUMBER>74ACT00</TYPE_NUMBER>
    <FUNCTION>Quad two-input advanced CMOS NAND gate</FUNCTION>
    <DIMENSIONS>
      <GEOMETRIC_UNITS>micrometre</GEOMETRIC_UNITS>
      <GEOMETRIC_ORIGIN X = "0" Y = "0" />
      <GEOMETRIC_VIEW>top</GEOMETRIC_VIEW>
      <DIE_SIZE X_SIZE = "1067" Y_SIZE = "1143" />
      <DIE_THICKNESS>356</DIE_THICKNESS>
      <LENGTH_TOLERANCE NEG="-20" POS="20"/>
      <WIDTH_TOLERANCE NEG="-20" POS="20"/>
      <THICKNESS_TOLERANCE NEG="-10" POS="10"/>
      <TERMINAL_X_POSITION_TOLERANCE NEG="-5" POS="5"/>
      <TERMINAL_Y_POSITION_TOLERANCE NEG="-5" POS="5"/>
    </DIMENSIONS>
    <MATERIALS>
      <TECHNOLOGY>CMOS</TECHNOLOGY>
      <SEMICONDUCTOR_MATERIAL>silicon</SEMICONDUCTOR_MATERIAL>
      <METALLISATION>Al</METALLISATION>
    </MATERIALS>
    <RATINGS>
      <MAX_TEMP>175</MAX_TEMP>
      <TEMPERATURE_RANGE MIN="-70" MAX="150"/>
    </RATINGS>
    <DIE_DELIVERY_FORM>Die, wafer</DIE_DELIVERY_FORM>
    <WAFER_DATA>
      <WAFER_SIZE DIAMETER="8" UNITS="inch"></WAFER_SIZE>
      <WAFER_THICKNESS>356</WAFER_THICKNESS>
      <WAFER_INDEX ORIENTATION="90" INDEX="flat"></WAFER_INDEX>
    </WAFER_DATA>
    <SUBSTRATE_CONNECTION>
      <REQUIREMENT>CONN</REQUIREMENT>
      <CONNECTED_TO>Vcc</CONNECTED_TO>
    </SUBSTRATE_CONNECTION>
    <TERMINAL_TYPES>
      <TERMINAL_TYPE_COUNT>1</TERMINAL_TYPE_COUNT>
      <TERMINAL_TYPE PADID = "PADR1" >
        <TERMINAL_TYPE_NAME>PADR1</TERMINAL_TYPE_NAME>
      </TERMINAL_TYPES>
  </DEVICE>
</DEVICES>
```

```

    <RECTANGLE X_SIZE = "97" Y_SIZE = "97" />
  </TERMINAL_TYPE>
</TERMINAL_TYPES>
<TERMINALS>
<TERMINAL_COUNT>28</TERMINAL_COUNT>
  <TERMINAL TERMID = "T_1" >
    <TERMINAL_IDENTIFIER>T_1</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>1</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
      <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "-385" Y = "422" />
    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>A1</SIGNAL_NAME>
    <SIGNAL_TYPE>I</SIGNAL_TYPE>
  </TERMINAL>
  <TERMINAL TERMID = "T_2" >
    <TERMINAL_IDENTIFIER>T_2</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>2</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
      <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "-385" Y = "176" />
    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>B1</SIGNAL_NAME>
    <SIGNAL_TYPE>I</SIGNAL_TYPE>
  </TERMINAL>
  <TERMINAL TERMID = "T_3" >
    <TERMINAL_IDENTIFIER>T_3</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>3</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
      <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "-385" Y = "11" />
    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>Y1</SIGNAL_NAME>
    <SIGNAL_TYPE>O</SIGNAL_TYPE>
  </TERMINAL>
  <TERMINAL TERMID = "T_4" >
    <TERMINAL_IDENTIFIER>T_4</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>4</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
      <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "-385" Y = "-236" />
    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>A2</SIGNAL_NAME>
    <SIGNAL_TYPE>I</SIGNAL_TYPE>
  </TERMINAL>
  <TERMINAL TERMID = "T_5" >
    <TERMINAL_IDENTIFIER>T_5</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>5</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
      <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "-208" Y = "-423" />
    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>B2</SIGNAL_NAME>
    <SIGNAL_TYPE>I</SIGNAL_TYPE>
  </TERMINAL>
  <TERMINAL TERMID = "T_6" >
    <TERMINAL_IDENTIFIER>T_6</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>6</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
      <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "-43" Y = "-423" />

```

```

    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>Y2</SIGNAL_NAME>
    <SIGNAL_TYPE>O</SIGNAL_TYPE>
</TERMINAL>
<TERMINAL_TERMID = "T_7" >
    <TERMINAL_IDENTIFIER>T_7</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>7</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
        <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "123" Y = "-423" />
    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>GND</SIGNAL_NAME>
    <SIGNAL_TYPE>G</SIGNAL_TYPE>
</TERMINAL>
<TERMINAL_TERMID = "T_8" >
    <TERMINAL_IDENTIFIER>T_8</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>8</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
        <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "385" Y = "-423" />
    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>Y3</SIGNAL_NAME>
    <SIGNAL_TYPE>O</SIGNAL_TYPE>
</TERMINAL>
<TERMINAL_TERMID = "T_9" >
    <TERMINAL_IDENTIFIER>T_9</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>9</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
        <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "385" Y = "-166" />
    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>B3</SIGNAL_NAME>
    <SIGNAL_TYPE>I</SIGNAL_TYPE>
</TERMINAL>
<TERMINAL_TERMID = "T_10" >
    <TERMINAL_IDENTIFIER>T_10</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>10</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
        <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "385" Y = "-1" />
    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>A3</SIGNAL_NAME>
    <SIGNAL_TYPE>I</SIGNAL_TYPE>
</TERMINAL>
<TERMINAL_TERMID = "T_11" >
    <TERMINAL_IDENTIFIER>T_11</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>11</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
        <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "385" Y = "164" />
    <ORIENTATION_ANGLE = "0" />
    <SIGNAL_NAME>Y4</SIGNAL_NAME>
    <SIGNAL_TYPE>O</SIGNAL_TYPE>
</TERMINAL>
<TERMINAL_TERMID = "T_12" >
    <TERMINAL_IDENTIFIER>T_12</TERMINAL_IDENTIFIER>
    <TERMINAL_NUMBER>12</TERMINAL_NUMBER>
    <TERMINAL_TYPE_NAME>
        <TERMINAL_TYPE_REF REF = "PADR1" />
    </TERMINAL_TYPE_NAME>
    <TERMINAL_POSITION X = "385" Y = "423" />
    <ORIENTATION_ANGLE = "0" />

```

```

<SIGNAL_NAME>B4</SIGNAL_NAME>
<SIGNAL_TYPE>I</SIGNAL_TYPE>
</TERMINAL>
<TERMINAL TERMID = "T_13" >
  <TERMINAL_IDENTIFIER>T_13</TERMINAL_IDENTIFIER>
  <TERMINAL_NUMBER>13</TERMINAL_NUMBER>
  <TERMINAL_TYPE_NAME>
    <TERMINAL_TYPE_REF REF = "PADR1" />
  </TERMINAL_TYPE_NAME>
  <TERMINAL_POSITION X = "38" Y = "423" />
  <ORIENTATION ANGLE = "0" />
  <SIGNAL_NAME>A4</SIGNAL_NAME>
  <SIGNAL_TYPE>I</SIGNAL_TYPE>
</TERMINAL>
<TERMINAL TERMID = "T_14" >
  <TERMINAL_IDENTIFIER>T_14</TERMINAL_IDENTIFIER>
  <TERMINAL_NUMBER>14</TERMINAL_NUMBER>
  <TERMINAL_TYPE_NAME>
    <TERMINAL_TYPE_REF REF = "PADR1" />
  </TERMINAL_TYPE_NAME>
  <TERMINAL_POSITION X = "-129" Y = "423" />
  <ORIENTATION ANGLE = "0" />
  <SIGNAL_NAME>VCC</SIGNAL_NAME>
  <SIGNAL_TYPE>V</SIGNAL_TYPE>
</TERMINAL>
</TERMINALS>
<TERMINAL_GROUPS>
  <TERMINAL_GROUP GROUPID="G_1">
    <GROUP_NAME>G_1</GROUP_NAME>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_1"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_2"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
  </TERMINAL_GROUP>
  <TERMINAL_GROUP GROUPID="G_2">
    <GROUP_NAME>G_2</GROUP_NAME>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_4"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_5"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
  </TERMINAL_GROUP>
  <TERMINAL_GROUP GROUPID="G_3">
    <GROUP_NAME>G_3</GROUP_NAME>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_9"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_10"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
  </TERMINAL_GROUP>
  <TERMINAL_GROUP GROUPID="G_4">
    <GROUP_NAME>G_4</GROUP_NAME>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_12"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_13"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
  </TERMINAL_GROUP>
  <TERMINAL_GROUP GROUPID="G_5">
    <GROUP_NAME>G_5</GROUP_NAME>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_3"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
  </TERMINAL_GROUP>

```

```

    </TERMINAL_OR_GROUP>
    <TERMINAL_OR_GROUP>
      <TERMINAL_GROUP_REF REF="G_1"></TERMINAL_GROUP_REF>
    </TERMINAL_OR_GROUP>
  </TERMINAL_GROUP>
  <TERMINAL_GROUP GROUPID="G_6">
    <GROUP_NAME>G_6</GROUP_NAME>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_6"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
    <TERMINAL_OR_GROUP>
      <TERMINAL_GROUP_REF REF="G_2"></TERMINAL_GROUP_REF>
    </TERMINAL_OR_GROUP>
  </TERMINAL_GROUP>
  <TERMINAL_GROUP GROUPID="G_7">
    <GROUP_NAME>G_7</GROUP_NAME>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_8"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
    <TERMINAL_OR_GROUP>
      <TERMINAL_GROUP_REF REF="G_3"></TERMINAL_GROUP_REF>
    </TERMINAL_OR_GROUP>
  </TERMINAL_GROUP>
  <TERMINAL_GROUP GROUPID="G_8">
    <GROUP_NAME>G_8</GROUP_NAME>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_11"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
    <TERMINAL_OR_GROUP>
      <TERMINAL_GROUP_REF REF="G_4"></TERMINAL_GROUP_REF>
    </TERMINAL_OR_GROUP>
  </TERMINAL_GROUP>
</TERMINAL_GROUPS>
<PERMUTABLE>
  <TERMINAL_REF REF="T_1"></TERMINAL_REF>
  <TERMINAL_REF REF="T_2"></TERMINAL_REF>
</PERMUTABLE>
<PERMUTABLE>
  <TERMINAL_REF REF="T_4"></TERMINAL_REF>
  <TERMINAL_REF REF="T_5"></TERMINAL_REF>
</PERMUTABLE>
<PERMUTABLE>
  <TERMINAL_REF REF="T_9"></TERMINAL_REF>
  <TERMINAL_REF REF="T_10"></TERMINAL_REF>
</PERMUTABLE>
<PERMUTABLE>
  <TERMINAL_REF REF="T_12"></TERMINAL_REF>
  <TERMINAL_REF REF="T_13"></TERMINAL_REF>
</PERMUTABLE>
<PERMUTABLE>
  <TERMINAL_GROUP_REF REF="G_5"></TERMINAL_GROUP_REF>
  <TERMINAL_GROUP_REF REF="G_6"></TERMINAL_GROUP_REF>
  <TERMINAL_GROUP_REF REF="G_7"></TERMINAL_GROUP_REF>
  <TERMINAL_GROUP_REF REF="G_8"></TERMINAL_GROUP_REF>
</PERMUTABLE>
<SIMULATORS>
  <SIMULATOR SIMID="S_1">
    <MODEL_FILE>SP74ACT00.MOD</MODEL_FILE>
    <MODEL_FILE_DATE>1997-09-17</MODEL_FILE_DATE>
    <SIMULATOR_NAME>pSpice</SIMULATOR_NAME>
    <SIMULATOR_VERSION>4.0.1</SIMULATOR_VERSION>
    <SIMULATOR_COMPLIANCE>2G6</SIMULATOR_COMPLIANCE>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_1"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
    <TERMINAL_OR_GROUP>
      <TERMINAL_REF REF="T_2"></TERMINAL_REF>
    </TERMINAL_OR_GROUP>
  </SIMULATOR>

```

```

</TERMINAL_OR_GROUP>
<TERMINAL_OR_GROUP>
  <TERMINAL_REF REF="T_4"></TERMINAL_REF>
</TERMINAL_OR_GROUP>
<TERMINAL_OR_GROUP>
  <TERMINAL_REF REF="T_5"></TERMINAL_REF>
</TERMINAL_OR_GROUP>
<TERMINAL_OR_GROUP>
  <TERMINAL_REF REF="T_9"></TERMINAL_REF>
</TERMINAL_OR_GROUP>
<TERMINAL_OR_GROUP>
  <TERMINAL_REF REF="T_10"></TERMINAL_REF>
</TERMINAL_OR_GROUP>
<TERMINAL_OR_GROUP>
  <TERMINAL_REF REF="T_12"></TERMINAL_REF>
</TERMINAL_OR_GROUP>
<TERMINAL_OR_GROUP>
  <TERMINAL_REF REF="T_13"></TERMINAL_REF>
</TERMINAL_OR_GROUP>
</SIMULATOR>
<SIMULATOR SIMID="S_2">
  <MODEL_FILE>SP74ACT00.S</MODEL_FILE>
  <MODEL_FILE_DATE>1998-11-05</MODEL_FILE_DATE>
  <SIMULATOR_NAME>Spectre</SIMULATOR_NAME>
  <SIMULATOR_VERSION>4.2.1, 1992</SIMULATOR_VERSION>
  <SIMULATOR_COMPLIANCE>2G6, Level-3</SIMULATOR_COMPLIANCE>
  <TERMINAL_OR_GROUP>
    <TERMINAL_GROUP_REF REF="G_5"></TERMINAL_GROUP_REF>
  </TERMINAL_OR_GROUP>
  <TERMINAL_OR_GROUP>
    <TERMINAL_GROUP_REF REF="G_6"></TERMINAL_GROUP_REF>
  </TERMINAL_OR_GROUP>
  <TERMINAL_OR_GROUP>
    <TERMINAL_GROUP_REF REF="G_7"></TERMINAL_GROUP_REF>
  </TERMINAL_OR_GROUP>
  <TERMINAL_OR_GROUP>
    <TERMINAL_GROUP_REF REF="G_8"></TERMINAL_GROUP_REF>
  </TERMINAL_OR_GROUP>
</SIMULATOR>
</SIMULATORS>
<FIDUCIAL_TYPES>
  <FIDUCIAL_TYPE FIDID="fiduc1">
    <FIDUCIAL_FILE>
      <FILE_NAME>7995FID1.JIF</FILE_NAME>
    </FIDUCIAL_FILE>
    <FIDUCIAL_SIZE X_SIZE="72" Y_SIZE="55"></FIDUCIAL_SIZE>
  </FIDUCIAL_TYPE>
</FIDUCIAL_TYPES>
<FIDUCIALS>
  <FIDUCIAL>
    <FIDUCIAL_IDENTIFIER></FIDUCIAL_IDENTIFIER>
    <FIDUCIAL_TYPE_NAME>
      <FIDUCIAL_TYPE_REF REF="fiduc1"></FIDUCIAL_TYPE_REF>
    </FIDUCIAL_TYPE_NAME>
    <FIDUCIAL_POSITION X="-612" Y="470"></FIDUCIAL_POSITION>
    <ORIENTATION ANGLE="0"></ORIENTATION>
  </FIDUCIAL>
</FIDUCIALS>
<QUALITY>
  <OUTGOING_QUALITY_LEVEL VALUE="10" UNITS = "ppm">
    <DESCRIPTION>25Cel</DESCRIPTION>
    <ELECTRICAL_PARAMETER_CONDITIONS>Vcc=5V
    </ELECTRICAL_PARAMETER_CONDITIONS>
  </OUTGOING_QUALITY_LEVEL>
  <STANDARDS_COMPLIANCE>IECQ</STANDARDS_COMPLIANCE>
  <ADDITIONAL_SCREENING>None</ADDITIONAL_SCREENING>
  <PRODUCT_STATUS>No changes planned</PRODUCT_STATUS>

```

```
</QUALITY>
<RELIABILITY VALUE = "100" UNITS = "FIT">
  <CONDITIONS>
    Temperature 25Cel and mobile phone application
  </CONDITIONS>
  <RELIABILITY_CALCULATION>
    <DOCUMENT_NAME>MIL-HDBK 217E</DOCUMENT_NAME>
  </RELIABILITY_CALCULATION>
</RELIABILITY>
<ASSEMBLY_AND_STORAGE>
  <ASSEMBLY_LIMITATIONS>
    Maximum 150Cel for 2s
  </ASSEMBLY_LIMITATIONS>
  <STORAGE_LIMITATIONS>
    Six months at 25Cel and 50%RH
  </STORAGE_LIMITATIONS>
</ASSEMBLY_AND_STORAGE>
</DEVICE>
</DEVICES>
```

Bibliography

Extensible Markup Language (XML) 1.0 (Third Edition): W3C Recommendation 04 February 2004 is available at <http://www.w3.org/TR/2004/REC-xml-20040204>

XSL Transformations (XSLT) Version 1.0: W3C Recommendation 16 November 1999 is available at <http://www.w3.org/TR/1999/REC-xslt-19991116>

LICENSED TO MECON Limited. - RANCHI/BANGALORE
FOR INTERNAL USE AT THIS LOCATION ONLY, SUPPLIED BY BOOK SUPPLY BUREAU.

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

3, rue de Varembé
P.O. Box 131
CH-1211 Geneva 20
Switzerland

Tel: + 41 22 919 02 11
Fax: + 41 22 919 03 00
info@iec.ch
www.iec.ch