

IEC TR 62627-06

Edition 1.0 2014-05

TECHNICAL REPORT



Copyrighted material licensed to BR Demo by Thomson Reuters (Scientific), Inc., subscriptions.techstreet.com, downloaded on Nov-27-2014 by James Madison. No further reproduction or distribution is permitted. Uncontrolled when print

Fibre optic interconnecting devices and passive components – Part 06: Mechanical design proving nutation test results for reinforced fibre cable terminated with optical connectors for high density patching applications





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office	Tel.: +41 22 919 02 11
3, rue de Varembé	Fax: +41 22 919 03 00
CH-1211 Geneva 20	info@iec.ch
Switzerland	www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.





Edition 1.0 2014-05

TECHNICAL REPORT



Fibre optic interconnecting devices and passive components – Part 06: Mechanical design proving nutation test results for reinforced fibre cable terminated with optical connectors for high density patching applications

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

ICS 33.180.20

ISBN 978-2-8322-1574-6

K

Warning! Make sure that you obtained this publication from an authorized distributor.

– 2 – IEC TR 62627-06:2014 © IEC 2014

CONTENTS

FOR	EWORD	
INTE	RODUCTION	
1	Scope	
2	Normative references	
3	Fibre operation in high density packaged system	
4	Tensile force measurements for reinforced fibre cable assemblies7	
5	Adequate tensile force for nutation test	
6	Nutation test method8	
7	Example of nutation test results9	
8	Conclusions10	
Figu Figu Figu	re 1 – High density packaged equipment	
Figure 4 – Nutetion toot opportug		
гıgu	16 4 – Nutation test apparatus	
Tabl	e 1 – Experimental results9	

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS –

Part 06: Mechanical design proving nutation test results for reinforced fibre cable terminated with optical connectors for high density patching applications

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.

Copyrighted material licensed to BR Demo by Thomson Reuters (Scientific), Inc., subscriptions.techstreet.com, downloaded on Nov-27-2014 by James Madison. No further reproduction or distribution is permitted. Uncontrolled when print

- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 62627-06, which is a technical report, has been prepared by subcommittee SC86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
86B/3714/DTR	86B/3751/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Optical connectors are widely used in a variety of optical communication systems. These connectors are sometimes used in high density equipment. When an optical fibre cable assembly is connected to a receptacle port, the optical fibre cable assembly connected to an adjacent port may be pulled to one side. During this operation, the pulling force has the potential to act on the optical fibre cable in an oblique direction. When an optical fibre cable assembly is pulled to one side, the tensile force acts on the optical connector in various directions. The optical connector has to possess mechanical durability to withstand the tensile force imposed on it, and an allowable tensile force should be defined to ensure that the system can continue to operate. Therefore test methods are used to evaluate the mechanical durability when an optical fibre cable assembly is pulled laterally. One of these tests methods is nutation.

The IEC Japan National Committee (JPNC) undertook research on a nutation test for optical connectors terminated with reinforced fibre cable.

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS –

Part 06: Mechanical design proving nutation test results for reinforced fibre cable terminated with optical connectors for high density patching applications

1 Scope

This part of IEC 62627, which is a technical report, describes the results of mechanical design proving tests for a high density systems application, carried out using the nutation test according to IEC 61300-2-35, performed on reinforced fibre cable terminated with optical connectors. A tensile load is suggested for the design proving requirements to be used to ensure that connectors meet the mechanical design requirements of connectors for specific application.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60794-2-50, Optical fibre cables – Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies

IEC 61300-2-35, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-35: Tests – Cable nutation

IEC 61300-2-51, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-51: Tests – Fibre optic connector test for transmission with applied tensile load – Singlemode and multimode

3 Fibre operation in high density packaged system

Optical connectors maybe used in high density equipment such as fibre termination modules (FTM) and integrated distribution modules (IDM) where several thousands of optical fibres are terminated (see Figure 1a). Today, compact optical transceivers such as small form-factor pluggable (SFP) modules may be densely packaged in system racks (see Figure 1b). When an optical fibre cable assembly is connected to a receptacle port, the optical fibre cable assembly connected to the adjacent port may be pulled to the side. During this operation, the applied pulling force has the potential to act on the optical fibre cable in a lateral direction. The optical signal in the adjacent fibre link should not be degraded by this operation, so the adjacent fibre optic connector has to have sufficient durability to withstand this force. A test method is used to evaluate mechanical durability when an optical fibre cable assembly is pulled sideways in a high density packaged system.





Figure 1a – Integrated distribution module (IDM) Figure 1b – System rack with densely packaged SFP

Figure 1 – High density packaged equipment

4 Tensile force measurements for reinforced fibre cable assemblies

The tensile force generated when installing an additional connectorized optical fibre cable assembly was measured. Figure 2 shows the experimental set-up for the measurement. The fibre optic connector adaptors are arranged in high density configuration. The tensile load on the fibre cable assembly connected to the adjacent port is measured with a strain gauge as a worker installs another optical fibre cable assembly.

Figure 3 shows a histogram of the tensile load measured. The results were provided by 9 operators, with each one installing the fibre connector 10 times as if in a field installation, without taking any special precautions. The figure also shows a fitting curve using an approximated exponential equation obtained using the frequency data. The maximum tensile load was 8.3 N with an average value of 2,4 N and a standard deviation of 1,8 N.



Figure 2 – Experimental set-up for tensile load measurement



- 8 -

Figure 3 – Tensile load histogram

5 Adequate tensile force for nutation test

Optical fibre cable assemblies should have sufficient durability to withstand a disturbance by the tensile forces imposed during operation. The quality of the signals being transmitted through an adjacent optical fibre may degrade, and a fatal error may occur, if the force damages the fibre optic connector. To achieve reliable system operation approved cable assemblies are necessary. To define the test requirements a necessary level of the applied tensile load shall be estimated.

Tensile force values can be found in IEC documents to be applied for the nutation test. According to IEC 61300-2-51, the preferred tensile loads are 2,4 N, 6,9 N, 14,7 and 19,6 N. IEC 61300-2-35 also specifies 10 N for the nutation test. When a worker installs a connector, the tensile force acts on the adjacent optical fibre cable assembly in an unknown direction. The optical connector must have mechanical durability to withstand tensile forces in any directions. A nutation test is suitable for evaluating such durability

A tensile load of 10 N in the nutation test is insufficient for field operations because various types of operations may occur. This technical report has calculated with a safety margin determining the load for this sideload to 14,7 N. When the failure mode of a tensile force application is a fracture mode, the result is a fatal failure. A load of 14,7 N has a sufficient margin to ensure a reliable network system.

6 Nutation test method

A nutation test according to IEC 61300-2-35 evaluates the mechanical durability of an optical fibre cable terminated with an optical connector when the fibre cable is pulled in a direction of 45° from the optical connector. Figure 4 shows the apparatus used for the nutation test. The optical connector plug attached to the fibre cable is connected to an adaptor fixed to the apparatus. The adaptor is rotating through 360° in the rotation fixture. The fibre cable is passed through a hole located in the rotation axis and a weight is attached to the fibre cable to supply the tensile force. The conical path length was set 28 cm which is described as the point of application of the load in IEC 61300-2-51. The apparatus enables the application of tensile force to the optical connector at a direction of 45° while the apparatus and adaptor are rotating.



Figure 4a – Schematic diagram

Figure 4b – Photograph

Figure 4 – Nutation test apparatus

7 Example of nutation test results

The validity of the nutation test described above was evaluated by using commercially available fibre optic connectors. In the nutation test, the rotation speed was 10 r/min for 100 revolutions. The test was performed with a tensile force of 14,7 N. Two criteria were considered when analysing the results. First, the attenuation of the cable assembly shall be less than 0,2 dB before and after the test. Second, the connector exhibits no damage during the test. Nine commercially available optical connectors including three types of connector (type I, II and III) terminated on 1,7 mm or 2,0 mm diameter reinforced fibre cable were tested. Table 1 shows the experimental nutation test results. Approximately 86 % of the connectors passed the nutation test and 14 % failed. All of the nutation test failures were the result of the plug breaking. The results indicate that mechanical durability is not directly related to connector type but depends on the connector's materials and design. Furthermore, the connector design of each connector manufacturer also has an effect on mechanical durability.

Table 1 – Experimental results

Manufacturer	Pass rate (n° of passing samples/ n° of samples) for tensile force 14,7 N	Connector type
A	100 % (72/72)	1
В	100 % (72/72)	I
С	97 % (35/36)	I
D	100 % (8/8)	II
E	100 % (5/5)	II
F	100 % (18/18)	
G	99 % (78/80)	I
Н	93 % (62/72)	I
I	18 % (11/60)	I

In a high density packaged system a tensile force of 14,7 N may sometimes be generated at frequency of 0,3 % according to the exponential fitting curve in Figure 3 on the adjacent port cable in a lateral direction.

Most of the failed samples were from one particular manufacturer. The failed connectors were the result of breakages caused when the inserted connector plugs were released from the adaptor. It was felt that the plugs that were broken in the nutation test would require some design improvements in order to satisfy the test requirements.

8 Conclusions

An allowable tensile load severity for the mechanical design proving nutation test to ensure network system reliability during fibre cable installations was investigated. It was confirmed that a tensile load severity of 14,7 N is needed for fibre optic connectors in high density systems. The nutation test results for optical connectors terminated with reinforced fibre cable were reported. In nutation test experiments with a tensile force of 14,7 N, most but not all commercially available fibre optic connectors exhibited the required performance. An analysis of the failed connectors revealed that design or material improvements were needed to ensure sufficient mechanical durability.

Finally, it is concluded that a nutation test with the proposed load of 14,7 N is effective in eliminating plugs that due to poor design or material selection could be damaged during fibre cable operation in high density systems applications

The 14,7 N design proving nutation test is an effective mechanism for the selection of suitable product.

Copyrighted material licensed to BR Demo by Thomson Reuters (Scientific), Inc., subscriptions.techstreet.com, downloaded on Nov-27-2014 by James Madison. No further reproduction or distribution is permitted. Uncontrolled when print

INTERNATIONAL ELECTROTECHNICAL COMMISSION

3, rue de Varembé PO Box 131 CH-1211 Geneva 20 Switzerland

Tel: + 41 22 919 02 11 Fax: + 41 22 919 03 00 info@iec.ch www.iec.ch