

INTERNATIONAL
STANDARD

ISO
5751-2

Sixth edition
2010-11-15

**Motorcycle tyres and rims (metric
series) —**

**Part 2:
Tyre dimensions and load-carrying
capacities**

*Pneumatiques et jantes pour motocycles (séries millimétriques) —
Partie 2: Cotes et capacités de charge des pneumatiques*



Reference number
ISO 5751-2:2010(E)

© ISO 2010

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Tyre designation	1
4.1 General	1
4.2 Tyre construction code	1
4.3 Other markings	2
5 Tyre dimensions	2
5.1 General	2
5.2 Measuring procedure	2
6 Tread configurations	3
7 Load ratings	3
7.1 General	3
7.2 Load capacity at reduced speeds	3
7.3 Load capacity at speeds higher than 210 km/h	3
8 Inflation pressures	4
Annex A (informative) Harmonized load indices	28
Bibliography.....	34

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5751-2 was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 10, *Cycle, moped, motorcycle tyres and rims*.

This sixth edition cancels and replaces the fifth edition (ISO 5751-2:2004), which has been technically revised.

ISO 5751 consists of the following parts, under the general title *Motorcycle tyres and rims (metric series)*:

- *Part 1: Design guides*
- *Part 2: Tyre dimensions and load-carrying capacities*
- *Part 3: Range of approved rim contours*

Motorcycle tyres and rims (metric series) —

Part 2: Tyre dimensions and load-carrying capacities

1 Scope

This part of ISO 5751 specifies the tyre size designation, dimensions and load-carrying capacities of metric series motorcycle tyres. It is applicable to such tyres with a height-to-width ratio of 100 % and below.

NOTE See ISO 4249 for motorcycle tyres and rims (code-designated series) of rim diameter codes 13 and above, and ISO 6054 for those of codes 12 and below.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4223-1, *Definitions of some terms used in the tyre industry — Part 1: Pneumatic tyres*

ISO 5751-1, *Motorcycle tyres and rims (metric series) — Part 1: Design guides*

ISO 5751-3, *Motorcycle tyres and rims (metric series) — Part 3: Range of approved rim contours*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4223-1 apply.

4 Tyre designation

4.1 General

The tyre designation shall be as specified in ISO 5751-1, completed by the addition of the service description, i.e. load index and speed symbol.

4.2 Tyre construction code

The tables in this part of ISO 5751 show, as examples, tyre size designations for tyres in diagonal construction. However, a motorcycle tyre having, for example, a

- nominal section width of 100 mm,
- nominal aspect ratio of 90,
- nominal rim diameter code of 18 M/C,

- load-carrying capacity of 224 kg (corresponding to load index 56), and
- reference speed of 150 km/h (corresponding to speed symbol “P”),

shall be marked, depending on its construction characteristics, as follows.

Diagonal-ply construction: **100/90 – 18M/C 56 P**

Bias-belted construction: **100/90 B 18M/C 56 P**

Radial-ply construction: **100/90 R 18M/C 56 P**

NOTE For tyres suitable for speeds greater than 240 km/h, see ISO 5751-1.

4.3 Other markings

For tyres having a nominal rim diameter code of 16 M/C or higher, the suffix M/C is not required if the tyre was manufactured before May 2003.

Extra-load version tyres shall be additionally marked either “Extra Load” or “REINF” (for *reinforced*).

5 Tyre dimensions

5.1 General

Tables 1 to 14 present the

- a) tyre size designation,
- b) measuring rim width code,
- c) design tyre dimensions, i.e. section width and overall diameter, and
- d) maximum tyre dimensions in service, i.e. overall width and diameter for the various types of tread configuration (see Clause 6) to be considered by vehicle manufacturers in designing for tyre clearances.

NOTE The maximum dimensions in service do not include the values of the centrifugal radius (see ISO 5751-1).

5.2 Measuring procedure

Mount the tyre on a chosen rim according to ISO 5751-3, approved for the respective tyre size and ready for fitting. Inflate as follows.

- a) For normal-load version tyres:
 - 225 kPa for speed symbols “S” and lower;
 - 280 kPa for speed symbols “T” and higher.
- b) For extra-load version tyres:
 - 280 kPa for speed symbols “P” and lower;
 - 330 kPa for speed symbols “Q” and higher.
- c) For light-load version tyres: 175 kPa.

Allow the tyre to stand for 24 h at normal room temperature, then readjust the inflation pressures to those specified in a), b) and c), before performing the measurements.

When measuring on rims having a rim width code that differs from that of the measuring rim width code given in the tables of this part of ISO 5751, the section-width and overall-width values of the tyre used for comparison with the data given in Tables 1 to 14 shall be adjusted as follows:

$$W = W_m + 0,4 (R - R_m)$$

where

W_m is the value measured;

R_m is the width, expressed in millimetres, of the rim used for the measurements;

R is the width, expressed in millimetres, of the measuring rim width code given in the tables.

6 Tread configurations

ISO 5751-1:—, Figure 1, shows various tread configurations. The following attributions of tread-type configurations to the type of service are to be considered as examples only. The choice of a given tread-type configuration for a given tyre is at the discretion of the tyre manufacturer alone.

- Tread type A is commonly adopted for highway-service low-speed tyres;
- tread type B is commonly adopted for highway-service high-speed tyres;
- tread type C is commonly adopted for tyres used in both on- and off-road service;
- tread type D is commonly adopted for tyres exclusively in off-road service.

7 Load ratings

7.1 General

Tables 15 to 29 show the standardized maximum tyre load-carrying capacity for each given tyre size designation.

7.2 Load capacity at reduced speeds

Subject to acceptance by the tyre manufacturer and taking into account the conditions of use of the motorcycle, the load capacities corresponding to the load indices indicated in Tables 15 to 29 may be modified by the percentages given in Table 30. This modification is possible when the maximum speed of motorcycle is different from the one associated with the speed symbol.

7.3 Load capacity at speeds higher than 210 km/h

For the load-carrying capacities of tyres marked with speed symbols "V" or "W" operating at speeds higher than 210 km/h, see ISO 5751-1.

8 Inflation pressures

The following inflation pressures are given as guidelines only. Inflation pressures used in practice are subject to agreement between the tyre and vehicle manufacturers and should take into account not only the load, but also the tyre construction, road holding, maximum speed, location of the tyre, operating conditions and mechanical characteristics of the vehicle.

The maximum load-carrying capacity corresponds to the following inflation pressures.

- a) For nominal rim diameter codes up to and including 12 (for series 80 and above):
 - 1) light-load version: 175 kPa
 - 2) normal-load version: 250 kPa
 - 3) extra-load version: 300 kPa
- b) For nominal rim diameter codes 13 and above (for series 70 and below, and also for nominal rim diameter codes 12 and below):
 - 1) light-load version: 175 kPa
 - 2) normal-load version:
 - for tyres marked with a speed symbol up to and including "P" 225 kPa
 - for tyres marked with a speed symbol "Q", "R" or "S" 250 kPa
 - for tyres marked with a speed symbol "T", "U" or "H" 280 kPa
 - for tyres marked with a speed symbol "V" or "W" 290 kPa
 - 3) extra-load version: increase the inflation pressure for the normal-load version by 50 kPa.

**Table 1 — Tyre dimensions (design and in-service) —
100 series tyres with nominal rim diameter codes 13 and above**

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service					
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i>			Maximum overall diameter ^b <i>D_{o,max}</i>	Tread types A and B	Tread types C and D
50/100 – 14 M/C	1.20	50	456	54	55	63	464	468	
60/100 – 14 M/C	1.40	60	476	64	66	75	484	490	
70/100 – 14 M/C	1.60	69	496	74	76	86	506	514	
80/100 – 14 M/C	1.85	80	516	86	88	100	528	536	
90/100 – 14 M/C	2.15	90	536	96	99	113	548	558	
70/100 – 15 M/C	1.60	69	521	74	76	86	531	537	
80/100 – 15 M/C	1.85	80	541	86	88	100	553	561	
90/100 – 15 M/C	2.15	90	561	96	99	113	573	583	
60/100 – 16 M/C	1.40	60	526	64	66	75	534	540	
70/100 – 16 M/C	1.60	69	546	74	76	86	556	562	
80/100 – 16 M/C	1.85	80	566	86	88	100	578	586	
90/100 – 16 M/C	2.15	90	586	96	99	113	598	608	
100/100 – 16 M/C	2.50	101	606	108	111	126	620	630	
130/100 – 16 M/C	3.00	129	666	138	142	161	684	698	
140/100 – 16 M/C	3.50	142	686	152	156	178	706	720	
50/100 – 17 M/C	1.20	50	532	54	55	63	540	544	
60/100 – 17 M/C	1.40	60	552	64	66	75	560	566	
70/100 – 17 M/C	1.60	69	572	74	76	86	582	588	
80/100 – 17 M/C	1.85	80	592	86	88	100	604	612	
90/100 – 17 M/C	2.15	90	612	96	99	113	624	634	
100/100 – 17 M/C	2.50	101	632	108	111	126	646	656	
110/100 – 17 M/C	2.50	109	652	117	120	136	668	678	
120/100 – 17 M/C	2.75	119	672	127	131	149	688	700	
130/100 – 17 M/C	3.00	129	692	138	142	161	710	724	
70/100 – 18 M/C	1.60	69	597	74	76	86	607	613	
80/100 – 18 M/C	1.85	80	617	86	88	100	629	637	
90/100 – 18 M/C	2.15	90	637	96	99	113	649	659	
100/100 – 18 M/C	2.50	101	657	108	111	126	671	681	
110/100 – 18 M/C	2.50	109	677	117	120	136	693	703	
120/100 – 18 M/C	2.75	119	697	127	131	149	713	725	
130/100 – 18 M/C	3.00	129	717	138	142	161	735	749	
70/100 – 19 M/C	1.60	69	623	74	76	86	633	639	
80/100 – 19 M/C	1.85	80	643	86	88	100	655	663	
90/100 – 19 M/C	2.15	90	663	96	99	113	675	685	
100/100 – 19 M/C	2.50	101	683	108	111	126	697	707	
110/100 – 19 M/C	2.50	109	703	117	120	136	719	729	
120/100 – 19 M/C	2.75	119	723	127	131	149	739	751	
130/100 – 19 M/C	3.00	129	743	138	142	161	761	775	
90/100 – 20 M/C	2.15	90	688	96	99	113	700	710	
70/100 – 21 M/C	1.60	69	673	74	76	86	683	689	
80/100 – 21 M/C	1.85	80	693	86	88	100	705	713	
90/100 – 21 M/C	2.15	90	713	96	99	113	725	735	

^a For appropriate tyre size designation, see Clause 4.^b Maximum overall diameters are related to service up to 150 km/h.^c Radial-ply tyres.^d Diagonal-ply and bias-belted tyres.

**Table 2 — Tyre dimensions (design and in-service) —
100 series tyres with nominal rim diameter codes 12 and below**

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service ^b	
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i>	Maximum overall diameter <i>D_{o,max}</i>
70/100 – 8	1.60	69	343	75	353
80/100 – 8	1.85	80	363	86	375
90/100 – 8	2.15	90	383	97	395
100/100 – 8	2.50	101	403	109	417
110/100 – 8	2.50	109	423	118	439
120/100 – 8	2.75	119	443	129	459
130/100 – 8	3.00	129	463	139	481
60/100 – 10	1.40	60	374	65	382
70/100 – 10	1.60	69	394	75	404
80/100 – 10	1.85	80	414	86	426
90/100 – 10	2.15	90	434	97	446
100/100 – 10	2.50	101	454	109	468
110/100 – 10	2.50	109	474	118	490
120/100 – 10	2.75	119	494	129	510
130/100 – 10	3.00	129	514	139	532
60/100 – 12	1.40	60	425	65	433
70/100 – 12	1.60	69	445	75	455
80/100 – 12	1.85	80	465	86	477
90/100 – 12	2.15	90	485	97	497
100/100 – 12	2.50	101	505	109	519
110/100 – 12	2.50	109	525	118	541
120/100 – 12	2.75	119	545	129	561
130/100 – 12	3.00	129	565	139	583

^a For appropriate tyre size designation, see Clause 4.^b Tread types A and B.

**Table 3 — Tyre dimensions (design and in-service) —
90 series tyres with nominal rim diameter codes 13 and above**

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service				
		Section width <i>s</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i>			Maximum overall diameter ^b <i>D_{o,max}</i>	
110/90 – 13 M/C	2.50	109	528	117	120	136	542	552
70/90 – 14 M/C	1.60	69	482	74	76	86	490	498
80/90 – 14 M/C	1.85	80	500	86	88	100	510	518
90/90 – 14 M/C	2.15	90	518	96	99	113	530	538
90/90 – 15 M/C	2.15	90	543	96	99	113	555	563
100/90 – 15 M/C	2.50	101	561	108	111	126	573	583
110/90 – 15 M/C	2.50	109	579	117	120	136	593	603
120/90 – 15 M/C	2.75	119	597	127	131	149	613	623
130/90 – 15 M/C	3.00	129	615	138	142	161	631	643
140/90 – 15 M/C	3.50	142	633	152	156	178	651	663
150/90 – 15 M/C	3.50	150	651	161	165	188	669	683
60/90 – 16 M/C	1.40	60	514	64	66	75	522	530
70/90 – 16 M/C	1.60	69	532	74	76	86	540	550
80/90 – 16 M/C	1.85	80	550	86	88	100	560	568
90/90 – 16 M/C	2.15	90	568	96	99	113	580	588
100/90 – 16 M/C	2.50	101	586	108	111	126	598	608
110/90 – 16 M/C	2.50	109	604	117	120	136	618	628
120/90 – 16 M/C	2.75	119	622	127	131	149	638	648
130/90 – 16 M/C	3.00	129	640	138	142	161	656	668
140/90 – 16 M/C	3.50	142	658	152	156	178	676	688
150/90 – 16 M/C	3.50	150	676	161	165	188	694	708
50/90 – 17 M/C	1.20	50	522	54	55	63	528	532
60/90 – 17 M/C	1.40	60	540	64	66	75	548	556
70/90 – 17 M/C	1.60	69	558	74	76	86	566	574
80/90 – 17 M/C	1.85	80	576	86	88	100	586	594
90/90 – 17 M/C	2.15	90	594	96	99	113	606	614
100/90 – 17 M/C	2.50	101	612	108	111	126	624	634
110/90 – 17 M/C	2.50	109	630	117	120	136	644	654
120/90 – 17 M/C	2.75	119	648	127	131	149	664	674
130/90 – 17 M/C	3.00	129	666	138	142	161	682	694
140/90 – 17 M/C	3.50	142	684	152	156	178	702	714
150/90 – 17 M/C	3.50	150	702	161	165	188	720	732
70/90 – 18 M/C	1.60	69	583	74	76	86	591	599
80/90 – 18 M/C	1.85	80	601	86	88	100	611	619
90/90 – 18 M/C	2.15	90	619	96	99	113	631	639
100/90 – 18 M/C	2.50	101	637	108	111	126	649	659
110/90 – 18 M/C	2.50	109	655	117	120	136	669	679
120/90 – 18 M/C	2.75	119	673	127	131	149	689	699
130/90 – 18 M/C	3.00	129	691	138	142	161	707	719
140/90 – 18 M/C	3.50	142	709	152	156	178	727	739
70/90 – 19 M/C	1.60	69	609	74	76	86	617	625
80/90 – 19 M/C	1.85	80	627	86	88	100	637	645
90/90 – 19 M/C	2.15	90	645	96	99	113	657	665
100/90 – 19 M/C	2.50	101	663	108	111	126	675	685
110/90 – 19 M/C	2.50	109	681	117	120	136	695	705
120/90 – 19 M/C	2.75	119	699	127	131	149	715	725
130/90 – 19 M/C	3.00	129	717	138	142	161	733	745
70/90 – 21 M/C	1.60	69	659	74	76	86	667	675
80/90 – 21 M/C	1.85	80	677	86	88	100	687	695
90/90 – 21 M/C	2.15	90	695	96	99	113	707	715
100/90 – 21 M/C	2.50	101	713	108	111	126	725	735

^a For appropriate tyre size designation, see Clause 4.^b Maximum overall diameters are related to service up to 150 km/h.^c Radial-ply tyres.^d Diagonal-ply and bias-belted tyres.

**Table 4 — Tyre dimensions (design and in-service) —
90 series tyres with nominal rim diameter codes 12 and below**

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service ^b	
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i>	Maximum overall diameter <i>D_{o,max}</i>
60/90 – 8	1.40	60	311	66	319
70/90 – 8	1.60	69	329	75	337
80/90 – 8	1.85	80	347	86	357
90/90 – 8	2.15	90	365	97	377
100/90 – 8	2.50	101	383	109	395
110/90 – 8	2.50	109	401	118	415
120/90 – 8	2.75	119	419	129	435
130/90 – 8	3.00	129	437	139	453
60/90 – 10	1.40	60	362	66	370
70/90 – 10	1.60	69	380	75	388
80/90 – 10	1.85	80	398	86	408
90/90 – 10	2.15	90	416	97	428
100/90 – 10	2.50	101	434	109	446
110/90 – 10	2.50	109	452	118	466
120/90 – 10	2.75	119	470	129	486
130/90 – 10	3.00	129	488	139	504
60/90 – 12	1.40	60	413	66	421
70/90 – 12	1.60	69	431	75	439
80/90 – 12	1.85	80	449	86	459
90/90 – 12	2.15	90	467	97	479
100/90 – 12	2.50	101	485	109	497
110/90 – 12	2.50	109	503	118	517
120/90 – 12	2.75	119	521	129	537
130/90 – 12	3.00	129	539	139	555

^a For appropriate tyre size designation, see Clause 4.^b Tread types A and B.

**Table 5 — Tyre dimensions (design and in-service) —
80 series tyres with nominal rim diameter codes 13 and above**

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service					
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i>			Maximum overall diameter ^b <i>D_{o,max}</i>		
				Tread types A, B and C ^c	Tread types A, B and C ^d	Tread type D	Tread types A and B	Tread types C and D	
120/80 – 13 M/C	2.75	119	522	127	131	149	536	546	
80/80 – 14 M/C	1.85	80	484	86	88	100	492	500	
90/80 – 14 M/C	2.15	90	500	96	99	113	510	518	
100/80 – 14 M/C	2.50	101	516	108	111	126	528	536	
110/80 – 14 M/C	2.50	109	532	117	120	136	542	554	
120/80 – 14 M/C	2.75	119	548	127	131	149	562	572	
130/80 – 14 M/C	3.00	129	564	138	142	161	578	588	
160/80 – 14 M/C	4.00	162	612	173	178	203	630	642	
180/80 – 14 M/C	4.50	183	644	196	201	229	664	678	
130/80 – 15 M/C	3.00	129	589	138	142	161	603	613	
140/80 – 15 M/C	3.50	142	605	152	156	178	621	631	
150/80 – 15 M/C	3.50	150	621	161	165	188	637	649	
160/80 – 15 M/C	4.00	162	637	173	178	203	655	667	
170/80 – 15 M/C	4.00	170	653	182	187	213	673	685	
80/80 – 16 M/C	1.85	80	534	86	88	100	542	550	
90/80 – 16 M/C	2.15	90	550	96	99	113	560	568	
100/80 – 16 M/C	2.50	101	566	108	111	126	578	586	
110/80 – 16 M/C	2.50	109	582	117	120	136	594	604	
120/80 – 16 M/C	2.75	119	598	127	131	149	612	622	
130/80 – 16 M/C	3.00	129	614	138	142	161	628	638	
140/80 – 16 M/C	3.50	142	630	152	156	178	646	656	
150/80 – 16 M/C	3.50	150	646	161	165	188	662	674	
160/80 – 16 M/C	4.00	162	662	173	178	203	680	692	
60/80 – 17 M/C	1.40	60	528	64	66	75	534	540	
70/80 – 17 M/C	1.60	69	544	74	76	86	552	558	
80/80 – 17 M/C	1.85	80	560	86	88	100	568	576	
90/80 – 17 M/C	2.15	90	576	96	99	113	586	594	
100/80 – 17 M/C	2.50	101	592	108	111	126	604	612	
110/80 – 17 M/C	2.50	109	608	117	120	136	620	630	
120/80 – 17 M/C	2.75	119	624	127	131	149	638	648	
130/80 – 17 M/C	3.00	129	640	138	142	161	654	664	
140/80 – 17 M/C	3.50	142	656	152	156	178	672	682	
150/80 – 17 M/C	3.50	150	672	161	165	188	688	700	
70/80 – 18 M/C	1.60	69	569	74	76	86	577	583	
80/80 – 18 M/C	1.85	80	585	86	88	100	593	601	
90/80 – 18 M/C	2.15	90	601	96	99	113	611	619	
100/80 – 18 M/C	2.50	101	617	108	111	126	629	637	
110/80 – 18 M/C	2.50	109	633	117	120	136	645	655	
120/80 – 18 M/C	2.75	119	649	127	131	149	663	673	
130/80 – 18 M/C	3.00	129	665	138	142	161	679	689	
140/80 – 18 M/C	3.50	142	681	152	156	178	697	707	
150/80 – 18 M/C	3.50	150	697	161	165	188	713	725	
160/80 – 18 M/C	4.00	162	713	173	178	203	731	743	
80/80 – 19 M/C	1.85	80	611	86	88	100	619	627	
90/80 – 19 M/C	2.15	90	627	96	99	113	637	645	
100/80 – 19 M/C	2.50	101	643	108	111	126	655	663	
110/80 – 19 M/C	2.50	109	659	117	120	136	671	681	
120/80 – 19 M/C	2.75	119	675	127	131	149	689	699	
130/80 – 19 M/C	3.00	129	691	138	142	161	705	715	
140/80 – 19 M/C	3.50	142	707	152	156	178	723	733	
80/80 – 21 M/C	1.85	80	661	86	88	100	669	677	
90/80 – 21 M/C	2.15	90	677	96	99	113	687	695	
100/80 – 21 M/C	2.50	101	693	108	111	126	705	713	

^a For appropriate tyre size designation, see Clause 4.^b Maximum overall diameters are related to service up to 150 km/h.^c Radial-ply tyres.^d Diagonal-ply and bias-belted tyres.

**Table 6 — Tyre dimensions (design and in-service) —
80 series tyres with nominal rim diameter codes 12 and below**

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service ^b	
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i>	Maximum overall diameter <i>D_{o,max}</i>
60/80 – 8	1.40	60	299	65	305
70/80 – 8	1.60	69	315	75	323
80/80 – 8	1.85	80	331	86	339
90/80 – 8	2.15	90	347	97	357
100/80 – 8	2.50	101	363	109	375
110/80 – 8	2.50	109	379	118	391
120/80 – 8	2.75	119	395	129	409
130/80 – 8	3.00	129	411	139	425
60/80 – 10	1.40	60	350	65	356
70/80 – 10	1.60	69	366	75	374
80/80 – 10	1.85	80	382	86	390
90/80 – 10	2.15	90	398	97	408
100/80 – 10	2.50	101	414	109	426
110/80 – 10	2.50	109	430	118	442
120/80 – 10	2.75	119	446	129	460
130/80 – 10	3.00	129	462	139	476
150/80 – 10	3.50	150	494	162	510
60/80 – 12	1.40	60	401	65	407
70/80 – 12	1.60	69	417	75	425
80/80 – 12	1.85	80	433	86	441
90/80 – 12	2.15	90	449	97	459
100/80 – 12	2.50	101	465	109	477
110/80 – 12	2.50	109	481	118	493
120/80 – 12	2.75	119	497	129	511
130/80 – 12	3.00	129	513	139	527
140/80 – 12	3.50	142	529	153	545

^a For appropriate tyre size designation, see Clause 4.^b Tread types A and B.

Table 7 — Tyre dimensions (design and in-service) — 75 series tyres

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service — Tread types A and B	
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i>	Maximum overall diameter ^b <i>D_{o,max}</i>
140/75 – 17 M/C	3.50	139	642	149	153

^a For appropriate tyre size designation, see Clause 4.^b Maximum overall diameters are related to service up to 150 km/h.

Table 8 — Tyre dimensions (design and in-service) — 70 series tyres

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service — Tread types A and B		Maximum overall diameter ^b $D_{o,max}$
		Section width S	Overall diameter D_o	Maximum overall width W_{max}	Radial	
80/70 – 16 M/C	2.15	79	518	85	87	526
100/70 – 16 M/C	2.75	100	546	107	110	556
100/70 – 17 M/C			572			582
100/70 – 18 M/C			597			607
100/70 – 19 M/C			623			633
110/70 – 11	3.00	110	433	118	119	443
110/70 – 12			459			469
110/70 – 16 M/C	3.00	110	560	118	121	570
110/70 – 17 M/C			586			596
110/70 – 18 M/C			611			621
110/70 – 19 M/C			637			647
120/70 – 10	3.50	122	422	131	132	434
120/70 – 11			447			457
120/70 – 12			473			485
120/70 – 13 M/C	3.50	122	498	131	134	510
120/70 – 14 M/C			524			536
120/70 – 15 M/C			549			561
120/70 – 16 M/C			574			586
120/70 – 17 M/C			600			612
120/70 – 18 M/C			625			637
120/70 – 19 M/C			651			663
120/70 – 21 M/C			701			713
130/70 – 8	3.50	129	385	138	139	397
130/70 – 10			436			448
130/70 – 11			461			471
130/70 – 12			487			499
130/70 – 13 M/C	3.50	129	512	138	142	524
130/70 – 16 M/C			588			600
130/70 – 17 M/C			614			626
130/70 – 18 M/C			639			651
130/70 – 19 M/C			665			677
130/70 – 24 M/C			792			804
140/70 – 8	3.75	139	399	149	150	413
140/70 – 12			501			515
140/70 – 14 M/C	3.75	139	552	149	153	566
140/70 – 15 M/C			577			591
140/70 – 16 M/C			602			616
140/70 – 17 M/C			628			642
140/70 – 18 M/C			653			667
140/70 – 19 M/C			679			693
140/70 – 21 M/C			729			743
150/70 – 13 M/C	4.25	151	540	162	166	554
150/70 – 14 M/C			566			580
150/70 – 16 M/C			616			630
150/70 – 17 M/C			642			656
150/70 – 18 M/C			667			681
150/70 – 19 M/C			693			707
160/70 – 16 M/C	4.50	161	630	172	177	646
160/70 – 17 M/C			656			672
160/70 – 18 M/C			681			697
160/70 – 19 M/C			707			723
170/70 – 15 M/C	4.50	168	619	180	185	635
170/70 – 16 M/C			644			660
180/70 – 15 M/C	5.00	180	633	193	198	651
180/70 – 16 M/C			658			676
200/70 – 15 M/C	5.50	200	661	214	220	681

^a For appropriate tyre size designation, see Clause 4.^b Maximum overall diameters are related to service up to 150 km/h.

Table 9 — Tyre dimensions (design and in-service) — 65 and 60 series tyres

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service — Tread types A and B		
		Section width <i>S</i>	Overall diameter <i>D₀</i>	Maximum overall width <i>W_{max}</i> Radial	Diagonal and bias-belted	Maximum overall diameter ^b <i>D_{0,max}</i>
65 series						
120/65 – 17 M/C	3.50	122	588	131	134	598
180/65 – 16 M/C	5.00	180	640	193	198	656
60 series						
110/60 – 16 M/C	3.00	110	538	118	121	548
110/60 – 17 M/C			564			574
110/60 – 18 M/C			589			599
110/60 – 19 M/C			615			625
120/60 – 16 M/C	3.50	122	550	131	134	560
120/60 – 17 M/C			576			586
120/60 – 18 M/C			601			611
120/60 – 19 M/C			627			637
130/60 – 13 M/C	3.50	129	486	138	142	496
130/60 – 16 M/C			562			572
130/60 – 17 M/C			588			598
130/60 – 18 M/C			613			623
130/60 – 19 M/C			639			649
130/60 – 23 M/C			740			750
140/60 – 12	4.00	141	473	151	152	485
140/60 – 13 M/C	3.75	139	498	149	153	510
140/60 – 14 M/C			524			536
140/60 – 16 M/C			574			586
140/60 – 17 M/C			600			612
140/60 – 18 M/C			625			637
140/60 – 19 M/C			651			663
150/60 – 13 M/C	4.25	151	510	162	166	522
150/60 – 14 M/C			536			548
150/60 – 16 M/C			586			598
150/60 – 17 M/C			612			624
150/60 – 18 M/C			637			649
150/60 – 19 M/C			663			657
160/60 – 14 M/C	4.50	161	548	172	177	562
160/60 – 15 M/C			573			587
160/60 – 16 M/C			598			612
160/60 – 17 M/C			624			638
160/60 – 18 M/C			649			663
160/60 – 19 M/C			675			689
170/60 – 16 M/C	4.50	168	610	180	185	624
170/60 – 17 M/C			636			650
170/60 – 18 M/C			661			675
170/60 – 19 M/C			687			701
180/60 – 16 M/C	5.00	180	622	193	198	638
180/60 – 17 M/C	5.00	188	648	193	198	664
190/60 – 17 M/C	5.00	188	660	201	207	676
200/60 – 16 M/C	5.50	200	646	214	220	662
210/60 – 16 M/C	6.00	212	658	227	233	676
230/60 – 15 M/C	6.25	229	657	245	252	677

^a For appropriate tyre size designation, see Clause 4.^b Maximum overall diameters are related to service up to 150 km/h.

Table 10 — Tyre dimensions (design and in-service) — 55 series tyres

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service — Tread types A and B		
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i>	Radial	Diagonal and bias-belted
130/55 – 16 M/C	4.00	129	550	138	142	560
130/55 – 17 M/C			576			586
130/55 – 18 M/C			601			611
130/55 – 19 M/C			627			637
140/55 – 16 M/C	4.50	141	560	151	155	570
140/55 – 17 M/C			586			596
140/55 – 18 M/C			611			621
140/55 – 19 M/C			637			647
150/55 – 16 M/C	4.50	148	572	158	163	584
150/55 – 17 M/C			598			610
150/55 – 18 M/C			623			635
150/55 – 19 M/C			649			661
160/55 – 16 M/C	5.00	160	582	171	176	594
160/55 – 17 M/C			608			620
160/55 – 18 M/C			633			645
160/55 – 19 M/C			659			671
170/55 – 16 M/C	5.50	172	594	184	189	608
170/55 – 17 M/C			620			634
170/55 – 18 M/C			645			659
170/55 – 19 M/C			671			685
180/55 – 16 M/C	5.50	178	604	190	196	618
180/55 – 17 M/C			630			644
180/55 – 18 M/C			655			669
180/55 – 19 M/C			681			695
190/55 – 16 M/C	6.00	190	616	203	209	630
190/55 – 17 M/C			642			656
190/55 – 18 M/C			667			681
190/55 – 19 M/C			693			707
200/55 – 16 M/C	6.25	200	626	214	220	642
200/55 – 17 M/C			652			668
200/55 – 18 M/C			677			693
210/55 – 18 M/C	6.50	209	689	224	230	705
240/55 – 16 M/C	7.50	239	670	256	263	688

^a For appropriate tyre size designation, see Clause 4.^b Maximum overall diameters are related to service up to 150 km/h.

Table 11 — Tyre dimensions (design and in-service) — 50 series tyres

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service — Tread types A and B		
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i>	Radial	Diagonal and bias-belted
160/50 – 16 M/C	5.00	160	566	171	176	578
160/50 – 17 M/C			592			604
160/50 – 18 M/C			617			629
160/50 – 19 M/C			643			655
170/50 – 16 M/C	5.50	172	576	184	189	588
170/50 – 17 M/C			602			614
170/50 – 18 M/C			627			639
170/50 – 19 M/C			653			665
180/50 – 16 M/C	5.50	178	586	190	196	598
180/50 – 17 M/C			612			624
180/50 – 18 M/C			637			649
180/50 – 19 M/C			663			675
190/50 – 16 M/C	6.00	190	596	203	209	610
190/50 – 17 M/C			622			636
190/50 – 18 M/C			647			661
190/50 – 19 M/C			673			687
200/50 – 17 M/C	6.25	200	632	214	221	646
200/50 – 18 M/C			657			671
210/50 – 17 M/C	6.50	209	642	224	230	656
240/50 – 16 M/C	7.50	239	646	256	263	662

^a For appropriate tyre size designation, see Clause 4.
^b Maximum overall diameters are related to service up to 150 km/h.

Table 12 — Tyre dimensions (design and in-service) — 40 series tyres

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service — Tread types A and B		
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i>	Radial	Diagonal and bias-belted
210/40 – 18 M/C	7.50	211	625	226	232	637
240/40 – 18 M/C	8.50	240	649	257	264	663
250/40 – 18 M/C	9.00	251	657	269	276	671
260/40 – 18 M/C	9.00	258	665	276	284	679
280/40 – 20 M/C	10.00	281	732	301	309	748
300/40 – 17 M/C	10.50	299	672	320	329	688

^a For appropriate tyre size designation, see Clause 4.
^b Maximum overall diameters are related to service up to 150 km/h.

Table 13 — Tyre dimensions (design and in-service) — 35 series tyres

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service — Tread types A and B		
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i> Radial	Diagonal and bias-belted	Maximum overall diameter ^b <i>D_{o,max}</i>
260/35 – 21 M/C	9.00	258	715	276	284	727
280/35 – 18 M/C	10.00	281	653	301	309	667
300/35 – 18 M/C	10.50	299	667	320	329	681

^a For appropriate tyre size designation, see Clause 4.
^b Maximum overall diameters are related to service up to 150 km/h.

Table 14 — Tyre dimensions (design and in-service) — 30 series tyres

Dimensions in millimetres

Tyre size designation ^a	Measuring rim width code	Design tyre		In-service — Tread types A and B		
		Section width <i>S</i>	Overall diameter <i>D_o</i>	Maximum overall width <i>W_{max}</i> Radial	Diagonal and bias-belted	Maximum overall diameter ^b <i>D_{o,max}</i>
330/30 – 17 M/C	11.50	328	630	351	361	644
360/30 – 18 M/C	13.00	362	673	387	398	689

^a For appropriate tyre size designation, see Clause 4.
^b Maximum overall diameters are related to service up to 150 km/h.

**Table 15 — Maximum tyre load ratings —
100 series tyres with nominal rim diameter codes 13 and above**

Tyre size designation ^a	Load index	Maximum load capacity ^b kg	Tyre size designation ^a	Load index	Maximum load capacity ^b kg
50/100 – 14 M/C	19 ^d	77.5	130/100 – 17 M/C	71 ^d	345
60/100 – 14 M/C	29 ^d	103		77 ^c	412
70/100 – 14 M/C	37 ^d	128	70/100 – 18 M/C	41 ^d	145
	42 ^c	150		47 ^c	175
80/100 – 14 M/C	43 ^d	155	80/100 – 18 M/C	47 ^d	175
	49 ^c	185		54 ^c	212
90/100 – 14 M/C	49 ^d	185	90/100 – 18 M/C	54 ^d	212
	55 ^c	218		60 ^c	250
70/100 – 15 M/C	38 ^d	132	100/100 – 18 M/C	59 ^d	243
80/100 – 15 M/C	44 ^d	160		65 ^c	290
90/100 – 15 M/C	50 ^d	190	110/100 – 18 M/C	64 ^d	280
60/100 – 16 M/C	31 ^d	109		70 ^c	335
	38 ^c	132	120/100 – 18 M/C	68 ^d	315
70/100 – 16 M/C	39 ^d	136		74 ^c	375
	45 ^c	165	130/100 – 18 M/C	72 ^d	355
80/100 – 16 M/C	45 ^d	165		78 ^c	425
	51 ^c	195	70/100 – 19 M/C	42 ^d	150
90/100 – 16 M/C	51 ^d	195		48 ^c	180
	58 ^c	236	80/100 – 19 M/C	49 ^d	185
100/100 – 16 M/C	57 ^d	230		55 ^c	218
130/100 – 16 M/C	70 ^d	335	90/100 – 19 M/C	55 ^d	218
	76 ^c	400		61 ^c	257
140/100 – 16 M/C	74 ^d	375	100/100 – 19 M/C	60 ^d	250
	80 ^c	450		66 ^c	300
50/100 – 17 M/C	23 ^d	87.5	110/100 – 19 M/C	65 ^d	290
60/100 – 17 M/C	33 ^d	115		71 ^c	345
	39 ^c	136	120/100 – 19 M/C	69 ^d	325
70/100 – 17 M/C	40 ^d	140		75 ^c	387
	46 ^c	170	130/100 – 19 M/C	73 ^d	365
80/100 – 17 M/C	46 ^d	170		79 ^c	437
	53 ^c	206	90/100 – 20 M/C	56 ^d	224
90/100 – 17 M/C	53 ^d	206		62 ^c	265
	59 ^c	243	70/100 – 21 M/C	44 ^d	160
100/100 – 17 M/C	58 ^d	236	80/100 – 21 M/C	51 ^d	195
	64 ^c	280	90/100 – 21 M/C	57 ^d	230
110/100 – 17 M/C	63 ^d	272			
	69 ^c	325			
120/100 – 17 M/C	67 ^d	307			
	73 ^c	365			

^a The full designation shall be as given in Clause 4.

^b See Clause 7.

^c Extra-load version.

^d Normal-load version.

**Table 16 — Maximum tyre load ratings —
100 series tyres with nominal rim diameter codes 12 and below**

Tyre size designation ^a	Load index	Maximum load capacity ^b kg	Tyre size designation ^a	Load index	Maximum load capacity ^b kg
70/100 – 8	26 ^e	95	110/100 – 10	54 ^e	212
	36 ^d	125		64 ^d	280
	41 ^c	145		69 ^c	325
80/100 – 8	34 ^e	118	120/100 – 10	59 ^e	243
	43 ^d	155		68 ^d	315
	48 ^c	180		73 ^c	365
90/100 – 8	40 ^e	140	130/100 – 10	64 ^e	280
	49 ^d	185		73 ^d	365
	54 ^c	212		78 ^c	425
100/100 – 8	45 ^e	165	60/100 – 12	26 ^e	95
	55 ^d	218		36 ^d	125
	60 ^c	250		41 ^c	145
110/100 – 8	50 ^e	190	70/100 – 12	34 ^e	118
	60 ^d	250		43 ^d	155
	65 ^c	290		48 ^c	180
120/100 – 8	55 ^e	218	80/100 – 12	41 ^e	145
	65 ^d	290		50 ^d	190
	70 ^c	335		55 ^c	218
130/100 – 8	60 ^e	250	90/100 – 12	46 ^e	170
	69 ^d	325		56 ^d	224
	74 ^c	375		61 ^c	257
60/100 – 10	23 ^e	87.5	100/100 – 12	52 ^e	200
	33 ^d	115		62 ^d	265
	38 ^c	132		67 ^c	307
70/100 – 10	30 ^e	106	110/100 – 12	58 ^e	236
	40 ^d	140		67 ^d	307
	45 ^c	165		72 ^c	355
80/100 – 10	38 ^e	132	120/100 – 12	62 ^e	265
	46 ^d	170		71 ^d	345
	52 ^c	200		76 ^c	400
90/100 – 10	43 ^e	155	130/100 – 12	66 ^e	300
	53 ^d	206		75 ^d	387
	58 ^c	236		80 ^c	450
100/100 – 10	49 ^e	185			
	59 ^d	243			
	64 ^c	280			

^a The full designation shall be as given in Clause 4.

^b See Clause 7.

^c Extra-load version.

^d Normal-load version.

^e Light-load version.

**Table 17 — Maximum tyre load ratings —
90 series tyres with nominal rim diameter codes 13 and above**

Tyre size designation ^a	Load index	Maximum load capacity ^b kg	Tyre size designation ^a	Load index	Maximum load capacity ^b kg
110/90 – 13 M/C	55 ^d	218	120/90 – 17 M/C	64 ^d	280
70/90 – 14 M/C	34 ^d	118	130/90 – 17 M/C	70 ^c	335
	40 ^c	140		68 ^d	315
80/90 – 14 M/C	40 ^d	140	140/90 – 17 M/C	74 ^c	375
	46 ^c	170		72 ^d	355
90/90 – 15 M/C	47 ^d	175	150/90 – 17 M/C	76 ^d	400
100/90 – 15 M/C	53 ^d	206	70/90 – 18 M/C	39 ^d	136
110/90 – 15 M/C	58 ^d	236	80/90 – 18 M/C	44 ^c	160
120/90 – 15 M/C	62 ^d	265		45 ^d	165
130/90 – 15 M/C	66 ^d	300	90/90 – 18 M/C	51 ^c	195
140/90 – 15 M/C	70 ^d	335		51 ^d	195
	76 ^c	400	100/90 – 18 M/C	57 ^c	230
150/90 – 15 M/C	74 ^d	375		56 ^d	224
	80 ^c	450	110/90 – 18 M/C	62 ^c	265
60/90 – 16 M/C	29 ^d	103		61 ^d	257
	35 ^c	121	120/90 – 18 M/C	67 ^c	307
70/90 – 16 M/C	36 ^d	125		65 ^d	290
	42 ^c	150	130/90 – 18 M/C	71 ^c	345
80/90 – 16 M/C	43 ^d	155		69 ^d	325
	48 ^c	180	140/90 – 18 M/C	75 ^c	387
90/90 – 16 M/C	48 ^d	180		73 ^d	365
	55 ^c	218	70/90 – 19 M/C	40 ^d	140
100/90 – 16 M/C	54 ^d	212	80/90 – 19 M/C	45 ^c	165
110/90 – 16 M/C	59 ^d	243		46 ^d	170
120/90 – 16 M/C	63 ^d	272	90/90 – 19 M/C	52 ^c	200
130/90 – 16 M/C	67 ^d	307		52 ^d	200
	73 ^c	365	100/90 – 19 M/C	58 ^c	236
140/90 – 16 M/C	71 ^d	345		57 ^d	230
	77 ^c	412	110/90 – 19 M/C	63 ^c	272
150/90 – 16 M/C	75 ^d	387		62 ^d	265
	81 ^c	462	120/90 – 19 M/C	68 ^c	315
50/90 – 17 M/C	21 ^d	82.5		66 ^d	300
60/90 – 17 M/C	30 ^d	106		72 ^c	355
	36 ^c	125	130/90 – 19 M/C	70 ^d	355
70/90 – 17 M/C	38 ^d	132		76 ^c	400
	43 ^c	155	70/90 – 21 M/C	43 ^d	155
80/90 – 17 M/C	44 ^d	160	80/90 – 21 M/C	48 ^d	180
	50 ^c	190	90/90 – 21 M/C	54 ^d	212
90/90 – 17 M/C	49 ^d	185	100/90 – 21 M/C	59 ^d	243
	56 ^c	224			
100/90 – 17 M/C	55 ^d	218			
	61 ^c	257			
110/90 – 17 M/C	60 ^d	250			
	66 ^c	300			

^a The full designation shall be as given in Clause 4.

^b See Clause 7.

^c Extra-load version.

^d Normal-load version.

**Table 18 — Maximum tyre load ratings —
90 series tyres with nominal rim diameter codes 12 and below**

Tyre size designation ^a	Load index	Maximum load capacity ^b kg	Tyre size designation ^a	Load index	Maximum load capacity ^b kg
60/90 – 8	16 ^e	71	110/90 – 10	51 ^e	195
	25 ^d	92,5		61 ^d	257
	30 ^c	106		66 ^c	300
70/90 – 8	24 ^e	90	120/90 – 10	57 ^e	230
	34 ^d	118		66 ^d	300
	39 ^c	136		71 ^c	345
80/90 – 8	31 ^e	109	130/90 – 10	61 ^e	257
	41 ^d	145		70 ^d	335
	46 ^c	170		75 ^c	387
90/90 – 8	38 ^e	132	60/90 – 12	24 ^e	90
	47 ^d	175		34 ^d	118
	52 ^c	200		39 ^c	136
100/90 – 8	43 ^e	155	70/90 – 12	31 ^e	109
	53 ^d	206		41 ^d	145
	58 ^c	236		46 ^c	170
110/90 – 8	48 ^e	180	80/90 – 12	39 ^e	136
	58 ^d	236		48 ^d	180
	63 ^c	272		53 ^c	206
120/90 – 8	52 ^e	200	90/90 – 12	44 ^e	160
	62 ^d	265		54 ^d	212
	67 ^c	307		59 ^c	243
130/90 – 8	57 ^e	230	100/90 – 12	49 ^e	185
	66 ^d	300		59 ^d	243
	71 ^c	345		64 ^c	280
60/90 – 10	20 ^e	80	110/90 – 12	54 ^e	212
	30 ^d	106		64 ^d	280
	35 ^c	121		69 ^c	325
70/90 – 10	28 ^e	100	120/90 – 12	60 ^e	250
	38 ^d	132		69 ^d	325
	43 ^c	155		74 ^c	375
80/90 – 10	35 ^e	121	130/90 – 12	64 ^e	280
	44 ^d	160		73 ^d	365
	49 ^c	185		78 ^c	425
90/90 – 10	41 ^e	145			
	50 ^d	190			
	55 ^c	218			
100/90 – 10	46 ^e	170			
	56 ^d	224			
	61 ^c	257			

^a The full designation shall be as given in Clause 4.

^b See Clause 7.

^c Extra-load version.

^d Normal-load version.

^e Light-load version.

**Table 19 — Maximum tyre load ratings —
80 series tyres with nominal rim diameter codes 13 and above**

Tyre size designation ^a	Load index	Maximum load capacity ^b kg	Tyre size designation ^a	Load index	Maximum load capacity ^b kg
120/80 – 13 M/C	56 ^d	224	110/80 – 17 M/C	57 ^d	230
	62 ^c	265		61 ^d	257
80/80 – 14 M/C	43 ^c	155	120/80 – 17 M/C	67 ^c	307
90/80 – 14 M/C	43 ^d	155		65 ^d	290
	49 ^c	185	130/80 – 17 M/C	69 ^d	325
100/80 – 14 M/C	48 ^d	180	140/80 – 17 M/C	72 ^d	355
	54 ^c	212	150/80 – 17 M/C	36 ^d	125
110/80 – 14 M/C	53 ^d	206		41 ^c	145
	59 ^c	243	70/80 – 18 M/C	42 ^d	150
120/80 – 14 M/C	58 ^d	236		48 ^c	180
130/80 – 14 M/C	62 ^d	265	80/80 – 18 M/C	47 ^d	175
160/80 – 14 M/C	72 ^d	355		54 ^c	212
180/80 – 14 M/C	78 ^d	425	100/80 – 18 M/C	53 ^d	206
130/80 – 15 M/C	63 ^d	272		59 ^c	243
140/80 – 15 M/C	67 ^d	307	110/80 – 18 M/C	58 ^d	236
	73 ^c	365		64 ^c	280
150/80 – 15 M/C	70 ^d	335	120/80 – 18 M/C	62 ^d	265
	76 ^c	400		68 ^c	315
160/80 – 15 M/C	74 ^d	375	130/80 – 18 M/C	66 ^d	300
170/80 – 15 M/C	77 ^d	412		72 ^c	355
	83 ^c	487	140/80 – 18 M/C	70 ^d	335
80/80 – 16 M/C	40 ^d	140		76 ^c	400
	45 ^c	165	150/80 – 18 M/C	73 ^d	365
90/80 – 16 M/C	45 ^d	165		79 ^c	437
	51 ^c	195	160/80 – 18 M/C	83 ^c	487
100/80 – 16 M/C	50 ^d	190	80/80 – 19 M/C	43 ^d	155
110/80 – 16 M/C	55 ^d	218	90/80 – 19 M/C	49 ^d	185
120/80 – 16 M/C	60 ^d	250	100/80 – 19 M/C	54 ^d	212
130/80 – 16 M/C	64 ^d	280	110/80 – 19 M/C	59 ^d	243
140/80 – 16 M/C	68 ^d	315	120/80 – 19 M/C	63 ^d	272
150/80 – 16 M/C	71 ^d	345	130/80 – 19 M/C	67 ^d	307
	77 ^c	412	140/80 – 19 M/C	71 ^d	345
160/80 – 16 M/C	75 ^d	387	80/80 – 21 M/C	45 ^d	165
	81 ^c	462	90/80 – 21 M/C	51 ^d	195
60/80 – 17 M/C	27 ^d	97.5	100/80 – 21 M/C	56 ^d	224
70/80 – 17 M/C	35 ^d	121			
80/80 – 17 M/C	41 ^d	145			
90/80 – 17 M/C	46 ^d	170			
100/80 – 17 M/C	52 ^d	200			

^a The full designation shall be as given in Clause 4.

^b See Clause 7.

^c Extra-load version.

^d Normal-load version.

**Table 20 — Maximum tyre load ratings —
80 series tyres with nominal rim diameter codes 12 and below**

Tyre size designation ^a	Load index	Maximum load capacity ^b kg	Tyre size designation ^a	Load index	Maximum load capacity ^b kg
60/80 – 8	13 ^e	65	110/80 – 10	48 ^e	180
	22 ^d	85		58 ^d	236
	27 ^c	97,5		63 ^c	272
70/80 – 8	20 ^e	80	120/80 – 10	52 ^e	200
	30 ^d	106		62 ^d	265
	35 ^c	121		67 ^c	307
80/80 – 8	27 ^e	97,5	130/80 – 10	57 ^e	230
	37 ^d	128		66 ^d	300
	42 ^c	150		71 ^c	345
90/80 – 8	34 ^e	118	150/80 – 10	65 ^e	290
	43 ^d	155		74 ^d	375
	48 ^c	180	60/80 – 12	20 ^e	80
100/80 – 8	40 ^e	140		30 ^d	106
	49 ^d	185		35 ^c	121
	54 ^c	212	70/80 – 12	28 ^e	100
110/80 – 8	44 ^e	160		38 ^d	132
	54 ^d	212		43 ^c	155
	59 ^c	243	80/80 – 12	35 ^e	121
120/80 – 8	49 ^e	185		44 ^d	160
	59 ^d	243		49 ^c	185
	64 ^c	280	90/80 – 12	41 ^e	145
130/80 – 8	53 ^e	206		50 ^d	190
	63 ^d	272		55 ^c	218
	68 ^c	315	100/80 – 12	46 ^e	170
60/80 – 10	17 ^e	73		56 ^d	224
	26 ^d	95		61 ^c	257
	31 ^c	109	110/80 – 12	51 ^e	195
70/80 – 10	25 ^e	92,5		61 ^d	257
	35 ^d	121		66 ^c	300
	40 ^c	140	120/80 – 12	55 ^e	218
80/80 – 10	31 ^e	109		65 ^d	290
	41 ^d	145		70 ^c	335
	46 ^c	170	130/80 – 12	60 ^e	250
90/80 – 10	38 ^e	132		69 ^d	325
	47 ^d	175		74 ^c	375
	52 ^c	200	140/80 – 12	74 ^d	375
100/80 – 10	43 ^e	155			
	53 ^d	206			
	58 ^c	236			

^a The full designation shall be as given in Clause 4.

^b See Clause 7.

^c Extra-load version.

^d Normal-load version.

^e Light-load version.

Table 21 — Maximum tyre load ratings — 75 series tyres

Tyre size designation ^a	Load index	Maximum load capacity ^b kg
140/75 – 17 M/C	67	307

^a The full designation shall be as given in Clause 4.
^b See Clause 7. Normal-load version.

Table 22 — Maximum tyre load ratings — 70 series tyres

Tyre size designation ^a	Load index	Maximum load capacity ^b kg	Tyre size designation ^a	Load index	Maximum load capacity ^b kg
80/70 – 16 M/C	43 ^c	155	130/70 – 16 M/C	61 ^d	257
100/70 – 16 M/C	47 ^d	175	130/70 – 17 M/C	62 ^d	265
100/70 – 17 M/C	49 ^d	185	130/70 – 18 M/C	63 ^d	272
100/70 – 18 M/C	50 ^d	190	130/70 – 19 M/C	69 ^c	325
100/70 – 19 M/C	51 ^d	195	130/70 – 24 M/C	64 ^d	280
110/70 – 12	47 ^d	175	140/70 – 8	53 ^d	206
110/70 – 16 M/C	52 ^d	200	140/70 – 12	60 ^d	250
110/70 – 17 M/C	54 ^d	212	140/70 – 14 M/C	65 ^c	290
110/70 – 18 M/C	55 ^d	218	140/70 – 15 M/C	62 ^d	265
110/70 – 19 M/C	56 ^d	224	140/70 – 16 M/C	68 ^c	315
120/70 – 10	48 ^d	180	140/70 – 17 M/C	69 ^c	325
	54 ^c	212	140/70 – 18 M/C	65 ^d	290
120/70 – 11	50 ^d	190	140/70 – 19 M/C	66 ^d	300
	56 ^c	224	140/70 – 21 M/C	67 ^d	307
120/70 – 12	44 ^e	160	140/70 – 21 M/C	68 ^d	315
	51 ^d	195	150/70 – 13 M/C	76 ^c	400
	58 ^c	236	150/70 – 14 M/C	64 ^d	280
120/70 – 13 M/C	53 ^d	206	150/70 – 14 M/C	66 ^d	300
120/70 – 14 M/C	55 ^d	218	150/70 – 16 M/C	72 ^c	355
	61 ^c	257	150/70 – 17 M/C	68 ^d	315
120/70 – 15 M/C	56 ^d	224	150/70 – 18 M/C	69 ^d	325
120/70 – 16 M/C	57 ^d	230	150/70 – 19 M/C	70 ^d	335
120/70 – 17 M/C	58 ^d	236	160/70 – 16 M/C	71 ^d	345
120/70 – 18 M/C	59 ^d	243	160/70 – 17 M/C	73 ^d	365
120/70 – 19 M/C	60 ^d	250	160/70 – 18 M/C	79 ^c	437
120/70 – 21 M/C	62 ^d	265	160/70 – 19 M/C	74 ^d	375
130/70 – 8	42 ^c	150	170/70 – 15 M/C	75 ^d	387
130/70 – 10	52 ^d	200	170/70 – 16 M/C	76 ^d	365
	59 ^c	243	180/70 – 15 M/C	73 ^d	365
130/70 – 11	54 ^d	212	180/70 – 16 M/C	75 ^d	387
	60 ^c	250	200/70 – 15 M/C	77 ^d	412
130/70 – 12	49 ^e	185	200/70 – 15 M/C	82 ^d	475
	56 ^d	224			
	62 ^c	265			
130/70 – 13 M/C	57 ^d	230			
	63 ^c	272			

^a The full designation shall be as given in Clause 4.^b See Clause 7.^c Extra-load version.^d Normal-load version.^e Light-load version.

Table 23 — Maximum tyre load ratings — 65 series tyres

Tyre size designation ^a	Load index	Maximum load capacity ^b kg
120/65 – 17 M/C	56 ^d	224
180/65 – 16 M/C	81 ^c	462

^a The full designation shall be as given in Clause 4.
^b See Clause 7.
^c Extra-load version.
^d Normal-load version.

Table 24 — Maximum tyre load ratings — 60 series tyres

Tyre size designation ^a	Load index	Maximum load capacity ^b kg	Tyre size designation ^a	Load index	Maximum load capacity ^b kg
110/60 – 16 M/C	49 ^d	185	150/60 – 13 M/C	61 ^d	257
110/60 – 17 M/C	50 ^d	190		66 ^c	300
110/60 – 18 M/C	51 ^d	195	150/60 – 14 M/C	62 ^d	256
110/60 – 19 M/C	53 ^d	206	150/60 – 16 M/C	65 ^d	290
120/60 – 16 M/C	53 ^d	206	150/60 – 17 M/C	66 ^d	300
120/60 – 17 M/C	55 ^d	218	150/60 – 18 M/C	67 ^d	307
120/60 – 18 M/C	56 ^d	224	150/60 – 19 M/C	68 ^d	315
120/60 – 19 M/C	57 ^d	230	160/60 – 14 M/C	65 ^d	290
	53 ^d	206	160/60 – 15 M/C	67 ^d	307
130/60 – 13 M/C	60 ^c	250	160/60 – 16 M/C	68 ^d	315
130/60 – 16 M/C	58 ^d	236	160/60 – 17 M/C	69 ^d	325
130/60 – 17 M/C	59 ^d	243	160/60 – 18 M/C	70 ^d	335
130/60 – 18 M/C	60 ^d	250	160/60 – 19 M/C	71 ^d	345
130/60 – 19 M/C	61 ^d	257	170/60 – 16 M/C	71 ^d	345
130/60 – 23 M/C	65 ^d	290	170/60 – 17 M/C	72 ^d	355
	56 ^d	224	170/60 – 18 M/C	73 ^d	365
140/60 – 12 M/C	62 ^c	265	170/60 – 19 M/C	74 ^d	375
	57 ^d	230	180/60 – 16 M/C	74 ^d	375
140/60 – 13 M/C	63 ^c	272	180/60 – 17 M/C	75 ^d	387
140/60 – 14 M/C	64 ^c	280	190/60 – 17 M/C	78 ^d	425
140/60 – 16 M/C	61 ^d	257	200/60 – 16 M/C	79 ^d	437
140/60 – 17 M/C	63 ^d	272	210/60 – 16 M/C	82 ^d	475
140/60 – 18 M/C	64 ^d	280	230/60 – 15 M/C	86 ^d	530
140/60 – 19 M/C	65 ^d	290			

^a The full designation shall be as given in Clause 4.
^b See Clause 7.
^c Extra-load version.
^d Normal-load version.

Table 25 — Maximum tyre load ratings — 55 series tyres

Tyre size designation ^a	Load index	Maximum load capacity ^b kg
130/55 – 16 M/C	55	218
130/55 – 17 M/C	57	230
130/55 – 18 M/C	58	236
130/55 – 19 M/C	59	243
140/55 – 16 M/C	59	243
140/55 – 17 M/C	60	250
140/55 – 18 M/C	61	257
140/55 – 19 M/C	62	265
150/55 – 16 M/C	63	272
150/55 – 17 M/C	64	280
150/55 – 18 M/C	65	290
150/55 – 19 M/C	66	300
160/55 – 16 M/C	65	290
160/55 – 17 M/C	67	307
160/55 – 18 M/C	68	315
160/55 – 19 M/C	69	325
170/55 – 16 M/C	69	325
170/55 – 17 M/C	70	335
170/55 – 18 M/C	71	345
170/55 – 19 M/C	72	355
180/55 – 16 M/C	71	345
180/55 – 17 M/C	73	365
180/55 – 18 M/C	74	375
180/55 – 19 M/C	75	387
190/55 – 16 M/C	74	375
190/55 – 17 M/C	75	387
190/55 – 18 M/C	76	400
190/55 – 19 M/C	77	412
200/55 – 16 M/C	77	412
200/55 – 17 M/C	78	425
200/55 – 18 M/C	79	437
210/55 – 18 M/C	82	462
240/55 – 16 M/C	86	530

^a The full designation shall be as given in Clause 4.^b See Clause 7. Normal-load version.

Table 26 — Maximum tyre load ratings — 50 series tyres

Tyre size designation ^a	Load index	Maximum load capacity ^b kg
160/50 – 16 M/C	63	272
160/50 – 17 M/C	64	280
160/50 – 18 M/C	65	290
160/50 – 19 M/C	66	300
170/50 – 16 M/C	66	300
170/50 – 17 M/C	67	307
170/50 – 18 M/C	68	315
170/50 – 19 M/C	69	325
180/50 – 16 M/C	69	325
180/50 – 17 M/C	70	335
180/50 – 18 M/C	71	345
180/50 – 19 M/C	72	355
190/50 – 16 M/C	72	355
190/50 – 17 M/C	73	365
190/50 – 18 M/C	74	375
190/50 – 19 M/C	75	387
200/50 – 17 M/C	75	387
200/50 – 18 M/C	76	400
210/50 – 17 M/C	78	425
240/50 – 16 M/C	84	500

^a The full designation shall be as given in Clause 4.
^b See Clause 7. Normal-load version.

Table 27 — Maximum tyre load ratings — 40 series tyres

Tyre size designation ^a	Load index	Maximum load capacity ^b kg
210/40 – 18 M/C	73	365
240/40 – 18 M/C	79	437
250/40 – 18 M/C	81	462
260/40 – 18 M/C	84	500
280/40 – 20 M/C	89	580
300/40 – 17 M/C	90	600

^a The full designation shall be as given in Clause 4.
^b See Clause 7. Normal-load version.

Table 28 — Maximum tyre load ratings — 35 series tyres

Tyre size designation ^a	Load index	Maximum load capacity ^b kg
260/35 – 21 M/C	83	487
280/35 – 18 M/C	84	500
300/35 – 18 M/C	87	545

^a The full designation shall be as given in Clause 4.
^b See Clause 7. Normal-load version.

Table 29 — Maximum tyre load ratings — 30 series tyres

Tyre size designation ^a	Load index	Maximum load capacity ^b kg
330/30 – 17 M/C	87	545
360/30 – 18 M/C	92	630

^a The full designation shall be as given in Clause 4.
^b See Clause 7. Normal-load version.

Table 30 — Variation of maximum load capacities of tyres according to maximum speed of motorcycle (see 7.2)

Maximum speed (km/h)	Maximum load variation (%) at various maximum speeds for tyres with speed symbol:					
	J	K	L	M	N	P and above
50	+30	+30		+30		
60	+23	+23		+23		
70	+16	+16		+16		
80	+10	+10		+10		+14
90	+5	+5		+7,5		+12
100	[0]	0		+5		+10
110	N/A	[0]		+2,5		+8
120	N/A	N/A	[0]	0	0	+6
130	N/A	N/A	N/A	[0]	0	+4
140	N/A	N/A	N/A	N/A	[0]	0

Square brackets identify the maximum speed for the speed symbol.
N/A Not applicable.

Annex A

(informative)

Harmonized load indices

The following load indices (Tables A.1 to A.12) are given for reference purposes and refer to standard load tyres. They conform to the load indices given in Tables 15 to 29.

The reference pressure is 225 kPa, except for 80 series and above tyres with rim diameter codes 12 and below for which the reference pressure is 250 kPa.

Table A.1 — Harmonized load indices — 30 series tyres

Nominal section width S_N	Nominal rim diameter code				
	16 M/C	17 M/C	18 M/C	19 M/C	21 M/C
330		87			
360			92		

Table A.2 — Harmonized load indices — 35 series tyres

Nominal section width S_N	Nominal rim diameter code				
	16 M/C	17 M/C	18 M/C	19 M/C	21 M/C
260					83
280			84		
300			87		

Table A.3 — Harmonized load indices — 40 series tyres

Nominal section width S_N	Nominal rim diameter code					
	16 M/C	17 M/C	18 M/C	19 M/C	20 M/C	21 M/C
210			73			
240			79			
250			81			
260			84			
280					89	
300		90				

Table A.4 — Harmonized load indices — 50 series tyres

Nominal section width S_N	Nominal rim diameter code				
	16 M/C	17 M/C	18 M/C	19 M/C	21 M/C
160	63	64	65	66	68
170	66	67	68	69	71
180	69	70	71	72	74
190	72	73	74	75	77
200	74	75	76	77	79
210	77	78	79	80	82
220	79	80	81	82	84
230	81	82	84	85	87
240	84	85	86	87	89

Table A.5 — Harmonized load indices — 55 series tyres

Nominal section width S_N	Nominal rim diameter code				
	16 M/C	17 M/C	18 M/C	19 M/C	21 M/C
130	55	57	58	59	
140	59	60	61	62	
150	63	64	65	66	
160	65	67	68	69	71
170	69	70	71	72	74
180	71	73	74	75	77
190	74	75	76	77	79
200	77	78	79	80	82
210	79	80	82	83	85
240	86				

Table A.6 — Harmonized load indices — 60 series tyres

Nominal section width S_N	Nominal rim diameter code									
	12	13 M/C	14 M/C	15 M/C	16 M/C	17 M/C	18 M/C	19 M/C	21 M/C	23 M/C
110		45	46	47	49	50	51	53		
120		49	51	52	53	55	56	57		
130	52	53	55	56	58	59	60	61		65
140	56	57	59	60	61	63	64	65		
150	59	61	62	64	65	66	67	68	70	
160	63	64	65	67	68	69	70	71	73	
170	66	67	69	70	71	72	73	74	76	
180	69	70	72	73	74	75	76	77	79	
190				75	77	78	79	80	82	
200				78	79	80	81	82	84	
210				81	82	83	84	85	87	
220				83	84	85	86	88	89	
230				86	87	88	89	90	91	

Table A.7 — Harmonized load indices — 65 series tyres

Nominal section width S_N	Nominal rim diameter code			
	16 M/C	17 M/C	18 M/C	19 M/C
100	45	47	48	49
110	50	52	53	54
120	55	56	57	58
130	59	60	61	63
140	63	64	65	66
150	66	67	69	70
160	69	70	72	73
170	73	74	75	76
180	75	76	77	78
190	78			

Table A.8 — Harmonized load indices — 70 series tyres

Nominal section width S_N	Nominal rim diameter code												
	8	10	11	12	13 M/C	14 M/C	15 M/C	16 M/C	17 M/C	18 M/C	19 M/C	21 M/C	24 M/C
80					33	34	36	37					
90					39	40	41	42					
100					43	45	46	47	49	50	51	53	
110	40	43		47	48	50	51	52	54	55	56	58	
120	44	48	50	51	53	55	56	57	58	59	60	62	
130	48	52	54	56	57	59	60	61	62	63	64	66	69
140	53	56		60	61	62	64	65	66	67	68	70	
150					64	66	67	68	69	70	71	73	
160							70	71	73	74	75	76	
170							73	75	76	77	78	79	
180							76	77	78	79	80	82	
190							79	80	81	82	83	85	
200							82	83	84	85	86	88	

Table A.9 — Harmonized load indices — 75 series tyres

Nominal section width S_N	Nominal rim diameter code				
	16 M/C	17 M/C	18 M/C	19 M/C	21 M/C
140		67			

Table A.10 — Harmonized load indices — 80 series tyres

Nominal section width S_N	Nominal rim diameter code											
	8	10	12	13 M/C	14 M/C	15 M/C	16 M/C	17 M/C	18 M/C	19 M/C	21 M/C	
60	22	26	30					27				
70	30	35	38	29	30	32	33	35	36	37		
80	37	41	44	36	37	39	40	41	42	43	45	
90	43	47	50	41	43	44	45	46	47	49	51	
100	49	53	56	46	48	49	50	52	53	54	56	
110	54	58	61	51	53	54	55	57	58	59	61	
120	59	62	65	56	58	59	60	61	62	63	65	
130	63	66	69		62	63	64	65	66	67	69	
140			74		65	67	68	69	70	71	73	
150		74			69	70	71	72	73	75	76	
160					72	74	75	76	77	78	79	
170					75	77	78	79	80	81	83	
180					78	79	81	82	83	84		

Table A.11 — Harmonized load indices — 90 series tyres

Nominal section width S_N	Nominal rim diameter code											
	8	10	12	13 M/C	14 M/C	15 M/C	16 M/C	17 M/C	18 M/C	19 M/C	21 M/C	
50								21				
60	25	30	34	24	26	27	29	30				
70	34	38	41	32	34	35	36	38	39	40	43	
80	41	44	48	39	40	41	43	44	45	46	48	
90	47	50	54	44	46	47	48	49	51	52	54	
100	53	56	59	50	51	53	54	55	56	57	59	
110	58	61	64	55	56	58	59	60	61	62	64	
120	62	66	69			62	63	64	65	66	68	
130	66	70	73			66	67	68	69	70	72	
140						70	71	72	73	74	76	
150						74	75	76	77	78	79	

Table A.12 — Harmonized load indices — 100 series tyres

Nominal section width S_N	Nominal rim diameter code										
	8	10	12	14 M/C	15 M/C	16 M/C	17 M/C	18 M/C	19 M/C	20 M/C	21 M/C
50				19			23				
60		33	36	29	30	31	33				
70	36	40	43	37	38	39	40	41	42		44
80	43	46	50	43	44	45	46	47	49		51
90	49	53	56	49	50	51	53	54	55	56	57
100	55	59	62			57	58	59	60		62
110	60	64	67			62	63	64	65		67
120	65	68	71			66	67	68	69		71
130	69	73	75			70	71	72	73		75
140						74	75	76	77		79

Bibliography

- [1] ISO 4249-1:1985, *Motorcycle tyres and rims (Code-designated series) — Part 1: Tyres*
- [2] ISO 4249-2:1990, *Motorcycle tyres and rims (Code-designated series) — Part 2: Tyre load ratings*
- [3] ISO 4249-3, *Motorcycle tyres and rims (Code-designated series) — Part 3: Rims*
- [4] ISO 6054-1:1994, *Motorcycle tyres and rims (Code-designated series) — Diameter codes 4 to 12 — Part 1: Tyres*
- [5] ISO 6054-2:1990, *Motorcycle tyres and rims (Code-designated series) — Diameter codes 4 to 12 — Part 2: Rims*

ICS 43.140; 83.160.10

Price based on 34 pages