INTERNATIONAL STANDARD

ISO 8536-4

Fifth edition 2010-10-01 **AMENDMENT 1** 2013-03-01

Infusion equipment for medical use — Part 4: Infusion sets for single use, gravity feed AMENDMENT 1

Matériel de perfusion à usage médical —

Partie 4: Appareils de perfusion non réutilisables, à alimentation par gravité

AMENDEMENT 1



Reference number ISO 8536-4:2010/Amd.1:2013(E)

ISO 8536-4:2010/Amd.1:2013(E)



COPYRIGHT PROTECTED DOCUMENT

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO 8536-4:2010was prepared by Technical Committee ISO/TC 76, *Transfusion, infusion and injection, and blood processing equipment for medical and pharmaceutical use.*

Infusion equipment for medical use —

Part 4:

Infusion sets for single use, gravity feed

AMENDMENT 1

Page 8, 9.1

In alignment with ISO 1135-4:2012, 8.1:

- the note between e) and f) becomes NOTE 1;
- at the end of 9.1 add the following note:

NOTE 2 The presence of substances of interest can be indicated by using symbol 2725 of ISO 7000 by replacing the "XXX" with the abbreviation of the substance. The absence of substances of interest can be indicated by crossing the respective symbol.

Page 8, 9.2

In alignment with ISO 1135-4:2012, 8.2, add the following note at the end of 9.2:

NOTE The presence of substances of interest can be indicated by using symbol 2725 of ISO 7000 by replacing the "XXX" with the abbreviation of the substance. The absence of substances of interest can be indicated by crossing the respective symbol.

Page 9, Clause 11

In alignment with ISO 1135-4:2012, Clause 10, add the following new Clause 11:

11 Disposal

Information for secure and environmentally sound disposal of single-use infusion sets should be given, e.g. "Always dispose of blood contaminated products in a manner consistent with established biohazard procedures.

Page 11, A.2

Replace the entire clause with the following:

A.2 Tests for leakage

- **A.2.1** At the beginning of the test, the whole system shall be tempered at the test temperature.
- **A.2.2** Connect the infusion set with air supply and close all other openings. Apply air with an internal excess pressure of 50 kPa to the infusion set for 15 s. Inspect the infusion set for any leakage of air under water at $40\,^{\circ}$ C.

Fill the infusion set with degassed, distilled water, connect it with its openings sealed to a vacuum device and subject it to an internal excess pressure of -20 kPa at 40 °C for 15 s. Atmospheric pressure shall be the reference pressure. Excess pressure, in accordance with ISO 80000-4, can assume positive or negative values. Ascertain whether air enters the infusion set.

Page 13, Figure A.1

To clarify that the test apparatus in Figure A.1 is an example, change the figure title to the following:

Figure A.1 — Example apparatus setup for testing the efficiency of the fluid filter

Page 13, A.6

Amend the second sentence as follows:

Fill the infusion set with water in such a manner that no air bubbles are trapped and apply a pressure of 20 kPa above the atmospheric air pressure.

Page 17, Bibliography

In alignment with ISO 1135-4:2012 and the modifications to 9.1 and 9.2, add the following reference:

[2] ISO 7000, Graphical symbols for use on equipment — Registered symbols

Renumber subsequent references accordingly.



ICS 11.040.20

Price based on 2 pages