INTERNATIONAL STANDARD

ISO 8626

First edition 1989-06-15 **AMENDMENT 1** 2016-12-01

Servo-hydraulic test equipment for generating vibration — Method of describing characteristics

AMENDMENT 1

Moyens d'essais servo-hydrauliques utilisés pour la génération de vibrations — Méthodes de description des caractéristiques

AMENDEMENT 1



Reference number ISO 8626:1989/Amd.1:2016(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 6, *Vibration and shock generating systems*.

Servo-hydraulic test equipment for generating vibration — Method of describing characteristics

AMENDMENT 1

Page 15, 7.1.11

Replace the whole subclause with the following:

7.1.11 Transverse motion of the test table

The manufacturer shall specify the transverse motion ratio, *T*, of the test table or the power take-off as a function of frequency as follows:

$$T = \max \left[\frac{\sqrt{a_x^2(t) + a_y^2(t)}}{A_z} \right] \times 100 \%$$

where

 $a_x(t)$, $a_y(t)$ are accelerations along two arbitrary orthogonal axes in the plane perpendicular to the operating axis z at the central fixing point;

 A_z is the specified amplitude of the sine acceleration along the operating axis z at the central fixing point.

If the central point is not accessible, the position of the reference point shall be indicated.

The measurements shall be made at no load and, if possible, at rated force. The manufacturer shall indicate the method employed and the value of the force.

Supplementary measurements of the transverse motion, such as measurements with test loads or measurements away from the central point, shall be carried out if agreed between the manufacturer and the user.

