## INTERNATIONAL STANDARD

ISO 9539

Second edition 2010-01-15 **AMENDMENT 1** 2013-12-15

# Gas welding equipment — Materials for equipment used in gas welding, cutting and allied processes —

#### **AMENDMENT 1**

Matériel de soudage aux gaz — Matériaux utilisés pour le matériel de soudage aux gaz, coupage et techniques connexes —
AMENDEMENT 1





#### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2, <a href="www.iso.org/directives">www.iso.org/directives</a>.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received, <a href="https://www.iso.org/patents">www.iso.org/patents</a>.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

The committee responsible for this document is ISO/TC 44, *Welding and allied processes*, Subcommittee SC 8, *Equipment for gas welding, cutting and allied processes*.

Requests for official interpretations of any aspect of this Amendment should be directed to the Secretariat of ISO/TC 44/SC 8 via your national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org">www.iso.org</a>.

### Gas welding equipment — Materials for equipment used in gas welding, cutting and allied processes —

#### AMENDMENT 1

Page 1, Clause 2

Update the title of ISO 1817

ISO 1817, Rubber, vulcanized or thermoplastic — Determination of the effect of liquids

#### Page 2, 4.2.1

The original wording of ISO 9539:2010 could be interpreted in two ways. It was not clear if there shall be a measurement after test steps a), b) ,and c), respectively, or if there shall be only one measurement after test step c). This amendment specifies a clear procedure.

Replace the existing text with the following.

Non-metallic materials (e.g. those used for seals and lubricants) liable to come into contact with acetylene shall be adequately resistant individually to acetone and dimethylformamide (DMF) solvents.

Non-metallic materials (e.g. those used for seals and lubricants) liable to come into contact with propane, butane and methylacetylene-propadiene mixtures shall be adequately resistant to n-pentane.

For the purposes of this International Standard, the term "adequate resistance" (to solvents) will be taken to mean that the material shall fulfill the following conditions.

The change in mass shall not exceed  $\pm 15$  % and the change in hardness shall not exceed  $\pm 15$  IRHD after the material has been conditioned as follows:

- a)  $(168 \pm 2)$  h in an atmosphere saturated with solvent as specified above at  $(23 \pm 2)$  °C;
- b) a subsequent period in air for  $(70 \pm 2)$  h at  $(40 \pm 2)$  °C;
- c) a subsequent period (24 ± 2) h at standard atmosphere 23/50 as specified in ISO 554.

The measurement of change of mass and hardness shall be carried out after test step c) in accordance with ISO 1817.

