

TECHNICAL REPORT ISO/TR 13593:1999 TECHNICAL CORRIGENDUM 1

Published 2005-12-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Enclosed gear drives for industrial applications

TECHNICAL CORRIGENDUM 1

Transmissions de puissance par engenages sous carter pour usage industriel

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to Technical Report ISO/TR 13593:1999 was prepared by Technical Committee ISO/TC 60, *Gears*.

Page 9, Equation (7)

Replace the equation with the following one:

$$\sigma_{\rm b} = \frac{32\ 000\ M\ d_{\rm she}}{\pi (d_{\rm she}^4 - d_{\rm shi}^4)}$$

Page 11, 5.5.4

Replace the last sentence of the subclause with

"See ISO 6336-5:1996, Clauses 1 and 4, and 5.1 and 6.1, for more information."

ISO/TR 13593:1999/Cor.1:2005(E)

Page 13, 5.6.2

Replace the line second from the top of the page with

" R_e is the tensile yield strength of the key material, in N/mm²;"

Page 72, E.7

Replace the last sentence of the clause with

"The seal shall be replaced before running."