INTERNATIONAL STANDARD

ISO 15534-3

First edition 2000-02-15

Ergonomic design for the safety of machinery —

Part 3: **Anthropometric data**

Conception ergonomique pour la sécurité des machines — Partie 3: Données anthropométriques



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 734 10 79
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

iii

Cor	ntents	Page
Fore	word	iv
Intro	duction	v
1	Scope	1
2	Normative references	1
3	General requirements	1
4	Anthropometric data	2
4.1	Human body measurements (anthropometric data from European survey)	2
42	Descriptions of human body measurements	Δ

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 15534 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 15534-3 was prepared by Technical Committee ISO/TC 159, *Ergonomics*, Subcommittee SC 3, *Anthropometry and biomechanics*.

ISO 15534 consists of the following parts, under the general title Ergonomic design for the safety of machinery:

- Part 1: Principles for determining the dimensions required for openings for whole-body access into machinery
- Part 2: Principles for determining the dimensions required for access openings
- Part 3: Anthropometric data

Introduction

This part of ISO 15534 is one of several ergonomics standards for the safety of machinery. EN 614-1:1995, *Safety of machinery — Ergonomic design principles — Part 1: Terminology and general principles*, describes the principles designers should adopt in order to take account of ergonomic factors.

This part of ISO 15534 is based on EN 547-3:1996 that was prepared as a harmonized standard conforming with the Machinery Directive and associated European Free Trade Association (EFTA) regulations.

© ISO 2000 – All rights reserved

Ergonomic design for the safety of machinery —

Part 3:

Anthropometric data

1 Scope

This part of ISO 15534 specifies current requirements for human body measurements (anthropometric data) that are required by ISO 15534-1 and ISO 15534-2 for the calculation of access-opening dimensions as applied to machinery.

The anthropometric data originate from static measurements of nude persons and do not take into account body movements, clothing, equipment, machinery-operating conditions or environmental conditions.

The data are based on information from anthropometric surveys representative of population groups within Europe comprising at least three million people. Both men and women are taken into account.

Measurements are given, as required by ISO 15534-1 and ISO 15534-2, for the 5th, 95th and 99th percentiles of the relevant population group within Europe.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 15534. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 15534 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 15534-1:2000, Ergonomic design for the safety of machinery — Part 1: Principles for determining the dimensions required for openings for whole-body access into machinery.

ISO 15534-2:2000, Ergonomic design for the safety of machinery — Part 2: Principles for determining the dimensions required for access openings.

ISO 7250:1996, Basic human body measurements for technological design. (EN ISO 7250:1997)

3 General requirements

Anthropometric measurements form the basis upon which minimum dimensions of access openings can be calculated. Where machinery requires access openings, the provisions of ISO 15534-1 (for whole body access) and ISO 15534-2 (for access of parts of the body) shall be complied with.

Table 1 gives the human body measurements necessary to calculate the size of access openings taking account of the known range of body sizes within Europe.

© ISO 2000 – All rights reserved

ISO 15534-3:2000(E)

The symbols used in Tables 1 and 2 are common to ISO 15534-1 and ISO 15534-2. Appropriate values from Table 1 shall be substituted in the formulae in clause 4 of ISO 15534-1:1999 and clause 4 of ISO 15534-2:1999, in order to calculate the dimensions of particular access openings.

4 Anthropometric data

4.1 Human body measurements (anthropometric data from European survey)

Table 1 shows the best approximation of currently available data from European surveys. The data estimate the values of the 5th, 95th and 99th percentiles for combined female and male populations.

Each of the anthropometric values in Table 1 is established according to one of the following two methods.

- National surveys with pooled female and male populations: the corresponding value of the 5th, 95th and 99th percentile is used.
- b) National surveys with separate female and male percentiles: the mean of the female and male value of the 5th percentile (value of the 95th and 99th percentile respectively) is calculated.

NOTE Although this is not strictly accurate statistically, it is a good practical approximation.

For the value of the 5th percentile, the lower of these calculated values is chosen as the European value. For the values of the 95th and 99th percentiles, the highest value is chosen.

Table 1 — Anthropometric data from European surveys

Symbol	Explanation	Value mm
h ₁	Stature (body height) P95	1 881
h ₁	Stature (body height) P99	1 944
h ₈	Ankle height	96
<i>a</i> ₁	Elbow-to-elbow breadth P95	545
<i>a</i> ₁	Elbow-to-elbow breadth P99	576
a_3	Hand breadth with thumb P95	120
a ₄	Hand breadth at metacarpals P95	97
a_5	Index finger breadth, proximal P95	23
<i>a</i> ₆	Foot breadth P95	113
<i>b</i> ₁	Body depth, standing P95	342
<i>b</i> ₂	Grip reach; forward reach P5	615
<i>b</i> ₂	Grip reach; forward reach P95	820
<i>b</i> ₂	Grip reach; forward reach P99	845
b_3	Hand depth at palm P95	30
<i>b</i> ₄	Hand depth at thumb P95	35
c ₁	Buttock-knee length (thigh length) P95	687
c ₁	Buttock-knee length (thigh length) P99	725
c ₂	Foot length P5	211
c ₂	Foot length P95	285
c ₂	Foot length P99	295
c ₃	Head length from tip of nose P95	240
d_1	Upper-arm diameter P95	121
d_2	Lower-arm diameter P95	120
d_3	Fist diameter P95	120
t ₁	Operating-arm length P5	340
t ₂	Forearm reach P5	170
t ₃		
t ₄	3 U. U. 4 DE	
t ₅ Hand length to thumb P5		88
t ₆	Index finger length P5	59

4.2 Descriptions of human body measurements

The descriptions of the human body measurements presented in ISO 15534-1 and ISO 15534-2 are taken in part from ISO 7250. Other human body measurements are produced by addition or subtraction of two measurements taken from ISO 7250 or by the multiplication of a measurement by a determined factor. Fixed measurements are presented when the variation within the population of interest is minimal.

The specific measurements and descriptions are given in Table 2.

Table 2 — Symbols of human body measurements

Symbol	Explanation	Definition See ISO 7250:1996, subclause	
h ₁	Stature (body height)	4.1.2	
h ₈	Ankle height: fixed value 96 mm	_	
a_1	Elbow-to-elbow breadth	4.2.10	
a_3	Hand breadth with thumb: hand breadth at metacarpals × determined factor 1,25	4.3.3	
a_4	Hand breadth at metacarpals	4.3.3	
a_5	Index finger breadth, proximal	4.3.5	
a_6	Foot breadth	4.3.8	
<i>b</i> ₁	Body depth, standing	4.1.10	
b_2	Grip reach; forward reach	4.4.2	
<i>b</i> ₃	Hand depth at palm: fixed value 30 mm	_	
<i>b</i> ₄	Hand depth at thumb: fixed value 35 mm	_	
<i>c</i> ₁	Buttock-knee length (thigh length)	4.4.7	
c_2	Foot length	4.3.7	
c_3	Head length from tip of nose: head length + fixed value 30 mm	4.3.9	
d_1	Upper-arm diameter: fixed value 121 mm	_	
d_2	Lower-arm diameter: hand breadth at metacarpals × determined factor 1,25	4.3.3	
d_3	Fist diameter: hand breadth at metacarpals × determined factor 1,25	4.3.3	
<i>t</i> ₁	Operating-arm length: grip reach minus fixed value 275 mm	4.4.2	
t_2	Forearm reach: elbow-grip length minus fixed value 121 mm	4.4.3	
<i>t</i> ₃	Arm reach to the side: grip reach minus fixed value 120 mm	4.4.2	
t_4	Hand length	4.3.1	
<i>t</i> ₅	Hand length to thumb: hand length × determined factor 0,58	4.3.1	
<i>t</i> ₆	Index-finger length	4.3.4	



Price based on 4 pages