

INTERNATIONAL  
STANDARD

ISO  
19378

First edition  
2003-03-01

---

---

**Lubricants, industrial oils and related  
products (class L) — Machine-tool  
lubricants — Categories and  
specifications**

*Lubrifiants, huiles industrielles et produits connexes (classe L) —  
Lubrifiants pour machines outils — Catégories et spécifications*

---

---

---

Reference number  
ISO 19378:2003(E)



© ISO 2003

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

|  | Page      |
|--|-----------|
| <b>Foreword .....</b>  | <b>iv</b> |
| <b>1 Scope.....</b>  | <b>1</b>  |
| <b>2 Normative references .....</b>  | <b>1</b>  |
| <b>3 Sampling .....</b>  | <b>2</b>  |
| <b>4 Categories of products for the lubrication of machine tools — Criteria for the choice .....</b>                             | <b>3</b>  |
| <b>5 Specifications of products .....</b>  | <b>3</b>  |
| <b>6 Packaging and labelling .....</b>   | <b>3</b>  |
| <b>Annex A (informative) Preliminary information about the future International Standard for specifications of greases .....</b> | <b>9</b>  |
| <b>Bibliography .....</b>  | <b>10</b> |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 19378 was prepared by Technical Committee ISO/TC 28, *Petroleum products and lubricants*, Subcommittee SC 4, *Classifications and specifications*.

This first edition cancels and replaces both ISO/TR 3498:1986 and ISO/TR 10481:1993, which have been technically revised.

# Lubricants, industrial oils and related products (class L) — Machine-tool lubricants — Categories and specifications

**WARNING —** The handling and use of products specified in this International Standard may be hazardous, if suitable precautions are not observed. This International Standard does not purport to address all of the safety problems associated with its use. It is the responsibility of the users of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

## 1 Scope

This International Standard provides the manufacturers and users of machine tools with criteria for the choice among the various categories of lubricants and gives specifications for these lubricants. This International Standard facilitates the application of ISO 5169 relating to the presentation of lubrication instructions for machine tools.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1817:1999, *Rubber, vulcanized — Determination of the effect of liquids*

ISO 2160:1998, *Petroleum products — Corrosiveness to copper — Copper strip test*

ISO 2592:2000, *Determination of flash and fire points — Cleveland open cup method*

ISO 2719:2002, *Determination of flash point — Pensky-Martens closed cup method*

ISO 2909:2002, *Petroleum products — Calculation of viscosity index from kinematic viscosity*

ISO 3016:1994, *Petroleum products — Determination of pour point*

ISO 3104:1994, *Petroleum products — Transparent and opaque liquids — Determination of kinematic viscosity and calculation of dynamic viscosity*

ISO 3104:1994, *Technical Corrigendum 1:1997*

ISO 3170:<sup>—1)</sup>, *Petroleum liquids — Manual sampling*

ISO 3448:1992, *Industrial liquid lubricants — ISO viscosity classification*

ISO 3675:1998, *Crude petroleum and liquid petroleum products — Laboratory determination of density — Hydrometer method*

1) To be published. (Revision of ISO 3170:1988)

ISO 4259:1992, *Petroleum products — Determination and application of precision data in relation to methods of test* [incl. Tech. Cor. 1:1993 (English only)]

ISO 4263-1:2003, *Petroleum and related products — Determination of the ageing behaviour of inhibited oils and fluids — TOST test — Part: Procedure for mineral oils*

ISO 5169:1977, *Machine tools — Presentation of lubrication instructions*

ISO 6247:1998, *Petroleum products — Determination of foaming characteristics of lubricating oils*

ISO 6614:1994, *Petroleum products — Determination of water separability of petroleum oils and synthetic fluids*

ISO 6618:1997, *Petroleum products and lubricants — Determination of acid or base number — Colour-indicator titration method*

ISO 6743-1:2002, *Lubricants, industrial oils and related products (class L) — Classification — Part 1: Family A (Total loss systems)*

ISO 6743-2:1981, *Lubricants, industrial oils and related products (class L) — Classification — Part 2: Family F (Spindle bearings, bearings and associated clutches)*

ISO 6743-4:1999, *Lubricants, industrial oils and related products (class L) — Classification — Part 4: Family H (Hydraulic systems)*

ISO 6743-6:1990, *Lubricants, industrial oils and related products (class L) — Classification — Part 6: Family C (Gears)*

ISO 6743-9:2003, *Lubricants, industrial oils and related products (class L) — Classification — Part 9: Family X (Greases)*

ISO 6743-13:2002, *Lubricants, industrial oils and related products (class L) — Classification — Part 13: Family G (Slideways)*

ISO 6743-99:2002, *Lubricants, industrial oils and related products (class L) — Classification — Part 99: General*

ISO 7120:1987, *Petroleum products and lubricants — Petroleum oils and other fluids — Determination of rust-preventing characteristics in the presence of water*

ISO 11158:1997, *Lubricants, industrial oils and related products (class L) — Family H (Hydraulic systems) — Specifications for categories HH, HL, HM, HR, HV and HG*

ISO 12925-1:1996, *Lubricants, industrial oils and related products (class L) — Family C (Gears) — Part 1: Specifications for lubricants for enclosed gear systems*

ISO 12925-1:1996, Technical Corrigendum 1:2002

XP T 60-183:1994, *Lubricants, industrial oils and related products — Lubricants for slideways — Anti-slick slip lubricating ability*

ASTM D4172-94, *Standard test method for wear preventive characteristics of lubricating fluid (Four-ball method)*

### 3 Sampling

Unless otherwise specified in a commodity specification, samples of lubricants shall be taken in accordance with ISO 3170.

## 4 Categories of products for the lubrication of machine tools — Criteria for the choice

The various mechanical parts of machine tools shall be lubricated with certain families of products defined and described in ISO 6743-1, ISO 6743-2, ISO 6743-4, ISO 6743-6, ISO 6743-9, ISO 6743-13 and ISO 6743-99.

Each part of ISO 6743 defines categories inside a lubricant family. Within each category, all the grades defined in accordance with ISO 3448 for liquid lubricants or ISO 6743-9 for greases are possible. For the lubrication of machine tools, all the categories of products and all the possible grades in each category are not useful. Therefore, to facilitate the selection by the manufacturers or the users of machine tools, it is advisable to limit the number of categories and grades of products.

Table 1 gives criteria for the applications and defines a limited range of products appearing underlined. It is recommended to the manufacturers of machine tools, whenever possible, to select the lubricants in the limited range.

Table 1 does not cover special applications requiring the use of specific lubricants. These special applications should be examined separately, case by case, by the manufacturers or users of machine tools.

## 5 Specifications of products

The products of Family H, classified in ISO 6743-4, are specified in ISO 11158 and the products of Family C, classified in ISO 6743-6, are specified in ISO 12925-1.

There is presently no specification covering the products of Family X, classified in ISO 6743-9.

**NOTE** At the time of publication of this International Standard, an International Standard for specifications of greases is in the course of development at the preliminary stage (see Annex A).

Table 2 gives the requirements of the categories of lubricants L-AN (ISO 6743-1), L-FC and L-FD (ISO 6743-2) and L-G (ISO 6743-13) covered by Table 1.

The properties are those applying to the products at the time of their delivery. The application of the accuracy in interpreting the results of tests is described in ISO 4259. This procedure shall be applied in case of dispute.

## 6 Packaging and labelling

### 6.1 Packaging

The lubricants shall be packed in suitable packaging and according to the regulations in use.

### 6.2 Labelling

The labelling shall comprise at least the following information:

- a) the commercial name of the product;
- b) the ISO designation code (including the viscosity grade);
- c) the batch number;
- d) the date of manufacturing;
- e) the legal labelling (transportation, safety) if the product is liable for this labelling.

**Table 1 — Range of machine-tool lubricants**

| <b>Code letter</b> | <b>General application</b>                         | <b>Particular application</b>                      | <b>More specific application</b>  | <b>Product type and/or performance requirements</b>  | <b>Symbol ISO L<sup>a</sup></b>   | <b>Typical applications</b>  | <b>Remarks</b>   |
|--------------------|--|--|---|--|---|--|--|
| A                  | Total loss systems                                 |  |   | Refined mineral oils   | <u>AN 32</u><br><u>AN 68</u><br><u>AN 220</u>   | Lightly loaded parts   |  |
| C                  | Gears  | Enclosed gears                                     | Continuous lubrication: splash lubrication, lubrication by circulation or spray | Refined mineral oils exhibiting improved properties of oxidation stability, corrosion protection (ferrous and non-ferrous metals), and foaming                             | <u>CKB 32</u><br><u>CKB 68</u><br><u>CKB 100</u><br><u>CKB 150</u>                                      | Enclosed gears, operating under moderate loads (see ISO 6743-6)<br>Bearings, headstocks, feed-boxes, carriages   | CKB 32 and CKB 68 oils can also be used for flood-lubricated, mechanically controlled clutches<br>CKB 68 may replace AN 68   |
| F                  | Spindle bearings, bearings and associated clutches |  |   | Refined mineral oils exhibiting improved properties of oxidation stability, corrosion protection (ferrous and non-ferrous metals), extreme-pressure, anti-wear and foaming | <u>CKC 68</u><br><u>CKC 100</u><br><u>CKC 150</u><br><u>CKC 220</u><br><u>CKC 320</u><br><u>CKC 460</u> | Enclosed gears, whose stabilized temperature of oil in service remains normal or average, and operating under high loads (see ISO 6743-6)<br>All types of enclosed gears (except hypoid gears)<br>Heavily loaded plain and roller bearings | These oils can also be used for manual or centralized lubrication of lead and feed screws and slideways operating under light loads, or whose conditions of use do not require any particular anti-stick-slip properties                   |
| F                  |  | Spindle bearings, bearings and associated clutches |   | Refined mineral oils exhibiting improved properties of oxidation stability and corrosion protection  | <u>FC 2</u><br><u>FC 5</u><br><u>FC 10</u><br><u>FC 22</u>  | Lubrication by recirculation, splash or oil mist of plain bearings, roller bearings and associated clutches  | These oils are intended for the lubrication of parts including clutches. Oils containing extreme-pressure and anti-wear agents are not allowed   |
| G                  | Slideways  | Lubrication  |   | Refined mineral oils exhibiting improved properties of oxidation stability, corrosion protection and anti-wear   | <u>FD 2</u><br><u>FD 5</u><br><u>FD 10</u><br><u>FD 22</u>  | Lubrication by recirculation, splash or oil mist of plain bearings and roller bearings   | These oils can also be used in applications requiring the use of particularly low viscosity oils, such as fine mechanisms, hydraulic or hydropneumatic mechanisms, electro-magnetic clutches, airline lubricators and hydrostatic bearings |
| G                  |  |  |   | Spindle bearings, bearings   |   |  | The GA oils may be replaced by HG oils (ISO 6743-4) of the same viscosity grade, provided that requirements of anti-stick-slip properties are met  |
| G                  |  |  |   | Lubrication of slideways systems in which the contacting surfaces are both metallic  | <u>GA 68</u><br><u>GA 100</u><br><u>GA 150</u><br><u>GA 220</u>   | Lubrication of machine-tool parts including plain slideways, nut-screw systems, ball nut-screw systems, plain bearings, in which anti-stick-slip and friction-reduction properties are essential   |  |

Table 1 (continued)

| Code letter | General application | Particular application | More specific application   | Product type and/or performance requirements   | Symbol ISO L <sup>a</sup>                         | Typical applications   | Remarks   |
|-------------|---------------------|------------------------|---|--|---|--|---|
|             |                     |                        | Lubrication of slideways systems in which one of the two contacting surfaces is constituted by a non-metallic material (pigmented polymer, resin, etc...) | Refined mineral oil exhibiting improved properties of wear protection, corrosion protection, tackiness and preventing discontinuous or intermittent motion of the slider (stick-slip)  | <u>GB 68</u><br>GB 100<br>GB 150<br><u>GB 220</u> | Lubrication of machine-tool parts including plain slideways with one non-metallic material sensitive to pollution by aqueous cutting fluids, nut-screw systems, ball nut-screw systems, plain bearings, in which anti-stick-slip and friction-reduction properties are essential | The considered compatibility is between the non-metallic sliding material and the slideways lubricant, in the presence of aqueous coolants  |
|             |                     |                        | Lubrication of slideways systems in which the contacting surfaces are both metallic   | Synthetic lubricants exhibiting improved properties of wear protection, corrosion protection, tackiness and preventing discontinuous or intermittent motion of the slider (stick-slip) | <u>GS 68</u><br><u>GS 220</u>                     | Lubrication of machine-tool parts including plain slideways, nut-screw systems, ball nut-screw systems, plain bearings, in which anti-stick-slip and friction-reduction properties and aqueous coolant compatibility are essential   | The considered compatibility is between the slideways lubricant and the aqueous coolant ; the contamination of the coolant by the slideways lubricant has a minimum impact on the coolant performance (the slideways lubricant is either emulsified or solubilized) |
| H           | Hydraulic systems   | Hydrostatic systems    |   | Refined mineral oils with improved anti-rust and anti-oxidation properties   | <u>HL 32</u><br>HL 46<br><u>HL 68</u>             | Lubrication of hydraulic systems not requiring any particular anti-wear properties<br>Splash or injection lubrication of lightly loaded gears, bearings and roller bearings  | HL 32 and HL 68 oils may replace, in the same applications, CKB 32 and CKB 68 oils  |

**Table 1 (continued)**

| <b>Code letter</b> | <b>General application</b>    | <b>Particular application</b> | <b>More specific application</b> | <b>Product type and/or performance requirements</b>  | <b>Symbol ISO L<sup>a</sup></b>   | <b>Typical applications</b>   | <b>Remarks</b>   |
|--------------------|-------------------------------|-------------------------------|----------------------------------|--|---|---|--|
| H(contd)           |                               |                               |                                  | Refined mineral oils with improved anti-rust, anti-oxidation, anti-wear and viscosity/temperature properties | HV 22<br>HV 32<br><u>HV 46</u>  | Applications in numerically controlled machine tools and in hydraulic circuits operating in a wide temperature range  | In some cases, it is possible to replace HM oils by HV oils.   |
|                    |                               | Hydraulic slideways systems   |                                  | Refined mineral oils with improved anti-rust, anti-oxidation, anti-wear and anti-stick-slip properties.      | <u>HG 32</u><br>HG 68   | Applications in machine tools fitted with a single circuit for hydraulic command and plain-bearing slideways for which, at low sliding speeds, the stick-slip phenomenon shall be prevented | These oils may be used for slideways lubrication, when a low-viscosity oil is required. A HG 68 may replace a GA 68 oil or a GB oil, provided it exhibits enough anti-stick-slip properties  |
| X                  | Applications requiring grease | Multi-purpose greases         |                                  | Greases with improved anti-oxidation and anti-corrosion properties   | XBCEA 00<br>XBCEA 0<br><u>XBCEA 1</u><br><u>XBCEA 2</u><br><u>XBCEA 3</u> | Plain and roller bearings, enclosed and open gears, and miscellaneous grease-lubricated parts   | Grease XBCEA 1 is used in centralized systems, whereas greases XBCEA 2 and XBCEA 3 are preferably dispensed by a cup or a hand-gum (see Annex A). The equipment manufacturer should identify the grease used for the initial filling of each item to ensure that the grease subsequently introduced is compatible with it. |

<sup>a</sup> A limited range of products appears underlined. It is recommended to the manufacturers of machine tools, whenever possible, to select the lubricants in the limited range (see Clause 4).

**Table 2 — Lubricants for machine tools and related products — Properties and requirements**

| No. | Property or test   | Unit                 | Reference of test method | Category AN      |                  |                               |                  | Category FD                   |                  |                               |                  | Categories FC and FD <sup>a</sup> |                  |                               |                  | Categories GA and GB <sup>b</sup> |                |                | Category GS      |                |                |                |
|-----|--|----------------------|--------------------------|------------------|------------------|-------------------------------|------------------|-------------------------------|------------------|-------------------------------|------------------|-----------------------------------|------------------|-------------------------------|------------------|-----------------------------------|----------------|----------------|------------------|----------------|----------------|----------------|
|     |  |                      |                          | Class            |                  | Class                         |                  | Class                         |                  | Class                         |                  | Class                             |                  | Class                         |                  | Class                             |                | Class          |                  |                |                |                |
| 1   | Viscosity grade <sup>c</sup>                                   | mm <sup>2</sup> /s   | ISO 3448                 | 32               | 68               | 220                           | 2                | 5                             | 10               | 22                            | 32               | 2                                 | 5                | 10                            | 22               | 32                                | 68             | 100            | 150              | 220            | 68             | 220            |
| 2   | Viscosity index  |                      | ISO 2909                 | + <sup>d</sup>   |                  |                               | Not applicable   | + <sup>e</sup>                | + <sup>f</sup>   | Not applicable                | + <sup>g</sup>   | + <sup>h</sup>                    | + <sup>i</sup>   | + <sup>j</sup>                | + <sup>k</sup>   | + <sup>l</sup>                    | + <sup>m</sup> | + <sup>n</sup> | + <sup>o</sup>   | + <sup>p</sup> | + <sup>q</sup> |                |
| 3   | Density at 15 °C   | kg/m <sup>3</sup>    | ISO 3675                 | + <sup>d</sup>   |                  |                               | + <sup>d</sup>   |                               |                  | + <sup>d</sup>                |                  | + <sup>d</sup>                    |                  | + <sup>d</sup>                |                  | + <sup>d</sup>                    | + <sup>d</sup> | + <sup>d</sup> | + <sup>d</sup>   | + <sup>d</sup> | + <sup>d</sup> |                |
| 4   | Acid number  | mg KOH/g             | ISO 6618                 | + <sup>d</sup>   |                  |                               | + <sup>d</sup>   |                               |                  | + <sup>d</sup>                |                  | + <sup>d</sup>                    |                  | + <sup>d</sup>                |                  | + <sup>d</sup>                    | + <sup>d</sup> | + <sup>d</sup> | + <sup>d</sup>   | + <sup>d</sup> | + <sup>d</sup> |                |
| 5   | Appearance   |                      | To be determined         | Clear and bright | Bright           |                               | Clear and bright |                               |                  | Clear and bright              |                  |                                   | Clear and bright |                               |                  | Clear and bright                  | Bright         |                | Clear and bright |                |                |                |
| 6   | Flash point (open cup)   | °C                   | ISO 2592                 | ≥ 140            | ≥ 180            |                               | Not applicable   |                               | ≥ 140            |                               | Not applicable   |                                   | Not applicable   |                               | ≥ 140            |                                   | ≥ 180          |                | ≥ 180            |                | ≥ 180          |                |
| 7   | Flash point (closed cup)                                       | °C                   | ISO 2719                 | No requirements  | ≥ 85             | ≥ 110                         | No requirement   | ≥ 85                          | ≥ 110            | No requirement                | ≥ 85             | ≥ 110                             | No requirement   | ≥ 85                          | ≥ 110            | No requirement                    | No requirement | No requirement | No requirement   | No requirement | No requirement | No requirement |
| 8   | Foaming characteristics at 24 °C at 93 °C at 24 °C after 93 °C | ml                   | ISO 6247                 | No requirements  | T<br>≤ 100       | S<br>≤ 10                         | T<br>≤ 100       | S<br>≤ 10                     | T<br>≤ 100       | S<br>≤ 10                         | No requirement | No requirement | No requirement   | No requirement | No requirement | No requirement |
| 9   | Copper corrosion (3 h at 100 °C)                               | rating               | ISO 2160                 | < 2              | < 2 <sup>d</sup> | < 2                           | < 2 <sup>d</sup> | < 2                           | < 2 <sup>d</sup> | < 2                           | < 2 <sup>d</sup> | < 2                               | < 2 <sup>d</sup> | < 2                           | < 2 <sup>d</sup> | < 2                               | < 2            | < 2            | < 2              | < 2            | < 2            |                |
| 10  | Corrosion-preventive properties                                | rating (procedure A) | ISO 7120                 | No requirement   |                  |                               |                  |                               |                  |                               |                  |                                   |                  |                               |                  |                                   | pass           | pass           | pass             | pass           | pass           | pass           |
| 11  | Pour point   | °C                   | ISO 3016                 | ≤ -9             | ≤ -9             | ≤ -6                          | ≤ -18            | ≤ -15                         | ≤ -18            | ≤ -15                         | ≤ -18            | ≤ -15                             | ≤ -18            | ≤ -15                         | ≤ -9             | ≤ -3                              | ≤ -9           | ≤ -3           | ≤ -9             | ≤ -9           | ≤ -9           | ≤ -9           |
| 12  | Anti-wear properties <sup>e</sup>                              |                      | ASTM D4172               | No requirement   |                  |                               | + <sup>f</sup>   |                               |                  | + <sup>f</sup>                |                  |                                   | + <sup>f</sup>   |                               |                  | + <sup>g</sup>                    | + <sup>g</sup> | + <sup>g</sup> | + <sup>g</sup>   | + <sup>g</sup> | + <sup>g</sup> |                |
| 13  | Demulsibility <sup>h</sup>                                     |                      | ISO 6614                 | No requirement   |                  |                               | + <sup>h</sup>   |                               |                  | + <sup>h</sup>                |                  |                                   | + <sup>h</sup>   |                               |                  | No requirement                    | No requirement | No requirement | No requirement   | No requirement | No requirement |                |
| 14  | Oxidation stability  |                      | ISO 4263-1               | Not applicable   | Not applicable   | ≥ 1 000 h to reach 2 mg KOH/g | Not applicable   | ≥ 1 000 h to reach 2 mg KOH/g | Not applicable   | ≥ 1 000 h to reach 2 mg KOH/g | Not applicable   | ≥ 1 000 h to reach 2 mg KOH/g     | Not applicable   | ≥ 1 000 h to reach 2 mg KOH/g | Not applicable   | No requirement                    | No requirement | No requirement | No requirement   | No requirement | No requirement |                |
| 15  | Compatibility with construction materials                      |                      | ISO 1817                 | + <sup>i</sup>   | + <sup>i</sup>   | + <sup>i</sup>                | + <sup>i</sup>   | + <sup>i</sup>                | + <sup>i</sup>   | + <sup>i</sup>                | + <sup>i</sup>   | + <sup>i</sup>                    | + <sup>i</sup>   | + <sup>i</sup>                | + <sup>i</sup>   | + <sup>i</sup>                    | + <sup>i</sup> | + <sup>i</sup> | + <sup>i</sup>   | + <sup>i</sup> |                |                |

**Table 2 (continued)**

| No.   | Property or test                          | Unit | Reference of test method | Category AN    |                | Category FD    |       | Categories FC and FD <sup>a</sup> |   |    |    | Categories GA and GB <sup>b</sup> |   |    | Category GS |    |    |     |     |     |
|---|---|------|--------------------------|----------------|----------------|----------------|-------|-----------------------------------|---|----|----|-----------------------------------|---|----|-------------|----|----|-----|-----|-----|
|   |   |      |                          | Class          | Class          | Class          | Class | 2                                 | 5 | 10 | 22 | 32                                | 5 | 10 | 22          | 32 | 68 | 100 | 150 | 220 |
| 16  | Friction characteristics                  |      | XP T 60-183              | Not applicable |                | No requirement |       | No requirement                    |   |    |    | + jk                              |   |    | + jk        |    |    | + j |     |     |
| 17  | Compatibility with aqueous cutting fluids |      |                          |                | Not applicable |                | + l   |                                   |   |    |    | + l                               |   |    | + l         |    |    | + m |     |     |
| <p><b>NOTE</b> T means tendency. S means stability. Sign + designates properties which are important to the manufacturer, but vary with machine design, construction, operating environment, etc. Values for these properties should be provided by the lubricant supplier and compared with the minimal requirements established by the manufacturer and/or the end user.</p> <p>a The anti-wear properties requirement only applies to the FD category.</p> <p>b The supplier should provide data demonstrating that the products are compatible with synthetic sliding materials in the presence of aqueous cutting fluids, on the basis of testing methods agreed with the manufacturer and/or the end user.</p> <p>c The kinematic viscosity at 40 °C, that shall be measured according to ISO 3104, shall be within the limits of viscosities defined in ISO 3448.</p> <p>d The temperature is limited to 60 °C for these low viscosity grades.</p> <p>e Although the four-ball method is debatable, it allows selection of lubricants exhibiting anti-wear properties over those that do not have any of these properties.</p> <p>f ASTM D4172, A conditions — Ambient temperatures for grades 2 and 5.</p> <p>g ASTM D4172, B conditions.</p> <p>h Adopt 25 °C for viscosity grades below 32.</p> <p>i The supplier should provide information to the manufacturer and/or to the end user about the behaviour of the product towards elastomers/synthetic materials.</p> <p>j AFNOR XP T 60-183 tribometer test method, or any other suitable method agreed with the manufacturer and/or the end user, may be used to demonstrate the frictional properties of the oil, and the absence of stick-slip phenomena (steel/steel contact).</p> <p>k For the GB category, the supplier should provide data on friction properties and absence of stick-slip phenomenon in synthetic material/steel contact on the basis of a method agreed with the manufacturer and / or the end user. AFNOR XP T 60-183, with a slider modified by insertion of synthetic material may be used.</p> <p>l The supplier should provide data on the basis of a method agreed with the end user.</p> <p>m The supplier should provide data demonstrating that the product, when leaking into an aqueous coolant, has no impact on the coolant performance.</p> |   |      |                          |                |                |                |       |                                   |   |    |    |                                   |   |    |             |    |    |     |     |     |

## Annex A (informative)

### Preliminary information about the future International Standard for specifications of greases

For product category X, the relevant International Standard (ISO 6743-9:1987) dealing with classification has been revised and will be published in 2003. The application of this classification, which defines the products in terms of high- and low-temperature operability, anti-rust protection, water resistance and ability to lubricate under high loads [Extreme-pressure properties (EP)], is tied up to the existence of specification limits for each of the properties mentioned.

The International Standard for specifications of greases is still in the course of development, and will be referenced as ISO 12924, *Lubricants, industrial oils and related products (class L) — Family X (Greases) — Specifications*.

At present, these specification limits are being established to determine how to evaluate the following properties:

- lower operating temperature — for symbol 1;
- upper operating temperature — for symbol 2;
- water contamination — for symbol 3;
- anti-rust protection — for symbol 3;
- ability to lubricate under high loads — for symbol 4.

Symbol 1: The applicability of greases at the various temperatures listed in Table 2 is defined by a flowability criterion at the said temperature, using one of the following methods: ISO 13737<sup>[3]</sup>, or DIN 51805<sup>[4]</sup> or ASTM D1478<sup>[8]</sup>.

Symbol 2: The applicability of greases at the various temperatures listed in Table 2 is defined by a life test in a bearing running at the said temperature, using either of the following methods: ASTM D3336<sup>[10]</sup> or DIN 51821-2<sup>[6]</sup>.

Symbol 3: This defines the level of water resistance and protection against corrosion; it corresponds to the combination of two properties, e.g. the resistance to water contamination and the level of anti-rust protection. The level of anti-rust protection is assessed using ISO 11007<sup>[1]</sup>. The resistance to water contamination is assessed using ISO 11009<sup>[2]</sup> for the water wash conditions, and using DIN 51807-1<sup>[5]</sup> for the static conditions.

Symbol 4: The ability to lubricate under high loads is defined by setting limits for the four-ball weld load using either IP 239<sup>[7]</sup> (European conditions) or ASTM D2596<sup>[9]</sup> (American conditions).

## Bibliography

- [1] ISO 11007:1997, *Petroleum products and lubricants — Determination of rust-prevention characteristics of lubricating greases*
- [2] ISO 11009:2000, *Petroleum products and lubricants — Determination of water washout characteristics of lubricating greases*
- [3] ISO 13737:—<sup>2</sup>), *Petroleum products — Determination of low-temperature cone penetration of lubricating greases*
- [4] DIN 51805:1974, *Testing of lubricants; determination of flow pressure of lubricating greases, Kesternich method*
- [5] DIN 51807-1:1979, *Testing of lubricants; Test of the behaviour of lubricating greases in the presence of water; Static test*
- [6] DIN 51821-2:1989, *Testing of lubricants; test using the FAG roller bearing grease testing apparatus FE9; Test method A/1500/6000*
- [7] IP 239/01, *Determination of extreme pressure and anti-wear properties of lubricating fluids — Four ball method (European conditions)*
- [8] ASTM D1478-97, *Standard test method for low-temperature torque of ball bearing grease*
- [9] ASTM D2596-02, *Standard test method for measurement of extreme-pressure properties of lubricating grease (Four-ball method)*
- [10] ASTM D3336-97, *Standard test method for life of lubricating greases in ball bearings at elevated temperatures*

---

2) To be published.

ANSI/NFPA 70-2017

---

---

---

---

---

---

---

---

---

---

---

---

## ICS 75.100

Price based on 10 pages