

To: Jeffrey Epstein[jeevacation@gmail.com]
From: Scott Denett
Sent: Fri 1/28/2011 8:27:30 PM
Subject: Re: specs

here is what nick gave me
 hope this helps. Let me know if you need anything else

[Remove TITAN Reference 1080p](#)

[Remove TITAN Reference 1080p 3D](#)

[Remove HIGHlite Cine 260 HC](#)



TITAN Reference 1080p

TITAN Reference 1080p 3D HIGHlite Cine 260 HC

Part Number	108-781	109-324	110-016
Aspect Ratio	16x9	16x9	16x9
Ansi Brightness	5000	5000	2000
Brightness Center	<i>Not applicable</i>	<i>Not applicable</i>	<i>Not applicable</i>
Contrast Ratio	5000	5500	20000
Display Type	DarkChip™ DMD	DarkChip™ DMD	DarkChip™ DMD
FanNoiseLevel	45	45	36
Fill Factor	87.00	87.00	<i>Not applicable</i>
HDTV Format	1080p, 1080i, 480p, 720p, 480i, 576p, 576i	1080p, 1080i, 480p, 720p, 480i, 576p, 576i	1080p, 1080i, 720p, 576p, 480i
Horizontal Scan Rate	15kHz to 100kHz	15kHz to 100kHz	<i>Not applicable</i>
Humidity	20 to 80% non-condensing	20 to 80% non-condensing	20% to 85%
Lens Mount	Zoom: Motorized horizontal and vertical lens shift, zoom and focus. Fixed: Manual Focus.	Zoom: Motorized horizontal and vertical lens shift, zoom and focus. Fixed: Manual Focus.	<i>Not applicable</i>
Mechanical Mounting	Front/Rear Table, Front/Rear Ceiling, Adjustable Front/Rear Feet	Front/Rear Table, Front/Rear Ceiling, Adjustable Front/Rear Feet	Front/Rear Table, Front/Rear Ceiling, Adjustable Front/Rear Feet
Native Resolution	1920 x 1080 Pixels	1920 x 1080 Pixels	1920 x 1080 Pixels
Operating Temperature	0 to 40°C	0 to 40°C	0 to 40 C
Power Consumption	850	850	450
Power Requirements	100-240 VAC ±10%, 50/60Hz single phase	100-240 VAC ±10%, 50/60Hz single phase	110-120/200-240 VAC
Remote Control	Remote wireless IR, Wired through 3.5mm stereo jack	Remote wireless IR, Wired through 3.5mm stereo jack	Remote wireless IR
Safety Regulation	CE, CCC	CE, CCC	CE, FCC Class A, UL
Sequential Color Management	3-chip DLP	3-chip DLP	<i>Not applicable</i>
Storage Temperature	-10 to 50°C	-10 to 50°C	-20 C to -60 C
Thermal Dissipation	2900	2900	1500

Vertical Scan Rate	24Hz to 85Hz	24Hz to 85Hz	43-85 HZ
Video Compatibility	HDTV, NTSC, PAL-M, PAL, NTSC 4:43, PAL-N, SECAM, HDCP Compliance	HDTV, NTSC, PAL-M, PAL, NTSC 4:43, PAL-N, SECAM, HDCP Compliance	HDTV, NTSC, PAL, SECAM, HDCP Compliance
Video Processing	Enhanced Seven-point Color Correction, Xenon Color Mode, User-selectable preset and downloadable parametric de-gamma, Pixel-based motion adaptive interpolation, Class-leading de-interlacing using 3:2 and 2:2 extraction, Frame Delay: as low as 1 frame, source, Auto mode selection - plug and play setup	Enhanced Seven-point Color Correction, Xenon Color Mode, User-selectable preset and downloadable parametric de-gamma, Pixel-based motion adaptive interpolation, Class-leading de-interlacing using 3:2 and 2:2 extraction, Frame Delay: as low as 1 frame, source, Auto mode selection - plug and play setup	User-selectable preset parametric de-gamma, motion adaptive interpolation, leading de-interlacing, 3:2 and 2:2 extraction, Auto mode selection - plug and play setup, 10-bit Full 10-bit deinterlacer, scaler, HDMI 1.3a
Automation Control	RS232 9-pin D sub / RJ45 LAN	RS232 9-pin D sub / RJ45 LAN	RS232 9-pin D sub / RJ45 LAN
Computer Compatibility	Up to 1920 x 1080	Up to 1920 x 1080	Up to 1920 x 1080
Height in Inches	10.00	10.00	8.60
Height in mm	253.50	253.50	218.60
Length in Inches	26.00	26.00	19.70
Length in mm	661.23	661.23	500.60
Width in Inches	21.50	21.50	19.70
Width in mm	547.00	547.00	499.20
Weight in pounds	68.00	68.00	47.00
WeightKg	31.00	31.00	<i>Not applicable</i>